

# VISVESVARAYA TECHNOLOGICAL UNIVERSITY

“JnanaSangama”, Belgaum -590014, Karnataka.



## LAB REPORT

on

## Big Data Analytics (23CS6PCBDA)

*Submitted by:*

Nischal Kiran (1BM22CS182)

Under the Guidance of

Vikranth B.M

Assistant Professor, BMSCE

*in partial fulfillment for the award of the degree of*

**BACHELOR OF ENGINEERING**

*in*

**COMPUTER SCIENCE AND ENGINEERING**



**B.M.S. COLLEGE OF ENGINEERING**

(Autonomous Institution under VTU)

**BENGALURU-560019**

**MARCH 2025 - June 2025**

**B. M. S. College of Engineering,  
Bull Temple Road, Bangalore 560019**  
(Affiliated To Visvesvaraya Technological University, Belgaum) **Department  
of Computer Science and Engineering**



**CERTIFICATE**

This is to certify that the Lab work entitled “**Big Data Analytics**” carried out by **Nischal Kiran (1BM22CS182)**, who is bonafide student of **B. M. S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum during the year 2025. The Lab report has been approved as it satisfies the academic requirements in respect of **Big Data Analytics - (22CS6PCBDA)** work prescribed for the said degree.

**Vikranth B.M**  
Assistant Professor  
Department of CSE  
BMSCE, Bengaluru

**Dr. Kavitha Sooda**  
Professor and Head  
Department of CSE  
BMSCE, Bengaluru

## Table Of Contents

S.No.	Experiment Title		Page No
1	Course Outcomes		
2	Experiments		
	2.1	Experiment - 1	1
	2.1.1	<b>Question:</b> <b>Perform the following DB operations using Cassandra.</b> <ul style="list-style-type: none"> <li>• Create a keyspace by name Employee</li> <li>• Create a column family by name, Employee-Info with attributes Emp_Id Primary Key, Emp_Name, Designation, Date_of_Joining, Salary, Dept_Name</li> <li>• Insert the values into the table in batch</li> <li>• Update Employee name and Department of Emp-Id 121</li> <li>• Sort the details of Employee records based on salary</li> <li>• Alter the schema of the table Employee_Info to add a column Projects which stores a</li> <li>• set of Projects done by the corresponding Employee.</li> <li>• Update the altered table to add project names.</li> <li>• Create a TTL of 15 seconds to display the values of Employees.</li> </ul>	
	2.1.2	Code with Output	
	2.2	Experiment - 2	5
	2.2.1	<b>Question:</b> <b>Perform the following DB operations using Cassandra:</b> <ul style="list-style-type: none"> <li>• Create a keyspace by name Library</li> <li>• Create a column family by name Library-Info with attributes Stud_Id Primary Key, Counter_value of type Counter, Stud_Name, Book-Name, Book-Id, Date_of_issue</li> <li>• Insert the values into the table in batch</li> <li>• Display the details of the table created and increase the value of the counter</li> <li>• Write a query to show that a student with id 112 has taken a book “BDA” 2 times.</li> <li>• Export the created column to a csv file</li> <li>• Import a given csv dataset from local file system into Cassandra column family.</li> </ul>	

		2.2.2	Code with Output	
	2.3	Experiment - 3		7
		2.3.1	Question: MongoDB- CRUD Demonstration.	

		2.3.2	Code with Output	
	2.4	Experiment - 4		10
		2.4.1	Question: Hadoop Installation Screenshot	
		2.4.2	Screenshot	
	2.5	Experiment - 5		12
		2.5.1	Question: Execution of HDFS Commands for interaction with Hadoop Environment. (Minimum 10 commands to be executed)	
		2.5.2	Code with Output	
	2.6	Experiment - 6		17
		2.6.1	Question: Implement WordCount Program on Hadoop framework.	
		2.6.2	Code with Output	
	2.7	Experiment - 7		21
		2.7.1	Question: <b>From the following link extract the weather data:</b> <a href="https://github.com/tomwhite/hadoop-book/tree/master/input/ncdc/all">https://github.com/tomwhite/hadoop-book/tree/master/input/ncdc/all</a>  <b>Create a Map Reduce program to:</b> a) Find average temperature for each year from NCDC data set. b) Find the mean max temperature for every month.	
		2.7.2	Code with Output	
	2.8	Experiment - 8		24
		2.8.1	Question: For a given Text file, Create a Map Reduce program to sort the content in an alphabetic order listing only top 10 maximum occurrences of words.	

		<b>2.8.2</b>	<b>Code with Output</b>	
--	--	--------------	-------------------------	--

## **1. Course Outcomes**

**CO1:** Apply the concepts of NoSQL, Hadoop, Spark for a given task

**CO2:** Analyse data analytic techniques for a given problem .

**CO3:** Conduct experiments using data analytics mechanisms for a given problem.

## **2. Experiments 2.1**

### **Experiment - 1**

#### **2.1.1 Question:**

**Perform the following DB operations using Cassandra.**

- Create a keyspace by name Employee
- Create a column family by name, Employee-Info with attributes Emp\_Id Primary Key, Emp\_Name, Designation, Date\_of\_Joining, Salary, Dept\_Name
- Insert the values into the table in batch
- Update Employee name and Department of Emp-Id 121
- Sort the details of Employee records based on salary
- Alter the schema of the table Employee\_Info to add a column Projects which stores a • set of Projects done by the corresponding Employee.
- Update the altered table to add project names.
- Create a TTL of 15 seconds to display the values of Employees.

#### **2.1.2 Code with Output:**

```

bmscscse@bmscscse-HP-Elite-Tower-800-G9-Desktop-PC: $ cqlsh
Connected to Test Cluster at 127.0.0.1:9042
[cqlsh 6.1.0 | Cassandra 4.1.4 | CQL spec 3.4.6 | Native protocol v5]
Use HELP for help.
cqlsh> create keyspace Employee with replication = {'class': 'SimpleStrategy', 'replication_factor': 1};
ConfigurationException (line 1:49) mismatched input ';' expecting ')' ... with replication = {'class': 'SimpleStrategy', 'replication_factor': 1}...
cqlsh> create keyspace Employee WITH replication={'class': 'SimpleStrategy', 'replication_factor': 1};
ConfigurationException: unrecognized strategy option (replication_factor) passed to SimpleStrategy for keyspace employee
cqlsh> create keyspace Employee WITH replication={'class': 'SimpleStrategy', 'replication_factor': 1};
cqlsh> DESCRIBE KEYSPACES

employee      system_auth      system_schema    system_views
system        system_distributed system_traces     system_virtual_schema

cqlsh> CREATE TABLE IF NOT EXISTS Employee_Info(
... Emp_id INT PRIMARY KEY,
... Emp_name TEXT,
... designation TEXT,
... date_of_joining DATE,
... Salary FLOAT,
... Dep_name TEXT,
... Projects SET<TEXT>);
InvalidRequest: Error from server: code=2200 [Invalid query] message="No keyspace has been specified. USE a keyspace, or explicitly specify keyspace.tablename"
cqlsh> USE EMPLOYEE
...
cqlsh> USE Employee
...
cqlsh> USE Employee;
cqlsh:employee> CREATE TABLE IF NOT EXISTS Employee_Info( Emp_id INT PRIMARY KEY, Emp_name TEXT, designation TEXT, date_of_joining DATE, Salary FLOAT, Dep_name TEXT, Projects SET<TEXT>);
cqlsh:employee> describe keyspace Employee

CREATE KEYSPACE employee WITH replication = {'class': 'SimpleStrategy', 'replication_factor': '1'} AND durable_writes = true;

CREATE TABLE employee.employee_info (
  emp_id int PRIMARY KEY,
  date_of_joining date,
  dep_name text,
  designation text,
  emp_name text,
  salary float,
  projects set<text>
) WITH additional_write_policy = '99p'
AND bloom_filter_fp_chance = 0.01
AND caching = {'keys': 'ALL', 'rows_per_partition': 'NONE'}
AND cdc = false
AND comment = ''
AND compaction = {'class': 'org.apache.cassandra.db.compaction.SizeTieredCompactionStrategy', 'max_threshold': '32', 'min_threshold': '4'}
AND compression = {'chunk_length_in_kb': '16', 'class': 'org.apache.cassandra.io.compress.LZ4Compressor'}
AND mentable = 'default'
AND crc_check_chance = 1.0
AND default_time_to_live = 0
AND extensions = {}
AND gc_grace_seconds = 864000
AND max_index_interval = 2048
AND mentable_flush_period_in_ms = 0
AND min_index_interval = 128

```

```
cqlsh:employee> update employee_info using ttl 15 set salary = 0 where emp_id = 121;
cqlsh:employee> select * from employee_info;
```

emp_id	bonus	date_of_joining	dep_name	designation	emp_name	projects	salary
120	12000	2024-05-06	Engineering	Developer	Priyanka GH	{'Project B', 'ProjectA'}	1e+06
123	null	2024-05-07	Engineering	Engineer	Sadhana	{'Project M', 'Project P'}	1.2e+06
122	null	2024-05-06	Management	HR	Rachana	{'Project C', 'Project M'}	9e+05
121	11000	2024-05-06	Management	Developer	Shreya	{'Project C', 'ProjectA'}	0

(4 rows)

```
cqlsh:employee> select * from employee_info;
```

emp_id	bonus	date_of_joining	dep_name	designation	emp_name	projects	salary
120	12000	2024-05-06	Engineering	Developer	Priyanka GH	{'Project B', 'ProjectA'}	1e+06
123	null	2024-05-07	Engineering	Engineer	Sadhana	{'Project M', 'Project P'}	1.2e+06
122	null	2024-05-06	Management	HR	Rachana	{'Project C', 'Project M'}	9e+05
121	11000	2024-05-06	Management	Developer	Shreya	{'Project C', 'ProjectA'}	null

(4 rows)

```
cqlsh:employee>
```

```
AND speculative_retry = '99p';
cqlsh:employee> select * from employee_info;
```

emp_id	date_of_joining	dep_name	designation	emp_name	projects	salary
120	2024-05-06	Engineering	Developer	Priyanka	{'Project B', 'ProjectA'}	1e+06
123	2024-05-07	Engineering	Engineer	Sadhana	{'Project M', 'Project P'}	1.2e+06
122	2024-05-06	Management	HR	Rachana	{'Project C', 'Project M'}	9e+05
121	2024-05-06	Management	Developer	Shreya	{'Project C', 'ProjectA'}	9e+05

(4 rows)

```
cqlsh:employee> update employee_info set emp_name = 'Priyanka GH' where emp_id = '120';
InvalidRequest: Error from server: code=2200 [invalid query] message=Invalid STRING constant (120) for "emp_id" of type int
```

```
cqlsh:employee> update employee_info set emp_name = 'Priyanka GH' where emp_id=120;
cqlsh:employee> select * from employee_info;
```

emp_id	date_of_joining	dep_name	designation	emp_name	projects	salary
120	2024-05-06	Engineering	Developer	Priyanka GH	{'Project B', 'ProjectA'}	1e+06
123	2024-05-07	Engineering	Engineer	Sadhana	{'Project M', 'Project P'}	1.2e+06
122	2024-05-06	Management	HR	Rachana	{'Project C', 'Project M'}	9e+05
121	2024-05-06	Management	Developer	Shreya	{'Project C', 'ProjectA'}	9e+05

(4 rows)

```
cqlsh:employee> select * from employee_info order by salary;
InvalidRequest: Error from server: code=2200 [invalid query] message="ORDER BY is only supported when the partition key is restricted by an EQ or an IN."
```

```
cqlsh:employee> alter table employee_info add bonus INT;
cqlsh:employee> select * from employee_info;
```

emp_id	bonus	date_of_joining	dep_name	designation	emp_name	projects	salary
120	null	2024-05-06	Engineering	Developer	Priyanka GH	{'Project B', 'ProjectA'}	1e+06
123	null	2024-05-07	Engineering	Engineer	Sadhana	{'Project M', 'Project P'}	1.2e+06
122	null	2024-05-06	Management	HR	Rachana	{'Project C', 'Project M'}	9e+05
121	null	2024-05-06	Management	Developer	Shreya	{'Project C', 'ProjectA'}	9e+05

(4 rows)

```
cqlsh:employee> update employee_info set bonus = 12000 where emp_id = 120;
cqlsh:employee> select * from employee_info;
```

emp_id	bonus	date_of_joining	dep_name	designation	emp_name	projects	salary
120	12000	2024-05-06	Engineering	Developer	Priyanka GH	{'Project B', 'ProjectA'}	1e+06
123	null	2024-05-07	Engineering	Engineer	Sadhana	{'Project M', 'Project P'}	1.2e+06
122	null	2024-05-06	Management	HR	Rachana	{'Project C', 'Project M'}	9e+05
121	null	2024-05-06	Management	Developer	Shreya	{'Project C', 'ProjectA'}	9e+05

(4 rows)

```
cqlsh:employee> update employee_info set bonus = 11000 where emp_id = 121;
cqlsh:employee> select * from employee_info using ttl 15 where emp_id = 123;
SyntaxException: line 1:28 mismatched input 'using' expecting EOF (select * from employee_info [using] ttl...)
cqlsh:employee> select * from employee_info where emp_id = 121 using ttl 15;
SyntaxException: line 1:47 no viable alternative at input 'using' (...employee_info where emp_id = 121 [using]...)
cqlsh:employee> update employee_info using ttl 15 set salary = 0 where emp_id = 121;
cqlsh:employee> select * from employee_info;
```

## 2.2 Experiment - 2 2.2.1

### Question:

Perform the following DB operations using Cassandra:

- Create a keyspace by name Library
- Create a column family by name Library-Info with attributes Stud\_Id Primary Key, Counter\_value of type Counter, Stud\_Name, Book-Name, Book-Id, Date\_of\_issue
- Insert the values into the table in batch
- Display the details of the table created and increase the value of the counter
- Write a query to show that a student with id 112 has taken a book “BDA” 2 times.
- Export the created column to a csv file
- Import a given csv dataset from local file system into Cassandra column family.



## 2.2.2 Code with Output:

```
bmscece@bmscece-HP-Elite-Tower-800-G9-Desktop-PC:~$ cqlsh
Connected to Test Cluster at 127.0.0.1:9042
[cqlsh 6.1.0 | Cassandra 4.1.4 | CQL spec 3.4.6 | Native protocol v5]
Use HELP for help.
cqlsh> CREATE KEYSPACE Students WITH REPLICATION={
... 'class':'SimpleStrategy','replication_factor':1};
cqlsh> DESCRIBE KEYSPACES

students      system_auth      system_schema      system_views
system        system_distributed  system_traces       system_virtual_schema

cqlsh> SELECT * FROM system.schema_keyspaces;
InvalidRequest: Error from server: code=2200 [Invalid query] message="table schema_keyspaces does not exist"
cqlsh> use Students;
cqlsh:students> create table Students_info(Roll_No int Primary key,StudName text,DateOfJoining timestamp,last_exam_Percent double);
cqlsh:students> describe tables;

students_info

cqlsh:students> describe table students;
Table 'students' not found in keyspace 'students'
cqlsh:students> describe table students_info;

CREATE TABLE students.students_info (
  roll_no int PRIMARY KEY,
  dateofjoining timestamp,
  last_exam_percent double,
  studname text
) WITH additional_write_policy = '99p'
AND bloom_filter_fp_chance = 0.01
AND caching = {'keys': 'ALL', 'rows_per_partition': 'NONE'}
AND cdc = false
AND comment = ''
AND compaction = {'class': 'org.apache.cassandra.db.compaction.SizeTieredCompactionStrategy', 'max_threshold': '32', 'min_threshold': '4'}
AND compression = {'chunk_length_in_kb': '16', 'class': 'org.apache.cassandra.io.compress.LZ4Compressor'}
AND memtable = 'default'
AND crc_check_chance = 1.0
AND default_time_to_live = 0
AND extensions = {}
AND gc_grace_seconds = 864000
AND max_index_interval = 2048
AND memtable_flush_period_in_ms = 0
AND min_index_interval = 128
AND read_repair = 'BLOCKING'
AND speculative_retry = '99p';

cqlsh:students> Begin batch insert into Students_info(Roll_no, StudName,DateOfJoining, last_exam_Percent) values(1,'Sadhana','2023-10-09', 98) insert into Students_info(Roll_no, StudName,DateOfJoining, last_exam_Percent) values(2,'Rutu','2023-10-10', 97) insert into Students_info(Roll_no, StudName,DateOfJoining, last_exam_Percent) values(3,'Rachana','2023-10-10', 97.5) insert into Students_info(Roll_no, StudName,DateOfJoining, last_exam_Percent) values(4,'Charu','2023-10-06', 96.5) apply batch;
cqlsh:students> select * from students_info;

roll_no | dateofjoining | last_exam_percent | studname
-----|-----|-----|-----
1 | 2023-10-08 18:30:00.000000+0000 | 98 | Sadhana
2 | 2023-10-09 18:30:00.000000+0000 | 97 | Rutu
4 | 2023-10-05 18:30:00.000000+0000 | 96.5 | Charu
3 | 2023-10-09 18:30:00.000000+0000 | 97.5 | Rachana

(4 rows)
cqlsh:students> select * from students_info where roll_no in (1,2,3);

roll_no | dateofjoining | last_exam_percent | studname
-----|-----|-----|-----
1 | 2023-10-08 18:30:00.000000+0000 | 98 | Sadhana
2 | 2023-10-09 18:30:00.000000+0000 | 97 | Rutu
3 | 2023-10-09 18:30:00.000000+0000 | 97.5 | Rachana

(3 rows)
cqlsh:students> select * from students_info where Studname='Charu';
InvalidRequest: Error from server: code=2200 [Invalid query] message="Cannot execute this query as it might involve data filtering and thus may have unpredictable performance. If you want to execute this query & write the performance unpredictability, use ALLOW FILTERING"
cqlsh:students> create index on Students_info(StudName);
cqlsh:students> select * from students_info where Studname='Charu';

roll_no | dateofjoining | last_exam_percent | studname
-----|-----|-----|-----
4 | 2023-10-05 18:30:00.000000+0000 | 96.5 | Charu

(1 rows)
cqlsh:students> select Roll_no,StudName from students_info LIMIT 2;
```

```

(4 rows)
cqlsh:students> select * from students_info where roll_no in (1,2,3);

roll_no | dateofjoining | last_exan_percent | studname
-----+-----+-----+-----
1 | 2023-10-08 18:30:00.000000+0000 | 98 | Sadhana
2 | 2023-10-09 18:30:00.000000+0000 | 97 | Rutu
3 | 2023-10-09 18:30:00.000000+0000 | 97.5 | Rachana

(3 rows)
cqlsh:students> select * from students_info where Studname='Charu';
InvalidRequest: Error from server: code=2200 [Invalid query] message="Cannot execute this query as it might involve data filtering and thus may have unpredictable performance. If you want to execute this query d
espite the performance unpredictability, use ALLOW FILTERING"
cqlsh:students> create index on Students_info(StudName);
cqlsh:students> select * from students_info where Studname='Charu';

roll_no | dateofjoining | last_exan_percent | studname
-----+-----+-----+-----
4 | 2023-10-05 18:30:00.000000+0000 | 96.5 | Charu

(1 rows)
cqlsh:students> select Roll_no,StudName from students_info LIMIT 2;

roll_no | studname
-----+-----
1 | Sadhana
2 | Rutu

(2 rows)
cqlsh:students> SELECT Roll_no as "USN" from Students_info;

USN
----
1
2
4
3

```

## 2.3 Experiment - 3 2.3.1

### Question:

MongoDB - CRUD Demonstration.

### 2.3.2 Code with Output:

1. Create a database “Student” with the following attributes Rollno, Name , Age, ContactNo, Email-Id, grade, hobby:

use Students

2. Insert 5 appropriate values according to the below queries.

```
db.students.insertMany([
  { "Rollno": 10, "Name": "John", "Age": 20, "ContactNo": "1234567890", "Email-Id":
"john@example.com", "grade": "A", "hobby": "Reading" },
  { "Rollno": 11, "Name": "Alice", "Age": 21, "ContactNo": "9876543210", "Email-Id":
"alice@example.com", "grade": "B", "hobby": "Painting" },
  { "Rollno": 12, "Name": "Bob", "Age": 22, "ContactNo": "2345678901", "Email-Id":
"bob@example.com", "grade": "C", "hobby": "Cooking" },
  { "Rollno": 13, "Name": "Eve", "Age": 23, "ContactNo": "3456789012", "Email-Id":
"eve@example.com", "grade": "A" },
  { "Rollno": 14, "Name": "Charlie", "Age": 24, "ContactNo": "4567890123", "Email-Id":
"charlie@example.com", "hobby": "Gardening" }
])
```

```
Atlas atlas-wanmtx-shard-0 [primary] Student> use Students
switched to db Students
Atlas atlas-wanmtx-shard-0 [primary] Students> show collections

Atlas atlas-wanmtx-shard-0 [primary] Students> db.students.insertMany([
...   { "Rollno": 10, "Name": "John", "Age": 20, "ContactNo": "1234567890", "Email-Id":
"john@example.com", "grade": "A", "hobby": "Reading" },
...   { "Rollno": 11, "Name": "Alice", "Age": 21, "ContactNo": "9876543210", "Email-Id":
"alice@example.com", "grade":
"B", "hobby": "Painting" },
...   { "Rollno": 12, "Name": "Bob", "Age": 22, "ContactNo": "2345678901", "Email-Id": "
bob@example.com", "grade": "C", "hobby": "Cooking" },
...   { "Rollno": 13, "Name": "Eve", "Age": 23, "ContactNo": "3456789012", "Email-Id": "
eve@example.com", "grade": "A"
},
...   { "Rollno": 14, "Name": "Charlie", "Age": 24, "ContactNo": "4567890123", "Email-Id
": "charlie@example.com", "hobby": "Gardening" }
... ])
{
  acknowledged: true,
  insertedIds: {
    '0': ObjectId("661ce9dc76a00ff8cc51dae1"),
    '1': ObjectId("661ce9dc76a00ff8cc51dae2"),
    '2': ObjectId("661ce9dc76a00ff8cc51dae3"),
    '3': ObjectId("661ce9dc76a00ff8cc51dae4"),
    '4': ObjectId("661ce9dc76a00ff8cc51dae5")
  }
}
```

3. Write query to update Email-Id of a student with rollno 10.

```
db.students.updateOne(
  { "Rollno": 10 },
```

```
{ $set: { "Email-Id": "john.doe@example.com" } }
```

```
)  
Atlas atlas-wanmtx-shard-0 [primary] Students> db.students.updateOne(  
... { "Rollno": 10 },  
... { $set: { "Email-Id": "john.doe@example.com" } }  
... )  
{  
  acknowledged: true,  
  insertedId: null,  
  matchedCount: 1,  
  modifiedCount: 1,  
  upsertedCount: 0  
}
```

4. Replace the student name from “Alice” to “Alicee” of rollno 11 db.students.updateOne(  
{ "Rollno": 11 },  
{ \$set: { "Name": "Alicee" } }

```
)  
Atlas atlas-wanmtx-shard-0 [primary] Students> db.students.updateOne(  
... { "Rollno": 11 },  
... { $set: { "Name": "Alicee" } }  
... )  
{  
  acknowledged: true,  
  insertedId: null,  
  matchedCount: 1,  
  modifiedCount: 1,  
  upsertedCount: 0  
}
```

5. Display Student Name and grade(Add if grade is not present)where the \_id column is  
1.

```
db.students.find({}, { "Name": 1, "grade": { $ifNull: ["$grade", "Not available"] }, " _id": 0 })
```

```
Atlas atlas-wanmtx-shard-0 [primary] Students> db.students.find({}, { "Name": 1, "grade":  
{ $ifNull: ["$grade", "Not available"] }, " _id": 0 })  
[  
  { Name: 'John', grade: 'A' },  
  { Name: 'Alicee', grade: 'B' },  
  { Name: 'Bob', grade: 'C' },  
  { Name: 'Eve', grade: 'A' },  
  { Name: 'Charlie', grade: 'Not available' }  
]
```

6. Update to add hobbies db.students.updateMany(  
{ "Name": "Eve" },  
{ \$set: { "hobby": "Dancing" } }

```
)
```

```
Atlas atlas-wanmtx-shard-0 [primary] Students> db.students.updateMany(
...   { "Name": "Eve" },
...   { $set: { "hobby": "Dancing" } }
... )
{
  acknowledged: true,
  insertedId: null,
  matchedCount: 1,
  modifiedCount: 1,
  upsertedCount: 0
}
```

7. Find documents where hobbies is set neither to Chess nor to Skating db.students.find({  
"hobby": { \$nin: ["Chess", "Skating"] } })

```
Atlas atlas-wanmtx-shard-0 [primary] Students> db.students.find({ "hobby": { $nin: ["Chess", "Skating"] } })
[
  {
    _id: ObjectId("661ce9dc76a00ff8cc51dae1"),
    Rollno: 10,
    Name: 'John',
    Age: 20,
    ContactNo: '1234567890',
    'Email-Id': 'john.doe@example.com',
    grade: 'A',
    hobby: 'Reading'
  },
  {
    _id: ObjectId("661ce9dc76a00ff8cc51dae2"),
    Rollno: 11,
    Name: 'Alice',
    Age: 21,
    ContactNo: '9876543210',
    'Email-Id': 'alice@example.com',
    grade: 'B',
    hobby: 'Painting'
  },
  {
    _id: ObjectId("661ce9dc76a00ff8cc51dae3"),
    Rollno: 12,
    Name: 'Bob',
    Age: 22,
    ContactNo: '2345678901',
    'Email-Id': 'bob@example.com',
    grade: 'C',
    hobby: 'Cooking'
  },
]
```

8. Find documents whose name begins with A db.students.find({ "Name": /^A/ })




```
Atlas atlas-wanmtx-shard-0 [primary] Students> db.students.find({ "Name": /^A/ })
[
  {
    _id: ObjectId("661ce9dc76a00ff8cc51dae2"),
    Rollno: 11,
    Name: 'Alice',
    Age: 21,
    ContactNo: '9876543210',
    'Email-Id': 'alice@example.com',
    grade: 'B',
    hobby: 'Painting'
  }
]
```

## 2.4 Experiment - 4 2.4.1

### Question:

Hadoop Installation Screenshot

### 2.4.2 Screenshot:



## All Applications

Cluster

- About
- Nodes
- Node Labels
- Applications
- NEW
- NEW\_SAVING
- SUBMITTED
- ACCEPTED
- RUNNING
- FINISHED
- FAILED
- KILLED
- Scheduler

Tools

Cluster Metrics						
Apps Submitted	Apps Pending	Apps Running	Apps Completed	Containers Running	Used Resources	Total Resources
0	0	0	0	0	<memory:0 B, vCores:0>	<memory:8 GB, vCores:8>

Cluster Nodes Metrics				
Active Nodes	Decommissioning Nodes	Decommissioned Nodes	Lost Nodes	Unhealthy Nodes
1	0	0	0	0

Scheduler Metrics			
Scheduler Type	Scheduling Resource Type	Minimum Allocation	Maximum Allocation
Capacity Scheduler	[memory-mb (unit=Mi), vcores]	<memory:1024, vCores:1>	<memory:8192, vCores:4>

Show 20 entries

ID	User	Name	Application Type	Queue	Application Priority	StartTime	LaunchTime	FinishTime	State	FinalStatus	Running Containers	Allocated CPU VCores	Allocated Memory MB	Allocated GPUs
No data available in table														

Showing 0 to 0 of 0 entries

# Experiment -

## Question:

2.5

5

### 2.5.1

Execution of HDFS Commands for interaction with Hadoop Environment. (Minimum 10 commands to be executed)

### 2.5.2 Code with Output:

```
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~$ cd ./Desktop/
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ start-all.sh
WARNING: Attempting to start all Apache Hadoop daemons as hadoop in 10 seconds.
WARNING: This is not a recommended production deployment configuration.
WARNING: Use CTRL-C to abort.
Starting namenodes on [localhost]
Starting datanodes
Starting secondary namenodes [bmscecse-HP-Elite-Tower-800-G9-Desktop-PC]
Starting resourcemanager
Starting nodemanagers
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -mkdir /Lab05
```

```
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop fs -ls /Hadoop
ls: '/Hadoop': No such file or directory
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop fs -ls /Lab05
```

```
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ touch test.txt
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ nano test.txt
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -put ./text.txt /Lab05/text.txt
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop fs -ls /Lab05
Found 1 items
-rw-r--r-- 1 hadoop supergroup 19 2024-05-13 14:33 /Lab05/text.txt
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -cat /Lab05/text.txt
Hello
How are you?
```

```
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop fs -ls /Lab05
Found 2 items
-rw-r--r-- 1 hadoop supergroup 15 2024-05-13 14:40 /Lab05/text.txt
-rw-r--r-- 1 hadoop supergroup 19 2024-05-13 14:33 /Lab05/text.txt
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -getmerge /Lab05 /text.txt /Lab05 /text.txt ../Downloads/Merged.txt
getmerge: '/text.txt': No such file or directory
getmerge: '/text.txt': No such file or directory
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -getmerge /Lab05/text.txt /Lab05/text.txt ../Downloads/Merged.txt
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hadoop fs -getfacl /Lab05
# file: /Lab05
# owner: hadoop
# group: supergroup
user::rwx
group::r-x
other::r-x
```

```
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -copyToLocal /Lab05/text.txt ../Documents
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -copyToLocal /Lab05/text.txt ../Documents
```

```
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -cat /Lab05/text.txt
Hello
How are you?
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -mv /Lab05 /test_Lab05
```

```
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -ls /test_Lab05
Found 2 items
-rw-r--r-- 1 hadoop supergroup      15 2024-05-13 14:40 /test_Lab05/test.txt
-rw-r--r-- 1 hadoop supergroup      19 2024-05-13 14:33 /test_Lab05/text.txt
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -cp /test_Lab05/ /Lab05
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -ls /Lab05
Found 2 items
-rw-r--r-- 1 hadoop supergroup      15 2024-05-13 14:51 /Lab05/test.txt
-rw-r--r-- 1 hadoop supergroup      19 2024-05-13 14:51 /Lab05/text.txt
hadoop@bmscecse-HP-Elite-Tower-800-G9-Desktop-PC:~/Desktop$ hdfs dfs -ls /test_Lab05
Found 2 items
-rw-r--r-- 1 hadoop supergroup      15 2024-05-13 14:40 /test_Lab05/test.txt
-rw-r--r-- 1 hadoop supergroup      19 2024-05-13 14:33 /test_Lab05/text.txt
```



## Experiment -

### Question:

2.6

6

#### 2.6.1

Implement WordCount Program on Hadoop framework.

#### 2.6.2 Code with Output:

##### Mapper Code:

```
import java.io.IOException; import
org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.LongWritable; import
org.apache.hadoop.io.Text;
import org.apache.hadoop.mapred.MapReduceBase;
import org.apache.hadoop.mapred.Mapper; import
org.apache.hadoop.mapred.OutputCollector; import
org.apache.hadoop.mapred.Reporter;
```

```
public class WCMapper extends MapReduceBase implements Mapper<LongWritable,Text, Text, IntWritable>
{
public void map(LongWritable key, Text value, OutputCollector<Text, IntWritable> output, Reporter rep)
throws IOException
{
String line = value.toString(); for
(String word : line.split(" "))
{
if (word.length() > 0)
{
output.collect(new Text(word), new IntWritable(1)); }
} } }
```

##### Reducer Code:

```
// Importing libraries import java.io.IOException;
import java.util.Iterator; import
org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.Text; import
org.apache.hadoop.mapred.MapReduceBase;
import org.apache.hadoop.mapred.OutputCollector;
import org.apache.hadoop.mapred.Reducer; import
org.apache.hadoop.mapred.Reporter;
public class WCReducer extends MapReduceBase implements Reducer<Text,IntWritable, Text,
IntWritable> { // Reduce function
public void reduce(Text key, Iterator<IntWritable> value,
OutputCollector<Text, IntWritable> output,
Reporter rep) throws IOException
{
int count = 0;
// Counting the frequency of each words while
(value.hasNext())
{
```

```

IntWritable i = value.next(); count
+= i.get();
}
output.collect(key, new IntWritable(count));
} }
Driver Code: WCDriver Java Class file. import
java.io.IOException; import
org.apache.hadoop.conf.Configured; import
org.apache.hadoop.fs.Path; import
org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.Text; import
org.apache.hadoop.mapred.FileInputFormat; import
org.apache.hadoop.mapred.FileOutputFormat; import
org.apache.hadoop.mapred.JobClient; import
org.apache.hadoop.mapred.JobConf; import
org.apache.hadoop.util.Tool; import
org.apache.hadoop.util.ToolRunner; public class WCDriver
extends Configured implements Tool { public int run(String
args[]) throws IOException
{
if (args.length < 2)
{
System.out.println("Please give valid inputs");
return -1;
}
JobConf conf = new JobConf(WCDriver.class);
FileInputFormat.setInputPaths(conf, new Path(args[0]));
FileOutputFormat.setOutputPath(conf, new Path(args[1]));
conf.setMapperClass(WCMapper.class);
conf.setReducerClass(WCReducer.class);
conf.setMapOutputKeyClass(Text.class);
conf.setMapOutputValueClass(IntWritable.class);
conf.setOutputKeyClass(Text.class);
conf.setOutputValueClass(IntWritable.class);
JobClient.runJob(conf)
; return 0; }
public static void main(String args[]) throws Exception
{
int exitCode = ToolRunner.run(new WCDriver(), args);
System.out.println(exitCode);
}
}

```

## 2.7

## 7

### 2.7.1

**From the following link extract the weather data:**

<https://github.com/tomwhite/hadoop-book/tree/master/input/ncdc/all>

**Create a Map Reduce program to:**

- c) Find average temperature for each year from NCDC data set.
- d) Find the mean max temperature for every month.

## Experiment -

### Question:

#### 2.7.2 Code with Output:

a) Find average temperature for each year from NCDC data set.

```
AverageDriver: package temp; import org.apache.hadoop.fs.Path;
import org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Job; import
org.apache.hadoop.mapreduce.lib.input.FileInputFormat; import
org.apache.hadoop.mapreduce.lib.output.FileOutputFormat; public
class AverageDriver {
public static void main(String[] args) throws Exception { if
(args.length != 2) {
System.err.println("Please Enter the input and output parameters");
System.exit(-1);
}
Job job = new Job();
job.setJarByClass(AverageDriver.class);
job.setJobName("Max temperature");
FileInputFormat.addInputPath(job, new Path(args[0]));
FileOutputFormat.setOutputPath(job, new Path(args[1]));
job.setMapperClass(AverageMapper.class);
job.setReducerClass(AverageReducer.class);
job.setOutputKeyClass(Text.class);
job.setOutputValueClass(IntWritable.class);
System.exit(job.waitForCompletion(true) ? 0 : 1);
}
}
```

```
AverageMapper: package temp; import
java.io.IOException; import
org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.LongWritable; import
org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Mapper;
public class AverageMapper extends Mapper<LongWritable, Text, Text, IntWritable> { public
static final int MISSING = 9999;
public void map(LongWritable key, Text value, Mapper<LongWritable, Text, Text,
IntWritable>.Context context) throws IOException, InterruptedException { int
temperature;
String line = value.toString(); String
year = line.substring(15, 19); if
(line.charAt(87) == '+') {
temperature =
Integer.parseInt(line.substring(88,
92));
} else {
temperature = Integer.parseInt(line.substring(87, 92)); }
}
```

```
String quality = line.substring(92, 93); if (temperature != 9999
&& quality.matches("[01459]")) context.write(new
Text(year), new IntWritable(temperature));
}
}
```

```
AverageReducer: package temp; import java.io.IOException; import
org.apache.hadoop.io.IntWritable; import org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Reducer; public class AverageReducer extends
Reducer<Text, IntWritable, Text, IntWritable> { public void reduce(Text key,
Iterable<IntWritable> values, Reducer<Text, IntWritable, Text, IntWritable>.Context
context) throws IOException, InterruptedException { int max_temp = 0; int count = 0; for
(IntWritable value : values) { max_temp += value.get(); count++;
}
context.write(key, new IntWritable(max_temp / count)); }}
```

```
C:\hadoop-3.3.0\sbin>hadoop jar C:\avgtemp.jar temp.AverageDriver /input_dir/temp.txt /avgtemp_outputdir
2021-05-15 14:52:50,635 INFO client.DefaultHadoopFailoverProxyProvider: Connecting to ResourceManager at /0.0.0.0:8032
2021-05-15 14:52:51,005 WARN mapreduce.JobResourceUploader: Hadoop command-line option parsing not performed. Implement the Tool interface and execute your application with ToolRunner to remedy this.
2021-05-15 14:52:51,111 INFO mapreduce.JobResourceUploader: Disabling Erasure Coding for path: /tmp/hadoop-yarn/staging/Anusree/.staging/job_1621060230696_0005
2021-05-15 14:52:51,735 INFO input.FileInputFormat: Total input files to process : 1
2021-05-15 14:52:52,751 INFO mapreduce.JobSubmitter: number of splits:1
2021-05-15 14:52:53,073 INFO mapreduce.JobSubmitter: Submitting tokens for job: job_1621060230696_0005
2021-05-15 14:52:53,073 INFO mapreduce.JobSubmitter: Executing with tokens: []
2021-05-15 14:52:53,237 INFO conf.Configuration: resource-types.xml not found
2021-05-15 14:52:53,238 INFO resource.ResourceUtils: Unable to find 'resource-types.xml'.
2021-05-15 14:52:53,312 INFO impl.YarnClientImpl: Submitted application application_1621060230696_0005
2021-05-15 14:52:53,352 INFO mapreduce.Job: The url to track the job: http://LAPTOP-JG329ESD:8088/proxy/application_1621060230696_0005/
2021-05-15 14:52:53,353 INFO mapreduce.Job: Running job: job_1621060230696_0005
2021-05-15 14:53:06,640 INFO mapreduce.Job: Job job_1621060230696_0005 running in uber mode : false
2021-05-15 14:53:06,643 INFO mapreduce.Job: map 0% reduce 0%
2021-05-15 14:53:12,758 INFO mapreduce.Job: map 100% reduce 0%
2021-05-15 14:53:19,860 INFO mapreduce.Job: map 100% reduce 100%
2021-05-15 14:53:25,967 INFO mapreduce.Job: Job job_1621060230696_0005 completed successfully
2021-05-15 14:53:26,096 INFO mapreduce.Job: Counters: 54
File System Counters
  FILE: Number of bytes read=72210
  FILE: Number of bytes written=674341
  FILE: Number of read operations=0
  FILE: Number of large read operations=0
  FILE: Number of write operations=0
  HDFS: Number of bytes read=894060
  HDFS: Number of bytes written=8
  HDFS: Number of read operations=0
  HDFS: Number of large read operations=0
  HDFS: Number of write operations=2
  HDFS: Number of bytes read erasure-coded=0
Job Counters
  Launched map tasks=1
  Launched reduce tasks=1
  Data-local map tasks=1
  Total time spent by all maps in occupied slots (ms)=3782
```

```
C:\hadoop-3.3.0\sbin>hdfs dfs -ls /avgtemp_outputdir
Found 2 items
-rw-r--r-- 1 Anusree supergroup      0 2021-05-15 14:53 /avgtemp_outputdir/_SUCCESS
-rw-r--r-- 1 Anusree supergroup      8 2021-05-15 14:53 /avgtemp_outputdir/part-r-00000

C:\hadoop-3.3.0\sbin>hdfs dfs -cat /avgtemp_outputdir/part-r-00000
1901    46

C:\hadoop-3.3.0\sbin>
```

**b) find the mean max temperature for every month**

```
MeanMaxDriver.class    package    meanmax;    import
org.apache.hadoop.fs.Path;                                import
org.apache.hadoop.io.IntWritable;                          import
org.apache.hadoop.io.Text;                                import
org.apache.hadoop.mapreduce.Job;                          import
org.apache.hadoop.mapreduce.lib.input.FileInputFormat;    import
org.apache.hadoop.mapreduce.lib.output.FileOutputFormat; public
class MeanMaxDriver {
public static void main(String[] args) throws Exception { if
(args.length != 2) {
System.err.println("Please Enter the input and output parameters"); System.exit(-1);
}
Job job = new Job();
job.setJarByClass(MeanMaxDriver.class);
job.setJobName("Max temperature");
FileInputFormat.addInputPath(job, new Path(args[0]));
FileOutputFormat.setOutputPath(job, new Path(args[1]));
job.setMapperClass(MeanMaxMapper.class);
job.setReducerClass(MeanMaxReducer.class);
job.setOutputKeyClass(Text.class);
job.setOutputValueClass(IntWritable.class);
System.exit(job.waitForCompletion(true) ? 0 : 1);
}
}
```

**MeanMaxMapper.class**

```
package meanmax; import
java.io.IOException;
import    org.apache.hadoop.io.IntWritable;
import    org.apache.hadoop.io.LongWritable;
import    org.apache.hadoop.io.Text;    import
org.apache.hadoop.mapreduce.Mapper;
public class MeanMaxMapper extends Mapper<LongWritable, Text, Text, IntWritable> { public
static final int MISSING = 9999;
public void map(LongWritable key, Text value, Mapper<LongWritable, Text, Text,
IntWritable>.Context context) throws IOException, InterruptedException { int
temperature;
String line = value.toString(); String
month = line.substring(19, 21); if
(line.charAt(87) == '+') {
temperature = Integer.parseInt(line.substring(88, 92));
} else {
```

```

temperature = Integer.parseInt(line.substring(87, 92));
}
String quality = line.substring(92, 93); if (temperature !=
9999 && quality.matches("[01459]"))
context.write(new Text(month), new IntWritable(temperature)); }
}

```

```

MeanMaxReducer.class package meanmax; import java.io.IOException; import
org.apache.hadoop.io.IntWritable; import org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Reducer; public class MeanMaxReducer extends
Reducer<Text, IntWritable, Text, IntWritable> { public void reduce(Text key,
Iterable<IntWritable> values, Reducer<Text, IntWritable, Text, IntWritable>.Context
context) throws IOException, InterruptedException { int max_temp = 0; int total_temp =
0; int count = 0; int days = 0;
for (IntWritable value : values) {
int temp = value.get(); if (temp
> max_temp) max_temp = temp;
count++; if (count == 3) {
total_temp += max_temp;
max_temp = 0; count = 0;
days++;
}
}
}
context.write(key, new IntWritable(total_temp / days));
}
}

```

```

C:\hadoop-3.3.0\sbin>hadoop jar C:\weanmax.jar weanmax.MeanMaxDriver /input_dir/temp.txt /meanmax_output
2021-05-21 20:28:05,250 INFO client.DefaultHadoopFailoverProxyProvider: Connecting to ResourceManager at /0.0.0.0:8032
2021-05-21 20:28:06,662 WARN mapreduce.JobResourceUploader: Hadoop command-line option parsing not performed. Implement the Tool interface and execute your application with ToolRunner to remedy this.
2021-05-21 20:28:06,916 INFO mapreduce.JobResourceUploader: Disabling Erasure Coding for path: /tmp/hadoop-yarn/staging/Anusree/.staging/job_1621608943095_0001
2021-05-21 20:28:08,426 INFO input.FileInputFormat: Total input files to process : 1
2021-05-21 20:28:09,107 INFO mapreduce.JobSubmitter: number of splits:1
2021-05-21 20:28:09,741 INFO mapreduce.JobSubmitter: Submitting tokens for job: job_1621608943095_0001
2021-05-21 20:28:09,741 INFO mapreduce.JobSubmitter: Executing with tokens: []
2021-05-21 20:28:10,029 INFO conf.Configuration: resource-types.xml not found
2021-05-21 20:28:10,030 INFO resource.ResourceUtils: Unable to find 'resource-types.xml'.
2021-05-21 20:28:10,676 INFO impl.YarnClientImpl: Submitted application application_1621608943095_0001
2021-05-21 20:28:11,005 INFO mapreduce.Job: The url to track the job: http://LAPTOP-J6329ESD:8080/proxy/application_1621608943095_0001/
2021-05-21 20:28:11,006 INFO mapreduce.Job: Running job: job_1621608943095_0001
2021-05-21 20:28:29,385 INFO mapreduce.Job: Job job_1621608943095_0001 running in uber mode : false
2021-05-21 20:28:29,389 INFO mapreduce.Job:  map 0% reduce 0%
2021-05-21 20:28:40,664 INFO mapreduce.Job:  map 100% reduce 0%
2021-05-21 20:28:50,832 INFO mapreduce.Job:  map 100% reduce 100%
2021-05-21 20:28:50,965 INFO mapreduce.Job: Job job_1621608943095_0001 completed successfully
2021-05-21 20:28:59,178 INFO mapreduce.Job: Counters: 54

  File System Counters
    FILE: Number of bytes read=59082
    FILE: Number of bytes written=640891
    FILE: Number of read operations=0
    FILE: Number of large read operations=0
    FILE: Number of write operations=0
    HDFS: Number of bytes read=894060
    HDFS: Number of bytes written=74
    HDFS: Number of read operations=0
    HDFS: Number of large read operations=0
    HDFS: Number of write operations=2
    HDFS: Number of bytes read erasure-coded=0
  Job Counters
    Launched map tasks=1
    Launched reduce tasks=1
    Data-local map tasks=1
    Total time spent by all maps in occupied slots (ms)=8077
    Total time spent by all reduces in occupied slots (ms)=7511
    Total time spent by all map tasks (ms)=8077
    Total time spent by all reduce tasks (ms)=7511
    Total vcore-milliseconds taken by all map tasks=8077
    Total vcore-milliseconds taken by all reduce tasks=7511
    Total megabyte-milliseconds taken by all map tasks=8270848
    Total megabyte-milliseconds taken by all reduce tasks=7691264

```

```

C:\hadoop-3.3.0\sbin>hdfs dfs -cat /meanmax_output/*
01      4
02      0
03      7
04     44
05    100
06    168
07    219
08    198
09    141
10    100
11     19
12      3

C:\hadoop-3.3.0\sbin>

```

## 2.8 Experiment - 8

### 2.8.1 Question:

For a given Text file, Create a Map Reduce program to sort the content in an alphabetic order listing only top 10 maximum occurrences of words.

**2.8.2 Code with Output: Driver-TopN.class**

```

package
samples.topn;    import    java.io.IOException;    import
java.util.StringTokenizer;    import
org.apache.hadoop.conf.Configuration;    import
org.apache.hadoop.fs.Path;    import
org.apache.hadoop.io.IntWritable;    import
org.apache.hadoop.io.Text;    import
org.apache.hadoop.mapreduce.Job;    import
org.apache.hadoop.mapreduce.Mapper;    import
org.apache.hadoop.mapreduce.lib.input.FileInputFormat;    import
org.apache.hadoop.mapreduce.lib.output.FileOutputFormat;
import org.apache.hadoop.util.GenericOptionsParser; public class
TopN {
public static void main(String[] args) throws Exception {
Configuration conf = new Configuration();
String[] otherArgs = (new GenericOptionsParser(conf, args)).getRemainingArgs(); if
(otherArgs.length != 2) {
System.err.println("Usage: TopN <in> <out>");
System.exit(2);
}
Job job = Job.getInstance(conf); job.setJobName("Top
N"); job.setJarByClass(TopN.class);
job.setMapperClass(TopNMapper.class);
job.setReducerClass(TopNReducer.class);
job.setOutputKeyClass(Text.class);
job.setOutputValueClass(IntWritable.class);
FileInputFormat.addInputPath(job, new Path(otherArgs[0]));
FileOutputFormat.setOutputPath(job, new Path(otherArgs[1]));
System.exit(job.waitForCompletion(true) ? 0 : 1);
}
public static class TopNMapper extends Mapper<Object, Text, Text, IntWritable> {
private static final IntWritable one = new IntWritable(1); private
Text word = new Text();
private String tokens = "[_!$#<>\\^=\\[\\]\\*^\\\\\\\\,;,.\\|-:()?!\"'"]";
public void map(Object key, Text value, Mapper<Object, Text, Text, IntWritable>.Context context)
throws IOException, InterruptedException {
String cleanLine = value.toString().toLowerCase().replaceAll(this.tokens, " ");
StringTokenizer itr = new StringTokenizer(cleanLine);
while (itr.hasMoreTokens()) {
this.word.set(itr.nextToken().trim());
context.write(this.word, one);
}
}
}
}
}
TopNCombiner.class package samples.topn; import java.io.IOException; import
org.apache.hadoop.io.IntWritable;    import    org.apache.hadoop.io.Text;    import

```



```

org.apache.hadoop.mapreduce.Reducer; public class TopNCombiner extends
Reducer<Text, IntWritable, Text, IntWritable> { public void reduce(Text key,
Iterable<IntWritable> values, Reducer<Text, IntWritable, Text, IntWritable>.Context
context) throws IOException, InterruptedException { int sum = 0;
for (IntWritable val : values) sum
+= val.get();
context.write(key, new IntWritable(sum));
}
}

```

```

TopNMapper.class package samples.topn;
import java.io.IOException; import
java.util.StringTokenizer; import
org.apache.hadoop.io.IntWritable; import
org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Mapper;
public class TopNMapper extends Mapper<Object, Text, Text, IntWritable> {
private static final IntWritable one = new IntWritable(1); private
Text word = new Text();
private String tokens = "[_!$#<>\\^=\\[\\]\\*\\/\\\\\\,;\\.\\-:()?!\"'"]";
public void map(Object key, Text value, Mapper<Object, Text, Text, IntWritable>.Context context)
throws IOException, InterruptedException {
String cleanLine = value.toString().toLowerCase().replaceAll(this.tokens, " ");
StringTokenizer itr = new StringTokenizer(cleanLine);
while (itr.hasMoreTokens()) {
this.word.set(itr.nextToken().trim());
context.write(this.word, one);
}
}
}

```

```

TopNReducer.class package
samples.topn; import
java.io.IOException; import
java.util.HashMap; import
java.util.Map;
import org.apache.hadoop.io.IntWritable;
import org.apache.hadoop.io.Text; import
org.apache.hadoop.mapreduce.Reducer;
import utils.MiscUtils;
public class TopNReducer extends Reducer<Text, IntWritable, Text, IntWritable> {
private Map<Text, IntWritable> countMap = new HashMap<>(); public void
reduce(Text key, Iterable<IntWritable> values, Reducer<Text, IntWritable, Text,
IntWritable>.Context context) throws IOException, InterruptedException { int sum = 0;
for (IntWritable val : values)
sum += val.get();
this.countMap.put(new Text(key), new IntWritable(sum));
}
protected void cleanup(Reducer<Text, IntWritable, Text, IntWritable>.Context context) throws
IOException, InterruptedException {

```

```

Map<Text, IntWritable> sortedMap = MiscUtils.sortByValues(this.countMap); int
counter = 0;
for (Text key : sortedMap.keySet()) {
if (counter++ == 20) break;
context.write(key, sortedMap.get(key));
}
}
}
}

```

```

C:\hadoop-3.3.0\sbin>jps
11072 DataNode
20528 Jps
5620 ResourceManager
15532 NodeManager
6140 NameNode

C:\hadoop-3.3.0\sbin>hdfs dfs -mkdir /input_dir

C:\hadoop-3.3.0\sbin>hdfs dfs -ls /
Found 1 items
drwxr-xr-x - Anusree supergroup 0 2021-05-08 19:46 /input_dir

C:\hadoop-3.3.0\sbin>hdfs dfs -copyFromLocal C:\input.txt /input_dir

C:\hadoop-3.3.0\sbin>hdfs dfs -ls /input_dir
Found 1 items
-rw-r--r-- 1 Anusree supergroup 36 2021-05-08 19:48 /input_dir/input.txt

C:\hadoop-3.3.0\sbin>hdfs dfs -cat /input_dir/input.txt
hello
world
hello
hadoop
bye

```

```

C:\hadoop-3.3.0\sbin>hadoop jar C:\sort.jar samples.topn.TopN /input_dir/input.txt /output_dir
2021-05-08 19:54:54,582 INFO client.DefaultHadoopFailoverProxyProvider: Connecting to ResourceManager at /0.0.0.0:8032
2021-05-08 19:54:55,291 INFO mapreduce.JobResourceUploader: Disabling Erasure Coding for path: /tmp/hadoop-yarn/staging/Anusree/.staging/job_1620483374279_0001
2021-05-08 19:54:55,821 INFO input.FileInputFormat: Total input files to process : 1
2021-05-08 19:54:56,261 INFO mapreduce.JobSubmitter: number of splits:1
2021-05-08 19:54:56,552 INFO mapreduce.JobSubmitter: Submitting tokens for job: job_1620483374279_0001
2021-05-08 19:54:56,552 INFO mapreduce.JobSubmitter: Executing with tokens: []
2021-05-08 19:54:56,843 INFO conf.Configuration: resource-types.xml not found
2021-05-08 19:54:56,843 INFO resource.ResourceUtils: Unable to find 'resource-types.xml'.
2021-05-08 19:54:57,387 INFO impl.YarnClientImpl: Submitted application application_1620483374279_0001
2021-05-08 19:54:57,507 INFO mapreduce.Job: The url to track the job: http://LAPTOP-J6329F5D:8088/proxy/application_1620483374279_0001/
2021-05-08 19:54:57,508 INFO mapreduce.Job: Running job: job_1620483374279_0001
2021-05-08 19:55:13,792 INFO mapreduce.Job: Job job_1620483374279_0001 running in uber mode : false
2021-05-08 19:55:13,794 INFO mapreduce.Job: map 0% reduce 0%
2021-05-08 19:55:20,020 INFO mapreduce.Job: map 100% reduce 0%
2021-05-08 19:55:27,116 INFO mapreduce.Job: map 100% reduce 100%
2021-05-08 19:55:33,199 INFO mapreduce.Job: Job job_1620483374279_0001 completed successfully
2021-05-08 19:55:33,334 INFO mapreduce.Job: Counters: 54
File System Counters:
FILE: Number of bytes read=65
FILE: Number of bytes written=530397
FILE: Number of read operations=0
FILE: Number of large read operations=0
FILE: Number of write operations=0
HDFS: Number of bytes read=142
HDFS: Number of bytes written=31
HDFS: Number of read operations=8
HDFS: Number of large read operations=0
HDFS: Number of write operations=2
HDFS: Number of bytes read erasure-coded=0

```

```
C:\hadoop-3.3.0\sbin>hdfs dfs -cat /output_dir/*  
hello 2  
hadoop 1  
world 1  
bye 1  
  
C:\hadoop-3.3.0\sbin>
```