

INDUSTRIAL LASER BAR ...	DS5100-X2XX	DS5100-X3XX	DS5100-X4XX
Reading distance (min/max)		Medium range: 200 - 1000 m...	
Max resolution	up to 0.2 mm (8mils)		
Scan rate	800 scan/s		
Focus adjustment	Mechanically adjustable focus with locking		
Scan pattern type	Linear / Oscillating Mirror / Deflection Mirror		
Aperture angle	65 degrees		
Multilabel reading	Up to 10 Codes in the same reading phase		
Bar code assignment technol...	Packtrack tracking technology on Long Range models DS5100-24xx only when configured in an ...		
Reconstruction code technol...	ACR4		
Readable codes	Code 2/5, Code39, Code 93, Code 128, EAN/UPC, EAN128, Codabar, Pharmacode, Plessey, IS...		
Case material	Aluminum		
Dimensions (typical value)	LIN: 101 x 85 x 42 mm (3.98 ...	LIN: 101 x 104.2 x 42 mm (3....	LIN: 117.75 x 104.6 x 42 mm ...
Weight	LIN: 580 g OM: 775 g	LIN: 520 g OM: 715 g	LIN: 550 g OM: 745 g
Operating temperature	0° to +50 °C (+32°F to +122 °F) Subzero version -35°C to +50°C (-31°F to +122 °F)*		
Storage temperature	-20° to +70° C (-4°F to +158 °F) Subzero version -35° to +70° C (-31°F to +158 °F)*		
Ip rating	IP65		
Embedded communication in...	Main port RS232/RS485-FD ...	Main port RS232/RS485-FD ...	PROFINET-10 Class B EBC ...
Fieldbus/ethernet	Fieldbus supported through ...	Embedded EtherNet/IP, PRO...	Embedded PROFINET-10
Digital inputs	2 Input (optocoupled, NPN/P...	2 Input (optocoupled, NPN/P...	1 Input (optocoupled, NPN/P...
Digital outputs	2 Outputs (optocoupled)	2 Outputs (non- optocoupled)	/
Operating modes	On-line, Serial On-line, Automatic, Continuous, Test, Verifier, Packtrack tracking technology on L...		
Display	16 x 2 characters		
Device programming	Genius (Windows™ based) software tool Serial Host Mode Programming sequences XPRESS i...		
Voltage supply/power consu...	DS5100 XX00		DS5100 XX20
	10-30V; 6W		10-30V; 7,5W
	DS5100 XX05		DS5100 XX25
	24V; 28,8W		24V; 31,2W