

		Framing Species G 0.49					Framing Species 0.49 > G 0.42					Framing Species G < 0.42				
							Panel Edge Nail Spacing (in.) ³									
		Blocked Diaphragms					Blocked Diaphragms					Blocked Diaphragms				
		6 ²	6	4	3	2 ¹	6 ²	6	4	3	2 ¹	6 ²	6	4	3	2 ¹
Sheathing Material	Sheathing Thickness	Nail Size	Allowable Shear Capacity (plf)													
Structural I	3/8	8d	250	380	505	740	840	210	310	415	610	685	160	245	330	485 545
	15/32	10d	300	450	595	895	1020	245	365	490	735	840	195	295	385	580 665
	3/8	6d	175	260	350	525	590	145	210	285	435	485	110	170	230	345 385
		8d	225	335	450	670	765	210	310	415	610	685	160	245	330	485 545
Sheathing Grade	7/16	8d	240	355	475	705	805	210	310	415	610	685	160	245	330	485 545
	15/32	8d	250	380	505	740	840	210	310	415	610	685	160	245	330	485 545
		10d	265	405	540	805	915	245	365	490	735	840	195	295	385	580 665
	19/32	10d	300	450	595	895	1020	245	365	490	735	840	195	295	385	580 665