

**1.0 Type**

FC 918 MP

**2.0 Capacity**

- 2.1 Mains connection
- 2.2 Nominal consumption
- 2.3 Working pressure
- 2.4 Water - volume flow
- 2.5 Operating temperature maximum

400 V 3 AC 50 Hz  
 5,3 kW 9,5 A  
 180 bar  
 14,5 l/min  
 70 °C

**3.0 Specification**

- 3.1 High pressure pump with 3 solid ceramic plungers
- 3.2 Unloader safety valve
- 3.3 protects the high pressure system
- 3.4 with injector 2,2 for the dosage of cleaning and preserving agents
- 3.5 Duplex-spray lance for pressure regulation
- 3.6 with low pressure stage for the dosage of cleaning and preserving agents
- 3.7 with rotating screw union
- 3.8 with mechanical spray gun
- 3.9 with high pressure flat jet nozzle
- 3.10 with low pressure flat jet nozzle
- 3.11 with high pressure hose 10 m
- 3.12 Electrical motor for high pressure pump drive
- 3.13 MP - Control "VarioStop" with cutoff delay
- 3.14 Connecting cable 5 x 1,5 mm<sup>2</sup>

|                   |           |            |
|-------------------|-----------|------------|
| Type NP 16/13     | Order nr. | 7041307000 |
| Type VS - ULH 180 | Order nr. | 2098857000 |
|                   | Order nr. | 2098290000 |
|                   | Order nr. | 2085600000 |
|                   | Order nr. | 7041097000 |
| Type 25045        | Order nr. | 7027160000 |
| Type 4040         | Order nr. | 7025330000 |
| Type DN 8         | Order nr. | 2051560000 |
| Capacity 4 kW     | Order nr. | 7040633000 |

6 m with mains plug 16A

**4.0 Dimensions with trolley (LxWxH)**

856x545x918 mm

**5.0 Weight**

76 kg