

Model Selection Chart

Basic Valve Size	Port Tap (NPTF)	Description		Large Top		Small Top		Cv	
								Port 1 to Port 2	Port 2 to Port 1
				psi	bar	psi	bar		
1/2"	1/2"	2WNC	Model No.	C284-2001		C284-2005		5.6	6.1
			Pressure Rating	500	34.0	450	31.0		
	3/4"	2WNC	Model No.	C284-2002		C284-2006		7.4	7.0
			Pressure Rating	500	34.0	450	31.0		
	1/2"	2WNO	Model No.	C284-2003		C284-2007		6.1	6.5
			Pressure Rating	500	34.0	375‡	26.0		
	3/4"	2WNO	Model No.	C284-2004		C284-2008		7.6	8.0
			Pressure Rating	500	34.0	375‡	26.0		
1"	1"	2WNC	Model No.	C284-4001		C284-4005		12.8	12.3
			Pressure Rating	500	34.0	375‡	26.0		
	1 1/4"	2WNC	Model No.	C284-4002		C284-4006		17.0	16.3
			Pressure Rating	500	34.0	375‡	26.0		
	1"	2WNO	Model No.	C284-4003		C284-4007		13.2	12.6
			Pressure Rating	500	34.0	275†	19.0		
	1 1/4"	2WNO	Model No.	C284-4004		C284-4008		17.9	17.0
			Pressure Rating	500	34.0	275†	19.0		
1 1/2"	1 1/2"	2WNC	Model No.	C284-6002		C284-6006		32.5	31.0
			Pressure Rating	500	34.0	250	17.2		
	1 1/2"	2WNO	Model No.	C284-6004		C284-6008		32.0	32.9
			Pressure Rating	450‡	31.0	200‡	13.8		

‡ Pressure rating shown is for use with inlet at Port 2. If inlet is piped to Port 1, line pressures up to 500 psi are permissible.