

1.0	Type	FC 918 MP		
2.0	Capacity			
2.1	Mains connection	400 V 3 AC 50 Hz		TÜV
2.2	Nominal consumption	5,3 kW 9,5 A		SUD
2.3	Working pressure	180 bar		TÜV MS Standard
2.4	Water - volume flow	14,5 l/min		
2.5	Operating temperature...	70 °C		
3.0	Specification			
3.1	High pressure pump w...	Type NP 16/13	Order nr.	7041307000
3.2	Unloader safety valve	Type VS - ULH 180	Order nr.	2098857000
3.3	protects the high press...			
3.4	with injector 2,2 for the...			
3.5	Duplex-spray lance for...		Order nr.	2098290000
3.6	with low pressure stag...			
3.7	with rotating screw union		Order nr.	2085600000
3.8	with mechanical spray ...		Order nr.	7041097000
3.9	with high pressure flat ...	Type 25045	Order nr.	7027160000
3.10	with low pressure flat j...	Type 4040	Order nr.	7025330000
3.11	with high pressure hos...	Type DN 8	Order nr.	2051560000
3.12	Electrical motor for hig...	Capacity 4 kW	Order nr.	7040633000
3.13	MP - Control "VarioSto...			
3.14	Connecting cable 5 x ...	6 m with mains plug 16A		
4.0	Dimensions with trolle...	856x545x918 mm		
5.0	Weight	76 kg		