

Parameter	min.	Value typ.	max.	Unit
Read heads				
Housing material	Reinforced PPS			
Ambient temperature	- 20	-	+60	°C
Degree of protection a...	IP 67			
Installation position	Any, alignment with actuator should be kept in mind (markings)			
Connection type	Molded cable with crimped ferrules / plug connector M8			
Switching current	24			V
Switching current I,	-	-	0.5	A
Method of operation	Magnetic, reed contact			
Mechanical life	100 x 106 operating cycles			
Vibration resistance	10 55 Hz, amplitude 1 mm			
Shock resistance	30 g / 11 ms			
EMC compliance	According to EN 60947-5-3			
Center offset m from a...	+ 2.5 mm at a distance of S = 3 mm			
Switch-on distance S	See ordering table and operating diagrams			
Switch-off distance Sr				
Contact elements				
Actuator				
Housing material	Reinforced PPS			
Ambient temperature	20	-	+60	°C
Degree of protection a...	IP 67			
Installation position	Any, alignment with read head should be kept in mind (markings)			
Method of operation	Magnetic			
Vibration resistance	10 ... 55 Hz, amplitude 1 mm			
Shock resistance	30 g / 11 ms			
Center offset m from r...	± 2.5 mm at a distance of S = 3 mm			
Switch-on distance S	See ordering table and operating diagrams			
Switch-off distance S				