

INDOOR UNIT		FTXM20PVMA	FTXM25PVMA	FTXM35PVMA	FTXM46PVMA	FTXM50PVMA	FTXM60PVMA	FTXM71PVMA	FTXM85PVMA	FTXM95PVMA
OUTDOOR UNIT		RXM20PVMA	RXM25PVMA	RXM35PVMA	RXM46PVMA	RXM50PVMA	RXM60PVMA	RXM71PVMA	RXM85PVMA	RXM95PVMA
Rated Capacity	Cool (kW)	2.0	2.5	3.5	4.6	5.0	6.0	7.1	8.5	9.4
	Heat (RW)	2.7	3.2	3.7	4.7	6.0	7.0	7.5	9.0	10.3
Capacity Range	Cool (kW)	0.9-2.8	0.9-3.4	0.9-4.1	0.9-5.4	1.1-6.1	1.1-6.8	2.0-8.8	2.0-10.5	2.0-11.2
	Heat [RW]	0.9-4.3	0.9-5.0	0.9-5.1	1.0-6.6	10-7.7	1.0-8.3	19-10.4	19-11.6	19-12.0
Indoor Airflow Rate [Hi]	Cool [l/s]	165	155	163	175	278	302	358	358	372
	Heat [l/s]	165	163	182	177	287	313	335	422	413
Indoor Fan Speeds		5 steps, quiet and automatic								
Energy Label/ Star Ratings	Cool	5	5	35	25	4	3	2.5	2	
	Heat	5	5	5	35	4	3.5	3	2.5	2
Front Panel Colour		White								
Power Supply		1 phase, 220-240, 50Hz								
Power Input [Rated]	Cool [RW]	0.41	0.51	0.86	1.24	118	1.55	1.94	2.49	2.79
	Heat [RW]	0.59	0.65	0.81	122	142	1.72	1.91	2.42	3.07
EER/C.O.P	Cool/Heat	4.88/4.58	4.9/4.92	4.07/4.57	3.71/3.85	4.24/4.23	3.87/4.07	3.66/3.93	3.41/3.72	3.37/3.36
A.E.E.R/A.CO.P	Cool/Heat	4.82/4.54	4.85/4.88	4.05/4.54	3.69/3.84	4.22/4.21	3.86/4.06	3.51/3.79	3.31/3.62	3.27/3.28
Dimensions (HxWxD)	Indoor (mm)	295x800x215	295x800x215	295x800x215	295x800x215	340x1050x259	340x1050x259	340x1050x259	340x1200x259	340x1200x259
	Outdoor (mm)	550x765x285	550x765x285	550x765x285	735x825x300	735x825x300	735x825x300	770x900x320	990x940x320	990x940x320
Weight	Indoor (kg)	9	10	10	10	15	15	15	17	18
	Outdoor (kg)	32	34	34	47	47	47	69	80	82
Compressor Type		Hermetically Sealed Swing Type								
Refrigerant Type		R32								
Max Pipe Length	(m)	20	20	20	30	30	30	30	30	30
Pipe Sizes	(m)	15	15	15	20	20	20	20	20	20
	Liquid (mm)	6.4	6.4	5.4	6.4	6.4	6.4	6.4	6.4	6.4
	Gas (mm)	9.5	9.5	9.5	12.7	12.7	12.7	15.9	15.9	15.9
Outdoor Operating Range (outdoor temp)	Cool (°CDB]	-10 to 46								
	Heat (°CWB)	-15 to 18								
Indoor Sound Level (H/SL)	Cool (dBA)	38/20	40/20	42/20	44/32	45/32	48/33	52/34	51/37	53/38
	Heat (dBA)	39/25	40/25	42/26	43/30	45/30	48/30	50/30	51/35	52/35
Outdoor Sound Level (H/SL)	Cool (dBA)	46/43	47/43	49/44	47/44	47/44	49/46	53/49	54/51	54/51
	Heat (dBA)	47/44	48/44	49/45	48/45	48/45	52/46	54/49	56/51	55/51
Outdoor EPA Sound Power Level [H]	Cool (dBA)	58	59	61	59	59	61	65	66	66
	Heat (dBA)	59	60	61	60	60	64	66	68	67