GeeksforGeeks A computer science portal for geeks

Custom Search	
Write an Article	Login

For-each loop in Java

Prerequisite: Decision making in Java

For-each is another array traversing technique like for loop, while loop, do-while loop introduced in Java5.

- It starts with the keyword for like a normal for-loop.
- Instead of declaring and initializing a loop counter variable, you declare a variable that is the same type as the base type of the array, followed by a colon, which is then followed by the array name.
- In the loop body, you can use the loop variable you created rather than using an indexed array element.
- It's commonly used to iterate over an array or a Collections class (eg, ArrayList)

Syntax:

```
for (type var : array)
{
    statements using var;
}
```

is equivalent to:

```
for (int i=0; i<arr.length; i++)
{
    type var = arr[i];
    statements using var;
}

// Java program to illustrate
// for-each loop
class For_Each
{
    public static void main(String[] arg)
    {
        int[] marks = { 125, 132, 95, 116, 110 };
        int highest_marks = maximum(marks);
        System.out.println("The highest score is " + highest_marks);
    }
    public static int maximum(int[] numbers)
}</pre>
```

Run on IDE

Output:

```
The highest score is 132
```

Limitations of for-each loop

鬥

1. For-each loops are not appropriate when you want to modify the array:

```
for (int num : marks)
{
    // only changes num, not the array element
    num = num*2;
}
```

2. For-each loops **do not keep track of index**. So we can not obtain array index using For-Each loop

```
for (int num : numbers)
{
    if (num == target)
    {
        return ???; // do not know the index of num
    }
}
```

3. For-each only iterates forward over the array in single steps

```
// cannot be converted to a for-each loop
for (int i=numbers.length-1; i>0; i--)
{
    System.out.println(numbers[i]);
}
```

4. For-each cannot process two decision making statements at once

```
// cannot be easily converted to a for-each loop
for (int i=0; i<numbers.length; i++)
{</pre>
```

```
if (numbers[i] == arr[i])
{ ...
}
```

Related Articles:

For-each in C++ vs Java

Iterator vs For-each in Java

This article is contributed by **Abhishek Verma**. If you like GeeksforGeeks and would like to contribute, you can also write an article using contribute.geeksforgeeks.org or mail your article to contribute@geeksforgeeks.org. See your article appearing on the GeeksforGeeks main page and help other Geeks.

Please write comments if you find anything incorrect, or you want to share more information about the topic discussed above.





Login to Improve this Article

Please write to us at contribute@geeksforgeeks.org to report any issue with the above content.

Recommended Posts:

For Loop in Java | Important points

Decision Making in Java (if, if-else, switch, break, continue, jump)

Loops in Java

Switch Statement in Java

Iterator vs Foreach In Java

Java | Converting an Image into Grayscale using cvtColor()

Java | Removing whitespaces using Regex

Java System.nanoTime() vs System.currentTimeMillis

Java toDegrees() method with Example

Java toRadians() method with Example

(Login to Rate)

1.6 Average Difficulty: 1.6/5.0 Based on 20 vote(s)



Add to TODO List
Mark as DONE

Basic Easy Medium Hard Expert

Writing code in comment? Please use ide.geeksforgeeks.org, generate link and share the link here.

Load Comments

Share this post!

A computer science portal for geeks

710-B, Advant Navis Business Park, Sector-142, Noida, Uttar Pradesh - 201305 feedback@geeksforgeeks.org

COMPANY

About Us
Careers
Privacy Policy
Contact Us

PRACTICE

Company-wise
Topic-wise
Contests
Subjective Questions

LEARN

Algorithms
Data Structures
Languages
CS Subjects
Video Tutorials

CONTRIBUTE

Write an Article
GBlog
Videos

@geeksforgeeks, Some rights reserved