

# Rajalakshmi Engineering College

Name: Nishanth R  
Email: 241801189@rajalakshmi.edu.in  
Roll no: 241801189  
Phone: 7358364486  
Branch: REC  
Department: AI & DS - Section 3  
Batch: 2028  
Degree: B.E - AI & DS

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### REC\_2028\_OOPS using Java\_Week 11

Attempt : 1  
Total Mark : 20  
Marks Obtained : 10

#### Section 1 : Project

##### 1. Problem Statement

In Café Central, the menu is cataloged and stored in a database.

To efficiently manage the restaurant's menu using Java and JDBC, you must build a Restaurant Management System that supports:

Adding new menu items

Updating menu item prices

Viewing details of a menu item

Displaying all menu items in sorted order

You are given two files:

File 1: MenuItem.java (POJO Class)

This class represents the MenuItem entity.

A MenuItem contains the following details:

Field	Description
itemId	Unique Menu Item ID (Integer)
name	Item Name (String)
category	Item Category (String)
price	Item Price (Double)

Students must write code in the marked area:

```
class MenuItem {  
    private int itemId;  
    private String name;  
    private String category;  
    private double price;  
  
    public MenuItem() {}  
  
    public MenuItem(int itemId, String name, String category, double price) {  
        // write your code here  
    }  
  
    // Include getters and setters  
}
```

Expected in this part:

Assign parameter values to instance variables inside the constructor.

Add getters and setters for all attributes.

File 2: MenuItemDAO.java (Data Access Layer)

This class handles all database operations using JDBC.

Students must complete the missing JDBC logic in the following methods:

```
class MenuItemDAO {

    public void addItem(Connection conn, MenuItem menuItem)
    throws SQLException {

        // write your code here

    }

    public void updateItemPrice(Connection conn, int itemId, double
    newPrice) throws SQLException {

        // write your code here

    }

    public void deleteMenuItem(Connection conn, int itemId) throws
    SQLException {

        // write your code here

    }

    public MenuItem viewItemDetails(Connection conn, int itemId) throws
    SQLException {

        // write your code here

    }

    public List<MenuItem> displayAllMenuItems(Connection conn) throws
    SQLException {

        // write your code here

    }

    private MenuItem mapToMenuItem(ResultSet rs) throws SQLException {
        return new MenuItem(
```

```
// write your code here  
);  
}  
}
```

Expected in this part:

Write SQL queries for INSERT, UPDATE, DELETE, SELECT.

Execute queries using PreparedStatement or Statement.

Map ResultSet rows to MenuItem objects using mapToMenuItem().

Return a List<MenuItem> where required.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri\_db

USER: test

PWD: test123

The menu table has already been created with the following structure:

Table Name: menu

### ***Input Format***

The first line of input consists of an integer choice, representing the operation to be performed (1 for Add Item, 2 for Restock item, 3 for reduce item, 4 for Display, 5 for Exit).

For choice 1 (Add Menu Item):

- The second line consists of an integer item\_id.
- The third line consists of a string name.
- The fourth line consists of a string category.
- The fifth line consists of a double price.

For choice 2 (Update Item Price):

- The second line consists of an integer item\_id.
- The third line consists of a double new\_price.

For choice 3 (View Item Details):

- The second line consists of an integer item\_id.

For choice 4 (Display All Menu Items):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

### ***Output Format***

For choice 1 (Add Menu Item):

- Print "Menu item added successfully" if the item was added.
- Print "Failed to add item." if the insertion failed.

For choice 2 (Update Item Price):

- Print "Item price updated successfully" if the price update was successful.
- Print "Item not found." if the specified item ID does not exist.

For choice 3 (View Item Details):

- Display the item details in the format:
- ID: [item\_id] | Name: [name] | Category: [category] | Price: [price]
- Print "Item not found." if the specified item ID does not exist.

For choice 4 (Display All Menu Items):

- Display each item on a new line in the format:
- ID | Name | Category | Price
- If no items are available, print nothing (or handle with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Restaurant Management System."

For invalid input:

- Print "Invalid choice. Please try again."

### **Sample Test Case**

Input: 1

11

Margherita Pizza

Main Course

12.99

4

5

Output: Menu item added successfully

ID | Name | Category | Price

11 | Margherita Pizza | Main Course | 12.99

Exiting Restaurant Management System.

### **Answer**

```
import java.sql.*;
```

```
import java.util.Scanner;
```

```
class RestaurantManagementSystem {
```

```
    public static void main(String[] args) {
```

```
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://localhost/ri_db", "test", "test123");
```

```
            Scanner scanner = new Scanner(System.in)) {
```

```
            boolean running = true;
```

```
            while (running) {
```

```
                int choice = scanner.nextInt();
```

```
                switch (choice) {
```

```
                    case 1:
```

```
                        addMenuItem(conn, scanner);
```

```
                        break;
```

```
                    case 2:
```

```
                        updateItemPrice(conn, scanner);
```

```
                        break;
```

```

        case 3:
            viewItemDetails(conn, scanner);
            break;
        case 4:
            displayAllMenuItems(conn);
            break;
        case 5:
            System.out.println("Exiting Restaurant Management System.");
            running = false;
            break;
        default:
            System.out.println("Invalid choice. Please try again.");
    }
}
} catch (SQLException e) {
    e.printStackTrace();
}
}
}

```

```

public static void addItem(Connection conn, Scanner scanner) throws
SQLException {

```

```

    int id = scanner.nextInt();
    scanner.nextLine();
    String name = scanner.nextLine();
    int quantity = scanner.nextInt();
    double price = scanner.nextDouble();

```

```

    String sql = "INSERT INTO items VALUES (?, ?, ?, ?)";
    PreparedStatement stmt = conn.prepareStatement(sql);
    stmt.setInt(1, id);
    stmt.setString(2, name);
    stmt.setInt(3, quantity);
    stmt.setDouble(4, price);

```

```

    int rows = stmt.executeUpdate();
    if (rows > 0)
        System.out.println("Item added successfully");
    else
        System.out.println("Failed to add item.");
}

```

```

public static void restockItem(Connection conn, Scanner scanner) throws
SQLException {

```

```

int id = scanner.nextInt();
int qtyAdd = scanner.nextInt();

String check = "SELECT quantity FROM items WHERE item_id = ?";
PreparedStatement ps = conn.prepareStatement(check);
ps.setInt(1, id);
ResultSet rs = ps.executeQuery();

if (!rs.next()) {
    System.out.println("Item not found.");
    return;
}

int newQty = rs.getInt(1) + qtyAdd;

String update = "UPDATE items SET quantity = ? WHERE item_id = ?";
PreparedStatement ps2 = conn.prepareStatement(update);
ps2.setInt(1, newQty);
ps2.setInt(2, id);
ps2.executeUpdate();

System.out.println("Item restocked successfully");
}

public static void reduceStock(Connection conn, Scanner scanner) throws
SQLException {
    int id = scanner.nextInt();
    int qtyRemove = scanner.nextInt();

    String check = "SELECT quantity FROM items WHERE item_id = ?";
    PreparedStatement ps = conn.prepareStatement(check);
    ps.setInt(1, id);
    ResultSet rs = ps.executeQuery();

    if (!rs.next()) {
        System.out.println("Item not found.");
        return;
    }

    int currentQty = rs.getInt(1);

    if (qtyRemove > currentQty) {

```



```
        System.out.println("Not enough stock to remove.");
        return;
    }
```

```
    int newQty = currentQty - qtyRemove;
```

```
    String update = "UPDATE items SET quantity = ? WHERE item_id = ?";
    PreparedStatement ps2 = conn.prepareStatement(update);
    ps2.setInt(1, newQty);
    ps2.setInt(2, id);
    ps2.executeUpdate();
```

```
    System.out.println("Stock reduced successfully");
}
```

```
public static void displayInventory(Connection conn) throws SQLException {
```

```
    System.out.println("ID | Name | Quantity | Price");
```

```
    String sql = "SELECT * FROM items ORDER BY item_id";
    PreparedStatement stmt = conn.prepareStatement(sql);
    ResultSet rs = stmt.executeQuery();
```

```
    while (rs.next()) {
        System.out.println(
            rs.getInt("item_id") + " | " +
            rs.getString("name") + " | " +
            rs.getInt("quantity") + " | " +
            String.format("%.2f", rs.getDouble("price"))
        );
    }
}
```

```
public static void addItem(Connection conn, Scanner scanner) {
    try {
        addItem(conn, scanner);
    } catch (SQLException e) {
        System.out.println("Failed to add item.");
    }
}
```

```
public static void updateItemPrice(Connection conn, Scanner scanner) {
```

```

    try {
        restockItem(conn, scanner);
    } catch (SQLException e) {
        System.out.println("Item not found.");
    }
}

public static void viewItemDetails(Connection conn, Scanner scanner) {
    try {
        reduceStock(conn, scanner);
    } catch (SQLException e) {
        System.out.println("Item not found.");
    }
}

public static void displayAllMenuItems(Connection conn) {
    try {
        displayInventory(conn);
    } catch (SQLException e) {
        System.out.println("Error displaying items.");
    }
}
}
//

```

**Status : Wrong**

**Marks : 0/10**

## 2. Problem Statement

Create a JDBC-based Inventory Management System that handles runtime input to manage items in an inventory. The system should allow users to:

Add a new item (item ID, name, quantity, price).

Restock an item by increasing its quantity.

Reduce the stock of an item, ensuring sufficient quantity.

Display all items in the inventory in a sorted order by item ID.

Exit the application.

Half of the code is given here; Only the remaining part should be completed.

The system should connect to a MySQL database using the following default credentials:

DB URL: jdbc:mysql://localhost/ri\_db

USER: test

PWD: test123

The items table has already been created with the following structure:

Table Name: items

### ***Input Format***

The first line of input consists of an integer choice, representing the operation to be performed (1 for Add Item, 2 for Restock item, 3 for reduce item, 4 for Display, 5 for Exit).

For choice 1 (Add Item):

- The second line consists of an integer item\_id.
- The third line consists of a string name.
- The fourth line consists of an integer quantity.
- The fifth line consists of a double price.

For choice 2 (Restock Item):

- The second line consists of an integer item\_id.
- The third line consists of an integer quantity\_to\_add (must be positive).

For choice 3 (Reduce Stock):

- The second line consists of an integer item\_id.
- The third line consists of an integer quantity\_to\_remove (must be positive).

For choice 4 (Display Inventory):

- No additional inputs are required.

For choice 5 (Exit):

- No additional inputs are required.

### ***Output Format***

For choice 1 (Add Item):

- Print "Item added successfully" if the item was added.
- Print "Failed to add item." if the insertion failed.

For choice 2 (Restock Item):

- Print "Item restocked successfully" if the restock was successful.
- Print "Item not found." if the specified item ID does not exist.

For choice 3 (Reduce Stock):

- Print "Stock reduced successfully" if the stock reduction was successful.
- Print "Not enough stock to remove." if there is insufficient quantity.
- Print "Item not found." if the specified item ID does not exist.

For choice 4 (Display Inventory):

- Display each item on a new line in the format:
  - ID | Name | Quantity | Price
- If no items are available, print nothing (or handle with an appropriate message if desired).

For choice 5 (Exit):

- Print "Exiting Inventory Management System."

For invalid input:

- Print "Invalid choice. Please try again."

### ***Sample Test Case***

Input: 1

101

Laptop

50

1200.00

4

5

Output: Item added successfully

ID | Name | Quantity | Price

101 | Laptop | 50 | 1200.00

Exiting Inventory Management System.

### **Answer**

```
import java.sql.*;
```

```
import java.util.Scanner;
```

```
class InventoryManagementSystem {
```

```
    public static void main(String[] args) {
```

```
        try (Connection conn = DriverManager.getConnection("jdbc:mysql://localhost/ri_db", "test", "test123"));
```

```
            Scanner scanner = new Scanner(System.in)) {
```

```
                boolean running = true;
```

```
                while (running) {
```

```
                    int choice = scanner.nextInt();
```

```
                    switch (choice) {
```

```
                        case 1:
```

```
                            addItem(conn, scanner);
```

```
                            break;
```

```
                        case 2:
```

```
                            restockItem(conn, scanner);
```

```
                            break;
```

```
                        case 3:
```

```
                            reduceStock(conn, scanner);
```

```
                            break;
```

```
                        case 4:
```

```
                            displayInventory(conn);
```

```
                            break;
```

```
                        case 5:
```

```

        System.out.println("Exiting Inventory Management System.");
        running = false;
        break;
    default:
        System.out.println("Invalid choice. Please try again.");
    }
}
} catch (SQLException e) {
    e.printStackTrace();
}
}

public static void addItem(Connection conn, Scanner scanner) throws
SQLException {
    int id = scanner.nextInt();
    scanner.nextLine();
    String name = scanner.nextLine();
    int quantity = scanner.nextInt();
    double price = scanner.nextDouble();

    String sql = "INSERT INTO items VALUES (?, ?, ?, ?)";
    PreparedStatement stmt = conn.prepareStatement(sql);
    stmt.setInt(1, id);
    stmt.setString(2, name);
    stmt.setInt(3, quantity);
    stmt.setDouble(4, price);

    int rows = stmt.executeUpdate();
    if (rows > 0)
        System.out.println("Item added successfully");
    else
        System.out.println("Failed to add item.");
}

public static void restockItem(Connection conn, Scanner scanner) throws
SQLException {
    int id = scanner.nextInt();
    int qtyAdd = scanner.nextInt();

    String check = "SELECT quantity FROM items WHERE item_id = ?";
    PreparedStatement ps = conn.prepareStatement(check);
    ps.setInt(1, id);
    ResultSet rs = ps.executeQuery();

```

```

        if (!rs.next()) {
            System.out.println("Item not found.");
            return;
        }

        int newQty = rs.getInt(1) + qtyAdd;

        String update = "UPDATE items SET quantity = ? WHERE item_id = ?";
        PreparedStatement ps2 = conn.prepareStatement(update);
        ps2.setInt(1, newQty);
        ps2.setInt(2, id);
        ps2.executeUpdate();

        System.out.println("Item restocked successfully");
    }

    public static void reduceStock(Connection conn, Scanner scanner) throws
    SQLException {
        int id = scanner.nextInt();
        int qtyRemove = scanner.nextInt();

        String check = "SELECT quantity FROM items WHERE item_id = ?";
        PreparedStatement ps = conn.prepareStatement(check);
        ps.setInt(1, id);
        ResultSet rs = ps.executeQuery();

        if (!rs.next()) {
            System.out.println("Item not found.");
            return;
        }

        int currentQty = rs.getInt(1);

        if (qtyRemove > currentQty) {
            System.out.println("Not enough stock to remove.");
            return;
        }

        int newQty = currentQty - qtyRemove;

        String update = "UPDATE items SET quantity = ? WHERE item_id = ?";

```

```

        PreparedStatement ps2 = conn.prepareStatement(update);
        ps2.setInt(1, newQty);
        ps2.setInt(2, id);
        ps2.executeUpdate();

        System.out.println("Stock reduced successfully");
    }

    public static void displayInventory(Connection conn) throws SQLException {

        System.out.println("ID | Name | Quantity | Price");

        String sql = "SELECT * FROM items ORDER BY item_id";
        PreparedStatement stmt = conn.prepareStatement(sql);
        ResultSet rs = stmt.executeQuery();

        while (rs.next()) {
            System.out.println(
                rs.getInt("item_id") + " | " +
                rs.getString("name") + " | " +
                rs.getInt("quantity") + " | " +
                String.format("%.2f", rs.getDouble("price"))
            );
        }
    }
}

```

**Status :** Correct

**Marks :** 10/10