


SMTP
POP3, IMAP
DNS
FTP
BitTorrent
Multimedia Streaming
DASH
CDN



*Computer Networking: A
Top-Down Approach*

8th edition

Jim Kurose, Keith Ross
Pearson, 2020

SMTP

Simple Mail Transfer Protocol


E-mail

Three major components:

- user agents
- mail servers
- simple mail transfer protocol: SMTP

User Agent

- a.k.a. “mail reader”
- composing, editing, reading mail messages
- e.g., Outlook, iPhone mail client
- outgoing, incoming messages stored on server




E-mail: mail servers

mail servers:

- *mailbox* contains incoming messages for user
- *message queue* of outgoing (to be sent) mail messages


SMTP protocol between mail servers to send email messages

- **client**: sending mail server
- **“server”**: receiving mail server




SMTP RFC (5321)

- uses TCP to reliably transfer email message from client (mail server initiating connection) to server, port 25
 - direct transfer: sending server (acting like client) to receiving server
- three phases of transfer
 - SMTP handshaking (greeting)
 - SMTP transfer of messages
 - SMTP closure
- command/response interaction (like HTTP)
 - **commands:** ASCII text
 - **response:** status code and phrase



Scenario: Alice sends e-mail to Bob

- 1) Alice uses UA to compose e-mail message "to" bob@some school.edu
- 2) Alice's UA sends message to her mail server using SMTP; message placed in message queue
- 3) client side of SMTP at mail server opens TCP connection with Bob's mail server
- 4) SMTP client sends Alice's message over the TCP connection
- 5) Bob's mail server places the message in Bob's mailbox
- 6) Bob invokes his user agent to read message



SMTP: observations

comparison with HTTP:

- HTTP: client pull
 - SMTP: client push
 - both have ASCII command/response interaction, status codes
 - HTTP: each object encapsulated in its own response message
 - SMTP: multiple objects sent in multipart message
- SMTP uses persistent connections
 - SMTP requires message (header & body) to be in 7-bit ASCII
 - SMTP server uses CRLF.CRLF to determine end of message

Mail message format

SMTP: protocol for exchanging e-mail messages, defined in RFC 5321 (like RFC 7231 defines HTTP)


RFC 2822 defines *syntax* for e-mail message itself (like HTML defines syntax for web documents)

- header lines, e.g.,

- To:
- From:
- Subject:

these lines, within the body of the email message area different from SMTP MAIL FROM:, RCPT TO: commands!


- Body: the “message”, ASCII characters only



Sample SMTP interaction

```
S: 220 hamburger.edu
C: HELO crepes.fr
S: 250 Hello crepes.fr, pleased to meet you
C: MAIL FROM: <alice@crepes.fr>
S: 250 alice@crepes.fr... Sender ok
C: RCPT TO: <bob@hamburger.edu>
S: 250 bob@hamburger.edu ... Recipient ok
C: DATA
S: 354 Enter mail, end with "." on a line by itself
C: Do you like ketchup?
C: How about pickles?
C: .
S: 250 Message accepted for delivery
C: QUIT
S: 221 hamburger.edu closing connection
```

Retrieving email: mail access protocols




- **SMTP**: delivery/storage of e-mail messages to receiver's server
- mail access protocol: retrieval from server
 - **IMAP**: Internet Mail Access Protocol [RFC 3501]: messages stored on server, IMAP provides retrieval, deletion, folders of stored messages on server
- **HTTP**: gmail, Hotmail, Yahoo!Mail, etc. provides web-based interface on top of SMTP (to send), IMAP (or POP) to retrieve e-mail messages

Threats to SMTP Security

- Unauthorized access to emails and data
- Spam and Phishing
- Malware
- DoS Attacks
- HOW TO MAKE SMPT SECURE?
 - SSL/TLS
 - End to end encryption
 - S/MIME
 - Pretty Good Privacy (PGP)
 - Bitmessage


FTP: the file transfer protocol



- ❖ transfer file to/from remote host
- ❖ client/server model
 - **client:** side that initiates transfer (either to/from remote)
 - **server:** remote host
- ❖ ftp: RFC 959
- ❖ ftp server: port 21

FTP: separate control, data connections


- FTP client contacts FTP server at port 21, using TCP
- client authorized over control connection
- client browses remote directory, sends commands over control connection
- when server receives file transfer command, *server* opens 2nd TCP data connection (for file) to client
- after transferring one file, server closes data connection



- ❖ server opens another TCP data connection to transfer another file
- ❖ control connection: *“out of band”*
- ❖ FTP server maintains “state”: current directory, earlier authentication

FTP: Control Connections

- Control Connection: Two steps
 - Server issues a passive open on the well-known port 21 and waits for a client
 - Client uses an ephemeral port and issues an active open




FTP: Data Connections

■ Data Connection: Three steps

- Client, not the server, issues a passive open using an ephemeral port.
- Client sends this port number to the server using the PORT command
- Server receives the port number and issues an active open using the well-known port 20 and received ephemeral port number.



a. Passive open by client



b. Sending ephemeral port number to server



c. Active open by server

DNS

Domain Name System

DNS: Domain Name System

people: many identifiers:

- SSN, name, passport #

Internet hosts, routers:

- IP address (32 bit) - used for addressing datagrams
- “name”, e.g., cs.umass.edu - used by humans

Q: how to map between IP address and name, and vice versa ?

Domain Name System (DNS):

- *distributed database* implemented in hierarchy of many *name servers*
- *application-layer protocol*: hosts, DNS servers communicate to *resolve* names (address/name translation)
 - *note*: core Internet function, implemented as application-layer protocol
 - complexity at network’s “edge”

DNS: services, structure

DNS services:

- hostname-to-IP-address translation
- host aliasing
 - canonical, alias names
- mail server aliasing
- load distribution
 - replicated Web servers: many IP addresses correspond to one name

Q: Why not centralize DNS?

- single point of failure
- traffic volume
- distant centralized database
- maintenance

A: doesn't scale!

- Comcast DNS servers alone: over 1.0T DNS queries/day
- Akamai DNS servers alone: 7.0T DNS queries/day

What is the fastest DNS in the world?

CloudFare

Thinking about the DNS

humongous distributed database:

- ~ billion records, each simple

handles many *trillions* of queries/day:

- *many* more reads than writes
- *performance matters*: almost every Internet transaction interacts with DNS - msec count!


organizationally, physically decentralized:

- millions of different organizations responsible for their records

“bulletproof”: reliability, security



DNS: a distributed, hierarchical database




Client wants IP address for `www.amazon.com`; 1st approximation:

- client queries root server to find `.com` DNS server
- client queries `.com` DNS server to get `amazon.com` DNS server
- client queries `amazon.com` DNS server to get IP address for `www.amazon.com`

DNS: root name servers


- official, contact-of-last-resort by name servers that can not resolve name



DNS: root name servers

- official, contact-of-last-resort by name servers that can not resolve name
- *incredibly important* Internet function
 - Internet couldn't function without it!
 - DNSSEC – provides security (authentication, message integrity)
- ICANN (Internet Corporation for Assigned Names and Numbers) manages root DNS domain


13 logical root name “servers”
worldwide each “server” replicated
many times (~200 servers in US)



Top-Level Domain, and authoritative servers

Top-Level Domain (TLD) servers:

- responsible for .com, .org, .net, .edu, .aero, .jobs, .museums, and all top-level country domains, e.g.: .cn, .uk, .fr, .ca, .jp
- Network Solutions: authoritative registry for .com, .net TLD
- Educause: .edu TLD



authoritative DNS servers:

- organization's own DNS server(s), providing authoritative hostname to IP mappings for organization's named hosts
- can be maintained by organization or service provider

Local DNS name servers


- when host makes DNS query, it is sent to its *local* DNS server
 - Local DNS server returns reply, answering:
 - from its local cache of recent name-to-address translation pairs (possibly out of date!)
 - forwarding request into DNS hierarchy for resolution
 - each ISP has local DNS name server; to find yours:
 - MacOS: `% scutil --dns`
 - Windows: `>ipconfig /all`
- local DNS server doesn't strictly belong to hierarchy

DNS name resolution: iterated query

Example: host at `engineering.nyu.edu` wants IP address for `gaia.cs.umass.edu`

Iterated query:

- contacted server replies with name of server to contact
- “I don’t know this name, but ask this server”




DNS name resolution: recursive query

Example: host at `engineering.nyu.edu` wants IP address for `gaia.cs.umass.edu`

Recursive query:

- puts burden of name resolution on contacted name server
- heavy load at upper levels of hierarchy?



Caching DNS Information

- once (any) name server learns mapping, it *cached* mapping, and *immediately* returns a cached mapping in response to a query
 - caching improves response time
 - cache entries timeout (disappear) after some time (TTL)
 - TLD servers typically cached in local name servers
- cached entries may be *out-of-date*
 - if named host changes IP address, may not be known Internet-wide until all TTLs expire!
 - *best-effort name-to-address translation!*

DNS records

DNS: distributed database storing resource records (RR)

RR format: (name, value, type, ttl)

type=A

- name is hostname
- value is IP address

type=NS

- name is domain (e.g., foo.com)
- value is hostname of authoritative name server for this domain

type=CNAME

- name is alias name for some “canonical” (the real) name
- www.ibm.com is really servereast.backup2.ibm.com
- value is canonical name

type=MX


- value is name of SMTP mail server associated with name

DNS protocol messages

DNS *query* and *reply* messages, both have same *format*:


message header:

- **identification**: 16 bit # for query, reply to query uses same #
- **flags**:
 - query or reply
 - recursion desired
 - recursion available
 - reply is authoritative



DNS protocol messages

DNS *query* and *reply* messages, both have same *format*:



Getting your info into the DNS

example: new startup “Network Utopia”

- register name networkutopia.com at *DNS registrar* (e.g., Network Solutions)
 - provide names, IP addresses of authoritative name server (primary and secondary)
 - registrar inserts NS, A RRs into .com TLD server:
`(networkutopia.com, dns1.networkutopia.com, NS)`
`(dns1.networkutopia.com, 212.212.212.1, A)`
- create authoritative server locally with IP address `212.212.212.1`
 - type A record for `www.networkutopia.com`
 - type MX record for `networkutopia.com`

DNS security

DDoS attacks

- bombard root servers with traffic
 - not successful to date
 - traffic filtering
 - local DNS servers cache IPs of TLD servers, allowing root server bypass
- bombard TLD servers
 - potentially more dangerous

Spoofing attacks

- intercept DNS queries, returning bogus replies
 - DNS cache poisoning
 - RFC 4033: DNSSEC authentication services


Bit Torrent

Peer to Peer File Distribution

File distribution: client-server vs P2P


Q: how much time to distribute file (size F) from one server to N peers?

- peer upload/download capacity is limited resource



File distribution time: client-server

- **server transmission:** must sequentially send (upload) N file copies:
 - time to send one copy: F/u_s
 - time to send N copies: NF/u_s
- **client:** each client must download file copy
 - d_{min} = min client download rate
 - min client download time: F/d_{min}




*time to distribute F
to N clients using
client-server approach*

$$D_{c-s} \geq \max\{NF/u_s, F/d_{min}\}$$

increases linearly in N

File distribution time: P2P

- **server transmission:** must upload at least one copy:
 - time to send one copy: F/u_s
- **client:** each client must download file copy
 - min client download time: F/d_{min}
- **clients:** as aggregate must download NF bits
 - max upload rate (limiting max download rate) is $u_s + \sum u_i$




time to distribute F
to N clients using
P2P approach

$$D_{P2P} \geq \max\{F/u_s, F/d_{min}, NF/(u_s + \sum u_i)\}$$

increases linearly in N ...
... but so does this, as each peer brings service capacity

Client-server vs. P2P: example

client upload rate = u , $F/u = 1$ hour, $u_s = 10u$, $d_{min} \geq u_s$




P2P file distribution: BitTorrent

- file divided into 256Kb chunks
- peers in torrent send/receive file chunks


tracker: tracks peers
participating in torrent

torrent: group of peers
exchanging chunks of a file



P2P file distribution: BitTorrent

- peer joining torrent:
 - has no chunks, but will accumulate them over time from other peers
 - registers with tracker to get list of peers, connects to subset of peers (“neighbors”)
- while downloading, peer uploads chunks to other peers
- peer may change peers with whom it exchanges chunks
- *churn*: peers may come and go
- once peer has entire file, it may (selfishly) leave or (altruistically) remain in torrent



BitTorrent: requesting, sending file chunks

Requesting chunks:


- at any given time, different peers have different subsets of file chunks
- periodically, Alice asks each peer for list of chunks that they have
- Alice requests missing chunks from peers, rarest first

Sending chunks: tit-for-tat

- Alice sends chunks to those four peers currently sending her chunks *at highest rate*
 - other peers are choked by Alice (do not receive chunks from her)
 - re-evaluate top 4 every 10 secs
- every 30 secs: randomly select another peer, starts sending chunks
 - “optimistically unchoke” this peer
 - newly chosen peer may join top 4

BitTorrent: tit-for-tat

- (1) Alice “optimistically unchokes” Bob
- (2) Alice becomes one of Bob’s top-four providers; Bob reciprocates
- (3) Bob becomes one of Alice’s top-four providers



Multimedia Streaming & Content Distribution Protocols

Video Streaming and CDNs: context


- stream video traffic: major consumer of Internet bandwidth
 - Netflix, YouTube, Amazon Prime: 80% of residential ISP traffic (2020)
- *challenge*: scale - how to reach ~1B users?
- *challenge*: heterogeneity
 - different users have different capabilities (e.g., wired versus mobile; bandwidth rich versus bandwidth poor)
- *solution*: distributed, application-level infrastructure



Multimedia: video

- video: sequence of images displayed at constant rate
 - e.g., 24 images/sec
- digital image: array of pixels
 - each pixel represented by bits
- coding: use redundancy *within* and *between* images to decrease # bits used to encode image
 - spatial (within image)
 - temporal (from one image to next)

spatial coding example: instead of sending N values of same color (all purple), send only two values: color value (*purple*) and number of repeated values (N)



frame i

temporal coding example: instead of sending complete frame at $i+1$, send only differences from frame i




frame $i+1$

Multimedia: video

- **CBR: (constant bit rate):** video encoding rate fixed
- **VBR: (variable bit rate):** video encoding rate changes as amount of spatial, temporal coding changes
- **examples:**
 - MPEG 1 (CD-ROM) 1.5 Mbps
 - MPEG2 (DVD) 3-6 Mbps
 - MPEG4 (often used in Internet, 64Kbps – 12 Mbps)

spatial coding example: instead of sending N values of same color (all purple), send only two values: color value (*purple*) and number of repeated values (N)



frame i


temporal coding example: instead of sending complete frame at $i+1$, send only differences from frame i



frame $i+1$

Streaming stored video


simple scenario:



Main challenges:


- server-to-client bandwidth will *vary* over time, with changing network congestion levels (in house, access network, network core, video server)
- packet loss, delay due to congestion will delay playout, or result in poor video quality

Streaming stored video




Streaming stored video: challenges

- **continuous playout constraint**: during client video playout, playout timing must match original timing
 - ... but **network delays are variable** (jitter), so will need **client-side buffer** to match continuous playout constraint
- other challenges:
 - client interactivity: pause, fast-forward, rewind, jump through video
 - video packets may be lost, retransmitted



Streaming stored video: playout buffering




- *client-side buffering and playout delay*: compensate for network-added delay, delay jitter

Streaming multimedia: DASH

*D*ynamic, *A*daptive
*S*treaming over *H*TTP

server:

- divides video file into multiple chunks
- each chunk encoded at multiple different rates
- different rate encodings stored in different files
- files replicated in various CDN nodes
- *manifest file*: provides URLs for different chunks




client:

- periodically estimates server-to-client bandwidth
- consulting manifest, requests one chunk at a time
 - chooses maximum coding rate sustainable given current bandwidth
 - can choose different coding rates at different points in time (depending on available bandwidth at time), and from different servers

Streaming multimedia: DASH

- “*intelligence*” at client: client determines
 - *when* to request chunk (so that buffer starvation, or overflow does not occur)
 - *what encoding rate* to request (higher quality when more bandwidth available)
 - *where* to request chunk (can request from URL server that is “close” to client or has high available bandwidth)



Streaming video = encoding + DASH + playout buffering

Content distribution networks (CDNs)

challenge: how to stream content (selected from millions of videos) to hundreds of thousands of *simultaneous* users?

- *option 1:* single, large “mega-server”
 - single point of failure
 - point of network congestion
 - long (and possibly congested) path to distant clients

....quite simply: this solution *doesn't scale*

Content distribution networks (CDNs)


challenge: how to stream content (selected from millions of videos) to hundreds of thousands of *simultaneous* users?

- *option 2:* store/serve multiple copies of videos at multiple geographically distributed sites (*CDN*)
 - *enter deep:* push CDN servers deep into many access networks
 - close to users
 - Akamai: 240,000 servers deployed in > 120 countries (2015)
 - *bring home:* smaller number (10's) of larger clusters in POPs near access nets
 - used by Limelight



Content distribution networks (CDNs)

- CDN: stores copies of content (e.g. MADMEN) at CDN nodes
- subscriber requests content, service provider returns manifest
 - using manifest, client retrieves content at highest supportable rate
 - may choose different rate or copy if network path congested



Content distribution networks (CDNs)



OTT challenges: coping with a congested Internet from the “edge”

- what content to place in which CDN node?
- from which CDN node to retrieve content? At which rate?

Summary

important topics:

- operation principles
- typical request/reply message exchange:
 - client requests info or service
 - server responds with data, status code
- message formats:
 - *headers*: fields giving info about data
 - *data*: info(payload) being communicated

important themes:

- centralized vs. decentralized
- stateless vs. stateful
- Scalability
- Security concerns
- reliable vs. unreliable message transfer
- “complexity at network edge”