

# Rajalakshmi Engineering College

Name: NISHANTH ELANGO RAJAN  
Email: 241901075@rajalakshmi.edu.in  
Roll no: 241901075  
Phone: 9444909050  
Branch: REC  
Department: I CSE (CS) FB  
Batch: 2028  
Degree: B.E - CSE (CS)

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 1\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

Janani is a tech enthusiast who loves working with polynomials. She wants to create a program that can add polynomial coefficients and provide the sum of their coefficients.

The polynomials will be represented as a linked list, where each node of the linked list contains a coefficient and an exponent. The polynomial is represented in the standard form with descending order of exponents.

##### *Input Format*

The first line of input consists of an integer  $n$ , representing the number of terms in the first polynomial.

The following  $n$  lines of input consist of two integers each: the coefficient and the exponent of the term in the first polynomial.

The next line of input consists of an integer m, representing the number of terms in the second polynomial.

The following m lines of input consist of two integers each: the coefficient and the exponent of the term in the second polynomial.

### **Output Format**

The output prints the sum of the coefficients of the polynomials.

### **Sample Test Case**

Input: 3

2 2

3 1

4 0

3

2 2

3 1

4 0

Output: 18

### **Answer**

```
#include <stdio.h>
```

```
#include <stdlib.h>
```

```
struct Node {  
    int coefficient;  
    int exponent;  
    struct Node *next;  
};
```

```
struct Node* createNode(int coefficient, int exponent) {  
    struct Node *newNode = (struct Node*) malloc(sizeof(struct Node));  
    newNode->coefficient = coefficient;  
    newNode->exponent = exponent;  
    newNode->next = NULL;  
    return newNode;  
}
```

```
int sumOfCoefficients(struct Node *poly1, struct Node *poly2) {  
    int sum = 0;
```

```
while (poly1 != NULL) {  
    sum += poly1->coefficient;  
    poly1 = poly1->next;  
}
```

```
while (poly2 != NULL) {  
    sum += poly2->coefficient;  
    poly2 = poly2->next;  
}
```

```
return sum;  
}
```

```
int main() {  
    int n, m;  
    scanf("%d", &n);  
    struct Node *poly1 = NULL, *tail1 = NULL;
```

```
    for (int i = 0; i < n; i++) {  
        int coeff, exp;  
        scanf("%d %d", &coeff, &exp);  
        struct Node *newNode = createNode(coeff, exp);  
        if (poly1 == NULL) {  
            poly1 = newNode;  
            tail1 = poly1;  
        } else {  
            tail1->next = newNode;  
            tail1 = newNode;  
        }  
    }  
}
```

```
    scanf("%d", &m);  
    struct Node *poly2 = NULL, *tail2 = NULL;
```

```
    for (int i = 0; i < m; i++) {  
        int coeff, exp;  
        scanf("%d %d", &coeff, &exp);  
        struct Node *newNode = createNode(coeff, exp);  
        if (poly2 == NULL) {  
            poly2 = newNode;  
            tail2 = poly2;  
        } else {  
            tail2->next = newNode;
```

```
        tail2 = newNode;
    }
}
int result = sumOfCoefficients(poly1, poly2);
printf("%d\n", result);

return 0;
}
```

**Status :** Correct

**Marks :** 10/10