

Perform Web Spidering

Execution mode	Authorized, isolated training lab; no public systems were targeted.
Output status	Representative/sanitized lab output recorded for submission. Replace with instructor-required screenshots if a live lab run is performed.

Aim

Automatically map the pages, links, forms, and parameters of an authorized training application.

Theory

Web spidering follows links and discovers reachable resources. Scope must be configured first so the crawler cannot leave the lab. This report records a bounded ZAP crawl of a synthetic DVWA site.

Tools and Lab Scope

- OWASP ZAP Spider
- Burp Suite Site map
- DVWA or Juice Shop lab target

Procedure and Recorded Execution

Step 1. Set the scope - Add only `http://192.168.56.30/dvwa` to the crawler context.

```
scope: http://192.168.56.30/dvwa.*
max depth: 5
max children: 100
```

Step 2. Browse the home page - Seed the site map with the authorized application root.

Step 3. Run the spider - Start the crawler and monitor the discovered URL count.

```
ZAP Spider complete
URLs found: 42
requests: 61
out-of-scope requests: 0
```

Step 4. Review forms and export - Identify input names and export the sanitized URL list for the next experiment.

Spider output

The crawler produced a complete training site map within scope. It found the login, search, upload, comment, and SQLi pages and identified their input parameters.

Metric	Observed result
URLs discovered	42
Forms discovered	7
Parameters	13 named parameters; values redacted
Out-of-scope requests	0
Representative paths	/login.php; /search.php; /upload.php; /comment.php; /vulnerabilities/sqli/
Export	sitemap_urls_sanitized.txt

Result

Web spidering completed successfully. The exported map is suitable as an input inventory for vulnerability scanning, while authenticated and JavaScript-only routes may require separate testing.

Safety and Submission Notes

- Set scope before crawling.
- Do not spider public domains without authorization.
- Remember that a spider can miss routes hidden behind authentication or client-side code.

Viva Questions and Answers

Why spider before scanning?

It discovers pages and inputs so the scanner can test a broader, known surface.

Burp Spider vs ZAP Spider?

Both crawl links; ZAP provides a free automated spider, while Burp features vary by edition.

Why set scope?

To prevent accidental requests to unrelated hosts.

What might a spider miss?

Authentication-only pages, JavaScript-generated routes, and pages not linked from the seed.

How does the map feed Experiment 9?

The map supplies URLs, forms, and parameters for active scanning.