IPC

SEREVR CODE

```
#include <sys/types.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <stdio.h>
#define SHMSZ 27
#include<stdlib.h>
int main()
{
char c;
int shmid,k;
int  key;
char *shm, *s;
printf("Your key is 5678");
key=5678;
if ((shmid = shmget(key, SHMSZ, IPC_CREAT | 0666)) < 0)
{
printf("error in shmget");
exit(0);
}
if ((shm = shmat(shmid, NULL, 0)) == (char *) -1)
{
printf("error in shmat");
exit(0);
}
s = shm;
printf("Enter value");
for(c='a';c<'z';c++)
{
*s=c;
*s++;
}
*s=NULL;
while (*shm != '*')
{
sleep(1);}
exit(0);
return 0;
}
```

CLIENT

```
#include <sys/types.h>
#include <sys/ipc.h>
#include <sys/shm.h>
#include <stdio.h>
```

```
#define SHMSZ 27
#include<stdlib.h>
main()
{
int shmid,k;
int key;
char *shm, *s;
printf("Enter Key to See Data");
scanf("%d",&key);
if ((shmid = shmget(key, SHMSZ, 0666)) < 0)
 {perror("shmget");
exit(1);
}
if ((shm = shmat(shmid, NULL, 0)) == (char *) -1)
{
perror("shmat");
exit(1);
}
for (s = shm; *s != NULL; s++)
putchar(*s);
putchar('\n');
*shm = '*';
exit(0);
}
```