

RDP_IP : 106.51.231.60
Username student
Password Cisco@12345

CCIE Data Center Lab Topology

Device Inventory, IP Addressing & Access Credentials Reference

This document consolidates all device access details for the CCIE Data Center examination lab topology spanning Data Center 1, Data Center 2, and Data Center 3. Devices are grouped by access category: GUI-managed platforms, physical switches, NDFC-managed lab devices, and the automation VM. Use this reference alongside the topology diagram for console, SSH, or browser-based access during lab exercises.

1. GUI-Based Devices

Device	IP Address	Username	Password
NDFC (Nexus Dashboard Fabric Controller)	10.1.1.220	admin	Cisco!123
vCenter	10.1.1.224	administrator@vsphere.local	Cisco!123
APIC	10.1.1.51	admin	Cisco!123
UCS	10.1.1.40	admin	Cisco!123

Access method: Web Browser (HTTPS)

2. Physical Switches

Device	IP Address	Username	Password
N5K-3	10.1.1.63	admin	Cisco!123
N5K-4	10.1.1.64	admin	Cisco!123
DC2-N7K-SW1	10.1.1.63	admin	Cisco!123
DC2-N7K-SW2	10.1.1.64	admin	Cisco!123

Note: IP addresses for N5K-3/N5K-4 and DC2-N7K-SW1/SW2 were provided identically in the source list (10.1.1.63 / 10.1.1.64). Please verify against the physical topology labels (N5K-3, N5K-4) before connecting, as this may indicate an overlap with the NDFC lab device range below.

3. NDFC Lab Devices (Data Center 1, 2 & 3)

Device	IP Address	Username	Password
DC1-N5K-1	10.1.1.61	admin	Cisco!123
DC1-N5K-2	10.1.1.62	admin	Cisco!123
DC1-N7K-1	10.1.1.71	admin	Cisco!123
DC1-N7K-2	10.1.1.72	admin	Cisco!123

Device	IP Address	Username	Password
DC1-N9K-BGW1	10.1.1.91	admin	Cisco!123
DC1-N9K-BGW2	10.1.1.92	admin	Cisco!123
DC2-N7K-IPN	10.1.1.82	admin	Cisco!123
DC2-N7K-1	10.1.1.81	admin	Cisco!123
DC2-N9K-1	10.1.1.93	admin	Cisco!123
DC2-N9K-2	10.1.1.94	admin	Cisco!123

Credentials are common across all NDFC-managed lab devices listed above.

4. Automation VM

Device	IP Address	Username	Password
automation-VM (Linux)	10.1.1.114	See MobaXterm / MPuTTY	Saved in session

Credentials for the automation-VM are pre-saved as a session profile under MobaXterm / MPuTTY on the Candidate RDP machine.

Device Access Notes

How to Reach Each Category of Device

General Access Method

The credentials and IP addresses listed in this document correspond to the complete CCIE Data Center examination lab topology (Data Center 1, Data Center 2, and Data Center 3). Access to each device depends on its category, as outlined below.

Category	Access Method
GUI-based devices (NDFC, vCenter, APIC, UCS)	Accessed directly through a web browser using the HTTPS URL / IP address and the credentials listed in Section 1.
Physical switches	Accessed via CLI using Mputty / MobaXterm, available on the Desktop of the Candidate RDP machine.
NDFC Lab Devices (N5K, N7K, N9K, BGW, IPN)	Accessed via CLI using Mputty / MobaXterm on the Candidate RDP machine. All devices in this category share the same admin credentials.
automation-VM (Linux)	Accessed via CLI using Mputty / MobaXterm. Credentials are pre-saved as a session profile on the Candidate RDP machine — no manual credential entry required.

Summary (as provided)

GUI based devices are accessed through a browser. Physical switches, all NDFC lab devices, and the automation-VM are accessed via CLI tools (Mputty / MobaXterm) available on the Desktop of the Candidate RDP machine, with credentials for the automation-VM already saved in the session profile.

Reference document generated from CCIE DC lab topology diagram and device access notes. Verify IP addresses and credentials on-site before the examination, as lab environments may be refreshed between sessions.

Below is the NDFC topology.

