ChatGPT

Get Plus ×

Share

Write a beginner-friendly C++ console program that generates funny roast messages that
ask the user to enter their name, Store at least 10 roast templates , Each template should contain a placeholder , Randomly select one roast each time the program runs, Replace {name} with the user's input before printing, Make sure different roast appears on different runs,Handle empty input (if user enters nothing, print "Invalid input"), Add clear comments so a beginner can understand the code

Here's a clean, beginner-friendly C++ console program that meets all your requirements 👇

✅ **Features covered:**

- Takes user name input
- Stores 10+ roast templates with `{name}` placeholder
- Randomly selects a roast each run

AI_Roast_Generaor.cpp

AI_Roast_Generaor.cpp > main()

```cpp
#include <iostream>
#include <vector>
#include <string>
#include <cstdlib>

using namespace std;

int main() {
    string name;

    cout << "Enter your name: ";
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
Asus@DESKTOP-AHJE1JQ MINGW64 /d/Nishchay's folder/FOCP-II - Assignments
$ g++ "AI_Roast_Generaor.cpp" -o "AI_Roast_Generaor" && ./AI_Roast_Generaor

Roast:
If procrastination were an Olympic sport, Nishchay would have gold.

Asus@DESKTOP-AHJE1JQ MINGW64 /d/Nishchay's folder/FOCP-II - Assignments
$ g++ "AI_Roast_Generaor.cpp" -o "AI_Roast_Generaor" && ./AI_Roast_Generaor
Enter your name: Nishchay

Roast:
If procrastination were an Olympic sport, Nishchay would have gold.

Asus@DESKTOP-AHJE1JQ MINGW64 /d/Nishchay's folder/FOCP-II - Assignments
$ g++ "AI_Roast_Generaor.cpp" -o "AI_Roast_Generaor" && ./AI_Roast_Generaor
Enter your name: Nishchay

Roast:
If procrastination were an Olympic sport, Nishchay would have gold.

Asus@DESKTOP-AHJE1JQ MINGW64 /d/Nishchay's folder/FOCP-II - Assignments
$
```

Ln 49, Col 2 Spaces: 4 UTF-8 CRLF { } C++ Signed out Win32

ChatGPT

Get Plus ×

Share

this code is giving the same output every time I run it.
I am using rand() to select random roasts, but it is not changing.
Can you fix this issue and explain why it is happening?

Yeah, this is a classic beginner issue with `rand()` — and your code is *almost* correct. The problem isn't what you wrote, it's **how `srand(time(0))` behaves in fast runs.**

🚨 Why you're getting the same output

You used:

```cpp
srand(time(0));
```

👉 `time(0)` returns the current time **in seconds**

AI_Roast_Generaor.cpp

AI_Roast_Generaor.cpp > main()

```cpp
#include <iostream>
#include <vector>
#include <string>
#include <cstdlib>
#include <ctime>

using namespace std;

int main() {
    string name;
```

PROBLEMS OUTPUT DEBUG CONSOLE TERMINAL PORTS

```
Asus@DESKTOP-AHJE1JQ MINGW64 /d/Nishchay's folder/FOCP-II - Assignments
$ g++ "AI_Roast_Generaor.cpp" -o "AI_Roast_Generaor" && ./AI_Roast_Generaor
Enter your name: Nishchay

≡fòÑ Roast:
If procrastination were an Olympic sport, Nishchay would have gold.

Asus@DESKTOP-AHJE1JQ MINGW64 /d/Nishchay's folder/FOCP-II - Assignments
$ g++ "AI_Roast_Generaor.cpp" -o "AI_Roast_Generaor" && ./AI_Roast_Generaor
Enter your name: Nishchay

≡fòÑ Roast:
Nishchay writes code so slow that even a turtle switched to Python.

Asus@DESKTOP-AHJE1JQ MINGW64 /d/Nishchay's folder/FOCP-II - Assignments
$
```

Ln 53, Col 2 Spaces: 4 UTF-8 CRLF { } C++ Signed out Win32