

Task 1: Check SELinux Status

Check current mode

- `getenforce`

Get detailed status

- `sestatus`

Task 2: Change to Permissive Mode

Check current mode:

- `getenforce`

Switch to permissive mode:

- `setenforce 0`

Verify:

- `getenforce`

Create a file

- `touch /var/www/html/testfile.html`

Check:

- `ls -l /var/www/html`

Return to Enforcing Mode

- `setenforce 1`

Verify:

- `getenforce`

Task 3: Display and Change SELinux Context

Display contexts:

- `ls -Z /var/www/html`

Change the context of a file:

- `chcon -t httpd_sys_content_t /var/www/html/testfile.html`

Verify:

- `ls -Z /var/www/html/testfile.html`

Task 4: Analyze SELinux Denials

Check recent SELinux denials:

- `tail -20 /var/log/audit/audit.log`

Analyze using audit2why:

- `grep AVC /var/log/audit/audit.log | audit2why`

Generate an SELinux policy suggestion:

- `grep AVC /var/log/audit/audit.log | audit2allow`

Fix for Upload Folder

Create upload directory:

- `mkdir -p /srv/foodie/images`

Assign the correct SELinux context:

- `chcon -R -t httpd_sys_rw_content_t /srv/foodie/images`

Verify:

- `ls -Zd /srv/foodie/images`