

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh

; <<> Dig 9.10.6 <<> app.teamX.test
; global options: +cmd
; Got answer:
; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 3185
; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

; OPT PSEUDOSECTION:
; EDNS: version: 0, flags: udp: 1232
; QUESTION SECTION:
; app.teamX.test.                IN      A

; ANSWER SECTION:
app.teamX.test.                0      IN      A      10.7.28.24

; Query time: 67 msec
; SERVER: 10.7.30.18953(10.7.30.18)
; WHEN: Tue Sep 29 18:36:54 IST 2026
; MSG SIZE rcvd: 59

nishthagupta@Nishthas-MacBook-Pro ~ % curl -v https://app.teamX.test/api/status
* Host app.teamX.test:443 was resolved.
* IPvi6: (none)
* IPv4: 10.7.28.24
* Trying 10.7.28.24:443...
* Connected to app.teamX.test (10.7.28.24) port 443
* ALPN: curl offers h2,http/1.1
* (304) (OUT), TLS handshake, Client hello (1):
* CAfile: /etc/ssl/cert.pem
* CApath: none
* (304) (IN), TLS handshake, Server hello (2):
* (304) (IN), TLS handshake, Unknown (8):
* (304) (IN), TLS handshake, Certificate (11):
* (304) (IN), TLS handshake, CERT verify (15):
* (304) (IN), TLS handshake, Finished (20):
* (304) (OUT), TLS handshake, Finished (20):
* SSL connection using TLSv1.3 / AEAD-CHACHA20-POLY1305-SHA256 / [blank] / UNDEF
* ALPN: server accepted http/1.1
* Server certificate:
* subject: CN=app.teamX.test
* start date: Sep 29 11:28:26 2026 GMT
* expire date: Sep 29 11:28:26 2027 GMT
* subjectAltName: host "app.teamX.test" matched cert's "app.teamX.test"
* issuer: CN=app.teamX.test
* SSL certificate verify ok.
* using HTTP/1.x
> GET /api/status HTTP/1.1
> Host: app.teamX.test
> User-Agent: curl/8.7.1
> Accept: */*
>
* Request completely sent off
< HTTP/1.1 200 OK
< Server: nginx/1.31.6
< Date: Tue, 29 Sep 2026 13:07:18 GMT
< Content-Type: application/json; charset=utf-8
< Content-Length: 29
< Connection: keep-alive
< X-Powered-By: Express
< X-Backend: A
< Cache-Control: max-age=60
< ETag: W/"1d-mMMZex8nVIDi44lSuobi0vFg/M"
< X-Edge: mac2
<
* Connection #0 to host app.teamX.test left intact
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh

>
* Request completely sent off
< HTTP/1.1 200 OK
< Server: nginx/1.31.6
< Date: Tue, 29 Sep 2026 13:07:18 GMT
< Content-Type: application/json; charset=utf-8
< Content-Length: 29
< Connection: keep-alive
< X-Powered-By: Express
< X-Backend: A
< Cache-Control: max-age=60
< ETag: W/"1d-mMMZex8nVIDi44lSuobi0vFg/M"
< X-Edge: mac2
<
* Connection #0 to host app.teamX.test left intact
{"backend":"A","status":"ok"}
nishthagupta@Nishthas-MacBook-Pro ~ % for i in {1..10}; do
echo "REQUEST $i"
curl -s https://app.teamX.test/api/status
echo
done
REQUEST 1 {"backend":"A","status":"ok"}
REQUEST 2 {"backend":"A","status":"ok"}
REQUEST 3 {"backend":"A","status":"ok"}
REQUEST 4 {"backend":"A","status":"ok"}
REQUEST 5 {"backend":"A","status":"ok"}
REQUEST 6 {"backend":"A","status":"ok"}
REQUEST 7 {"backend":"A","status":"ok"}
REQUEST 8 {"backend":"A","status":"ok"}
REQUEST 9 {"backend":"A","status":"ok"}
REQUEST 10 {"backend":"A","status":"ok"}
nishthagupta@Nishthas-MacBook-Pro ~ % for i in {1..10}; do
echo -n "REQUEST $i: "
curl -s --no-keepalive https://app.teamX.test/api/status
echo
done
REQUEST 1: {"backend":"A","status":"ok"}
REQUEST 2: {"backend":"A","status":"ok"}
REQUEST 3: {"backend":"A","status":"ok"}
REQUEST 4: {"backend":"A","status":"ok"}
REQUEST 5: {"backend":"A","status":"ok"}
REQUEST 6: {"backend":"A","status":"ok"}
REQUEST 7: {"backend":"A","status":"ok"}
REQUEST 8: {"backend":"A","status":"ok"}
REQUEST 9: {"backend":"A","status":"ok"}
REQUEST 10: {"backend":"A","status":"ok"}
nishthagupta@Nishthas-MacBook-Pro ~ % curl -s https://app.teamX.test/api/status
{"backend":"A","status":"ok"}
nishthagupta@Nishthas-MacBook-Pro ~ % dig app.teamX.test

; <<> Dig 9.10.6 <<> app.teamX.test
; global options: +cmd
; Got answer:
; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 61988
; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                +

nishthagupta@Nishthas-MacBook-Pro ~ % for i in {1..10}; do
echo -n "REQUEST $i: "
curl -s --no-keepalive https://app.teamX.test/api/status
echo
done
REQUEST 1: {"backend":"A","status":"ok"}
REQUEST 2: {"backend":"A","status":"ok"}
REQUEST 3: {"backend":"A","status":"ok"}
REQUEST 4: {"backend":"A","status":"ok"}
REQUEST 5: {"backend":"A","status":"ok"}
REQUEST 6: {"backend":"A","status":"ok"}
REQUEST 7: {"backend":"A","status":"ok"}
REQUEST 8: {"backend":"A","status":"ok"}
REQUEST 9: {"backend":"A","status":"ok"}
REQUEST 10: {"backend":"A","status":"ok"}
nishthagupta@Nishthas-MacBook-Pro ~ % curl -s https://app.teamX.test/api/status
nishthagupta@Nishthas-MacBook-Pro ~ % dig app.teamX.test

<> DId 9.10.6 <> app.teamX.test
;; global options: +cmd
;; Got answer:
;; ->HEADER<- opcode: QUERY, status: NOERROR, id: 61980
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags: udp: 1232
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; ANSWER SECTION:
app.teamX.test.                0      IN      A      10.7.28.24

;; Query time: 117 msec
;; SERVER: 10.7.38.18#53(10.7.38.18)
;; WHEN: Tue Sep 29 18:52:17 IST 2026
;; MSG SIZE rcvd: 59

nishthagupta@Nishthas-MacBook-Pro ~ % curl -v --no-keepalive https://app.teamX.test/api/status
* Host app.teamX.test:443 was resolved.
* IPv6: (none)
* IPV4: 10.7.28.24
* Trying 10.7.28.24:443...
* Connected to app.teamX.test (10.7.28.24) port 443
* ALPN: curl offers h2,http/1.1
* (304) (GUT), TLS handshake, Client hello (1):
* CAfile: /etc/ssl/cert.pem
* CApath: none
* (304) (IN), TLS handshake, Server hello (2):
* (304) (IN), TLS handshake, Unknown (8):
* (304) (IN), TLS handshake, Certificate (11):
* (304) (IN), TLS handshake, CERT verify (15):
* (304) (IN), TLS handshake, Finished (20):
* (304) (GUT), TLS handshake, Finished (20):
* SSL connection using TLSv1.3 / AEAD-CHACHA20-POLY1305-SHA256 / [blank] / UNDEF
* ALPN: server accepted http/1.1
* Server certificate:
* subject: CN=app.teamX.test
* start date: Sep 29 11:28:26 2026 GMT
* expire date: Sep 29 11:28:26 2027 GMT
* subjectAltName: host "app.teamX.test" matched cert's "app.teamX.test"
* issuer: CN=app.teamX.test
* SSL certificate verify ok.
* using HTTP/1.x
> GET /api/status HTTP/1.1
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                +

nishthagupta@Nishthas-MacBook-Pro ~ % curl -v --no-keepalive https://app.teamX.test/api/status
* Host app.teamX.test:443 was resolved.
* IPv6: (none)
* IPV4: 10.7.28.24
* Trying 10.7.28.24:443...
* Connected to app.teamX.test (10.7.28.24) port 443
* ALPN: curl offers h2,http/1.1
* (304) (GUT), TLS handshake, Client hello (1):
* CAfile: /etc/ssl/cert.pem
* CApath: none
* (304) (IN), TLS handshake, Server hello (2):
* (304) (IN), TLS handshake, Unknown (8):
* (304) (IN), TLS handshake, Certificate (11):
* (304) (IN), TLS handshake, CERT verify (15):
* (304) (IN), TLS handshake, Finished (20):
* (304) (GUT), TLS handshake, Finished (20):
* SSL connection using TLSv1.3 / AEAD-CHACHA20-POLY1305-SHA256 / [blank] / UNDEF
* ALPN: server accepted http/1.1
* Server certificate:
* subject: CN=app.teamX.test
* start date: Sep 29 11:28:26 2026 GMT
* expire date: Sep 29 11:28:26 2027 GMT
* subjectAltName: host "app.teamX.test" matched cert's "app.teamX.test"
* issuer: CN=app.teamX.test
* SSL certificate verify ok.
* using HTTP/1.x
> GET /api/status HTTP/1.1
Host: app.teamX.test
User-Agent: curl/8.7.1
Accept: */*

* Request completely sent off
< HTTP/1.1 200 OK
< Server: nginx/1.31.6
< Date: Tue, 29 Sep 2026 13:22:40 GMT
< Content-Type: application/json; charset=utf-8
< Content-Length: 29
< Connection: keep-alive
< X-Powered-By: Express
< X-Backend: A
< Cache-Control: max-age=60
< ETag: W/"1d-/mMMZex8nvIDi44lSUobi8vFg/M"
< X-Edge: mac2
<
* Connection #0 to host app.teamX.test left intact
{"backend":"A","status":"ok"}
nishthagupta@Nishthas-MacBook-Pro ~ % curl -sI https://app.teamX.test/api/status
HTTP/1.1 200 OK
Server: nginx/1.31.6
Date: Tue, 29 Sep 2026 13:29:05 GMT
Content-Type: application/json; charset=utf-8
Content-Length: 29
Connection: keep-alive
X-Powered-By: Express
X-Backend: A
Cache-Control: max-age=60
ETag: W/"1d-/mMMZex8nvIDi44lSUobi8vFg/M"
X-Edge: mac2

{"backend":"A","status":"ok"}
nishthagupta@Nishthas-MacBook-Pro ~ % curl -sI -H 'If-None-Match: W/"1d-/mMMZex8nvIDi44lSUobi8vFg/M"' https://app.teamX.test/api/status
HTTP/1.1 304 Not Modified
Server: nginx/1.31.6
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                +

X-Edge: mac2

[{"backend":"A","status":"ok"}]
nishthagupta@Nishthas-MacBook-Pro ~ % curl -sI -H 'If-None-Match: W/"1d-/mMZX8nvIDi44ISUobi0vFg/M"' https://app.teamX.test/api/status
HTTP/1.1 200 OK
Server: nginx/1.31.6
Date: Tue, 29 Sep 2020 13:29:35 GMT
Connection: keep-alive
X-Powered-By: Express
X-Backend: A
Cache-Control: max-age=60
ETag: W/"1d-/mMZX8nvIDi44ISUobi0vFg/M"
X-Edge: mac2

[nishthagupta@Nishthas-MacBook-Pro ~ % curl -sI http://localhost:3001/api/status
HTTP/1.1 200 OK
X-Powered-By: Express
X-Backend: A
Cache-Control: max-age=60
Content-Type: application/json; charset=utf-8
Content-Length: 29
ETag: W/"1d-/mMZX8nvIDi44ISUobi0vFg/M"
Date: Tue, 29 Sep 2020 16:13:46 GMT
Connection: keep-alive
Keep-Alive: timeout=5

[{"backend":"A","status":"ok"}]
nishthagupta@Nishthas-MacBook-Pro ~ % dig @8.8.8.8 app.teamX.test

;<<> Dig 9.10.6 <<> @8.8.8.8 app.teamX.test
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NXDOMAIN, id: 30206
;; flags: qr rd ra ad; QUERY: 1, ANSWER: 0, AUTHORITY: 1, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 512
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; AUTHORITY SECTION:
.                86384   IN      SOA      a.root-servers.net. nstld.verisign-grs.com. 2020092900 1800 900 604800 86400

;; Query time: 10 msec
;; SERVER: 8.8.8.8#53(8.8.8.8)
;; WHEN: Tue Sep 29 21:44:31 IST 2020
;; MSG SIZE rcvd: 118

nishthagupta@Nishthas-MacBook-Pro ~ % dig @10.7.30.18 app.teamX.test

;<<> Dig 9.10.6 <<> @10.7.30.18 app.teamX.test
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 42937
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; ANSWER SECTION:
app.teamX.test.                0       IN      A        10.7.28.24

;; Query time: 11 msec
;; SERVER: 10.7.30.18#53(10.7.30.18)
;; WHEN: Tue Sep 29 21:45:50 IST 2020
;; MSG SIZE rcvd: 59

nishthagupta@Nishthas-MacBook-Pro ~ % dig @10.7.30.18 app.teamX.test

;<<> Dig 9.10.6 <<> @10.7.30.18 app.teamX.test
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 36820
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; ANSWER SECTION:
app.teamX.test.                0       IN      A        10.7.28.24

;; Query time: 8 msec
;; SERVER: 10.7.30.18#53(10.7.30.18)
;; WHEN: Tue Sep 29 21:50:13 IST 2020
;; MSG SIZE rcvd: 59

nishthagupta@Nishthas-MacBook-Pro ~ % dig @10.7.30.18 app.teamX.test

;<<> Dig 9.10.6 <<> @10.7.30.18 app.teamX.test
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 8739
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; ANSWER SECTION:
app.teamX.test.                0       IN      A        10.7.9.8

;; Query time: 26 msec
;; SERVER: 10.7.30.18#53(10.7.30.18)
;; WHEN: Tue Sep 29 21:55:04 IST 2020
;; MSG SIZE rcvd: 59

nishthagupta@Nishthas-MacBook-Pro ~ % nc -vz 10.7.9.8 3001
Connection to 10.7.9.8 port 3001 [tcp/redwood-broker] succeeded!
nishthagupta@Nishthas-MacBook-Pro ~ % nc -vz 10.7.9.8 3999
nc: connectx to 10.7.9.8 port 3999 (tcp) failed: Connection refused
nishthagupta@Nishthas-MacBook-Pro ~ %
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                +

;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; ANSWER SECTION:
app.teamX.test.                0       IN      A        10.7.28.24

;; Query time: 11 msec
;; SERVER: 10.7.30.18#53(10.7.30.18)
;; WHEN: Tue Sep 29 21:45:50 IST 2020
;; MSG SIZE rcvd: 59

nishthagupta@Nishthas-MacBook-Pro ~ % dig @10.7.30.18 app.teamX.test

;<<> Dig 9.10.6 <<> @10.7.30.18 app.teamX.test
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 36820
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; ANSWER SECTION:
app.teamX.test.                0       IN      A        10.7.28.24

;; Query time: 8 msec
;; SERVER: 10.7.30.18#53(10.7.30.18)
;; WHEN: Tue Sep 29 21:50:13 IST 2020
;; MSG SIZE rcvd: 59

nishthagupta@Nishthas-MacBook-Pro ~ % dig @10.7.30.18 app.teamX.test

;<<> Dig 9.10.6 <<> @10.7.30.18 app.teamX.test
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 8739
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; ANSWER SECTION:
app.teamX.test.                0       IN      A        10.7.9.8

;; Query time: 26 msec
;; SERVER: 10.7.30.18#53(10.7.30.18)
;; WHEN: Tue Sep 29 21:55:04 IST 2020
;; MSG SIZE rcvd: 59

nishthagupta@Nishthas-MacBook-Pro ~ % nc -vz 10.7.9.8 3001
Connection to 10.7.9.8 port 3001 [tcp/redwood-broker] succeeded!
nishthagupta@Nishthas-MacBook-Pro ~ % nc -vz 10.7.9.8 3999
nc: connectx to 10.7.9.8 port 3999 (tcp) failed: Connection refused
nishthagupta@Nishthas-MacBook-Pro ~ %
```

```
-- -zsh                                ~/desktop/CN_PROJECT/backend-A -- -zsh                                ~/desktop/CN_PROJECT/backend-A -- -zsh                                +

flags      : Request A records
reach      : 0x00020002 (Reachable,Directly Reachable Address)

resolver #2
domain     : local
options    : mdns
timeout    : 5
flags      : Request A records
reach      : 0x00000000 (Not Reachable)
order      : 300000

resolver #3
domain     : 254.169.in-addr.arpa
options    : mdns
timeout    : 5
flags      : Request A records
reach      : 0x00000000 (Not Reachable)
order      : 300200

resolver #4
domain     : 8.e.f.ip6.arpa
options    : mdns
timeout    : 5
flags      : Request A records
reach      : 0x00000000 (Not Reachable)
order      : 300400

resolver #5
domain     : 9.e.f.ip6.arpa
options    : mdns
timeout    : 5
flags      : Request A records
reach      : 0x00000000 (Not Reachable)
order      : 300600

resolver #6
domain     : a.e.f.ip6.arpa
options    : mdns
timeout    : 5
flags      : Request A records
reach      : 0x00000000 (Not Reachable)
order      : 300800

resolver #7
domain     : b.e.f.ip6.arpa
options    : mdns
timeout    : 5
flags      : Request A records
reach      : 0x00000000 (Not Reachable)
order      : 301000

DNS configuration (for scoped queries)

resolver #1
nameserver[0] : 10.7.30.18
if_index      : 11 (en0)
flags         : Scoped, Request A records
reach         : 0x00020002 (Reachable,Directly Reachable Address)
nishthagupta@Nishthas-MacBook-Pro ~ % dscacheutil -q host -a name app.teamX.test
nishthagupta@Nishthas-MacBook-Pro ~ % curl --interface en0 -v https://app.teamX.test/api/status
* Could not resolve host: app.teamX.test
* Closing connection
curl: (6) Could not resolve host: app.teamX.test
nishthagupta@Nishthas-MacBook-Pro ~ % sudo killall -INFO mDNSResponder
```

```
-- -zsh                                ~/desktop/CN_PROJECT/backend-A -- -zsh                                ~/desktop/CN_PROJECT/backend-A -- -zsh                                +

if_index : 11 (en0)
flags     : Scoped, Request A records
reach     : 0x00020002 (Reachable,Directly Reachable Address)
nishthagupta@Nishthas-MacBook-Pro ~ % dscacheutil -q host -a name app.teamX.test
nishthagupta@Nishthas-MacBook-Pro ~ % curl --interface en0 -v https://app.teamX.test/api/status
* Could not resolve host: app.teamX.test
* Closing connection
curl: (6) Could not resolve host: app.teamX.test
nishthagupta@Nishthas-MacBook-Pro ~ % sudo killall -INFO mDNSResponder
Password:
nishthagupta@Nishthas-MacBook-Pro ~ % log show --last 1m --predicate 'process == "mDNSResponder"' --info | grep -i "teamX\[10.7.30.18" | tail -30
nishthagupta@Nishthas-MacBook-Pro ~ % nslookup app.teamX.test 10.7.30.18
;; connection timed out; no servers could be reached

nishthagupta@Nishthas-MacBook-Pro ~ % nslookup app.teamX.test 10.7.30.18
Server:      10.7.30.18
Address:     10.7.30.18#53

Name:   app.teamX.test
Address: 10.7.28.24

nishthagupta@Nishthas-MacBook-Pro ~ % curl -v https://app.teamX.test/api/status
* Could not resolve host: app.teamX.test
* Closing connection
curl: (6) Could not resolve host: app.teamX.test
nishthagupta@Nishthas-MacBook-Pro ~ % for i in {1..10}; do
echo "TEST $i"
dig @10.7.30.18 app.teamX.test +short
sleep 1
done
TEST 1
10.7.28.24
TEST 2
10.7.28.24
TEST 3
10.7.28.24
TEST 4
10.7.28.24
TEST 5
10.7.28.24
TEST 6
10.7.28.24
TEST 7
10.7.28.24
TEST 8
10.7.28.24
TEST 9
10.7.28.24
TEST 10
10.7.28.24
nishthagupta@Nishthas-MacBook-Pro ~ % dscacheutil -q host -a name app.teamX.test
nishthagupta@Nishthas-MacBook-Pro ~ % ping -c 1 app.teamX.test
ping: cannot resolve app.teamX.test: Unknown host
nishthagupta@Nishthas-MacBook-Pro ~ % curl -v --resolve app.teamX.test:443:10.7.28.24 https://app.teamX.test/api/status
* Added app.teamX.test:443:10.7.28.24 to DNS cache
* Hostname app.teamX.test was found in DNS cache
* Trying 10.7.28.24:443...
* connect to 10.7.28.24 port 443 from 10.7.9.8 port 68668 failed: Operation timed out
* Failed to connect to app.teamX.test port 443 after 75005 ms: Couldn't connect to server
* Closing connection
curl: (28) Failed to connect to app.teamX.test port 443 after 75005 ms: Couldn't connect to server
nishthagupta@Nishthas-MacBook-Pro ~ % nc -vz -g 5 10.7.28.24 443
nc: connectx to 10.7.28.24 port 443 (tcp) failed: Operation timed out
nishthagupta@Nishthas-MacBook-Pro ~ % nc -vz -g 5 10.7.28.24 443
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh

nishthagupta@Nishthas-MacBook-Pro ~ % dscacheutil -q host -a name app.teamX.test
nishthagupta@Nishthas-MacBook-Pro ~ % ping -c 1 app.teamX.test
ping: cannot resolve app.teamX.test: Unknown host
nishthagupta@Nishthas-MacBook-Pro ~ % curl -v --resolve app.teamX.test:443:10.7.28.24 https://app.teamX.test/api/status
* Added app.teamX.test:443:10.7.28.24 to DNS cache
* Hostname app.teamX.test was found in DNS cache
*   Trying 10.7.28.24:443...
* connect to 10.7.28.24 port 443 from 10.7.9.8 port 68668 failed: Operation timed out
* Failed to connect to app.teamX.test port 443 after 75885 ms: Couldn't connect to server
* Closing connection
curl: (28) Failed to connect to app.teamX.test port 443 after 75885 ms: Couldn't connect to server
nishthagupta@Nishthas-MacBook-Pro ~ % nc -vz -s 10.7.28.24 443
nc: connect to 10.7.28.24 port 443 (tcp) failed: Operation timed out
nishthagupta@Nishthas-MacBook-Pro ~ % nc -vz -s 10.7.28.24 443
Connection to 10.7.28.24 port 443 [tcp/https] succeeded!
nishthagupta@Nishthas-MacBook-Pro ~ % curl -v --resolve app.teamX.test:443:10.7.28.24 https://app.teamX.test/api/status
* Added app.teamX.test:443:10.7.28.24 to DNS cache
* Hostname app.teamX.test was found in DNS cache
*   Trying 10.7.28.24:443...
* Connected to app.teamX.test (10.7.28.24) port 443
* ALPN: curl offers h2,http/1.1
* (304) (OUT), TLS handshake, Client hello (1):
* CAfile: /etc/ssl/cert.pem
* CAPath: none
* (304) (IN), TLS handshake, Server hello (2):
* (304) (IN), TLS handshake, Unknown (8):
* (304) (IN), TLS handshake, Certificate (11):
* SSL certificate problem: self signed certificate
* Closing connection
curl: (60) SSL certificate problem: self signed certificate
More details here: https://curl.se/docs/sslcerts.html

curl failed to verify the legitimacy of the server and therefore could not
establish a secure connection to it. To learn more about this situation and
how to fix it, please visit the web page mentioned above.
nishthagupta@Nishthas-MacBook-Pro ~ % sudo security add-trusted-cert -d -r trustRoot -k /Library/Keychains/System.Keychain ~/Downloads/edge.crt
>Password:
nishthagupta@Nishthas-MacBook-Pro ~ % security verify-cert -c ~/Downloads/edge.crt -p ssl -s app.teamX.test
...certificate verification successful.
---
No extended validation result found
Certificate Transparency (CT) status: not verified
Unable to find at least 2 signed certificate timestamps (SCTs) from approved logs
nishthagupta@Nishthas-MacBook-Pro ~ % curl -v --resolve app.teamX.test:443:10.7.28.24 https://app.teamX.test/api/status
* Added app.teamX.test:443:10.7.28.24 to DNS cache
* Hostname app.teamX.test was found in DNS cache
*   Trying 10.7.28.24:443...
* Connected to app.teamX.test (10.7.28.24) port 443
* ALPN: curl offers h2,http/1.1
* (304) (OUT), TLS handshake, Client hello (1):
* CAfile: /etc/ssl/cert.pem
* CAPath: none
* (304) (IN), TLS handshake, Server hello (2):
* (304) (IN), TLS handshake, Unknown (8):
* (304) (IN), TLS handshake, Certificate (11):
* (304) (IN), TLS handshake, CERT verify (15):
* (304) (IN), TLS handshake, Finished (20):
* (304) (OUT), TLS handshake, Finished (20):
* SSL connection using TLSv1.3 / AEAD-CHACHA20-POLY1305-SHA256 / [blank] / UNDEF
* ALPN: server accepted http/1.1
* Server certificate:
* subject: CN=app.teamX.test
* start date: Sep 29 11:28:26 2026 GMT
* expire date: Sep 29 11:28:26 2027 GMT
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh

* Added app.teamX.test:443:10.7.28.24 to DNS cache
* Hostname app.teamX.test was found in DNS cache
*   Trying 10.7.28.24:443...
* Connected to app.teamX.test (10.7.28.24) port 443
* ALPN: curl offers h2,http/1.1
* (304) (OUT), TLS handshake, Client hello (1):
* CAfile: /etc/ssl/cert.pem
* CAPath: none
* (304) (IN), TLS handshake, Server hello (2):
* (304) (IN), TLS handshake, Unknown (8):
* (304) (IN), TLS handshake, Certificate (11):
* (304) (IN), TLS handshake, CERT verify (15):
* (304) (IN), TLS handshake, Finished (20):
* (304) (OUT), TLS handshake, Finished (20):
* SSL connection using TLSv1.3 / AEAD-CHACHA20-POLY1305-SHA256 / [blank] / UNDEF
* ALPN: server accepted http/1.1
* Server certificate:
* subject: CN=app.teamX.test
* start date: Sep 29 11:28:26 2026 GMT
* expire date: Sep 29 11:28:26 2027 GMT
* subjectAltName: host "app.teamX.test" matched cert's "app.teamX.test"
* issuer: CN=app.teamX.test
* SSL certificate verify ok.
* using HTTP/1.1
> GET /api/status HTTP/1.1
> Host: app.teamX.test
> User-Agent: curl/8.7.1
> Accept: */*
>
* Request completely sent off
< HTTP/1.1 200 OK
< Server: nginx/1.31.6
< Date: Tue, 29 Sep 2026 13:03:03 GMT
< Content-Type: application/json; charset=utf-8
< Content-Length: 29
< Connection: keep-alive
< X-Powered-By: Express
< X-Backend: A
< Cache-Control: max-age=60
< ETag: W/"1d"/mMMZex8nVDi441Suobi0vFg/M"
< X-Edge: mac2
<
* Connection #0 to host app.teamX.test left intact
{"backend":"A","status":"ok"}
nishthagupta@Nishthas-MacBook-Pro ~ % scutil --dns | grep -A5 -B2 "10.7.30.18"

resolver #1
  nameserver[0] : 10.7.30.18
  nameserver[1] : 8.8.8.8
  nameserver[2] : 127.0.0.1
  flags        : Request A records, Request AAAA records
  reach        : 0x00020002 (Reachable,Directly Reachable Address)

--

resolver #1
  nameserver[0] : 10.7.30.18
  nameserver[1] : 8.8.8.8
  nameserver[2] : 127.0.0.1
  if_index      : 11 (en0)
  flags        : Scoped, Request A records, Request AAAA records
  reach        : 0x00020002 (Reachable,Directly Reachable Address)
nishthagupta@Nishthas-MacBook-Pro ~ % networksetup -getdnsservers Wi-Fi
10.7.30.18
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                +

flags      : Request A records, Request AAAA records
reach      : 0x00020002 (Reachable,Directly Reachable Address)

--

resolver #1
nameserver[0] : 10.7.30.18
nameserver[1] : 8.8.8.8
nameserver[2] : 127.0.0.1
if_index : 11 (en0)
flags      : Scoped, Request A records, Request AAAA records
reach      : 0x00020002 (Reachable,Directly Reachable Address)
nischthagupta@Nishthas-MacBook-Pro ~ % networksetup -getdnsservers Wi-Fi
10.7.30.18
8.8.8.8
127.0.0.1
nischthagupta@Nishthas-MacBook-Pro ~ % dig app.teamX.test

; <<> Dig 9.10.6 <<> app.teamX.test
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NXDOMAIN, id: 41434
;; flags: qr rd ra ad; QUERY: 1, ANSWER: 0, AUTHORITY: 1, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags: udp: 512
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; AUTHORITY SECTION:
.                               86388   IN      SOA      a.root-servers.net. nstld.verisign-grs.com. 2026092900 1800 900 604800 86400

;; Query time: 19 msec
;; SERVER: 8.8.8.8#53(8.8.8.8)
;; WHEN: Tue Sep 29 18:35:01 IST 2026
;; MSG SIZE rcvd: 118

nischthagupta@Nishthas-MacBook-Pro ~ % networksetup -getdnsservers Wi-Fi
10.7.30.18
8.8.8.8
127.0.0.1
nischthagupta@Nishthas-MacBook-Pro ~ % dscacheutil -q host -a name app.teamX.test
nischthagupta@Nishthas-MacBook-Pro ~ % ls -la /etc/resolver
ls: /etc/resolver: No such file or directory
nischthagupta@Nishthas-MacBook-Pro ~ % sudo mkdir -p /etc/resolver
nischthagupta@Nishthas-MacBook-Pro ~ % sudo sh -c 'echo "nameserver 10.7.30.18" > /etc/resolver/teamX.test'
nischthagupta@Nishthas-MacBook-Pro ~ % cat /etc/resolver/teamX.test
nameserver 10.7.30.18
nischthagupta@Nishthas-MacBook-Pro ~ % dig app.teamX.test

; <<> Dig 9.10.6 <<> app.teamX.test
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 3185
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags: udp: 1232
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; ANSWER SECTION:
app.teamX.test.                0       IN      A          10.7.28.24

;; Query time: 39 msec
;; SERVER: 10.7.30.18#53(10.7.30.18)
;; WHEN: Tue Sep 29 16:32:14 IST 2026
;; MSG SIZE rcvd: 59
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                +

--- 10.7.11.140 ping statistics ---
4 packets transmitted, 4 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 49.222/93.489/167.968/47.355 ms
nischthagupta@Nishthas-MacBook-Pro ~ % dig app.teamX.test

; <<> Dig 9.10.6 <<> app.teamX.test
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 8657
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags: udp: 1232
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; ANSWER SECTION:
app.teamX.test.                0       IN      A          10.7.28.24

;; Query time: 39 msec
;; SERVER: 10.7.30.18#53(10.7.30.18)
;; WHEN: Tue Sep 29 16:32:14 IST 2026
;; MSG SIZE rcvd: 59

nischthagupta@Nishthas-MacBook-Pro ~ % sudo networksetup -setdnsservers Wi-Fi 10.7.30.18
Password:
nischthagupta@Nishthas-MacBook-Pro ~ % sudo dscacheutil -flushcache
nischthagupta@Nishthas-MacBook-Pro ~ % sudo killall -HUP mDNSResponder
nischthagupta@Nishthas-MacBook-Pro ~ % dig app.teamX.test

; <<> Dig 9.10.6 <<> app.teamX.test
;; global options: +cmd
;; connection timed out; no servers could be reached
nischthagupta@Nishthas-MacBook-Pro ~ % ping -c 4 10.7.30.18
PING 10.7.30.18 (10.7.30.18): 56 data bytes
64 bytes from 10.7.30.18: icmp_seq=0 ttl=32 time=246.461 ms
64 bytes from 10.7.30.18: icmp_seq=1 ttl=32 time=125.330 ms
64 bytes from 10.7.30.18: icmp_seq=2 ttl=32 time=51.696 ms
64 bytes from 10.7.30.18: icmp_seq=3 ttl=32 time=1000.640 ms

--- 10.7.30.18 ping statistics ---
4 packets transmitted, 4 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 51.695/356.033/1000.646/378.688 ms
nischthagupta@Nishthas-MacBook-Pro ~ % networksetup -getdnsservers Wi-Fi
10.7.30.18
nischthagupta@Nishthas-MacBook-Pro ~ % dig @10.7.30.18 app.teamX.test

; <<> Dig 9.10.6 <<> @10.7.30.18 app.teamX.test
; (1 server found)
;; global options: +cmd
;; connection timed out; no servers could be reached
nischthagupta@Nishthas-MacBook-Pro ~ % nc -vz 10.7.30.18 53
Connection to 10.7.30.18 port 53 [tcp/domain] succeeded
nischthagupta@Nishthas-MacBook-Pro ~ % dig @10.7.30.18 app.teamX.test

; <<> Dig 9.10.6 <<> @10.7.30.18 app.teamX.test
; (1 server found)
;; global options: +cmd
;; Got answer:
;; ->HEADER<<- opcode: QUERY, status: NOERROR, id: 54982
;; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags: udp: 1232
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh

Connection to 10.7.30.18 port 53 [tcp/domain] succeeded!
nishthagupta@Nishthas-MacBook-Pro ~ % dig @10.7.30.18 app.teamX.test

; <>> Dig 9.10.6 <<> @10.7.30.18 app.teamX.test
; (1 server found)
; global options: +cmd
; Got answer:
; ->HEADER<- opcode: QUERY, status: NOERROR, id: 54982
; flags: qr aa rd ra; QUERY: 1, ANSWER: 1, AUTHORITY: 0, ADDITIONAL: 1

;; OPT PSEUDOSECTION:
; EDNS: version: 0, flags:; udp: 1232
;; QUESTION SECTION:
;app.teamX.test.                IN      A

;; ANSWER SECTION:
app.teamX.test.                0       IN      A      10.7.28.24

;; Query time: 76 msec
;; SERVER: 10.7.30.18#53(10.7.30.18)
;; WHEN: Tue Sep 29 17:14:46 IST 2026
;; MSG SIZE rcvd: 59

nishthagupta@Nishthas-MacBook-Pro ~ % curl -s https://app.teamX.test/api/status
nishthagupta@Nishthas-MacBook-Pro ~ % curl -s https://app.teamX.test/api/status
nishthagupta@Nishthas-MacBook-Pro ~ % curl -v https://app.teamX.test/api/status
* Could not resolve host: app.teamX.test
* Closing connection
curl: (6) Could not resolve host: app.teamX.test
nishthagupta@Nishthas-MacBook-Pro ~ % networksetup -getdnsservers Wi-Fi
10.7.30.18
nishthagupta@Nishthas-MacBook-Pro ~ % scutil --dns | grep -E 'nameserver\{[0-9]+\}'
nameserver[0] : 10.7.30.18
nameserver[0] : 10.7.30.18
nishthagupta@Nishthas-MacBook-Pro ~ % dscacheutil -q host -a name app.teamX.test
nishthagupta@Nishthas-MacBook-Pro ~ % ping -c 1 app.teamX.test
ping: cannot resolve app.teamX.test: Unknown host
nishthagupta@Nishthas-MacBook-Pro ~ % sudo dscacheutil -flushcache
Password:
nishthagupta@Nishthas-MacBook-Pro ~ % sudo killall -HUP mDNSResponder
nishthagupta@Nishthas-MacBook-Pro ~ % networksetup -setairportpower en0 off
nishthagupta@Nishthas-MacBook-Pro ~ % sleep 3
nishthagupta@Nishthas-MacBook-Pro ~ % networksetup -setairportpower en0 on
nishthagupta@Nishthas-MacBook-Pro ~ % networksetup -setairportpower en0 off
nishthagupta@Nishthas-MacBook-Pro ~ % sleep 3
nishthagupta@Nishthas-MacBook-Pro ~ % networksetup -setairportpower en0 on
nishthagupta@Nishthas-MacBook-Pro ~ % dscacheutil -q host -a name app.teamX.test
ping: cannot resolve app.teamX.test: Unknown host
nishthagupta@Nishthas-MacBook-Pro ~ % scutil --dns
DNS configuration

resolver #1
nameserver[0] : 10.7.30.18
flags : Request A records
reach : 0x00020002 (Reachable, Directly Reachable Address)

resolver #2
domain : local
options : mdns
timeout : 5
flags : Request A records
reach : 0x00000000 (Not Reachable)
order : 30000
```

```
-- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh                                ~/desktop/CN_PROJECT/backend-A -- zsh

Last login: Tue Sep 29 18:37:53 on ttys004
nishthagupta@Nishthas-MacBook-Pro ~ % ifconfig en0 | grep 'inet '
    inet 10.7.9.8 netmask 0xffff0000 broadcast 10.7.31.255
nishthagupta@Nishthas-MacBook-Pro ~ % netstat -nr | grep default
default      10.7.0.1      UGScp        en0
default      fe80::Mutun0  UGcIg        utun0
default      fe80::Mutun1  UGcIg        utun1
default      fe80::Mutun2  UGcIg        utun2
default      fe80::Mutun3  UGcIg        utun3
nishthagupta@Nishthas-MacBook-Pro ~ % ping -c 4 10.7.30.18
PING 10.7.30.18 (10.7.30.18): 56 data bytes
64 bytes from 10.7.30.18: icmp_seq=0 ttl=32 time=87.195 ms
64 bytes from 10.7.30.18: icmp_seq=1 ttl=32 time=449.980 ms
64 bytes from 10.7.30.18: icmp_seq=2 ttl=32 time=37.280 ms
64 bytes from 10.7.30.18: icmp_seq=3 ttl=32 time=1364.838 ms

--- 10.7.30.18 ping statistics ---
4 packets transmitted, 4 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 37.280/534.803/1364.838/536.211 ms
nishthagupta@Nishthas-MacBook-Pro ~ % ping -c 4 10.7.28.24
PING 10.7.28.24 (10.7.28.24): 56 data bytes
64 bytes from 10.7.28.24: icmp_seq=0 ttl=64 time=264.032 ms
64 bytes from 10.7.28.24: icmp_seq=1 ttl=64 time=177.151 ms
64 bytes from 10.7.28.24: icmp_seq=2 ttl=64 time=92.070 ms
64 bytes from 10.7.28.24: icmp_seq=3 ttl=64 time=111.928 ms

--- 10.7.28.24 ping statistics ---
4 packets transmitted, 4 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 92.070/161.293/264.032/67.150 ms
nishthagupta@Nishthas-MacBook-Pro ~ % ping -c 4 10.7.11.140
PING 10.7.11.140 (10.7.11.140): 56 data bytes
64 bytes from 10.7.11.140: icmp_seq=0 ttl=64 time=199.311 ms
64 bytes from 10.7.11.140: icmp_seq=1 ttl=64 time=94.212 ms
64 bytes from 10.7.11.140: icmp_seq=2 ttl=64 time=116.856 ms
64 bytes from 10.7.11.140: icmp_seq=3 ttl=64 time=50.858 ms

--- 10.7.11.140 ping statistics ---
4 packets transmitted, 4 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 50.858/115.309/199.311/53.986 ms
nishthagupta@Nishthas-MacBook-Pro ~ % curl http://10.7.11.140:3002
{"message":"Backend B is running"}
nishthagupta@Nishthas-MacBook-Pro ~ % ping -c 4 10.7.30.18
PING 10.7.30.18 (10.7.30.18): 56 data bytes
64 bytes from 10.7.30.18: icmp_seq=0 ttl=64 time=127.233 ms
Request timeout for icmp_seq 1
64 bytes from 10.7.30.18: icmp_seq=2 ttl=64 time=150.272 ms
64 bytes from 10.7.30.18: icmp_seq=3 ttl=64 time=20.303 ms

--- 10.7.30.18 ping statistics ---
4 packets transmitted, 3 packets received, 25.0% packet loss
round-trip min/avg/max/stddev = 20.303/99.269/150.272/56.624 ms
nishthagupta@Nishthas-MacBook-Pro ~ % ping -c 4 10.7.11.140
PING 10.7.11.140 (10.7.11.140): 56 data bytes
64 bytes from 10.7.11.140: icmp_seq=0 ttl=64 time=167.968 ms
64 bytes from 10.7.11.140: icmp_seq=1 ttl=64 time=55.947 ms
64 bytes from 10.7.11.140: icmp_seq=2 ttl=64 time=49.222 ms
64 bytes from 10.7.11.140: icmp_seq=3 ttl=64 time=180.819 ms

--- 10.7.11.140 ping statistics ---
4 packets transmitted, 4 packets received, 0.0% packet loss
round-trip min/avg/max/stddev = 49.222/93.489/167.968/47.355 ms
nishthagupta@Nishthas-MacBook-Pro ~ % dig app.teamX.test

; <>> Dig 9.10.6 <<> app.teamX.test
```