



# Traditionaire Colonial Decorative Post-Top Luminaires

100W, 150W, 250W HPS

## PRODUCT OVERVIEW



### Applications:

- City Streets
- Residential Neighborhoods
- Parks
- Campuses
- Small Shopping Centers

#### A...Housing & Cover

Hinged (stainless steel hinge pins) die-cast aluminum housing and cover with cupola. Standard color is black polyester powder coat.

1" ANSI wattage/source label.

#### B...Refractor

Injection molded polycarbonate refractor panels.

#### C...Socket

Mogul-base porcelain socket.

#### D...Ballast

Ballast assembly with encapsulated starter. Tunnel type compression terminal lugs.

#### E...Screws

Captive retaining screws.


#### F...Mounting

Self-aligning pole-top fitter—fits 3" O.D. pole tops or vertical tenons

### Entergy Part Number:


Entergy #	Cooper #	Description
24624	UTR10SR233U0118	100w HPS, NPF-R, 120v, Type III, PCR
24474	UTR10SR255U0117	100w HPS, NPF-R, 120v Type V, PCR
16116	UTR15SR255U0047	150w HPS, NPF-R, 120v Type V, PCR
16117	UTR25SWW55U0048	250w HPS, MT/120v Type V

### DIMENSIONS



#### Effective Projected Area (EPA)



The EPA for the Traditionaire Series is 2.3 sq. ft.  
Approx Weight: 37LB



# Traditionaire Colonial

## Decorative Post-Top Luminaire

### PHOTOMETRIC INFORMATION



### Footcandle Table:

Select mounting height and read across for footcandle values of each isofootcandle line. Distance in units of mounting height.

Mounting Height UTR-1	Footcandle Values for Isofootcandle Lines				
	A	B	C	D	E
15'	2.00	1.00	0.80	0.25	0.10

### Footcandle Table:

Select mounting height and read across for footcandle values of each isofootcandle line. Distance in units of mounting height.

Mounting Height UTR-2	Footcandle Values for Isofootcandle Lines				
	A	B	C	D	E
15'	3.54	1.77	0.89	0.44	0.18
20'	2.00	1.00	0.50	0.25	0.10
25'	1.28	0.64	0.32	0.16	0.06