Untitled65.ipynb

File Edit View Insert Runtime Tools Help

Commands + Code + Text Run all

RAM Disk

[1]
```
# Conditional Statements
```

[2]
```
# IF - ELSE - ELIF(IFS)
```

[5] 1s
```
age = int(input("Enter your age : - "))

if age >= 18:
  print("You are eligible to vote")
```
```
Enter your age : - 20
You are eligible to vote
```

[8] 1s
```
age = int(input("Enter your age : - "))

if age >= 18:
  print("You are eligible to vote")
else:
  print("You are not eligible")
```
```
Enter your age : - 18
You are eligible to vote
```

[10] 1s
```
num = int(input("Enter the number : - "))

if num % 2 == 0:
  print("Even No")
else:
  print("Odd No")
```
```
Enter the number : - 6
Even No
```

[15] 1s
```
marks = int(input("Enter the marks : - "))

if marks >= 90:
  print("Grade A")
elif marks >= 70:
  print("Grade B")
elif marks >= 50:
  print("Grade C")
elif marks >= 35:
  print("Grade D")
else:
  print("Fail")
```
```
Enter the marks : - 34
Fail
```

[20] 4s
```
# Nested if else

username = str(input("Enter The Username : - "))


if username == "admin":
  password = int(input("Enter The Password"))
  if password == 1234:
    print("Login Successfully")
  else:
    print("Incorrect Password")
else:
  print("Incorrect username")
```
```
Enter The Username : - admin
Enter The Password1234
Login Successfully
```

[21]
```
# Statements - Break , COntinue , Pass
```

[24] 0s
```
for i in range(1,11):
  if i == 5:
    break
  print(i)
```
```
1
2
3
4
```

[25] 0s
```
for i in range(1,11):
  if i == 5:
    continue
  print(i)
```
```
1
2
3
4
6
7
8
9
10
```

[27]
```
age = 20
if age >= 18:
  pass
```

[28]
```
# list - for - dict - if else
```

[29]
```
# NUMPY - PANDAS - MATPLOTLIB - SEABORN
```

[30]
```
# numpy - numerical python
# calculating mean , median, standard deviation, variance
# minimum, maximum, percentile, quantile
# filtering the data, sorting the data, counting the data
# handling missing values
#
```

[31]
```
# numpy library - always install or import
```

[32]
```
!pip install numpy  # pip - python installing package
```
```
Requirement already satisfied: numpy in /usr/local/lib/python3.13/dist-packages (2.1.3)
```

[33]
```
import numpy
```

[34]
```
# AS - Alias - Temp Name -
```

[35]
```
import numpy as np
```

[36]
```
a = [1200,1500,1800,2000,2500,3000]
```

[37] 0s
```
type(a)
```
```
list
```

[38]
```
# Array - to store the multiple data
```

[39]
```
# 1D , 2D, 3D D- DIMENTIONS
```

[41]
```
array = np.array(a)
```

[42] 0s
```
array
```
```
array([1200, 1500, 1800, 2000, 2500, 3000])
```

[43] 0s
```
type(array)
```
```
numpy.ndarray
```

[44] 0s
```
np.arange(1,11)
```
```
array([ 1,  2,  3,  4,  5,  6,  7,  8,  9, 10])
```

[45] 0s
```
array
```
```
array([1200, 1500, 1800, 2000, 2500, 3000])
```

[46] 0s
```
array.shape
```
```
(6,)
```

[50]
```
b = np.array([[1,2,3,4,5,6],[9,8,7,6,5,4]])
```

[51] 0s
```
b
```
```
array([[1, 2, 3, 4, 5, 6],
       [9, 8, 7, 6, 5, 4]])
```

[52] 0s
```
b.shape
```
```
(2, 6)
```

[53] 0s
```
b.ndim
```
```
2
```

[54] 0s
```
b.size
```
```
12
```

[55] 0s
```
b.dtype
```
```
dtype('int64')
```

[56] 0s
```
np.sum(b)
```
```
np.int64(60)
```

[57] 0s
```
np.mean(b)
```
```
np.float64(5.0)
```

[58]
```
np.median(b)
```
```
np.float64(5.0)
```

[59]
```
np.min(b)
```
```
np.int64(1)
```

[60]
```
np.max(b)
```
```
np.int64(9)
```

[61]
```
np.std(b)
```
```
np.float64(2.273030282830976)
```

[62]
```
np.var(b)
```
```
np.float64(5.166666666666667)
```

[65]
```
np.percentile(b, 25)
```
```
np.float64(3.75)
```

[66]
```
np.quantile(b, 0.25)
```
```
np.float64(3.75)
```

[68]
```
# np.where
# new cilumns which having two outputs
# low, high
```

[69]
```
sales = np.array([1200,1500,1800,2000,2500,3000])
```

[70]
```
np.where(sales>=2000, "High", "Low")
```
```
array(['Low', 'Low', 'Low', 'High', 'High', 'High'], dtype='<U4')
```

[ ]
```
Start coding or generate with AI.
```

Colab paid products - Cancel contracts here