

Branch Prediction and OoO Techniques

Axel Feldmann

(slides adapted from prior 6.823 offerings)

Since Last Time...

1. Branch Prediction

- Relates to your lab 2!
- Covered several different schemes, from simple to more complex...

2. Speculation

- Data-in-ROB vs. unified-register-file
- Centralized vs. distributed
- ROB vs. issue queue + commit queue


Branch Prediction

Control Flow Dependences. How to handle them?

- Stall: Delay until we know the next PC
- Speculate: Guess next value
- Do something else: Multi-threading

Branch Predictors

- 1-bit predictor
- 2-bit predictor




Branch Predictors


Two empirical observations

1. A branch's outcome can be correlated with other branches' outcomes
 - Global branch correlation
2. A branch's outcome can be correlated with past outcomes of the same branch
 - Local branch correlation


History-based Prediction




Two-level Predictor



Tournament Predictors



TAGE Predictor



- Entry tagging:
Helps avoid aliasing between different branch scenarios
- Entry selection:
Use branch address + history to accurately identify different branch scenario for same branch
- Longer branch histories as required:
Use long histories for branches that actually benefit

Lab 2 Due Oct 20

- Get going early
- Incrementally build more complex predictors
 - 2-bit predictor
 - Local history predictor
 - Tournament predictor
- Recommend researching more advanced predictors for full credit
 - TAGE, Perceptron, etc...