

Contents					
1 Misc	2	3.4 PBDS Order Set	6	5.19 polygon / convex tangent point	11
1.1 Default Code	2	3.5 Segment Tree Add Set	6	5.20 polygon / halfplane intersection	11
1.2 Run	2	3.6 Segment Tree Li Chao Line	6	5.21 polygon / minkowski sum	11
1.3 Custom Set PQ Sort	2	3.7 Segment Tree Li Chao Segment	7	5.22 struct Cir	11
1.4 Dynamic Bitset	2	3.8 Segment Tree Persistent	7	5.23 Cir / Cir intersect	12
1.5 Enumerate Subset	2	3.9 Sparse Table	8	5.24 Cir / point tangent	12
1.6 Fast Input	2	3.10 Treap2	8	5.25 Geometry Struct 3D	12
1.7 OEIS	2	3.11 Trie	8	5.26 Pick's Theorem	12
1.8 OEIS	2	4 Dynamic-Programming	9	6 Graph	12
1.9 Pragma	3	4.1 Digit DP	9	6.1 SAT	12
1.10 Python	3	4.2 Integer Partition	9	6.2 Augment Path	13
1.11 Xor Basis	3	4.3 Knapsack On Tree	9	6.3 C3C4	13
1.12 diff	3	4.4 SOS DP	9	6.4 Cut BCC	13
1.13 disable ASLR	3	5 Geometry	9	6.5 Dinic	13
1.14 hash command	3	5.1 misc	9	6.6 Dominator Tree	14
1.15 hash windows	3	5.2 SVG writer	9	6.7 EdgeBCC	14
1.16 random int	3	5.3 struct point	10	6.8 EnumeratePlanarFace	15
1.17 vimrc	3	5.4 point / basic operation	10	6.9 HLD	15
2 Convolution	4	5.5 point / operators	10	6.10 Kosaraju	15
2.1 FFT	4	5.6 point / banana	10	6.11 Kuhn Munkres	16
2.2 FFT any mod	4	5.7 point / rayHitSeg	10	6.12 LCA	16
2.3 FWT	4	5.8 point / else	10	6.13 MCMF	17
2.4 Min Convolution Concave Concave	4	5.9 struct line	10	6.14 Tarjan	17
2.5 NTT mod 998244353	4	5.10 line / else	10	6.15 Tarjan Find AP	17
2.6 PolyInv	5	5.11 struct polygon	10	6.16 Theorem	17
2.7 PolySqrt	5	5.12 polygon / make convex hull	10	6.17 Tree Isomorphism	17
3 Data-Structure	5	5.13 polygon / in polygon	10	6.18 圓方樹	18
3.1 BIT	5	5.14 polygon / in convex	10	6.19 最大權閉合圖	19
3.2 Disjoint Set Persistent	5	5.15 polygon / cycle search	11	7 Math	19
3.3 PBDS GP Hash Table	6	5.16 polygon / line cut convex	11	7.1 Burnside's Lemma	19
		5.17 polygon / convex line intersect	11	7.2 CRT	19
		5.18 polygon / segment pass convex interior	11	7.3 Catalan Number	20
				7.4 Floor Sum	20
				7.5 Josephus Problem	20
				7.6 Lagrange any x	20
				7.7 Lagrange continuous x	20
				7.8 Linear Mod Inverse	20
				7.9 Lucas's Theorem	20
				7.10 Matrix	20
				7.11 Matrix 01	21
				7.12 Matrix Tree Theorem	21
				7.13 Miller Rabin	21
				7.14 Pollard Rho	21
				7.15 Polynomial	22
				7.16 Stirling's formula	23
				7.17 Theorem	23
				7.18 josephus	23
				7.19 二元一次方程式	23
				7.20 數論分塊	23
				7.21 最大質因數	23
				7.22 歐拉公式	23
				7.23 歐拉定理	23
				7.24 錯排公式	23
				8 String	23
				8.1 AC automation	23
				8.2 Enumerate Runs	24
				8.3 Hash	24
				8.4 KMP	24
				8.5 Manacher	24
				8.6 Min Rotation	24
				8.7 Suffix Array	24
				8.8 Wildcard Matching	25
				8.9 Z Algorithm	25
				8.10 k-th Substring1	25

1 Misc

1.1 Default Code [24a798]

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 #define int long long
4 #define debug(a...) cerr << #a << " = ", dout(a)
5 void dout() { cerr << "\n"; }
6 template <typename A, typename... B>
7 void dout(A a, B... b) { cerr << a << ' ', dout(b...); }
8
9 void solve(){
10
11 }
12
13 signed main(){
14     ios::sync_with_stdio(0), cin.tie(0);
15
16     int t = 1;
17     while (t--){
18         solve();
19     }
20
21     return 0;
22 }
```

1.2 Run

```
1 from os import *
2
3 f = "pA"
4
5 while 1:
6     i = input("input: ")
7     system("clear")
8     p = listdir(".")
9     if i != "":
10         f = i
11         print(f"file = {f}")
12         if system(f"g++ {f}.cpp -std=c++17 -Wall -Wextra -Wshadow
13             -O2 -D LOCAL -g -fsanitize=undefined,address -o {f}
14             "):
15             print("CE")
16             continue
17
18     for x in sorted(p):
19         if f in x and ".in" in x:
20             print(x)
21             if system(f"./{f} < {x}"):
22                 print("RE")
23             print()
```

1.3 Custom Set PQ Sort [d4df55]

```
1 // 所有自訂的結構體，務必檢查相等的 case，給所有元素一個排序
2 // 的依據
3 struct my_struct{
4     int val;
5     my_struct(int _val) : val(_val) {}
6 };
7
8 auto cmp = [](my_struct a, my_struct b) {
9     return a.val > b.val;
10 };
```

```
10
11 set<my_struct, decltype(cmp)> ss({1, 2, 3}, cmp);
12 priority_queue<my_struct, vector<my_struct>, decltype(cmp)>
13     pq(cmp, {1, 2, 3});
14 map<my_struct, my_struct, decltype(cmp)> mp({{1, 4}, {2, 5},
15     {3, 6}}, cmp);
```

1.4 Dynamic Bitset [c78aa8]

```
1 const int MAXN = 2e5 + 5;
2 template <int len = 1>
3 void solve(int n) {
4     if (n > len) {
5         solve<min(len*2, MAXN)>(n);
6         return;
7     }
8     bitset<len> a;
9 }
```

1.5 Enumerate Subset [a13e46]

```
1 // 時間複雜度  $O(3^n)$ 
2 // 枚舉每個 mask 的子集
3 for (int mask=0; mask<(1<<n); mask++){
4     for (int s=mask; s>=0; s=(s-1)&m){
5         // s 是 mask 的子集
6         if (s==0) break;
7     }
8 }
```

1.6 Fast Input [6f8879]

```
1 // fast IO
2 // 6f8879
3 inline char readchar(){
4     static char buffer[BUFSIZ], *now = buffer + BUFSIZ, *
5     end = buffer + BUFSIZ;
6     if (now == end)
7     {
8         if (end < buffer + BUFSIZ)
9             return EOF;
10        end = (buffer + fread(buffer, 1, BUFSIZ, stdin));
11        now = buffer;
12    }
13    return *now++;
14 }
15 inline int nextint(){
16     int x = 0, c = readchar(), neg = false;
17     while(('0' > c || c > '9') && c!='-' && c!=EOF) c =
18         readchar();
19     if(c == '-') neg = true, c = readchar();
20     while('0' <= c && c <= '9') x = (x<<3) + (x<<1) + (c^'0')
21     , c = readchar();
22     if(neg) x = -x;
23     return x; // returns 0 if EOF
24 }
```

1.7 OEIS [25cf74]

```
1
2 // 若一個線性遞迴有 k 項，給他恰好 2*k 個項可以求出線性遞迴
3 // s = 1 1 3 7 17, 則它會回傳 1 2
4 vector<int> BerlekampMassey(vector<int> s) {
```

```
5     if (s.empty()) return vector<int>();
6     int n = s.size(), L = 0, m = 0;
7     vector<int> C(n), B(n), T;
8     C[0] = B[0] = 1;
9
10    int b = 1;
11    for (int i=0; i<n; i++) {
12        ++m; int d = s[i]%MOD;
13        for (int j=1; j<L+1; j++) d = (d+C[j]*s[i-j])%MOD;
14        if (!d) continue;
15        T = C; int coef = d*qp(b, MOD-2, MOD)%MOD;
16        for (int j=m; j<n; j++) C[j] = (C[j]-coef*B[j-m])%
17            MOD;
18        if (2*L>i) continue;
19        L = i+1-L; B=T; b=d; m=0;
20    }
21    C.resize(L+1); C.erase(C.begin());
22    for (int &x : C) x = (MOD-x)%MOD;
23    reverse(C.begin(), C.end());
24    return C;
25 }
```

1.8 OEIS

```
1 from fractions import Fraction
2
3 def BerlekampMassey(a: list[Fraction]) -> list[Fraction]:
4     def scale(v: list[Fraction], c: Fraction) -> list[
5         Fraction]:
6         return [x * c for x in v]
7
8     s: list[Fraction] = []
9     best: list[Fraction] = []
10    bestPos = 0
11
12    for i in range(len(a)):
13        error: Fraction = a[i]
14        for j in range(len(s)):
15            error -= s[j] * a[i - 1 - j]
16        if error == 0:
17            continue
18
19        if not s:
20            s = [Fraction(0)] * (i + 1)
21            bestPos = i
22            best = [Fraction(1, error)]
23            continue
24
25        fix = scale(best, error)
26        fix = [Fraction(0)] * (i - bestPos - 1) + fix
27
28        if len(fix) >= len(s):
29            best = scale(s, Fraction(-1, error))
30            best.insert(0, Fraction(1, error))
31            bestPos = i
32            if len(s) < len(fix):
33                s += [Fraction(0)] * (len(fix) - len(s))
34
35        for j in range(len(fix)):
36            s[j] += fix[j]
37
38    return list(reversed(s))
39
40 n = int(input())
41 l = list(map(Fraction, input().split()))
```

```

41 for i in range(len(l)):
42     coeffs = BerlekampMassey(l[:i+1])
43     for x in coeffs:
44         print(x, end=" ")
45     print()

```

1.9 Pragma [09d13e]

```

1 #pragma GCC optimize("O3,unroll-loops")
2 #pragma GCC target("avx,avx2,sse,sse2,sse3,sse4,popcnt")

```

1.10 Python

```

1 # Decimal
2 from decimal import *
3 getcontext().prec = 6
4
5 # system setting
6 sys.setrecursionlimit(100000)
7 sys.set_int_max_str_digits(10000)
8
9 # turtle
10 from turtle import *
11
12 N = 3000000010
13 setworldcoordinates(-N, -N, N, N)
14 hideturtle()
15 speed(100)
16
17 def draw_line(a, b, c, d):
18     teleport(a, b)
19     goto(c, d)
20
21 def write_dot(x, y, text, diff=1): # diff = 文字的偏移
22     teleport(x, y)
23     dot(5, "red")
24
25     teleport(x+N/100*diff, y+N/100*diff)
26     write(text, font=("Arial", 5, "bold"))
27
28 # usage
29 draw_line(*a[i], *(a[i-1]))
30 write_dot(*a[i], str(a[i]))
31 # 以自己左方 100 單位為圓心向前畫一個 90 度的弧 / 正五邊形
   ( 參數可以是負的 )
32 circle(100, extent = 90)
33 circle(100, steps = 5)
34 left(90) # 左轉 90 度
35 fd(-100) # 倒退 100 單位
36 penup()
37 pendown()
38
39 tracer(0, 0) # IO 優化 · 必須在程式碼最後手動 update()
40 pos() # 回傳目前座標
41 heading() # 回傳目前方向：0 是右方、90 是上方
42 color("red") # 改變顏色 · 可以用文字或是 #000000 的格式
43
44 # OOP
45 class Point:
46     def __init__(self, x, y):
47         self.x = x
48         self.y = y
49

```

```

50     def __add__(self, o): # use dir(int) to know operator
51         name
52         return Point(self.x+o.x, self.y+o.y)
53
54     @property
55     def distance(self):
56         return (self.x**2 + self.y**2)**(0.5)
57
58 a = Point(3, 4)
59 print(a.distance)
60
61 # Fraction
62 from fractions import Fraction
63 a = Fraction(Decimal(1.1))
64 a.numerator # 分子
65 a.denominator # 分母

```

1.11 Xor Basis [840136]

```

1 vector<int> basis;
2 void add_vector(int x){
3     for (auto v : basis){
4         x=min(x, x^v);
5     }
6     if (x) basis.push_back(x);
7 }
8
9 // 給一數字集合 S · 求能不能 XOR 出 x
10 bool check(int x){
11     for (auto v : basis){
12         x=min(x, x^v);
13     }
14     return 0;
15 }
16
17 // 給一數字集合 S · 求能 XOR 出多少數字
18 // 答案等於 2^basis 的大小}
19
20 // 給一數字集合 S · 求 XOR 出最大的數字
21 int get_max(){
22     int ans=0;
23     for (auto v : basis){
24         ans=max(ans, ans^v);
25     }
26     return ans;
27 }

```

1.12 diff

```

1 set -e
2 g++ ac.cpp -o ac
3 g++ wa.cpp -o wa
4 for ((i=0;;i++))
5 do
6     echo "$i"
7     python3 gen.py > input
8     ./ac < input > ac.out
9     ./wa < input > wa.out
10    diff ac.out wa.out || break
11 done

```

1.13 disable ASLR [29a49f]

```

1 // Disable randomization of memory addresses
2 // setarch $(uname -m) -R /bin/bash
3
4 #include <sys/personality.h>
5 #include <bits/stdc++.h>
6 int main(int argc, char* argv[]){
7     personality(ADDR_NO_RANDOMIZE);
8     execv(argv[1], argv+1);
9 }

```

1.14 hash command

```

1 cat file.cpp | cpp -dD -P -fpreprocessed | tr -d "[:space:]"
   | md5sum | cut -c-6

```

1.15 hash windows

```

1 def get_hash(path):
2     from subprocess import run, PIPE
3     from hashlib import md5
4
5     p = run(
6         ["cpp", "-dD", "-P", "-fpreprocessed", path],
7         stdout = PIPE,
8         stderr = PIPE,
9         text = True
10    )
11
12    if p.returncode != 0:
13        raise RuntimeError(p.stderr)
14
15    s = ''.join(p.stdout.split())
16    ret = md5(s.encode()).hexdigest()
17    return ret[:6]
18
19 print(get_hash("Suffix_Array.cpp"))

```

1.16 random int [9cc603]

```

1 mt19937 seed(chrono::steady_clock::now().time_since_epoch().
   count());
2 int rng(int l, int r){
3     return uniform_int_distribution<int>(l, r)(seed);
4 }

```

1.17 vimrc

```

1 se nu rnu bs=2 sw=4 ts=4 hls ls=2 si acd bo=all mouse=a
2
3 :inoremap " ""<Esc>i
4 :inoremap {<CR> {<CR><Esc>ko
5 :inoremap { {<ESC>i
6
7 ca hash w !cpp -dD -P -fpreprocessed \\\ tr -d "[:space:]" \\\
   md5sum \\\ cut -c-6
8
9 " i+<esc>25A---<esc>
10 " o|<esc>25A |<esc>
11 " ggVGyG35pGdd

```

2 Convolution

2.1 FFT [16591a]

```

1 typedef complex<double> cd;
2
3 // 778272
4 void FFT(vector<cd> &a) {
5     int n = a.size(), L = 31-__builtin_clz(n);
6     vector<complex<long double>> R(2, 1);
7     vector<cd> rt(2, 1);
8     for (int k=2 ; k<n ; k*=2){
9         R.resize(n);
10        rt.resize(n);
11        auto x = polar(1.0L, acos(-1.0L) / k);
12        for (int i=k ; i<2*k ; i++){
13            rt[i] = R[i] = (i&1 ? R[i/2]*x : R[i/2]);
14        }
15    }
16    vector<int> rev(n);
17    for (int i=0 ; i<n ; i++) rev[i] = (rev[i/2] | (i&1)<<L)
18    /2;
19    for (int i=0 ; i<n ; i++) if (i<rev[i]) swap(a[i], a[rev[i]]);
20    for (int k=1 ; k<n ; k*=2){
21        for (int i=0 ; i<n ; i+=2*k){
22            for (int j=0 ; j<k ; j++){
23                // cd z = rt[j+k] * a[i+j+k];
24                auto x = (double *)&rt[j+k], y = (double *)&a
25                [i+j+k];
26                cd z(x[0]*y[0] - x[1]*y[1], x[0]*y[1] + x[1]*
27                y[0]);
28                a[i+j+k] = a[i+j]-z;
29                a[i+j] += z;
30            }
31        }
32    }
33 }
34
35 // 192528
36 vector<double> PolyMul(const vector<double> a, const vector<
37 double> b){
38     if (a.empty() || b.empty()) return {};
39     vector<double> res(a.size()+b.size()-1);
40     int L = 32 - __builtin_clz(res.size()), n = 1<<L;
41     vector<cd> in(n), out(n);
42     copy(a.begin(), a.end(), in.begin());
43     for (int i=0 ; i<b.size() ; i++) in[i].imag(b[i]);
44     FFT(in);
45     for (cd& x : in) x *= x;
46     for (int i=0 ; i<n ; i++) out[i] = in[-i & (n - 1)] -
47     conj(in[i]);
48     FFT(out);
49     for (int i=0 ; i<res.size() ; i++) res[i] = imag(out[i])
50     / (4 * n);
51     return res;
52 }

```

2.2 FFT any mod [412000]

```

1 // n=524288, ~400ms
2 const int MOD = 998244353;
3 typedef complex<double> cd;
4
5 // bb6d94
6 void FFT(vector<cd> &a) {

```

```

8     int n = a.size(), L = 31-__builtin_clz(n);
9     vector<complex<long double>> R(2, 1);
10    vector<cd> rt(2, 1);
11    for (int k=2 ; k<n ; k*=2){
12        R.resize(n);
13        rt.resize(n);
14        auto x = polar(1.0L, acos(-1.0L) / k);
15        for (int i=k ; i<2*k ; i++){
16            rt[i] = R[i] = (i&1 ? R[i/2]*x : R[i/2]);
17        }
18    }
19    vector<int> rev(n);
20    for (int i=0 ; i<n ; i++) rev[i] = (rev[i/2] | (i&1)<<L)
21    /2;
22    for (int i=0 ; i<n ; i++) if (i<rev[i]) swap(a[i], a[rev[i]]);
23    for (int k=1 ; k<n ; k*=2){
24        for (int i=0 ; i<n ; i+=2*k){
25            for (int j=0 ; j<k ; j++){
26                auto x = (double *)&rt[j+k];
27                auto y = (double *)&a[i+j+k];
28                cd z(x[0]*y[0] - x[1]*y[1], x[0]*y[1] + x[1]*
29                y[0]);
30                a[i+j+k] = a[i+j]-z;
31                a[i+j] += z;
32            }
33        }
34    }
35 }
36
37 // c3dcf6
38 vector<int> PolyMul(vector<int> a, vector<int> b){
39     if (a.empty() || b.empty()) return {};
40     vector<int> res(a.size()+b.size()-1);
41     int B = 32-__builtin_clz(res.size()), n = (1<<B), cut = (
42     int)(sqrt(MOD));
43     vector<cd> L(n), R(n), outs(n), outl(n);
44
45     for (int i=0 ; i<a.size() ; i++) L[i] = cd((int) a[i]/cut
46     , (int)a[i]%cut);
47     for (int i=0 ; i<b.size() ; i++) R[i] = cd((int) b[i]/cut
48     , (int)b[i]%cut);
49     FFT(L), FFT(R);
50     for (int i=0 ; i<n ; i++){
51         int j = -i&(n-1);
52         outl[j] = (L[i]+conj(L[j])) * R[i]/(2.0*n);
53         outs[j] = (L[i]-conj(L[j])) * R[i]/(2.0*n)/1i;
54     }
55     FFT(outl), FFT(outs);
56     for (int i=0 ; i<res.size() ; i++){
57         int av = (int)(real(outl[i])+0.5), cv = (int)(imag(
58         outs[i])+0.5);
59         int bv = (int)(imag(outl[i])+0.5) + (int)(real(outs[i]
60         )+0.5);
61         res[i] = ((av%MOD*cut+bv) % MOD*cut+cv) % MOD;
62     }
63     return res;
64 }

```

2.3 FWT [e50788]

```

1 // 已經把 mint 刪掉 · 需要增加註解
2 vector<int> xor_convolution(vector<int> a, vector<int> b, int
3 k) {

```

```

4     if (k==0) return vector<int>{a[0]*b[0]};
5     vector<int> aa(1 << (k - 1)), bb(1 << (k - 1));
6     for (int i=0 ; i<(1<<(k-1)) ; i++){
7         aa[i] = a[i] + a[i + (1 << (k - 1))];
8         bb[i] = b[i] + b[i + (1 << (k - 1))];
9     }
10    vector<int> X = xor_convolution(aa, bb, k - 1);
11    for (int i=0 ; i<(1<<(k-1)) ; i++){
12        aa[i] = a[i] - a[i + (1 << (k - 1))];
13        bb[i] = b[i] - b[i + (1 << (k - 1))];
14    }
15    vector<int> Y = xor_convolution(aa, bb, k - 1);
16    vector<int> c(1 << k);
17    for (int i=0 ; i<(1<<(k-1)) ; i++){
18        c[i] = (X[i] + Y[i]) / 2;
19        c[i + (1 << (k - 1))] = (X[i] - Y[i]) / 2;
20    }
21    return c;
22 }

```

2.4 Min Convolution Concave Concave [ffb28d]

```

1 // 需要增加註解
2 // min convolution
3 vector<int> mkk(vector<int> a, vector<int> b) {
4     vector<int> slope;
5     FOR (i, 1, ssize(a) - 1) slope.pb(a[i] - a[i - 1]);
6     FOR (i, 1, ssize(b) - 1) slope.pb(b[i] - b[i - 1]);
7     sort(all(slope));
8     slope.insert(begin(slope), a[0] + b[0]);
9     partial_sum(all(slope), begin(slope));
10    return slope;
11 }

```

2.5 NTT mod 998244353 [976c8d]

```

1
2 const int MOD = (119 << 23) + 1, ROOT = 62; // = 998244353
3 // For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 <<
4 // 21
5 // and 483 << 21 (same root). The last two are > 10^9.
6
7 // 7e041b
8 vector<int> rt(2, 1);
9 void NTT_init(int n){
10     static bool lastInit = 0;
11     if (lastInit<n){
12         lastInit = n;
13         for (int k=2, s=2 ; k<n ; k*=2, s++){
14             rt.resize(n);
15             int z[] = {1, qp(ROOT, MOD)>>s, MOD});
16             for (int i=k ; i<2*k ; i++) rt[i] = rt[i/2]*z[i
17             &1]%MOD;
18         }
19     }
20 }
21 // fec4b8
22 void NTT(vector<int> &a, int isInverse = false) {
23     int n = a.size();
24     int L = 31-__builtin_clz(n);
25     NTT_init(n);
26
27     vector<int> rev(n);
28     for (int i=0 ; i<n ; i++) rev[i] = (rev[i/2]|(i&1)<<L)/2;

```

```

28 for (int i=0 ; i<n ; i++){
29     if (i<rev[i]) swap(a[i], a[rev[i]]);
30 }
31
32 for (int k=1 ; k<n ; k*=2){
33     for (int i=0 ; i<n ; i+=2*k){
34         for (int j=0 ; j<k ; j++){
35             int z = rt[j+k]*a[i+j+k]%MOD, &ai = a[i+j];
36             a[i+j+k] = ai-z+(z>ai ? MOD : 0);
37             ai += (ai+z>MOD ? z-MOD : z);
38         }
39     }
40 }
41
42 if (isInverse) {
43     reverse(a.begin()+1, a.end());
44     int n_inv = qp(n, MOD-2, MOD);
45     for (int i=0 ; i<n ; i++) a[i] = a[i]*n_inv%MOD;
46 }
47 }
48
49 // 771576
50 vector<int> polyMul(vector<int> a, vector<int> b){
51     if (a.empty() || b.empty()) return {};
52     int s = a.size()+b.size()-1, B = 32-__builtin_clz(s), n =
53         1<<B;
54     vector<int> L(a), R(b), out(n);
55     L.resize(n), R.resize(n);
56     NTT(L), NTT(R);
57     for (int i=0 ; i<n ; i++) out[i] = L[i]*R[i]%MOD;
58     NTT(out, true);
59     out.resize(s);
60     return out;
61 }

```

2.6 PolyInv [b388fb]

```

1 vector<int> polyInv(vector<int> a){
2     int n = a.size();
3     vector<int> ret(1, qp(a[0], MOD-2, MOD));
4
5     for (int m=1 ; m<n ; m<=1){
6         if (n<2*m) a.resize(2*m);
7         vector<int> v1(a.begin(), a.begin()+2*m), v2 = ret;
8         v1.resize(4*m), v2.resize(4*m);
9         NTT(v1), NTT(v2);
10        for (int i=0 ; i<4*m ; i++) v1[i] = v1[i]*v2[i]%MOD*
11            v2[i]%MOD;
12        NTT(v1, true);
13        ret.resize(2*m);
14        for (int i=0 ; i<m ; i++) ret[i] = (ret[i]+ret[i])%
15            MOD;
16        for (int i=0 ; i<2*m ; i++) ret[i] = ((ret[i]-v1[i])%
17            MOD+MOD)%MOD;
18    }
19    ret.resize(n);
20    return ret;
21 }

```

2.7 PolySqrt [1ea321]

```

1 // ---- sqrt for formal power series over MOD=998244353 ----
2

```

```

3 int mod_sqrt(int a) { // Tonelli-Shanks; return -1 if no
4     solution
5     a %= MOD; if (a < 0) a += MOD;
6     if (a == 0) return 0;
7     if (qp(a, (MOD - 1) / 2, MOD) == MOD - 1) return -1; //
8     non-residue
9     if (MOD % 4 == 3) return qp(a, (MOD + 1) / 4, MOD);
10    int q = MOD - 1, s = 0;
11    while ((q & 1) == 0) q >>= 1, ++s;
12    int z = 2;
13    while (qp(z, (MOD - 1) / 2, MOD) != MOD - 1) ++z; // find
14    non-residue
15    long long c = qp(z, q, MOD);
16    long long x = qp(a, (q + 1) / 2, MOD);
17    long long t = qp(a, q, MOD);
18    int m = s;
19    while (t != 1) {
20        int i = 1;
21        long long tt = t * t % MOD;
22        while (tt != 1) {
23            tt = tt * tt % MOD;
24            ++i;
25            if (i == m) return -1; // shouldn't happen
26        }
27        long long b = qp(c, 1LL << (m - i - 1), MOD);
28        x = x * b % MOD;
29        long long b2 = b * b % MOD;
30        t = t * b2 % MOD;
31        c = b2;
32        m = i;
33    }
34    return (int)x;
35 }
36
37 vector<int> polySqrt(vector<int> a) {
38     int n = (int)a.size();
39
40     // all zero -> zero
41     bool all0 = true;
42     for (int x : a) if (x % MOD != 0) { all0 = false; break; }
43     if (all0) return vector<int>(n, 0);
44
45     // first nonzero position
46     int k = 0;
47     while (k < n && a[k] == 0) ++k;
48     if (k & 1) return {}; // odd -> impossible
49     int shift = k / 2;
50
51     // strip x^k
52     vector<int> f;
53     f.reserve(n - k);
54     for (int i = k; i < n; ++i) f.push_back(a[i]);
55
56     // constant term sqrt, choose canonical sign
57     int c0 = (f.empty() ? 0 : f[0] % MOD);
58     int s0 = mod_sqrt(c0);
59     if (s0 == -1) return {};
60     if (s0 > MOD - s0) s0 = MOD - s0; // choose the smaller
61     nonnegative root
62
63     // We must produce N terms after placing the shift =>
64     need = N - shift;
65     int need = n - shift;
66     if ((int)f.size() < need) f.resize(need, 0);
67 }

```

```

68 // Newton: g_{new} = (g + f/g) / 2 (mod x^m)
69 const int INV2 = (MOD + 1) / 2;
70 vector<int> g(1, s0);
71
72 for (int m = 1; m < need; m <= 1) {
73     int lim = min(need, m << 1);
74
75     vector<int> g_cut = g; g_cut.resize(lim);
76     vector<int> inv_g = polyInv(g_cut); // inv up
77     to lim
78     vector<int> f_cut(f.begin(), f.begin() + lim);
79
80     vector<int> q = polyMul(inv_g, f_cut);
81     if ((int)q.size() > lim) q.resize(lim);
82
83     g.resize(lim);
84     for (int i = 0; i < lim; ++i) {
85         long long gi = (i < (int)g_cut.size() ? g_cut[i]
86             : 0);
87         long long qi = (i < (int)q.size() ? q[i] : 0);
88         g[i] = (gi + qi) % MOD * 1LL * INV2 % MOD;
89     }
90     g.resize(need);
91
92     // place back the x^{k/2} shift
93     vector<int> res(n, 0);
94     for (int i = 0; i < need && i + shift < n; ++i) res[i +
95         shift] = g[i];
96     return res;
97 }

```

3 Data-Structure

3.1 BIT [7ef3a9]

```

1 vector<int> BIT(MAX_SIZE);
2
3 // const int MAX_N = (1<<20)
4 int k_th(int k){ // 回傳 BIT 中第 k 小的元素 (based-1)
5     int res = 0;
6     for (int i=MAX_N>>1 ; i>=1 ; i>=1){
7         if (BIT[res+i]<k)
8             k -= BIT[res+i];
9     }
10    return res+1;
11 }

```

3.2 Disjoint Set Persistent [447002]

```

1 struct Persistent_Disjoint_Set{
2     Persistent_Segment_Tree arr, sz;
3
4     void init(int n){
5         arr.init(n);
6         vector<int> v1;
7         for (int i=0 ; i<n ; i++){
8             v1.push_back(i);
9         }
10        arr.build(v1, 0);
11
12        sz.init(n);
13        vector<int> v2;
14        for (int i=0 ; i<n ; i++){
15            v2.push_back(1);
16        }
17    }
18 }

```

```

17     sz.build(v2, 0);
18 }
19
20 int find(int a){
21     int res = arr.query_version(a, a+1, arr.version.size()
22     (-1).val;
23     if (res==a) return a;
24     return find(res);
25 }
26
27 bool unite(int a, int b){
28     a = find(a);
29     b = find(b);
30
31     if (a!=b){
32
33         int sz1 = sz.query_version(a, a+1, arr.version.size()
34         (-1).val;
35         int sz2 = sz.query_version(b, b+1, arr.version.size()
36         (-1).val;
37
38         if (sz1<sz2){
39             arr.update_version(a, b, arr.version.size()
40             (-1);
41             sz.update_version(b, sz1+sz2, arr.version.size()
42             (-1);
43         }else{
44             arr.update_version(b, a, arr.version.size()
45             (-1);
46             sz.update_version(a, sz1+sz2, arr.version.size()
47             (-1);
48         }
49         return true;
50     }
51     return false;
52 }
53
54 };

```

3.3 PBDS GP Hash Table [866cf6]

```

1 #include <ext/pb_ds/assoc_container.hpp>
2 using namespace __gnu_pbds;
3 typedef tree<int,null_type,less<int>,rb_tree_tag,
4 tree_order_statistics_node_update> order_set;
5 struct custom_hash {
6     static uint64_t splitmix64(uint64_t x) {
7         // http://xorshift.di.unimi.it/splitmix64.c
8         x += 0x9e3779b97f4a7c15;
9         x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
10        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
11        return x ^ (x >> 31);
12    }
13
14    size_t operator()(uint64_t x) const {
15        static const uint64_t FIXED_RANDOM = chrono::
16        steady_clock::now().time_since_epoch().count();
17        return splitmix64(x + FIXED_RANDOM);
18    }
19 };
20
21 gp_hash_table<int, int, custom_hash> ss;

```

3.4 PBDS Order Set [231774]

```

1 // .find_by_order(k) 回傳第 k 小的值 (based-0)

```

```

2 // .order_of_key(k) 回傳有多少元素比 k 小
3 // 不能在 #define int long long 後 #include 檔案
4 #include <ext/pb_ds/assoc_container.hpp>
5 #include <ext/pb_ds/tree_policy.hpp>
6 using namespace __gnu_pbds;
7 typedef tree<int,null_type,less<int>,rb_tree_tag,
8 tree_order_statistics_node_update> order_set;

```

3.5 Segment Tree Add Set [bb1898]

```

1 // [ll, rr), based-0
2 // 使用前記得 init(陣列大小), build(陣列名稱)
3 // add(ll, rr): 區間修改
4 // set(ll, rr): 區間賦值
5 // query(ll, rr): 區間求和 / 求最大值
6 struct SegmentTree{
7     struct node{
8         int add_tag = 0;
9         int set_tag = 0;
10        int sum = 0;
11        int ma = 0;
12    };
13
14    vector<node> arr;
15
16    SegmentTree(int n){
17        arr.resize(n<<2);
18    }
19
20    node pull(node A, node B){
21        node C;
22        C.sum = A.sum+B.sum;
23        C.ma = max(A.ma, B.ma);
24        return C;
25    }
26
27    // cce0c8
28    void push(int idx, int ll, int rr){
29        if (arr[idx].set_tag!=0){
30            arr[idx].sum = (rr-ll)*arr[idx].set_tag;
31            arr[idx].ma = arr[idx].set_tag;
32            if (rr-ll>1){
33                arr[idx*2+1].add_tag = 0;
34                arr[idx*2+1].set_tag = arr[idx].set_tag;
35                arr[idx*2+2].add_tag = 0;
36                arr[idx*2+2].set_tag = arr[idx].set_tag;
37            }
38            arr[idx].set_tag = 0;
39        }
40        if (arr[idx].add_tag!=0){
41            arr[idx].sum += (rr-ll)*arr[idx].add_tag;
42            arr[idx].ma += arr[idx].add_tag;
43            if (rr-ll>1){
44                arr[idx*2+1].add_tag += arr[idx].add_tag;
45                arr[idx*2+2].add_tag += arr[idx].add_tag;
46            }
47            arr[idx].add_tag = 0;
48        }
49    }
50
51    void build(vector<int> &v, int idx = 0, int ll = 0, int
52    rr = n){
53        if (rr-ll==1){
54            arr[idx].sum = v[ll];
55            arr[idx].ma = v[ll];
56        }
57        else{
58            build(v, idx*2+1, ll, (ll+rr)/2);
59            build(v, idx*2+2, (ll+rr)/2, rr);
60            arr[idx] = pull(arr[idx*2+1], arr[idx*2+2]);
61        }
62    }
63
64    void add(int q1, int q2, int val, int idx = 0, int ll =
65    0, int rr = n){
66        push(idx, ll, rr);
67        if (rr==q1 || rr==q2) return;
68        if (q1<=ll && rr<=q2){
69            arr[idx].add_tag += val;
70            push(idx, ll, rr);
71            return;
72        }
73        int mid = (ll+rr)/2;
74        add(q1, q2, val, idx*2+1, ll, mid);
75        add(q1, q2, val, idx*2+2, mid, rr);
76        arr[idx] = pull(arr[idx*2+1], arr[idx*2+2]);
77    }
78
79    void set(int q1, int q2, int val, int idx=0, int ll=0,
80    int rr=n){
81        push(idx, ll, rr);
82        if (rr==q1 || rr==q2) return;
83        if (q1<=ll && rr<=q2){
84            arr[idx].add_tag = 0;
85            arr[idx].set_tag = val;
86            push(idx, ll, rr);
87            return;
88        }
89        int mid = (ll+rr)/2;
90        set(q1, q2, val, idx*2+1, ll, mid);
91        set(q1, q2, val, idx*2+2, mid, rr);
92        arr[idx] = pull(arr[idx*2+1], arr[idx*2+2]);
93    }
94
95    node query(int q1, int q2, int idx = 0, int ll = 0, int
96    rr = n){
97        push(idx, ll, rr);
98        if (rr==q1 || rr==q2) return node();
99        if (q1<=ll && rr<=q2) return arr[idx];
100        int mid = (ll+rr)/2;
101        return pull(query(q1, q2, idx*2+1, ll, mid), query(q1,
102        q2, idx*2+2, mid, rr));
103    }
104 } ST;

```

```

55 }else{
56     int mid = (ll+rr)/2;
57     build(v, idx*2+1, ll, mid);
58     build(v, idx*2+2, mid, rr);
59     arr[idx] = pull(arr[idx*2+1], arr[idx*2+2]);
60 }
61 }
62
63 void add(int q1, int q2, int val, int idx = 0, int ll =
64 0, int rr = n){
65     push(idx, ll, rr);
66     if (rr==q1 || rr==q2) return;
67     if (q1<=ll && rr<=q2){
68         arr[idx].add_tag += val;
69         push(idx, ll, rr);
70         return;
71     }
72     int mid = (ll+rr)/2;
73     add(q1, q2, val, idx*2+1, ll, mid);
74     add(q1, q2, val, idx*2+2, mid, rr);
75     arr[idx] = pull(arr[idx*2+1], arr[idx*2+2]);
76 }
77
78 void set(int q1, int q2, int val, int idx=0, int ll=0,
79 int rr=n){
80     push(idx, ll, rr);
81     if (rr==q1 || rr==q2) return;
82     if (q1<=ll && rr<=q2){
83         arr[idx].add_tag = 0;
84         arr[idx].set_tag = val;
85         push(idx, ll, rr);
86         return;
87     }
88     int mid = (ll+rr)/2;
89     set(q1, q2, val, idx*2+1, ll, mid);
90     set(q1, q2, val, idx*2+2, mid, rr);
91     arr[idx] = pull(arr[idx*2+1], arr[idx*2+2]);
92 }
93
94 node query(int q1, int q2, int idx = 0, int ll = 0, int
95 rr = n){
96     push(idx, ll, rr);
97     if (rr==q1 || rr==q2) return node();
98     if (q1<=ll && rr<=q2) return arr[idx];
99
100     int mid = (ll+rr)/2;
101     return pull(query(q1, q2, idx*2+1, ll, mid), query(q1,
102     q2, idx*2+2, mid, rr));
103 }
104 } ST;

```

3.6 Segment Tree Li Chao Line [45b8ba]

```

1 // 全部都是 0-based
2 // 宣告: LC_Segment_Tree st(n);
3 // 函式:
4 // update({a, b}): 插入一條 y=ax+b 的全域直線
5 // query(x): 查詢所有直線在位置 x 的最小值
6 const int MAX_V = 1e6+10; // 值域最大值
7
8 struct LC_Segment_Tree{
9     struct Node{ // y = ax+b
10         int a = 0;
11         int b = INF;
12     };
13
14     vector<Node> arr;
15
16     void init(int n){
17         arr.resize(n<<2);
18     }
19
20     void push(int idx, int ll, int rr){
21         if (rr==ll) return;
22         if (arr[idx].a==0) return;
23         int mid = (ll+rr)/2;
24         push(idx*2+1, ll, mid);
25         push(idx*2+2, mid, rr);
26         arr[idx] = pull(arr[idx*2+1], arr[idx*2+2]);
27     }
28
29     Node pull(Node A, Node B){
30         Node C;
31         C.a = min(A.a, B.a);
32         C.b = min(A.b, B.b);
33         return C;
34     }
35
36     void build(int n){
37         init(n);
38         push(1, 0, n);
39     }
40
41     int query(int x){
42         push(1, 0, n);
43         return arr[1].b;
44     }
45
46     void update(int a, int b){
47         push(1, 0, n);
48         arr[1] = pull(arr[1], Node{a, b});
49     }
50 }

```



```

13     int y(int x){
14         return a*x+b;
15     }
16 };
17 vector<Node> arr;
18
19 LC_Segment_Tree(int n = 0){
20     arr.resize(4*n);
21 }
22
23 void update(Node val, int idx = 0, int ll = 0, int rr =
24     MAX_V){
25     if (rr-ll==0) return;
26     if (rr-ll==1){
27         if (val.y(ll)<arr[idx].y(ll)){
28             arr[idx] = val;
29         }
30         return;
31     }
32     int mid = (ll+rr)/2;
33     if (arr[idx].a > val.a) swap(arr[idx], val); // 原本
34     // 的線斜率要比較小
35     if (arr[idx].y(mid) < val.y(mid)){ // 交點在左邊
36         update(val, idx*2+1, ll, mid);
37     }else{ // 交點在右邊
38         swap(arr[idx], val); // 在左子樹中，新線比舊線還
39         // 要好
40         update(val, idx*2+2, mid, rr);
41     }
42     return;
43 }
44
45 int query(int x, int idx = 0, int ll = 0, int rr = MAX_V)
46 {
47     if (rr-ll==0) return INF;
48     if (rr-ll==1){
49         return arr[idx].y(ll);
50     }
51     int mid = (ll+rr)/2;
52     if (x<mid){
53         return min(arr[idx].y(x), query(x, idx*2+1, ll,
54             mid));
55     }else{
56         return min(arr[idx].y(x), query(x, idx*2+2, mid,
57             rr));
58     }
59 }
60 };

```

3.7 Segment Tree Li Chao Segment [2cb0a4]

```

1 // 全部都是 0-based
2 // 宣告：LC_Segment_Tree st(n);
3 // 函式：
4 // update_segment({a, b}, ql, qr)：在 [ql, qr) 插入一條 y=ax+
5 // b 的線段
6 // query(x)：查詢所有直線在位置 x 的最小值
7 const int MAX_V = 1e6+10; // 值域最大值
8 struct LC_Segment_Tree{
9     struct Node{ // y = ax+b
10         int a = 0;

```

```

11         int b = INF;
12     };
13     vector<Node> arr;
14
15     LC_Segment_Tree(int n = 0){
16         arr.resize(4*n);
17     }
18
19     void update(Node val, int idx = 0, int ll = 0, int rr =
20         MAX_V){
21         if (rr-ll==0) return;
22         if (rr-ll==1){
23             if (val.y(ll)<arr[idx].y(ll)){
24                 arr[idx] = val;
25             }
26             return;
27         }
28         int mid = (ll+rr)/2;
29         if (arr[idx].a > val.a) swap(arr[idx], val); // 原本
30         // 的線斜率要比較小
31         if (arr[idx].y(mid) < val.y(mid)){ // 交點在左邊
32             update(val, idx*2+1, ll, mid);
33         }else{ // 交點在右邊
34             swap(arr[idx], val); // 在左子樹中，新線比舊線還
35             // 要好
36             update(val, idx*2+2, mid, rr);
37         }
38         return;
39     }
40
41     // 在 [ql, qr) 加上一條 val 的線段
42     void update_segment(Node val, int ql, int qr, int idx =
43         0, int ll = 0, int rr = MAX_V){
44         if (rr-ll==0) return;
45         if (rr<=ql || qr<=ll) return;
46         if (ql<=ll && rr<=qr){
47             update(val, idx, ll, rr);
48             return;
49         }
50         int mid = (ll+rr)/2;
51         update_segment(val, ql, qr, idx*2+1, ll, mid);
52         update_segment(val, ql, qr, idx*2+2, mid, rr);
53         return;
54     }
55
56     int query(int x, int idx = 0, int ll = 0, int rr = MAX_V)
57     {
58         if (rr-ll==0) return INF;
59         if (rr-ll==1){
60             return arr[idx].y(ll);
61         }
62         int mid = (ll+rr)/2;
63         if (x<mid){
64             return min(arr[idx].y(x), query(x, idx*2+1, ll,
65                 mid));
66         }else{
67             return min(arr[idx].y(x), query(x, idx*2+2, mid,
68                 rr));
69         }
70     }

```

```

69     }
70 }
71 };

```

3.8 Segment Tree Persistent [3b5aa9]

```

1 // 全部都是 0-based
2 // Persistent_Segment_Tree st(n+q);
3 // st.build(v, 0);
4 // 函式：
5 // update_version(pos, val, ver)：對版本 ver 的 pos 位置改成
6 // val
7 // query_version(ql, qr, ver)：對版本 ver 查詢 [ql, qr) 的區
8 // 間和
9 // clone_version(ver)：複製版本 ver 到最新的版本
10 struct Persistent_Segment_Tree{
11     int node_cnt = 0;
12     struct Node{
13         int lc = -1;
14         int rc = -1;
15         int val = 0;
16     };
17     vector<Node> arr;
18     vector<int> version;
19
20     Persistent_Segment_Tree(int sz){
21         arr.resize(32*sz);
22         version.push_back(node_cnt++);
23     }
24
25     void pull(Node &c, Node a, Node b){
26         c.val = a.val+b.val;
27         return;
28     }
29
30     void build(vector<int> &v, int idx, int ll = 0, int rr =
31         n){
32         auto &now = arr[idx];
33         if (rr-ll==1){
34             now.val = v[ll];
35             return;
36         }
37         int mid = (ll+rr)/2;
38         now.lc = node_cnt++;
39         now.rc = node_cnt++;
40         build(v, now.lc, ll, mid);
41         build(v, now.rc, mid, rr);
42         pull(now, arr[now.lc], arr[now.rc]);
43         return;
44     }
45
46     void update(int pos, int val, int idx, int ll = 0, int rr
47         = n){
48         auto &now = arr[idx];
49         if (rr-ll==1){
50             now.val = val;
51             return;
52         }
53         int mid = (ll+rr)/2;
54         if (pos<mid){

```

```

56     arr[node_cnt] = arr[now.lc];
57     now.lc = node_cnt;
58     node_cnt++;
59     update(pos, val, now.lc, ll, mid);
60 }else{
61     arr[node_cnt] = arr[now.rc];
62     now.rc = node_cnt;
63     node_cnt++;
64     update(pos, val, now.rc, mid, rr);
65 }
66 pull(now, arr[now.lc], arr[now.rc]);
67 return;
68 }
69 void update_version(int pos, int val, int ver){
70     update(pos, val, version[ver]);
71 }
72
73 Node query(int ql, int qr, int idx, int ll = 0, int rr =
74     n){
75     auto &now = arr[idx];
76
77     if (ql<=ll && rr<=qr) return now;
78     if (rr<=ql || qr<=ll) return Node();
79
80     int mid = (ll+rr)/2;
81
82     Node ret;
83     pull(ret, query(ql, qr, now.lc, ll, mid), query(ql,
84         qr, now.rc, mid, rr));
85     return ret;
86 }
87 Node query_version(int ql, int qr, int ver){
88     return query(ql, qr, version[ver]);
89 }
90
91 void clone_version(int ver){
92     version.push_back(node_cnt);
93     arr[node_cnt] = arr[version[ver]];
94     node_cnt++;
95 }
96 };

```

3.9 Sparse Table [31f22a]

```

1 struct SparseTable{
2     vector<vector<int>> st;
3     void build(vector<int> v){
4         int h = __lg(v.size());
5         st.resize(h+1);
6         st[0] = v;
7
8         for (int i=1 ; i<=h ; i++){
9             int gap = (1<<(i-1));
10            for (int j=0 ; j+gap<st[i-1].size() ; j++){
11                st[i].push_back(min(st[i-1][j], st[i-1][j+gap
12                    ]));
13            }
14        }
15    }
16
17    // 回傳 [ll, rr) 的最小值
18    int query(int ll, int rr){
19        int h = __lg(rr-ll);

```

```

19         return min(st[h][ll], st[h][rr-(1<<h)]);
20     }
21 };

```

3.10 Treap2 [3b0cca]

```

1 // 1-based · 請注意 MAX_N 是否足夠大
2 int root = 0;
3 int lc[MAX_N], rc[MAX_N];
4 int pri[MAX_N], val[MAX_N];
5 int sz[MAX_N], tag[MAX_N], fa[MAX_N], total[MAX_N];
6 // tag 為不包含自己 (僅要給子樹) 的資訊
7 int nodeCnt = 0;
8 int& new_node(int v){
9     nodeCnt++;
10    val[nodeCnt] = v;
11    total[nodeCnt] = v;
12    sz[nodeCnt] = 1;
13    pri[nodeCnt] = rand();
14    return nodeCnt;
15 }
16
17 void apply(int x, int V){
18     val[x] += V;
19     tag[x] += V;
20     total[x] += V*sz[x];
21 }
22
23 void push(int x){
24     if (tag[x]){
25         if (lc[x]) apply(lc[x], tag[x]);
26         if (rc[x]) apply(rc[x], tag[x]);
27     }
28     tag[x] = 0;
29 }
30 int pull(int x){
31     if (x){
32         fa[x] = 0;
33         sz[x] = 1+sz[lc[x]]+sz[rc[x]];
34         total[x] = val[x]+total[lc[x]]+total[rc[x]];
35         if (lc[x]) fa[lc[x]] = x;
36         if (rc[x]) fa[rc[x]] = x;
37     }
38     return x;
39 }
40
41 int merge(int a, int b){
42     if (!a or !b) return a|b;
43     push(a), push(b);
44
45     if (pri[a]>pri[b]){
46         rc[a] = merge(rc[a], b);
47         return pull(a);
48     }else{
49         lc[b] = merge(a, lc[b]);
50         return pull(b);
51     }
52 }
53
54 // [1, k] [k+1, n]
55 void split(int x, int k, int &a, int &b) {
56     if (!x) return a = b = 0, void();
57     push(x);
58     if (sz[lc[x]] >= k) {
59         split(lc[x], k, a, lc[x]);

```

```

60     b = x;
61     pull(a); pull(b);
62 }else{
63     split(rc[x], k - sz[lc[x]] - 1, rc[x], b);
64     a = x;
65     pull(a); pull(b);
66 }
67 }
68
69 // functions
70 // 回傳 x 在 Treap 中的位置
71 int get_pos(int x){
72     vector<int> sta;
73     while (fa[x]){
74         sta.push_back(x);
75         x = fa[x];
76     }
77     while (sta.size()){
78         push(x);
79         x = sta.back();
80         sta.pop_back();
81     }
82     push(x);
83
84     int res = sz[x] - sz[rc[x]];
85     while (fa[x]){
86         if (rc[fa[x]]==x){
87             res += sz[fa[x]]-sz[x];
88         }
89         x = fa[x];
90     }
91     return res;
92 }
93
94 // 1-based <前 [1, l-1] 個元素, [l, r] 個元素, [r+1, n] 個元
95 // 素>
96 array<int, 3> cut(int x, int l, int r){
97     array<int, 3> ret;
98     split(x, r, ret[1], ret[2]);
99     split(ret[1], l-1, ret[0], ret[1]);
100    return ret;
101 }
102 void print(int x){
103     push(x);
104     if (lc[x]) print(lc[x]);
105     cerr << val[x] << " ";
106     if (rc[x]) print(rc[x]);
107 }

```

3.11 Trie [b6475c]

```

1 struct Trie{
2     struct Data{
3         int nxt[2]={0, 0};
4     };
5
6     int sz=0;
7     vector<Data> arr;
8
9     void init(int n){
10        arr.resize(n);
11    }
12
13    void insert(int n){

```



```

14     int now=0;
15     for (int i=N ; i>=0 ; i--){
16         int v=(n>>i)&1;
17         if (!arr[now].nxt[v]){
18             arr[now].nxt[v]=++sz;
19         }
20         now=arr[now].nxt[v];
21     }
22 }
23
24 int query(int n){
25     int now=0, ret=0;
26     for (int i=N ; i>=0 ; i--){
27         int v=(n>>i)&1;
28         if (arr[now].nxt[1-v]){
29             ret+=(1<<i);
30             now=arr[now].nxt[1-v];
31         }else if (arr[now].nxt[v]){
32             now=arr[now].nxt[v];
33         }else{
34             return ret;
35         }
36     }
37     return ret;
38 }
39
40 } tr;

```

4 Dynamic-Programming

4.1 Digit DP [133f00]

```

1 #include <bits/stdc++.h>
2 using namespace std;
3
4 long long l, r;
5 long long dp[20][10][2][2]; // dp[pos][pre][Limit] = 後 pos
6 // 位 · pos 前一位是 pre · (是/否) 有上界 · (是/否) 有前綴零
7 // 的答案數量
8
9 long long memorize_search(string &s, int pos, int pre, bool
10 limit, bool lead){
11
12     // 已經被找過了 · 直接回傳值
13     if (dp[pos][pre][limit][lead]!=-1) return dp[pos][pre][
14 limit][lead];
15
16     // 已經搜尋完畢 · 紀錄答案並回傳
17     if (pos==(int)s.size()){
18         return dp[pos][pre][limit][lead] = 1;
19     }
20
21     // 枚舉目前的位數數字是多少
22     long long ans = 0;
23     for (int now=0 ; now<=(limit ? s[pos]-'0' : 9) ; now++){
24         if (now==pre){
25
26             // 1~9 絕對不能連續出現
27             if (pre!=0) continue;
28
29             // 如果已經不在前綴零的範圍內 · 0 不能連續出現
30             if (lead==false) continue;
31         }
32     }
33 }

```

```

29     ans += memorize_search(s, pos+1, now, limit&(now==(s[
30 pos]-'0')), lead&(now==0));
31 }
32
33 // 已經搜尋完畢 · 紀錄答案並回傳
34 return dp[pos][pre][limit][lead] = ans;
35 }
36
37 // 回傳 [0, n] 有多少數字符合條件
38 long long find_answer(long long n){
39     memset(dp, -1, sizeof(dp));
40     string tmp = to_string(n);
41
42     return memorize_search(tmp, 0, 0, true, true);
43 }
44
45 int main(){
46     // input
47     cin >> l >> r;
48
49     // output - 計算 [l, r] 有多少數字任意兩個位數都不相同
50     cout << find_answer(r)-find_answer(l-1) << "\n";
51
52     return 0;
53 }

```

4.2 Integer Partition

$dp[i][x]$ = 要將整數 x 拆成 i 堆的「組合數」

$dp[i+1][x+1] += dp[i][x]$ (創造新的一堆)

$dp[i][x+i] += dp[i][x]$ (把每一堆都增加 1)

4.3 Knapsack On Tree [df69b1]

```

1 // 需要重構 · 需要增加註解
2 #include <bits/stdc++.h>
3 #define F first
4 #define S second
5 #define all(x) begin(x), end(x)
6 using namespace std;
7
8 #define chmax(a, b) (a) = (a) < (b) ? (b) : (a)
9 #define chmin(a, b) (a) = (a) < (b) ? (a) : (b)
10
11 #define ll long long
12
13 #define FOR(i, a, b) for (int i = a; i <= b; i++)
14
15 int N, W, cur;
16 vector<int> w, v, sz;
17 vector<vector<int>> adj, dp;
18
19 void dfs(int x) {
20     sz[x] = 1;
21     for (int i : adj[x]) dfs(i), sz[x] += sz[i];
22     cur++;
23     // choose x
24     for (int i=w[x] ; i<=W ; i++){
25         dp[cur][i] = dp[cur - 1][i - w[x]] + v[x];
26     }
27     // not choose x
28     for (int i=0 ; i<=W ; i++){
29         chmax(dp[cur][i], dp[cur - sz[x]][i]);
30     }
31 }

```

```

31 }
32
33 signed main() {
34     cin >> N >> W;
35     adj.resize(N + 1);
36     w.assign(N + 1, 0);
37     v.assign(N + 1, 0);
38     sz.assign(N + 1, 0);
39     dp.assign(N + 2, vector<int>(W + 1, 0));
40     for (int i=1 ; i<=N ; i++){
41         int p; cin >> p;
42         adj[p].push_back(i);
43     }
44
45     for (int i=1 ; i<=N ; i++) cin >> w[i];
46     for (int i=1 ; i<=N ; i++) cin >> v[i];
47     dfs(0);
48     cout << dp[N + 1][W] << '\n';
49 }

```

4.4 SOS DP [8dfa8b]

```

1 // 總時間複雜度為  $O(n \cdot 2^n)$ 
2 // 計算  $dp[i] = i$  所有 bit mask 子集的和
3 for (int i=0 ; i<n ; i++){
4     for (int mask=0 ; mask<(1<<n) ; mask++){
5         if ((mask>>i)&1){
6             dp[mask] += dp[mask^(1<<i)];
7         }
8     }
9 }

```

5 Geometry

5.1 misc [3ef351]

```

1 using ld = double;
2
3 // 判斷數值正負: {1:正數,0:零,-1:負數}
4 int sign(long long x) {return (x >= 0) ? ((bool)x) : -1; }
5 int sign(ld x) {return (abs(x) < 1e-9) ? 0 : (x>0 ? 1 : -1);}

```

5.2 SVG writer [5bf313]

```

1
2 class SVG {
3     void p(string_view s) { o << s; }
4     void p(string_view s, auto v, auto... vs) {
5         auto i = s.find('$');
6         o << s.substr(0, i) << v, p(s.substr(i + 1), vs...);
7     }
8     ofstream o;
9     string c = "red";
10    public:
11    SVG(auto f, auto x1, auto y1, auto x2, auto y2) : o(f) {
12        p("<svg xmlns='http://www.w3.org/2000/svg' "
13        "viewBox='$ $ $ $'\n"
14        "<style>{*stroke-width:0.5%;}</style>\n",
15        x1, -y2, x2 - x1, y2 - y1);
16    }
17    ~SVG() { p("</svg>\n"); }
18    void color(string nc) { c = nc; }
19    void line(auto x1, auto y1, auto x2, auto y2) {
20        p("<line x1='$' y1='$' x2='$' y2='$' stroke='$' />\n",

```

```

21 |     x1, -y1, x2, -y2, c);
22 | }
23 | void circle(auto x, auto y, auto r) {
24 |     p("<<circle cx='$' cy='$' r='$' stroke='$' "
25 |       "fill='$'>\n", x, -y, r, c, "#none");
26 | }
27 | void text(auto x, auto y, string s, int w = 12) {
28 |     p("<text x='$' y='$' font-size='$px'></text>\n",
29 |       x, -y, w, s);
30 | }
31 | };
32 | // declare : SVG svg("test.svg", -99, -99, 100, 100);

```

5.3 struct point [f21f07]

```

1 | template<typename T>
2 | struct point {
3 |     T x, y;
4 |     point() {}
5 |     point(const T &x0, const T &y0) : x(x0), y(y0) {}
6 |     explicit operator point<ld>() {return point<ld>(x, y); }
7 | };

```

5.4 point / basic operation [c415da]

```

1 | point operator+(point b) {return {x+b.x, y+b.y}; }
2 | point operator-(point b) {return {x-b.x, y-b.y}; }
3 | point operator*(T b) {return {x*b, y*b}; }
4 | point operator/(T b) {return {x/b, y/b}; }
5 | bool operator==(point b) {return x==b.x && y==b.y; }
6 |
7 | T operator*(point b) {return x * b.x + y * b.y; }
8 | T operator^(point b) {return x * b.y - y * b.x; }

```

5.5 point / operators [fc43e4]

```

1 | // 逆時針極角排序
2 | bool side() const{return (y == 0) ? (x > 0) : (y < 0); }
3 | bool operator<(const point &b) const {
4 |     return side() == b.side() ?
5 |         (x*b.y > b.x*y) : side() < b.side();
6 | }
7 | friend ostream& operator<<(ostream& os, point p) {
8 |     return os << "(" << p.x << ", " << p.y << ")";
9 | }
10 | // 判斷 ab 到 ac 的方向 : {1:逆時鐘,0:重疊,-1:順時鐘}
11 | friend int ori(point a, point b, point c) {
12 |     return sign((b-a)^(c-a));
13 | }
14 | friend bool btw(point a, point b, point c) {
15 |     return ori(a, b, c) == 0 && sign((a-c)*(b-c)) <= 0;
16 | }

```

5.6 point / banana [09fd7c]

```

1 | // 判斷線段 ab, cd 是否相交
2 | friend bool banana(point a, point b, point c, point d) {
3 |     if (btw(a, b, c) || btw(a, b, d)
4 |         || btw(c, d, a) || btw(c, d, b)) return true;
5 |     int u = ori(a, b, c) * ori(a, b, d);
6 |     int v = ori(c, d, a) * ori(c, d, b);
7 |     return u < 0 && v < 0;
8 | }

```

5.7 point / rayHitSeg [db541a]

```

1 | // 判斷 "射線 ab" 與 "線段 cd" 是否相交
2 | friend bool rayHitSeg(point a, point b, point c, point d) {
3 |     if (a == b) return btw(c, d, a); // Special case
4 |     if (((a - b) ^ (c - d)) == 0) {
5 |         return btw(a, c, b) || btw(a, d, b) || banana(a, b, c
6 |             , d);
7 |     }
8 |     point u = b - a, v = d - c, s = c - a;
9 |     return sign(s ^ v) * sign(u ^ v) >= 0 && sign(s ^ u)
10 |        * sign(u ^ v) >= 0 && abs(s ^ u) <= abs(u ^ v);

```

5.8 point / else [f46547]

```

1 | // 旋轉 Arg(b) 的角度 (小心溢位)
2 | point rotate(point b){return {x*b.x-y*b.y, x*b.y+y*b.x};}
3 | // 回傳極座標角度・值域: [-π, +π]
4 | friend ld Arg(point b) {
5 |     return (b.x != 0 || b.y != 0) ? atan2(b.y, b.x) : 0;
6 | }
7 | friend T abs2(point b) {return b * b; }

```

5.9 struct line [210dc8]

```

1 | template<typename T>
2 | struct line {
3 |     point<T> p1, p2;
4 |     // ax + by + c = 0
5 |     T a, b, c; // |a|, |b| ≤ 2C, |c| ≤ 8C²
6 |     line() {}
7 |     line(const point<T> &x, const point<T> &y) : p1(x), p2(y){
8 |         build();
9 |     }
10 |    void build() {
11 |        a = p1.y - p2.y;
12 |        b = p2.x - p1.x;
13 |        c = (-a*p1.x)-b*p1.y;
14 |    }
15 | };

```

5.10 line / else [09bcc9]

```

1 | // 判斷點和有向直線的關係 : {1:左邊,0:在線上,-1:右邊}
2 | int ori(point<T> &p) {
3 |     return sign((p2-p1) ^ (p-p1));
4 | }
5 | // 判斷直線斜率是否相同
6 | bool parallel(line &l) {
7 |     return ((p1-p2) ^ (l.p1-l.p2)) == 0;
8 | }
9 | // 兩直線交點
10 | point<ld> line_intersection(line &l) {
11 |     using P = point<ld>;
12 |     point<T> u = p2-p1, v = l.p2-l.p1, s = l.p1-p1;
13 |     return P(p1) + P(u) * ((ld(s^v)) / (u^v));
14 | }

```

5.11 struct polygon [171a85]

```

1 | template<typename T>
2 | struct polygon {

```

```

3 |     vector<point<T>> v;
4 |     polygon() {}
5 |     polygon(const vector<point<T>> &u) : v(u) {}
6 | };

```

5.12 polygon / make convex hull [2bb3ef]

```

1 | // simple 為 true 的時候會回傳任意三點不共線的凸包
2 | void make_convex_hull(int simple) {
3 |     auto cmp = [&](point<T> &p, point<T> &q) {
4 |         return (p.x == q.x) ? (p.y < q.y) : (p.x < q.x);
5 |     };
6 |     simple = (bool)simple;
7 |     sort(v.begin(), v.end(), cmp);
8 |     v.resize(unique(v.begin(), v.end()) - v.begin());
9 |     if (v.size() <= 1) return;
10 |    vector<point<T>> hull;
11 |    for (int t = 0; t < 2; ++t){
12 |        int sz = hull.size();
13 |        for (auto &i:v) {
14 |            while (hull.size() >= sz+2 && ori(hull[hull.
15 |                size()-2], hull.back(), i) < simple) {
16 |                hull.pop_back();
17 |            }
18 |            hull.push_back(i);
19 |        }
20 |        hull.pop_back();
21 |        reverse(v.begin(), v.end());
22 |    }
23 |    swap(hull, v);
24 | }

```

5.13 polygon / in polygon [f11340]

```

1 | // 可以在有 n 個點的簡單多邊形內・用 O(n) 判斷一個點 :
2 | // {1 : 在多邊形內, 0 : 在多邊形上, -1 : 在多邊形外}
3 | int in_polygon(point<T> a){
4 |     const T MAX_POS = 1e9 + 5; // [記得修改] 座標的最大值
5 |     point<T> pre = v.back(), b(MAX_POS, a.y + 1);
6 |     int cnt = 0;
7 |
8 |     for (auto &i:v) {
9 |         if (btw(pre, i, a)) return 0;
10 |        if (banana(a, b, pre, i)) cnt++;
11 |        pre = i;
12 |    }
13 |
14 |     return cnt%2 ? 1 : -1;
15 | }

```

5.14 polygon / in convex [e64f1e]

```

1 | /// 警告 : 以下所有凸包專用的函式都只接受逆時針排序且任三點不
2 | | 共線的凸包 ///
3 | // 可以在有 n 個點的凸包內・用 O(Log n) 判斷一個點 :
4 | // {1 : 在凸包內, 0 : 在凸包邊上, -1 : 在凸包外}
5 | int in_convex(point<T> p) {
6 |     int n = v.size();
7 |     int a = ori(v[0], v[1], p), b = ori(v[0], v[n-1], p);
8 |     if (a < 0 || b > 0) return -1;
9 |     if (btw(v[0], v[1], p)) return 0;
10 |    if (btw(v[0], v[n-1], p)) return 0;
11 |    int l = 1, r = n - 1, mid;

```

```

11 while (l + 1 < r) {
12     mid = (l + r) >> 1;
13     if (ori(v[0], v[mid], p) >= 0) l = mid;
14     else r = mid;
15 }
16 int k = ori(v[l], v[r], p);
17 if (k <= 0) return k;
18 return 1;
19 }

```

5.15 polygon / cycle search [fe2f51]

```

1 // 凸包專用的環狀二分搜·回傳 0-based index
2 int cycle_search(auto &f) {
3     int n = v.size(), l = 0, r = n;
4     if (n == 1) return 0;
5     bool rv = f(1, 0);
6     while (r - l > 1) {
7         int m = (l + r) / 2;
8         if (f(0, m) ? rv : f(m, (m + 1) % n)) r = m;
9         else l = m;
10    }
11    return f(1, r % n) ? 1 : r % n;
12 }

```

5.16 polygon / line cut convex [b6a4c8]

```

1 // 可以在有  $n$  個點的凸包內·用  $O(\log n)$  判斷一條直線：
2 // {1 : 穿過凸包, 0 : 剛好切過凸包, -1 : 沒碰到凸包}
3 int line_cut_convex(line<T> L) {
4     L.build();
5     point<T> p(L.a, L.b);
6     auto gt = [&](int neg) {
7         auto f = [&](int x, int y) {
8             return sign((v[x] - v[y]) * p) == neg;
9         };
10        return -(v[cycle_search(f)] * p);
11    };
12    T x = gt(1), y = gt(-1);
13    if (L.c < x || y < L.c) return -1;
14    return not (L.c == x || L.c == y);
15 }

```

5.17 polygon / convex line intersect [47e699]

```

1 // return edge endpoint index
2 // but if (first == second) => intersect at a vertex
3 vector<pair<int,int>> convex_line_intersect(line<T> L) {
4     auto dis = [&](int p) {
5         return (L.p2 - L.p1) ^ (v[p] - L.p1);
6     };
7     auto gao = [&](int s) {
8         auto f = [&](int i, int j) {
9             return sign(dis(i) - dis(j)) == s;
10        };
11        return cycle_search(f);
12    };
13    int x = gao(1), y = gao(-1), n = v.size();
14    if (sign(dis(x)) < 0 || sign(dis(y)) > 0) return {};
15    if (sign(dis(x)) == 0 || sign(dis(y)) == 0) {
16        int j = ((sign(dis(x)) == 0 ? x : y) + n - 1) % n;
17        vector<pair<int,int>> ret;
18        for (int i = 0; i < 3; ++i, j = (j + 1) % n)
19            if (sign(dis(j)) == 0) ret.emplace_back(j, j);

```

```

20    return ret;
21 }
22 auto g = [&](int l, int r, int s) -> pair<int,int> {
23     while ((l + 1) % n != r) {
24         int m = ((l + r + (l < r ? 0 : n)) / 2) % n;
25         (sign(dis(m)) == s ? l : r) = m;
26     }
27     return {sign(dis(r)) ? l : r, r};
28 };
29 return {g(x, y, 1), g(y, x, -1)};
30 }

```

5.18 polygon / segment pass convex interior [7a3f22]

```

1 // 可以在有  $n$  個點的凸包內·用  $O(\log n)$  判斷一個線段：
2 // {1 : 線段上存在某一點位於凸包內部 (邊上不算),
3 // 0 : 線段上存在某一點碰到凸包的邊但線段上任一點均不在凸包
4 // -1 : 線段完全在凸包外面}
5 int segment_pass_convex_interior(line<T> L) {
6     if (in_convex(L.p1) == 1 || in_convex(L.p2) == 1) return
7         1;
8     L.build();
9     auto res = convex_line_intersect(L);
10    if (res.empty()) return -1;
11    bool cntp = 0, cntn = 0;
12    for (auto &[i, j] : res) if (banana(v[i], v[j], L.p1, L.
13        p2)) {
14        int now = L.ori(v[(i + 1) % v.size()]);
15        cntp |= (now == 1);
16        cntn |= (now == -1);
17    }
18    return (-1 + cntp + cntn);
19 }

```

5.19 polygon / convex tangent point [a6f66b]

```

1 // 回傳點過凸包的兩條切線的切點的 0-based index (不保證兩條
2 // 切線的順逆時針關係)
3 pair<int,int> convex_tangent_point(point<T> p) {
4     int n = v.size(), z = -1, edg = -1;
5     auto gt = [&](int neg) {
6         auto check = [&](int x) {
7             if (v[x] == p) z = x;
8             if (btw(v[x], v[(x + 1) % n], p)) edg = x;
9             if (btw(v[(x + n - 1) % n], v[x], p)) edg = (x +
10                n - 1) % n;
11        };
12        auto f = [&](int x, int y) {
13            check(x); check(y);
14            return ori(p, v[x], v[y]) == neg;
15        };
16        return cycle_search(f);
17    };
18    int x = gt(1), y = gt(-1);
19    if (z != -1) {
20        return {(z + n - 1) % n, (z + 1) % n};
21    }
22    else if (edg != -1) {
23        return {edg, (edg + 1) % n};
24    }
25    else {
26        return {x, y};
27    }

```

```

26 }

```

5.20 polygon / halfplane intersection [102d48]

```

1 friend int halfplane_intersection(vector<line<T>> &s, polygon
2 <T> &P) {
3     auto angle_cmp = [&](line<T> &A, line<T> &B) {
4         point<T> a = A.p2-A.p1, b = B.p2-B.p1;
5         return (a < b);
6     };
7     sort(s.begin(), s.end(), angle_cmp); // 線段左側為該線段
8     int L, R, n = s.size();
9     vector<point<T>> px(n);
10    vector<line<T>> q(n);
11    q[L = R = 0] = s[0];
12    for (int i = 1; i < n; ++i) {
13        while (L < R && s[i].ori(px[R-1]) <= 0) --R;
14        while (L < R && s[i].ori(px[L]) <= 0) ++L;
15        q[++R] = s[i];
16        if (q[R].parallel(q[R-1])) {
17            --R;
18            if (q[R].ori(s[i].p1) > 0) q[R] = s[i];
19        }
20        if (L < R) px[R-1] = q[R-1].line_intersection(q[R]);
21    }
22    while (L < R && q[L].ori(px[R-1]) <= 0) --R;
23    P.v.clear();
24    if (R - L <= 1) return 0;
25    px[R] = q[R].line_intersection(q[L]);
26    for (int i = L; i <= R; ++i) P.v.push_back(px[i]);
27    return R - L + 1;

```

5.21 polygon / minkowski sum [aba519]

```

1 void minkowski(vector<point<T>> a, vector<point<T>> b) {
2     // a, b: convex polygon's inside vector, CCW order
3     auto cmp = [&](auto &a, auto &b) {
4         return tie(a.y, a.x) < tie(b.y, b.x);
5     };
6     auto reorder = [&](auto &u) {
7         auto it = min_element(u.begin(), u.end(), cmp);
8         rotate(u.begin(), it, u.end());
9     };
10    reorder(a); reorder(b);
11    a.push_back(a[0]); a.push_back(a[1]);
12    b.push_back(b[0]); b.push_back(b[1]);
13    v.clear();
14    for (int i = 0, j = 0; i+2<a.size() || j+2<b.size(); ) {
15        v.push_back(a[i] + b[j]);
16        auto val = (a[i + 1] - a[i]) ^ (b[j + 1] - b[j]);
17        if (val >= 0) ++i;
18        if (val <= 0) ++j;
19    }
20 }

```

5.22 struct Cir [87198d]

```

1 struct Cir {
2     point<ld> o; ld r;
3     friend ostream& operator<<(ostream& os, Cir c) {
4         return os << "(x" << "+"[c.o.x >= 0] << abs(c.o.x)
5             << ")^2 + (y" << "+"[c.o.y >= 0] << abs(c.o.y)
6             << ")^2 = " << c.r * c.r;

```

```

5   }
6   bool covers(Cir b) {
7       return sqrt((ld)abs2(o - b.o)) + b.r <= r;
8   }
9   };

```

5.23 Cir / Cir intersect [330a1c]

```

1 vector<point<ld>> Cir_intersect(Cir c) {
2     ld d2 = abs2(o - c.o), d = sqrt(d2);
3     if (d < max(r, c.r) - min(r, c.r) || d > r + c.r) return
4         {};
5     auto sqdf = [&](ld x, ld y) { return x*x - y*y; };
6     point<ld> u = (o + c.o) / 2 + (o - c.o) * (sqdf(c.r, r) /
7         (2 * d2));
8     ld A = sqrt(sqdf(r + d, c.r) * sqdf(c.r, d - r));
9     point<ld> v = (c.o - o).rotate({0,1}) * A / (2 * d2);
10    if (sign(v.x) == 0 && sign(v.y) == 0) return {u};
11    return {u - v, u + v};
12 }

```

5.24 Cir / point tangent [0067e6]

```

1 auto point_tangent(point<ld> p) {
2     vector<point<ld>> res;
3     ld d_sq = abs2(p - o);
4     if (sign(d_sq - r * r) <= 0) {
5         res.pb(p + (p - o).rotate({0, 1}));
6     } else if (d_sq > r * r) {
7         ld s = d_sq - r * r;
8         point<ld> v = p + (o - p) * s / d_sq;
9         point<ld> u = (o - p).rotate({0, 1}) * sqrt(s) * r /
10            d_sq;
11         res.pb(v + u);
12         res.pb(v - u);
13     }
14     return res;
15 }

```

5.25 Geometry Struct 3D [4a50c9]

```

1 using ld = long double;
2
3 // 判斷數值正負：{1:正數,0:零,-1:負數}
4 int sign(long long x) {return (x >= 0) ? ((bool)x) : -1; }
5 int sign(ld x) {return (abs(x) < 1e-9) ? 0 : (x>0 ? 1 : -1); }
6
7 template<typename T>
8 struct pt3 {
9     T x, y, z;
10    pt3(){}
11    pt3(const T &x, const T &y, const T &z):x(x),y(y),z(z){}
12    explicit operator pt3<ld>() {return pt3<ld>(x, y, z); }
13
14    pt3 operator+(pt3 b) {return {x+b.x, y+b.y, z+b.z}; }
15    pt3 operator-(pt3 b) {return {x-b.x, y-b.y, z-b.z}; }
16    pt3 operator*(T b) {return {x * b, y * b, z * b}; }
17    pt3 operator/(T b) {return {x / b, y / b, z / b}; }
18    bool operator==(pt3 b){return x==b.x&&y==b.y&&z==b.z;}
19
20    T operator*(pt3 b) {return x*b.x+y*b.y+z*b.z; }
21    pt3 operator^(pt3 b) {
22        return pt3(y * b.z - z * b.y,
23            z * b.x - x * b.z,

```

```

24            x * b.y - y * b.x);
25    }
26    friend T abs2(pt3 b) {return b * b; }
27    friend T len (pt3 b) {return sqrt(abs2(b)); }
28    friend ostream& operator<<(ostream& os, pt3 p) {
29        return os << "(" << p.x << ", " <<
30            p.y << ", " << p.z << ")";
31    }
32 };
33
34 template<typename T>
35 struct face {
36     int a, b, c; // 三角形在 vector 裡面的 index
37     pt3<T> q; // 面積向量 (朝外)
38 };
39
40 /// 警告；v 在過程中可能被修改，回傳的 face 以修改後的為準
41 /// O(n^2) · 最多只有 2n-4 個面
42 /// 當凸包退化時會回傳空的凸包，否則回傳凸包上的每個面
43 template<typename T>
44 vector<face<T>> hull3(vector<pt3<T>> &v) {
45     int n = v.size();
46     if (n < 3) return {};
47     // don't use "==" when you use ld
48     sort(all(v), [&](pt3<T> &p, pt3<T> &q) {
49         return sign(p.x - q.x) ? (p.x < q.x) :
50             (sign(p.y - q.y) ? p.y < q.y : p.z < q.z);
51     });
52     v.resize(unique(v.begin(), v.end()) - v.begin());
53     for (int i = 2; i <= n; ++i) {
54         if (i == n) return {};
55         if (sign(len(((v[i] - v[0]) ^ (v[i] - v[0]))))) {
56             swap(v[2], v[i]);
57             break;
58         }
59     }
60     pt3<T> tmp_q = (v[1] - v[0]) ^ (v[2] - v[0]);
61     for (int i = 3; i <= n; ++i) {
62         if (i == n) return {};
63         if (sign((v[i] - v[0]) * tmp_q)) {
64             swap(v[3], v[i]);
65             break;
66         }
67     }
68
69     vector<face<T>> f;
70     vector<vector<int>> dead(n, vector<int>(n, true));
71     auto add_face = [&](int a, int b, int c) {
72         f.emplace_back(a, b, c, (v[b] - v[a]) ^ (v[c] - v[a])
73             );
74         dead[a][b] = dead[b][c] = dead[c][a] = false;
75     };
76     add_face(0, 1, 2);
77     add_face(0, 2, 1);
78
79     for (int i = 3; i < n; ++i) {
80         vector<face<T>> f2;
81         for (auto &[a, b, c, q] : f) {
82             if (sign((v[i] - v[a]) * q) > 0)
83                 dead[a][b] = dead[b][c] = dead[c][a] = true;
84             else f2.emplace_back(a, b, c, q);
85         }
86         f.clear();
87         for (face<T> &f2 : f2) {
88             int arr[3] = {F.a, F.b, F.c};

```

```

88         for (int j = 0; j < 3; ++j) {
89             int a = arr[j], b = arr[(j + 1) % 3];
90             if (dead[b][a]) add_face(b, a, i);
91         }
92     }
93     f.insert(f.end(), all(f2));
94 }
95 return f;
96 } // 15ef50

```

5.26 Pick's Theorem

給定頂點坐標均是整點的簡單多邊形，面積 = 內部格點數 + 邊上格點數/2 - 1

6 Graph

6.1 SAT [5a6317]

```

1 struct TWO_SAT {
2     int n, N;
3     vector<vector<int>> G, rev_G;
4     deque<bool> used;
5     vector<int> order, comp;
6     deque<bool> assignment;
7     void init(int _n) {
8         n = _n;
9         N = _n * 2;
10        G.resize(N + 5);
11        rev_G.resize(N + 5);
12    }
13    void dfs1(int v) {
14        used[v] = true;
15        for (int u : G[v]) {
16            if (!used[u])
17                dfs1(u);
18        }
19        order.push_back(v);
20    }
21    void dfs2(int v, int c1) {
22        comp[v] = c1;
23        for (int u : rev_G[v]) {
24            if (comp[u] == -1)
25                dfs2(u, c1);
26        }
27    }
28    bool solve() {
29        order.clear();
30        used.assign(N, false);
31        for (int i = 0; i < N; ++i) {
32            if (!used[i])
33                dfs1(i);
34        }
35        comp.assign(N, -1);
36        for (int i = 0, j = 0; i < N; ++i) {
37            int v = order[N - i - 1];
38            if (comp[v] == -1)
39                dfs2(v, j++);
40        }
41        assignment.assign(n, false);
42        for (int i = 0; i < N; i += 2) {
43            if (comp[i] == comp[i + 1])
44                return false;
45            assignment[i / 2] = (comp[i] > comp[i + 1]);
46        }
47        return true;
48    }
49 }

```

```

49 // A or B 都是 0-based
50 void add_disjunction(int a, bool na, int b, bool nb) {
51     // na is true => ~a, na is false => a
52     // nb is true => ~b, nb is false => b
53     a = 2 * a ^ na;
54     b = 2 * b ^ nb;
55     int neg_a = a ^ 1;
56     int neg_b = b ^ 1;
57     G[neg_a].push_back(b);
58     G[neg_b].push_back(a);
59     rev_G[b].push_back(neg_a);
60     rev_G[a].push_back(neg_b);
61     return;
62 }
63 void get_result(vector<int>& res) {
64     res.clear();
65     for (int i = 0; i < n; i++)
66         res.push_back(assignment[i]);
67 }
68 };

```

6.2 Augment Path [f8a5dd]

```

1 struct AugmentPath{
2     int n, m;
3     vector<vector<int>> G;
4     vector<int> mx, my;
5     vector<int> visx, visy;
6     int stamp;
7
8     AugmentPath(int _n, int _m) : n(_n), m(_m), G(n), mx(n,
9         -1), my(m, -1), visx(n), visy(n){
10         stamp = 0;
11     }
12
13     void add(int x, int y){
14         G[x].push_back(y);
15     }
16
17     // bb03e2
18     bool dfs1(int now){
19         visx[now] = stamp;
20
21         for (auto x : G[now]){
22             if (my[x]==-1){
23                 mx[now] = x;
24                 my[x] = now;
25                 return true;
26             }
27         }
28         for (auto x : G[now]){
29             if (visx[my[x]]!=stamp && dfs1(my[x])){
30                 mx[now] = x;
31                 my[x] = now;
32                 return true;
33             }
34         }
35         return false;
36     }
37
38     vector<pair<int, int>> find_max_matching(){
39         vector<pair<int, int>> ret;
40
41         while (true){
42             stamp++;

```

```

42         int tmp = 0;
43         for (int i=0 ; i<n ; i++){
44             if (mx[i]==-1 && dfs1(i)) tmp++;
45         }
46         if (tmp==0) break;
47     }
48
49     for (int i=0 ; i<n ; i++){
50         if (mx[i]!=-1){
51             ret.push_back({i, mx[i]});
52         }
53     }
54     return ret;
55 }
56
57 // 645577
58 void dfs2(int now){
59     visx[now] = true;
60
61     for (auto x : G[now]){
62         if (my[x]!=-1 && visy[x]==false){
63             visy[x] = true;
64             dfs2(my[x]);
65         }
66     }
67 }
68
69 // 要先執行 find_max_matching 一次
70 vector<pair<int, int>> find_min_vertex_cover(){
71     fill(visx.begin(), visx.end(), false);
72     fill(visy.begin(), visy.end(), false);
73
74     vector<pair<int, int>> ret;
75     for (int i=0 ; i<n ; i++){
76         if (mx[i]==-1) dfs2(i);
77     }
78
79     for (int i=0 ; i<n ; i++){
80         if (visx[i]==false) ret.push_back({1, i});
81     }
82     for (int i=0 ; i<m ; i++){
83         if (visy[i]==true) ret.push_back({2, i});
84     }
85     return ret;
86 }
87
88 };

```

6.3 C3C4 [875ea3]

```

1 // 0-based
2 void C3C4(vector<int> deg, vector<array<int, 2>> edges){
3     int N = deg.size();
4     int M = edges.size();
5
6     vector<int> ord(N), rk(N);
7     iota(ord.begin(), ord.end(), 0);
8     sort(ord.begin(), ord.end(), [&](int x, int y) { return
9         deg[x] > deg[y]; });
10    for (int i=0 ; i<N ; i++) rk[ord[i]] = i;
11
12    vector<vector<int>> D(N), adj(N);
13    for (auto [u, v] : edges) {
14        if (rk[u] > rk[v]) swap(u, v);
15        D[u].emplace_back(v);

```

```

15        adj[u].emplace_back(v);
16        adj[v].emplace_back(u);
17    }
18
19    vector<int> vis(N);
20
21    int c3 = 0, c4 = 0;
22    for (int x : ord) { // c3
23        for (int y : D[x]) vis[y] = 1;
24        for (int y : D[x]) for (int z : D[y]){
25            c3 += vis[z]; // xyz is C3
26        }
27        for (int y : D[x]) vis[y] = 0;
28    }
29    for (int x : ord) { // c4
30        for (int y : D[x]) for (int z : adj[y])
31            if (rk[z] > rk[x]) c4 += vis[z]++;
32        for (int y : D[x]) for (int z : adj[y])
33            if (rk[z] > rk[x]) --vis[z];
34    } // both are O(M*sqrt(M)), test @ 2022 CCPC guangzhou
35    cout << c4 << "\n";
36 }

```

6.4 Cut BCC [2af809]

```

1 #include <bits/stdc++.h>
2 using namespace std;
3
4 const int N = 200005;
5 vector<int> G[N];
6 int low[N], depth[N];
7 bool vis[N];
8 vector<vector<int>> bcc;
9 stack<int> stk;
10
11 void dfs(int v, int p) {
12     stk.push(v);
13     vis[v] = true;
14     low[v] = depth[v] = (p == -1 ? 1 : depth[p] + 1);
15     for (int u : G[v]) {
16         if (u == p) continue;
17         if (!vis[u]) {
18             /// (v, u) 是樹邊
19             dfs(u, v);
20             low[v] = min(low[v], low[u]);
21             /// u 無法在不經過父邊的情況走到 v 的祖先
22             if (low[u] >= depth[v]) {
23                 bcc.emplace_back();
24                 while (stk.top() != u) {
25                     bcc.back().push_back(stk.top());
26                     stk.pop();
27                 }
28                 bcc.back().push_back(stk.top());
29                 stk.pop();
30                 bcc.back().push_back(v);
31             }
32         } else {
33             /// (v, u) 是回邊
34             low[v] = min(low[v], depth[u]);
35         }
36     }
37 }

```

6.5 Dinic [961b34]


```

1 // 一般圖:  $O(EV^2)$ 
2 // 二分圖:  $O(EV)$ 
3 struct Flow{
4     using T = int; // 可以換成別的类型別
5     struct Edge{
6         int v; T rc; int rid;
7     };
8     vector<vector<Edge>> G;
9     void add(int u, int v, T c){
10         G[u].push_back({v, c, G[v].size()});
11         G[v].push_back({u, 0, G[u].size()-1});
12     }
13     vector<int> dis, it;
14
15     Flow(int n){
16         G.resize(n);
17         dis.resize(n);
18         it.resize(n);
19     }
20
21     // ce56d6
22     T dfs(int u, int t, T f){
23         if (u == t || f == 0) return f;
24         for (int &i=it[u] ; i<G[u].size() ; i++){
25             auto &[v, rc, rid] = G[u][i];
26             if (dis[v]!=dis[u]+1) continue;
27             T df = dfs(v, t, min(f, rc));
28             if (df <= 0) continue;
29             rc -= df;
30             G[v][rid].rc += df;
31             return df;
32         }
33         return 0;
34     }
35
36     // e22e39
37     T flow(int s, int t){
38         T ans = 0;
39         while (true){
40             fill(dis.begin(), dis.end(), INF);
41             queue<int> q;
42             q.push(s);
43             dis[s] = 0;
44
45             while (q.size()){
46                 int u = q.front(); q.pop();
47                 for (auto [v, rc, rid] : G[u]){
48                     if (rc <= 0 || dis[v] < INF) continue;
49                     dis[v] = dis[u] + 1;
50                     q.push(v);
51                 }
52             }
53             if (dis[t]==INF) break;
54
55             fill(it.begin(), it.end(), 0);
56             while (true){
57                 T df = dfs(s, t, INF);
58                 if (df <= 0) break;
59                 ans += df;
60             }
61         }
62         return ans;
63     }
64 }
65 // the code below constructs minimum cut

```

```

66 void dfs_mincut(int now, vector<bool> &vis){
67     vis[now] = true;
68     for (auto &[v, rc, rid] : G[now]){
69         if (vis[v] == false && rc > 0){
70             dfs_mincut(v, vis);
71         }
72     }
73 }
74
75 vector<pair<int, int>> construct(int n, int s, vector<
76     pair<int, int>> &E){
77     // E is G without capacity
78     vector<bool> vis(n);
79     dfs_mincut(s, vis);
80     vector<pair<int, int>> ret;
81     for (auto &[u, v] : E){
82         if (vis[u] == true && vis[v] == false){
83             ret.emplace_back(u, v);
84         }
85     }
86     return ret;
87 }

```

6.6 Dominator Tree [52b249]

```

1 // 全部都是  $\theta$ -based
2 // G 要是向有無權圖
3 // 一開始要初始化 G(N, root)
4 // 用完之後要 build
5 // G[i] = 從 root 走到 i 時，一定要走到的點且離 i 最近
6 struct DominatorTree{
7     int N;
8     vector<vector<int>> G;
9     vector<vector<int>> buckets, rg;
10     // dfn[x] = the DFS order of x
11     // rev[x] = the vertex with DFS order x
12     // par[x] = the parent of x
13     vector<int> dfn, rev, par;
14     vector<int> sd, dom, idom;
15     vector<int> fa, val;
16     int stamp;
17     int root;
18
19     int operator [] (int x){
20         return idom[x];
21     }
22
23     DominatorTree(int _N, int _root) :
24         N(_N),
25         G(N), buckets(N), rg(N),
26         dfn(N, -1), rev(N, -1), par(N, -1),
27         sd(N, -1), dom(N, -1), idom(N, -1),
28         fa(N, -1), val(N, -1)
29     {
30         stamp = 0;
31         root = _root;
32     }
33
34     void add_edge(int u, int v){
35         G[u].push_back(v);
36     }
37
38     void dfs(int x){
39         rev[dfn[x] = stamp] = x;

```

```

40         fa[stamp] = sd[stamp] = val[stamp] = stamp;
41         stamp++;
42
43         for (int u : G[x]){
44             if (dfn[u]==-1){
45                 dfs(u);
46                 par[dfn[u]] = dfn[x];
47             }
48             rg[dfn[u]].push_back(dfn[x]);
49         }
50     }
51
52     int eval(int x, bool first){
53         if (fa[x]==x) return !first ? -1 : x;
54         int p = eval(fa[x], false);
55
56         if (p==-1) return x;
57         if (sd[val[x]]>sd[val[fa[x]]]) val[x] = val[fa[x]];
58         fa[x] = p;
59
60         return !first ? p : val[x];
61     }
62
63     void link(int x, int y){
64         fa[x] = y;
65     }
66
67     void build(){
68         dfs(root);
69
70         for (int x=stamp-1 ; x>=0 ; x--){
71             for (int y : rg[x]){
72                 sd[x] = min(sd[x], sd[eval(y, true)]);
73             }
74             if (x>0) buckets[sd[x]].push_back(x);
75             for (int u : buckets[x]){
76                 int p = eval(u, true);
77                 if (sd[p]==x) dom[u] = x;
78                 else dom[u] = p;
79             }
80             if (x>0) link(x, par[x]);
81         }
82
83         idom[root] = root;
84         for (int x=1 ; x<stamp ; x++){
85             if (sd[x]!=dom[x]) dom[x] = dom[dom[x]];
86         }
87         for (int i=1 ; i<stamp ; i++) idom[rev[i]] = rev[dom[i]];
88     }
89 }

```

6.7 EdgeBCC [d09eb1]

```

1 // d09eb1
2 //  $\theta$ -based · 支援重邊
3 struct EdgeBCC{
4     int n, m, dep, sz;
5     vector<vector<pair<int, int>>> G;
6     vector<vector<int>> bcc;
7     vector<int> dfn, low, stk, isBridge, bccId;
8     vector<pair<int, int>> edge, bridge;
9

```



```

10 EdgeBCC(int _n) : n(_n), m(0), sz(0), dfn(n), low(n), G(n
11 ), bcc(n), bccId(n) {}
12
13 void add_edge(int u, int v) {
14     edge.push_back({u, v});
15     G[u].push_back({v, m});
16     G[v].push_back({u, m++});
17 }
18
19 void dfs(int now, int pre) {
20     dfn[now] = low[now] = ++dep;
21     stk.push_back(now);
22
23     for (auto [x, id] : G[now]){
24         if (!dfn[x]){
25             dfs(x, id);
26             low[now] = min(low[now], low[x]);
27         } else if (id != pre){
28             low[now] = min(low[now], dfn[x]);
29         }
30     }
31
32     if (low[now] == dfn[now]){
33         if (pre != -1) isBridge[pre] = true;
34         int u;
35         do{
36             u = stk.back();
37             stk.pop_back();
38             bcc[sz].push_back(u);
39             bccId[u] = sz;
40             while (u != now);
41             sz++;
42         }
43     }
44
45     void get_bcc() {
46         isBridge.assign(m, 0);
47         dep = 0;
48         for (int i=0; i<n; i++){
49             if (!dfn[i]) dfs(i, -1);
50         }
51
52         for (int i=0; i<m; i++){
53             if (isBridge[i]){
54                 bridge.push_back({edge[i].first, edge[i].
55                     second});
56             }
57         }
58     }
59 }
60
61 };

```

6.8 EnumeratePlanarFace [5498a7]

```

1 // 0-based
2 struct PlanarGraph{
3     int n, m, id;
4     vector<point<int>> v;
5     vector<vector<pair<int, int>>> G;
6     vector<int> conv, nxt, vis;
7
8     PlanarGraph(int n, int m, vector<point<int>> _v) :
9         n(n), m(m), id(0),
10         v(_v), G(n),
11         conv(2*m), nxt(2*m), vis(2*m) {}
12

```

```

13 void add_edge(int x, int y){
14     G[x].push_back({y, 2*id});
15     G[y].push_back({x, 2*id+1});
16     conv[2*id] = x;
17     conv[2*id+1] = y;
18     id++;
19 }
20
21 vector<int> enumerate_face(){
22     for (int i=0; i<n; i++){
23         sort(G[i].begin(), G[i].end(), [&](pair<int, int>
24             a, pair<int, int> b){
25             return (v[a.first]-v[i])<(v[b.first]-v[i]);
26         });
27
28         int sz = G[i].size(), pre = sz-1;
29         for (int j=0; j<sz; j++){
30             nxt[G[i][pre].second] = G[i][j].second^1;
31             pre = j;
32         }
33     }
34
35     vector<int> ret;
36     for (int i=0; i<2*m; i++){
37         if (vis[i]==false){
38             int area = 0, now = i;
39             vector<int> pt;
40
41             while (!vis[now]){
42                 vis[now] = true;
43                 pt.push_back(conv[now]);
44                 now = nxt[now];
45             }
46
47             pt.push_back(pt.front());
48             for (int j=0; j+1<pt.size(); j++){
49                 area -= (v[pt[j]]^v[pt[j+1]]);
50             }
51
52             // pt = face boundary
53             if (area>0){
54                 ret.push_back(area);
55             } else{
56                 // pt is outer face
57             }
58         }
59     }
60     return ret;
61 }

```

6.9 HLD [f57ec6]

```

1 #include <bits/stdc++.h>
2 #define int long long
3 using namespace std;
4
5 const int N = 100005;
6 vector<int> G[N];
7 struct HLD {
8     vector<int> pa, sz, depth, mxson, topf, id;
9     int n, idcnt = 0;
10     HLD(int _n) : n(_n), pa(_n + 1), sz(_n + 1), depth(_n +
11         1), mxson(_n + 1), topf(_n + 1), id(_n + 1) {}
12     void dfs1(int v = 1, int p = -1) {

```

```

13         pa[v] = p; sz[v] = 1; mxson[v] = 0;
14         depth[v] = (p == -1 ? 0 : depth[p] + 1);
15         for (int u : G[v]) {
16             if (u == p) continue;
17             dfs1(u, v);
18             sz[v] += sz[u];
19             if (sz[u] > sz[mxson[v]]) mxson[v] = u;
20         }
21     }
22     void dfs2(int v = 1, int top = 1) {
23         id[v] = ++idcnt;
24         topf[v] = top;
25         if (mxson[v]) dfs2(mxson[v], top);
26         for (int u : G[v]) {
27             if (u == mxson[v] || u == pa[v]) continue;
28             dfs2(u, u);
29         }
30     }
31     // query 為區間資料結構
32     int path_query(int a, int b) {
33         int res = 0;
34         while (topf[a] != topf[b]) { // 若不在同一條鍊上
35             if (depth[topf[a]] < depth[topf[b]]) swap(a, b);
36             res = max(res, 011); // query : l = id[topf[a]],
37             r = id[a]
38             a = pa[topf[a]];
39         }
40         // 此時已在同一條鍊上
41         if (depth[a] < depth[b]) swap(a, b);
42         res = max(res, 011); // query : l = id[b], r = id[a]
43         return res;
44     }
45 };

```

6.10 Kosaraju [c7d5aa]

```

1 // 給定一個有向圖，迴傳傳縮點後的圖、SCC 的資訊
2 // 所有點都以 based-0 編號
3 // 函式：
4 // .compress: O(n log n) 計算 G3、SCC、SCC_id 的資訊，並把縮
5 // 點後的結果存在 result 裡
6 // SCC[i] = 某個 SCC 中的所有點
7 // SCC_id[i] = 第 i 個點在第幾個 SCC
8 struct SCC_compress{
9     int N, M, sz;
10     vector<vector<int>> G, inv_G, result;
11     vector<pair<int, int>> edges;
12     vector<bool> vis;
13     vector<int> order;
14
15     vector<vector<int>> SCC;
16     vector<int> SCC_id;
17
18     SCC_compress(int _N) :
19         N(_N), M(0), sz(0),
20         G(N), inv_G(N),
21         vis(N), SCC_id(N)
22         {}
23
24     vector<int> operator [] (int x){
25         return result[x];
26     }
27
28     void add_edge(int u, int v){

```

```

28     G[u].push_back(v);
29     inv_G[v].push_back(u);
30     edges.push_back({u, v});
31     M++;
32 }
33
34 void dfs1(vector<vector<int>> &G, int now){
35     vis[now] = 1;
36     for (auto x : G[now]) if (!vis[x]) dfs1(G, x);
37     order.push_back(now);
38 }
39
40 void dfs2(vector<vector<int>> &G, int now){
41     SCC_id[now] = SCC.size()-1;
42     SCC.back().push_back(now);
43     vis[now] = 1;
44     for (auto x : G[now]) if (!vis[x]) dfs2(G, x);
45 }
46
47 void compress(){
48     fill(vis.begin(), vis.end(), 0);
49     for (int i=0 ; i<N ; i++) if (!vis[i]) dfs1(G, i);
50
51     fill(vis.begin(), vis.end(), 0);
52     reverse(order.begin(), order.end());
53     for (int i=0 ; i<N ; i++){
54         if (!vis[order[i]]){
55             SCC.push_back(vector<int>());
56             dfs2(inv_G, order[i]);
57         }
58     }
59
60     result.resize(SCC.size());
61     sz = SCC.size();
62     for (auto [u, v] : edges){
63         if (SCC_id[u]!=SCC_id[v]) result[SCC_id[u]].
64             push_back(SCC_id[v]);
65     }
66     for (int i=0 ; i<SCC.size() ; i++){
67         sort(result[i].begin(), result[i].end());
68         result[i].resize(unique(result[i].begin(), result
69             [i].end())-result[i].begin());
70     }
71 }
72
73 };

```

6.11 Kuhn Munkres [e66c35]

```

1 // O(n^3) 找到最大權匹配
2 struct KuhnMunkres{
3     int n; // max(n, m)
4     vector<vector<int>> G;
5     vector<int> match, lx, ly, visx, visy;
6     vector<int> slack;
7     int stamp = 0;
8
9     KuhnMunkres(int n) : n(n), G(n, vector<int>(n)), lx(n),
10         ly(n), slack(n), match(n), visx(n), visy(n) {}
11
12     void add(int x, int y, int w){
13         G[x][y] = max(G[x][y], w);
14     }
15
16     bool dfs(int i, bool aug){ // aug = true 表示要更新 match
17         if (visx[i]==stamp) return false;

```

```

17         visx[i] = stamp;
18
19         for (int j=0 ; j<n ; j++){
20             if (visy[j]==stamp) continue;
21             int d = lx[i]+ly[j]-G[i][j];
22
23             if (d==0){
24                 visy[j] = stamp;
25                 if (match[j]==-1 || dfs(match[j], aug)){
26                     if (aug){
27                         match[j] = i;
28                     }
29                     return true;
30                 }
31             }else{
32                 slack[j] = min(slack[j], d);
33             }
34         }
35         return false;
36     }
37
38     bool augment(){
39         for (int j=0 ; j<n ; j++){
40             if (visy[j]!=stamp && slack[j]==0){
41                 visy[j] = stamp;
42                 if (match[j]==-1 || dfs(match[j], false)){
43                     return true;
44                 }
45             }
46         }
47         return false;
48     }
49
50     void relabel(){
51         int delta = INF;
52         for (int j=0 ; j<n ; j++){
53             if (visy[j]!=stamp) delta = min(delta, slack[j]);
54         }
55         for (int i=0 ; i<n ; i++){
56             if (visx[i]==stamp) lx[i] -= delta;
57         }
58         for (int j=0 ; j<n ; j++){
59             if (visy[j]==stamp) ly[j] += delta;
60             else slack[j] -= delta;
61         }
62     }
63
64     int solve(){
65
66         for (int i=0 ; i<n ; i++){
67             lx[i] = 0;
68             for (int j=0 ; j<n ; j++){
69                 lx[i] = max(lx[i], G[i][j]);
70             }
71         }
72
73         fill(ly.begin(), ly.end(), 0);
74         fill(match.begin(), match.end(), -1);
75
76         for (int i = 0; i < n; i++) {
77             fill(slack.begin(), slack.end(), INF);
78             stamp++;
79             if(dfs(i, true)) continue;
80
81             while(augment()==false) relabel();
82             stamp++;

```

```

83         dfs(i, true);
84     }
85
86     int ans = 0;
87     for (int j=0 ; j<n ; j++){
88         if (match[j]!=-1){
89             ans += G[match[j]][j];
90         }
91     }
92     return ans;
93 }
94 };

```

6.12 LCA [5b6a5b]

```

1 // 1-based · 可以支援森林 · 0 是超級源點 · 所有樹都要跟他建邊
2 struct Tree{
3     int N, M = 0, H;
4     vector<int> parent, dep;
5     vector<vector<int>> G, LCA;
6
7     Tree(int _N) : N(_N+1), H(__lg(N)+1), parent(N, -1), dep(
8         N), G(N){
9         LCA.resize(H, vector<int>(N, 0));
10    }
11
12    void add_edge(int u, int v){
13        M++;
14        G[u].push_back(v);
15        G[v].push_back(u);
16    }
17
18    void dfs(int now = 0, int pre = 0){
19        dep[now] = dep[pre]+1;
20        parent[now] = pre;
21        for (auto x : G[now]){
22            if (x==pre) continue;
23            dfs(x, now);
24        }
25    }
26
27    void build_LCA(int root = 0){
28        dfs();
29        for (int i=0 ; i<N ; i++) LCA[0][i] = parent[i];
30        for (int i=1 ; i<H ; i++){
31            for (int j=0 ; j<N ; j++){
32                LCA[i][j] = LCA[i-1][LCA[i-1][j]];
33            }
34        }
35    }
36
37    int jump(int u, int step){
38        for (int i=0 ; i<H ; i++){
39            if (step&(1<<i)) u = LCA[i][u];
40        }
41        return u;
42    }
43
44    int get_LCA(int u, int v){
45        if (dep[u]<dep[v]) swap(u, v);
46        u = jump(u, dep[u]-dep[v]);
47        if (u==v) return u;
48        for (int i=H-1 ; i>=0 ; i--){
49            if (LCA[i][u]!=LCA[i][v]){
50                u = LCA[i][u];

```

```

50         v = LCA[i][v];
51     }
52 }
53     return parent[u];
54 }
55 };

```

6.13 MCMF [0d5244]

```

1 struct Flow {
2     struct Edge {
3         int u, rc, k, rv;
4     };
5
6     vector<vector<Edge>> G;
7     vector<int> par, par_eid;
8     Flow(int n) : G(n+1), par(n+1), par_eid(n+1) {}
9
10    // v->u, capacity: c, cost: k
11    void add(int v, int u, int c, int k){
12        G[v].push_back({u, c, k, G[u].size()});
13        G[u].push_back({v, 0, -k, G[v].size()-1});
14    }
15
16    // 6d1140
17    int spfa(int s, int t){
18        fill(par.begin(), par.end(), -1);
19        vector<int> dis(par.size(), INF);
20        vector<bool> in_q(par.size(), false);
21        queue<int> Q;
22        dis[s] = 0;
23        in_q[s] = true;
24        Q.push(s);
25
26        while (!Q.empty()){
27            int v = Q.front();
28            Q.pop();
29            in_q[v] = false;
30
31            for (int i=0; i<G[v].size(); i++){
32                auto [u, rc, k, rv] = G[v][i];
33                if (rc>0 && dis[v]+k<dis[u]){
34                    dis[u] = dis[v]+k;
35                    par[u] = v;
36                    par_eid[u] = i;
37                    if (!in_q[u]) Q.push(u);
38                    in_q[u] = true;
39                }
40            }
41        }
42
43        return dis[t];
44    }
45
46    // return <max flow, min cost>, d7e7ad
47    pair<int, int> flow(int s, int t){
48        int fl = 0, cost = 0, d;
49        while ((d = spfa(s, t))<INF){
50            int cur = INF;
51            for (int v=t; v!=s; v=par[v])
52                cur = min(cur, G[par[v]][par_eid[v]].rc);
53            fl += cur;
54            cost += d*cur;
55            for (int v=t; v!=s; v=par[v]){
56                G[par[v]][par_eid[v]].rc -= cur;

```

```

57        G[v][G[par[v]][par_eid[v]].rv].rc += cur;
58    }
59 }
60     return {fl, cost};
61 }
62 };

```

6.14 Tarjan [8b2350]

```

1 struct tarjan_SCC {
2     int now_T, now_SCCs;
3     vector<int> dfn, low, SCC;
4     stack<int> S;
5     vector<vector<int>> E;
6     vector<bool> vis, in_stack;
7
8     tarjan_SCC(int n) {
9         init(n);
10    }
11    void init(int n) {
12        now_T = now_SCCs = 0;
13        dfn = low = SCC = vector<int>(n);
14        E = vector<vector<int>>(n);
15        S = stack<int>();
16        vis = in_stack = vector<bool>(n);
17    }
18    void add(int u, int v) {
19        E[u].push_back(v);
20    }
21    void build() {
22        for (int i = 0; i < dfn.size(); ++i) {
23            if (!dfn[i]) dfs(i);
24        }
25    }
26    void dfs(int v) {
27        now_T++;
28        vis[v] = in_stack[v] = true;
29        dfn[v] = low[v] = now_T;
30        S.push(v);
31        for (auto &i:E[v]) {
32            if (!vis[i]) {
33                vis[i] = true;
34                dfs(i);
35                low[v] = min(low[v], low[i]);
36            }
37            else if (in_stack[i]) {
38                low[v] = min(low[v], dfn[i]);
39            }
40        }
41        if (low[v] == dfn[v]) {
42            int tmp;
43            do {
44                tmp = S.top();
45                S.pop();
46                SCC[tmp] = now_SCCs;
47                in_stack[tmp] = false;
48            } while (tmp != v);
49            now_SCCs += 1;
50        }
51    }
52 };

```

6.15 Tarjan Find AP [1daed6]

```

1 vector<int> dep(MAX_N), low(MAX_N), AP;

```

```

2 bitset<MAX_N> vis;
3
4 void dfs(int now, int pre){
5     int cnt = 0;
6     bool ap = 0;
7     vis[now] = 1;
8     low[now] = dep[now] = (now==1 ? 0 : dep[pre]+1);
9
10    for (auto x : G[now]){
11        if (x==pre){
12            continue;
13        }else if (vis[x]==0){
14            cnt++;
15            dfs(x, now);
16            low[now] = min(low[now], low[x]);
17            if (low[x]>=dep[now]) ap=1;
18        }else{
19            low[now] = min(low[now], dep[x]);
20        }
21    }
22
23    if ((now==pre && cnt==2) || (now!=pre && ap)){
24        AP.push_back(now);
25    }
26 }

```

6.16 Theorem

- 任意圖
 - 最大匹配 + 最小邊覆蓋 = n (不能有孤點)
 - 點覆蓋的補集是獨立集，最小點覆蓋 + 最大獨立集 = n
 - $w(\text{最小權點覆蓋}) + w(\text{最大權獨立集}) = \sum w_v$
 - (帶點權的二分圖可以用最小割解，構造請參考 Augment Path.cpp)
- 二分圖
 - 最小點覆蓋 = 最大匹配 = n - 最大獨立集
- 只有邊帶權的二分圖
 - w-vertex-cover (帶權點覆蓋)：每條邊的兩個連接點被選中的次數總和至少要是 w_e 。
 - w-weight matching (帶權匹配)
 - minimum vertex count of w-vertex-cover = maximum weight count of w-weight matching (一個點可以被選很多次，但邊不行)
- 點、邊都帶權的二分圖的定理
 - b-matching：假設 v 的點權是 b_v ，那所有 v 的匹配邊 e 的權重都要滿足 $\sum w_e \leq b_v$ 。
 - The maximum w-weight of a b-matching equals the minimum b-weight of vertices in a w-vertex-cover.

6.17 Tree Isomorphism [cd2bbc]

```

1 #include <bits/stdc++.h>
2 #pragma GCC optimize("O3,unroll-loops")
3 #define fastio ios::sync_with_stdio(0), cin.tie(0), cout.tie(0)
4 #define dbg(x) cerr << #x << " = " << x << endl
5 #define int long long
6 using namespace std;
7
8 // declare
9 const int MAX_SIZE = 2e5+5;

```

```

10 const int INF = 9e18;
11 const int MOD = 1e9+7;
12 const double EPS = 1e-6;
13 typedef vector<vector<int>> Graph;
14 typedef map<vector<int>, int> Hash;
15
16 int n, a, b;
17 int id1, id2;
18 pair<int, int> c1, c2;
19 vector<int> sz1(MAX_SIZE), sz2(MAX_SIZE);
20 vector<int> we1(MAX_SIZE), we2(MAX_SIZE);
21 Graph g1(MAX_SIZE), g2(MAX_SIZE);
22 Hash m1, m2;
23 int testcase=0;
24
25 void centroid(Graph &g, vector<int> &s, vector<int> &w, pair<
    int, int> &rec, int now, int pre){
26     s[now]=1;
27     w[now]=0;
28     for (auto x : g[now]){
29         if (x!=pre){
30             centroid(g, s, w, rec, x, now);
31             s[now]+=s[x];
32             w[now]=max(w[now], s[x]);
33         }
34     }
35     w[now]=max(w[now], n-s[now]);
36     if (w[now]<=n/2){
37         if (rec.first==0) rec.first=now;
38         else rec.second=now;
39     }
40 }
41
42 int dfs(Graph &g, Hash &m, int &id, int now, int pre){
43     vector<int> v;
44     for (auto x : g[now]){
45         if (x!=pre){
46             int add=dfs(g, m, id, x, now);
47             v.push_back(add);
48         }
49     }
50     sort(v.begin(), v.end());
51
52     if (m.find(v)!=m.end()){
53         return m[v];
54     }else{
55         m[v]=++id;
56         return id;
57     }
58 }
59
60 void solve1(){
61
62     // init
63     id1=0;
64     id2=0;
65     c1={0, 0};
66     c2={0, 0};
67     fill(sz1.begin(), sz1.begin()+n+1, 0);
68     fill(sz2.begin(), sz2.begin()+n+1, 0);
69     fill(we1.begin(), we1.begin()+n+1, 0);
70     fill(we2.begin(), we2.begin()+n+1, 0);
71     for (int i=1; i<=n; i++){
72         g1[i].clear();

```

```

73         g2[i].clear();
74     }
75     m1.clear();
76     m2.clear();
77
78     // input
79     cin >> n;
80     for (int i=0; i<n-1; i++){
81         cin >> a >> b;
82         g1[a].push_back(b);
83         g1[b].push_back(a);
84     }
85     for (int i=0; i<n-1; i++){
86         cin >> a >> b;
87         g2[a].push_back(b);
88         g2[b].push_back(a);
89     }
90
91     // get tree centroid
92     centroid(g1, sz1, we1, c1, 1, 0);
93     centroid(g2, sz2, we2, c2, 1, 0);
94
95     // process
96     int res1=0, res2=0, res3=0;
97     if (c2.second!=0){
98         res1=dfs(g1, m1, id1, c1.first, 0);
99         m2=m1;
100         id2=id1;
101         res2=dfs(g2, m1, id1, c2.first, 0);
102         res3=dfs(g2, m2, id2, c2.second, 0);
103     }else if (c1.second!=0){
104         res1=dfs(g2, m1, id1, c2.first, 0);
105         m2=m1;
106         id2=id1;
107         res2=dfs(g1, m1, id1, c1.first, 0);
108         res3=dfs(g1, m2, id2, c1.second, 0);
109     }else{
110         res1=dfs(g1, m1, id1, c1.first, 0);
111         res2=dfs(g2, m1, id1, c2.first, 0);
112     }
113
114     // output
115     cout << (res1==res2 || res1==res3 ? "YES" : "NO") << endl;
116
117     return;
118 }
119
120 signed main(void){
121     fastio;
122
123     int t=1;
124     cin >> t;
125     while (t--){
126         solve1();
127     }
128     return 0;
129 }

```

6.18 圖方樹 [675aec]

```

1 #include <bits/stdc++.h>
2 #define lp(i,a,b) for(int i=a;i<(b);i++)
3 #define pii pair<int,int>
4 #define pb push_back

```

```

5 #define ins insert
6 #define ff first
7 #define ss second
8 #define opa(x) cerr << #x << " = " << x << ", ";
9 #define op(x) cerr << #x << " = " << x << endl;
10 #define ops(x) cerr << x;
11 #define etr cerr << endl;
12 #define spc cerr << ' ';
13 #define BAE(x) (x).begin(), (x).end()
14 #define STL(x) cerr << #x << " : "; for(auto &qwe:x) cerr <<
    qwe << ' '; cerr << endl;
15 #define deb1 cerr << "deb1" << endl;
16 #define deb2 cerr << "deb2" << endl;
17 #define deb3 cerr << "deb3" << endl;
18 #define deb4 cerr << "deb4" << endl;
19 #define deb5 cerr << "deb5" << endl;
20 #define bye exit(0);
21 using namespace std;
22
23 const int mxn = (int)(2e5) + 10;
24 const int mxlg = 17;
25 int last_special_node = (int)(1e5) + 1;
26 vector<int> E[mxn], F[mxn];
27
28 struct edg{
29     int fr, to;
30     edg(int _fr, int _to){
31         fr = _fr;
32         to = _to;
33     }
34 };
35 ostream& operator<<(ostream& os, edg x){os << x.fr << "--" <<
    x.to;}
36 vector<edg> EV;
37
38 void tarjan(int v, int par, stack<int>& S){
39     static vector<int> dfn(mxn), low(mxn);
40     static vector<bool> to_add(mxn);
41     static int nowT = 0;
42
43     int childs = 0;
44     nowT += 1;
45     dfn[v] = low[v] = nowT;
46     for(auto &ne:E[v]){
47         int i = EV[ne].to;
48         if(i == par) continue;
49         if(!dfn[i]){
50             S.push(ne);
51             tarjan(i, v, S);
52             childs += 1;
53             low[v] = min(low[v], low[i]);
54
55             if(par >= 0 && low[i] >= dfn[v]){
56                 vector<int> bcc;
57                 int tmp;
58                 do{
59                     tmp = S.top(); S.pop();
60                     if(!to_add[EV[tmp].fr]){
61                         to_add[EV[tmp].fr] = true;
62                         bcc.pb(EV[tmp].fr);
63                     }
64                     if(!to_add[EV[tmp].to]){
65                         to_add[EV[tmp].to] = true;
66                         bcc.pb(EV[tmp].to);
67                     }
68                 }while(tmp != ne);

```

```

69     for(auto &j:bcc){
70         to_add[j] = false;
71         F[last_special_node].pb(j);
72         F[j].pb(last_special_node);
73     }
74     last_special_node += 1;
75 }
76 }
77 else{
78     low[v] = min(low[v], dfn[i]);
79     if(dfn[i] < dfn[v]){ // edge i--v will be visited
80         twice at here, but we only need one.
81         S.push(ne);
82     }
83 }
84 }
85 }
86 int dep[mxn], jmp[mxn][mxlg];
87 void dfs_lca(int v, int par, int depth){
88     dep[v] = depth;
89     for(auto &i:F[v]){
90         if(i == par) continue;
91         jmp[i][0] = v;
92         dfs_lca(i, v, depth + 1);
93     }
94 }
95 inline void build_lca(){
96     jmp[1][0] = 1;
97     dfs_lca(1, -1, 1);
98     lp(j,1,mxlg){
99         lp(i,1,mxn){
100             jmp[i][j] = jmp[jmp[i][j-1]][j-1];
101         }
102     }
103 }
104 }
105 inline int lca(int x, int y){
106     if(dep[x] < dep[y]){ swap(x, y); }
107     int diff = dep[x] - dep[y];
108     lp(j,0,mxlg){
109         if((diff >> j) & 1){
110             x = jmp[x][j];
111         }
112     }
113     if(x == y) return x;
114     for(int j = mxlg - 1; j >= 0; j--){
115         if(jmp[x][j] != jmp[y][j]){
116             x = jmp[x][j];
117             y = jmp[y][j];
118         }
119     }
120     return jmp[x][0];
121 }
122 }
123 inline bool can_reach(int fr, int to){
124     if(dep[to] > dep[fr]) return false;
125     int diff = dep[fr] - dep[to];
126     lp(j,0,mxlg){
127         if((diff >> j) & 1){
128             fr = jmp[fr][j];
129         }
130     }
131 }

```

```

134 }
135 return fr == to;
136 }
137 }
138 int main(){
139     ios::sync_with_stdio(false); cin.tie(0);
140     // freopen("test_input.txt", "r", stdin);
141     int n, m, q; cin >> n >> m >> q;
142     lp(i,0,m){
143         int u, v; cin >> u >> v;
144         E[u].pb(EV.size());
145         EV.pb(edge(u, v));
146         E[v].pb(EV.size());
147         EV.pb(edge(v, u));
148     }
149     E[0].pb(EV.size());
150     EV.pb(edge(0, 1));
151     stack<int> S;
152     tarjan(0, -1, S);
153     build_lca();
154 }
155 lp(queries,0,q){
156     int fr, to, relay; cin >> fr >> to >> relay;
157     if(fr == relay || to == relay){
158         cout << "NO\n";
159         continue;
160     }
161     if((can_reach(fr, relay) || can_reach(to, relay)) &&
162         dep[relay] >= dep[lca(fr, to)]){
163         cout << "NO\n";
164         continue;
165     }
166     cout << "YES\n";
167 }

```

6.19 最大權閉合圖 [6ca663]

```

1 // 邊 u → v 表示選 u 就要選 v (0-based)
2 // 保證回傳值非負
3 // 構造：從 S 開始 dfs，不走最小割的邊。
4 // 所有經過的點就是要選的那些點。
5 // 一般圖：O(n²m) / 二分圖：O(m√n)
6 template<typename U>
7 U maximum_closure(vector<U> w, vector<pair<int,int>> EV) {
8     int n = w.size(), S = n + 1, T = n + 2;
9     Flow G(T + 5); // Graph/Dinic.cpp
10     U sum = 0;
11     for (int i = 0; i < n; ++i) {
12         if (w[i] > 0) {
13             G.add(S, i, w[i]);
14             sum += w[i];
15         }
16         else if (w[i] < 0) {
17             G.add(i, T, abs(w[i]));
18         }
19     }
20     for (auto &[u, v] : EV) { // 請務必確保 INF > Σw_i
21         G.add(u, v, INF);
22     }
23     U cut = G.flow(S, T);
24     return sum - cut;
25 }

```

7 Math

7.1 Burnside's Lemma

$$\sum_{k=1}^n \frac{c(k)}{n}$$

- n : 有多少種置換方式 (例如：旋轉方式)
- $c(k)$: 所有可能中，經過 k 次旋轉後，仍不會和別人相同的方式的數量

7.2 CRT [682ac6]

```

1 // 求出 d = gcd(a,b) 並找出 x, y 使 ax + by = d
2 tuple<int, int, int> extgcd(int a, int b){
3     if (!b) return {a, 1, 0};
4     auto [d, x, y] = extgcd(b, a%b);
5     return {d, y, x-a/b*y};
6 }
7
8 // CRT maybe need use int128
9 int CRT_m_coprime(vector<int> &a, vector<int> &m) {
10     int n = a.size(), p = 1, ans = 0;
11     vector<int> M(n), invM(n);
12
13     for (int i=0; i<n; i++) p *= m[i];
14     for (int i=0; i<n; i++){
15         M[i] = p/m[i];
16         auto [d, x, y] = extgcd(M[i], m[i]);
17         invM[i] = x;
18         ans += a[i]*invM[i]*M[i];
19         ans %= p;
20     }
21     return (ans%p+p)%p;
22 }
23
24 // CRT maybe need use int128
25 int CRT_m_not_coprime(vector<int> &a, vector<int> &m) {
26     int n = a.size();
27
28     for (int i=1; i<n; i++){
29         int g = __gcd(m[0], m[i]);
30         if ((a[i]-a[0])%g!=0) return -1;
31
32         auto [d, x, y] = extgcd(m[0], m[i]);
33         x = (a[i]-a[0])*x/g;
34
35         a[0] = x*m[0]+a[0];
36         m[0] = m[0]*m[i]/g;
37         a[0] = (a[0]%m[0]+m[0])%m[0];
38     }
39
40     if (a[0]<0) return a[0]+m[0];
41     return a[0];
42 }
43
44 // ans = a / b (mod m)
45 // ans = ret.F + k * ret.S, k is integer
46 pair<int, int> div(int a, int b, int m) {
47     int flag = 1;
48     if (a < 0) { a = -a; flag *= -1; }
49     if (b < 0) { b = -b; flag *= -1; }
50     int t = -1, k = -1;
51     int res = extgcd_abc(b, m, a, t, k);
52     if (res == INF) return {INF, INF};

```

```

53 |     m = abs(m / res);
54 |     t = t * flag;
55 |     t = (t % m + m) % m;
56 |     return {t, m};
57 | }

```

7.3 Catalan Number

任意括號序列: $C_n = \frac{1}{n+1} \binom{2n}{n}$

7.4 Floor Sum [5d1c9e]

```

1 | // Returns sum_{i=0}^{n-1} floor((a*i + b) / m)
2 | // Log( max(a, m) )
3 | int floor_sum(int n, int m, int a, int b) {
4 |     int ans = 0;
5 |     while (true) {
6 |         if (a >= m) {
7 |             ans += (n - 1) * n * (a / m) / 2;
8 |             a %= m;
9 |         }
10 |        if (b >= m) {
11 |            ans += n * (b / m);
12 |            b %= m;
13 |        }
14 |        int y_max = a * n + b;
15 |        if (y_max < m) break;
16 |        n = y_max / m;
17 |        b = y_max % m;
18 |        swap(m, a);
19 |    }
20 |    return ans;
21 | }

```

7.5 Josephus Problem [e0ed50]

```

1 | // 有 n 個人，第偶數個報數的人被刪掉，問第 k 個被踢掉的是誰
2 | int solve(int n, int k){
3 |     if (n==1) return 1;
4 |     if (k==(n+1)/2){
5 |         if (2*k>n) return 2*k%n;
6 |         else return 2*k;
7 |     }else{
8 |         int res=solve(n/2, k-(n+1)/2);
9 |         if (n&1) return 2*res+1;
10 |        else return 2*res-1;
11 |     }
12 | }

```

7.6 Lagrange any x [1f2c26]

```

1 | // init: (x1, y1), (x2, y2) in a vector
2 | struct Lagrange{
3 |     int n;
4 |     vector<pair<int, int>> v;
5 |
6 |     Lagrange(vector<pair<int, int>> &v){
7 |         n = _v.size();
8 |         v = _v;
9 |     }
10 |
11 |     // O(n^2 log MAX_A)
12 |     int solve(int x){
13 |         int ret = 0;
14 |         for (int i=0; i<n; i++){

```

```

15 |             int now = v[i].second;
16 |             for (int j=0; j<n; j++){
17 |                 if (i==j) continue;
18 |                 now *= ((x-v[j].first)+MOD)%MOD;
19 |                 now %= MOD;
20 |                 now *= (qp((v[i].first-v[j].first+MOD)%MOD,
21 |                     MOD-2)+MOD)%MOD;
22 |                 now %= MOD;
23 |             }
24 |             ret = (ret+now)%MOD;
25 |         }
26 |         return ret;
27 |     }
28 | };

```

7.7 Lagrange continuous x [57536a]

```

1 | #include <bits/stdc++.h>
2 | using namespace std;
3 |
4 | const int MAX_N = 5e5 + 10;
5 | const int mod = 1e9 + 7;
6 |
7 | long long inv_fac[MAX_N];
8 |
9 | inline int fp(long long x, int y) {
10 |     int ret = 1;
11 |     for (; y; y >= 1) {
12 |         ret = (y & 1) ? (ret * x % mod) : ret;
13 |         x = x * x % mod;
14 |     }
15 |     return ret;
16 | }
17 |
18 | // TO USE THIS TEMPLATE, YOU MUST MAKE SURE THAT THE MOD
19 | // NUMBER IS A PRIME.
20 | struct Lagrange {
21 |     /*
22 |      * Initialize a polynomial with f(x_0), f(x_0 + 1), ..., f(
23 |      * x_0 + n).
24 |      * This determines a polynomial f(x) whose degree is at most
25 |      * n.
26 |      * Then you can call sample(x) and you get the value of f(x)
27 |      * .
28 |      * Complexity of init() and sample() are both O(n).
29 |      */
30 |     int m, shift; // m = n + 1
31 |     vector<int> v, mul;
32 |     // You can use this function if you don't have inv_fac array
33 |     // already.
34 |     void construct_inv_fac() {
35 |         long long fac = 1;
36 |         for (int i = 2; i < MAX_N; ++i) {
37 |             fac = fac * i % mod;
38 |         }
39 |         inv_fac[MAX_N - 1] = fp(fac, mod - 2);
40 |         for (int i = MAX_N - 1; i >= 1; --i) {
41 |             inv_fac[i - 1] = inv_fac[i] * i % mod;

```

```

42 |         shift = ((1 - X_0) % mod + mod) % mod;
43 |         if (v.size() == 1) v.push_back(v[0]);
44 |         m = v.size();
45 |         mul.resize(m);
46 |     }
47 |     // You can use sample(x) instead of sample(x % mod).
48 |     int sample(int x) {
49 |         x = ((long long)x + shift) % mod;
50 |         x = (x < 0) ? (x + mod) : x;
51 |         long long now = 1;
52 |         for (int i = m; i >= 1; --i) {
53 |             mul[i - 1] = now;
54 |             now = now * (x - i) % mod;
55 |         }
56 |         int ret = 0;
57 |         bool neg = (m - 1) & 1;
58 |         now = 1;
59 |         for (int i = 1; i <= m; ++i) {
60 |             int up = now * mul[i - 1] % mod;
61 |             int down = inv_fac[m - i] * inv_fac[i - 1] % mod;
62 |             int tmp = ((long long)v[i - 1] * up % mod) * down
63 |                 % mod;
64 |             ret += (neg && tmp) ? (mod - tmp) : (tmp);
65 |             ret = (ret >= mod) ? (ret - mod) : ret;
66 |             now = now * (x - i) % mod;
67 |             neg ^= 1;
68 |         }
69 |         return ret;
70 |     }
71 | };
72 |
73 | int main() {
74 |     int n; cin >> n;
75 |     vector<int> v(n);
76 |     for (int i = 0; i < n; ++i) {
77 |         cin >> v[i];
78 |     }
79 |     Lagrange L;
80 |     L.construct_inv_fac();
81 |     L.init(0, v);
82 |     int x; cin >> x;
83 |     cout << L.sample(x);

```

7.8 Linear Mod Inverse [ecf71e]

```

1 | // 線性求 1-based a[i] 對 p 的乘法反元素
2 | vector<int> s(n+1, 1), invS(n+1), invA(n+1);
3 | for (int i=1; i<=n; i++) s[i] = s[i-1]*a[i]%p;
4 | invS[n] = qp(s[n], p-2, p);
5 | for (int i=n; i>=1; i--) invS[i-1] = invS[i]*a[i]%p;
6 | for (int i=1; i<=n; i++) invA[i] = invS[i]*s[i-1]%p;

```

7.9 Lucas's Theorem [b37dcf]

```

1 | // 對於很大的 C^n_m 對質數 p 取模，只要 p 不大就可以用。
2 | int Lucas(int n, int m, int p){
3 |     if (m==0) return 1;
4 |     return (C(n%p, m%p, p)*Lucas(n/p, m/p, p)%p);
5 | }

```

7.10 Matrix [8d1a23]

```

1 | struct Matrix{

```



```

2   int n, m;
3   vector<vector<int>> arr;
4
5   Matrix(int _n, int _m){
6       n = _n;
7       m = _m;
8       arr.assign(n, vector<int>(m));
9   }
10
11  vector<int> & operator [] (int i){
12      return arr[i];
13  }
14
15  Matrix operator * (Matrix b){
16      Matrix ret(n, b.m);
17      for (int i=0 ; i<n ; i++){
18          for (int j=0 ; j<b.m ; j++){
19              for (int k=0 ; k<m ; k++){
20                  ret.arr[i][j] += arr[i][k]*b.arr[k][j]%
21                      MOD;
22                  ret.arr[i][j] %= MOD;
23              }
24          }
25      }
26      return ret;
27  }
28
29  Matrix pow(int p){
30      Matrix ret(n, n), mul = *this;
31      for (int i=0 ; i<n ; i++){
32          ret.arr[i][i] = 1;
33      }
34
35      for ( ; p ; p>=1){
36          if (p&1) ret = ret*mul;
37          mul = mul*mul;
38      }
39
40      return ret;
41  }
42
43  int det(){
44      vector<vector<int>> arr = this->arr;
45      bool flag = false;
46      for (int i=0 ; i<n ; i++){
47          int target = -1;
48          for (int j=i ; j<n ; j++){
49              if (arr[j][i]){
50                  target = j;
51                  break;
52              }
53          }
54          if (target==-1) return 0;
55          if (i!=target){
56              swap(arr[i], arr[target]);
57              flag = !flag;
58          }
59
60          for (int j=i+1 ; j<n ; j++){
61              if (!arr[j][i]) continue;
62              int freq = arr[j][i]*qp(arr[i][i], MOD-2)%MOD;
63
64              for (int k=i ; k<n ; k++){
65                  arr[j][k] -= freq*arr[i][k];
66                  arr[j][k] = (arr[j][k]%MOD+MOD)%MOD;

```

```

66          }
67      }
68  }
69
70  int ret = !flag ? 1 : MOD-1;
71  for (int i=0 ; i<n ; i++){
72      ret *= arr[i][i];
73      ret %= MOD;
74  }
75  return ret;
76  }
77  };

```

7.11 Matrix 01 [8d542a]

```

1   const int MAX_N = (1LL<<12);
2   struct Matrix{
3       int n, m;
4       vector<bitset<MAX_N>> arr;
5
6       Matrix(int _n, int _m){
7           n = _n;
8           m = _m;
9           arr.resize(n);
10      }
11
12      Matrix operator * (Matrix b){
13          Matrix b_t(b.m, b.n);
14          for (int i=0 ; i<b.n ; i++){
15              for (int j=0 ; j<b.m ; j++){
16                  b_t.arr[j][i] = b.arr[i][j];
17              }
18          }
19
20          Matrix ret(n, b.m);
21          for (int i=0 ; i<n ; i++){
22              for (int j=0 ; j<b.m ; j++){
23                  ret.arr[i][j] = (arr[i]&b_t.arr[j]).count()
24                      &1;
25              }
26          }
27      }
28  };

```

7.12 Matrix Tree Theorem

目標：給定一張無向圖，問他的生成樹數量。
方法：先把所有自環刪掉，定義 Q 為以下矩陣

$$Q_{i,j} = \begin{cases} \deg(v_i) & \text{if } i = j \\ -(\text{邊 } v_i v_j \text{ 的數量}) & \text{otherwise} \end{cases}$$

接著刪掉 Q 的第一個 row 跟 column，它的 determinant 就是答案。
目標：給定一張有向圖，問他的以 r 為根，可以走到所有點生成樹數量。

方法：先把所有自環刪掉，定義 Q 為以下矩陣

$$Q_{i,j} = \begin{cases} \deg_{in}(v_i) & \text{if } i = j \\ -(\text{邊 } v_i v_j \text{ 的數量}) & \text{otherwise} \end{cases}$$

接著刪掉 Q 的第 r 個 row 跟 column，它的 determinant 就是答案。

7.13 Miller Rabin [24bd0d]

```

1   // O(k Log^3 n), k = llsprp.size()
2   typedef Uint unsigned long long;
3   Uint modmul(Uint a, Uint b, Uint m) {
4       int ret = a*b - m*(Uint)((long double)a*b/m);
5       return ret + m*(ret < 0) - m*(ret >= (int)m);
6   }
7
8   int qp(int b, int p, int m){
9       int ret = 1;
10      for ( ; p ; p>=1){
11          if (p&1) ret = modmul(ret, b, m);
12          b = modmul(b, b, m);
13      }
14      return ret;
15  }
16
17  // ed23aa
18  vector<int> llsprp = {2, 325, 9375, 28178, 450775, 9780504,
19      1795265022};
20  bool is_prime(int n, vector<int> sprp = llsprp){
21      if (n==2) return 1;
22      if (n<2 || n%2==0) return 0;
23
24      int t = 0;
25      int u = n-1;
26      for ( ; u%2==0 ; t++) u>>=1;
27
28      for (int i=0 ; i<sprp.size() ; i++){
29          int a = sprp[i]%n;
30          if (a==0 || a==1 || a==n-1) continue;
31          int x = qp(a, u, n);
32          if (x==1 || x==n-1) continue;
33          for (int j=0 ; j<t ; j++){
34              x = modmul(x, x, n);
35              if (x==1) return 0;
36              if (x==n-1) break;
37          }
38
39          if (x==n-1) continue;
40          return false;
41      }
42
43      return true;

```

7.14 Pollard Rho [a5daef]

```

1   mt19937 seed(chrono::steady_clock::now().time_since_epoch().
2       count());
3   int rnd(int l, int r){
4       return uniform_int_distribution<int>(l, r)(seed);
5   }
6
7   // O(n^{1/4}) 回傳 1 或自己的因數、記得先判斷 n 是不是質數
8   // (用 Miller-Rabin)
9   // c1670c
10  int Pollard_Rho(int n){
11      int s = 0, t = 0;
12      int c = rnd(1, n-1);
13
14      int step = 0, goal = 1;
15      int val = 1;

```

```

15 for (goal=1 ; ; goal<=1, s=t, val=1){
16     for (step=1 ; step<=goal ; step++){
17
18         t = ((__int128)t*t+c)%n;
19         val = ((__int128)val*abs(t-s)%n;
20
21         if ((step % 127) == 0){
22             int d = __gcd(val, n);
23             if (d>1) return d;
24         }
25     }
26
27     int d = __gcd(val, n);
28     if (d>1) return d;
29 }
30 }

```

7.15 Polynomial [51ca3b]

```

1 struct Poly {
2     int len, deg;
3     int *a;
4     // len = 2^k >= the original length
5     Poly(): len(0), deg(0), a(nullptr) {}
6     Poly(int _n) {
7         len = 1;
8         deg = _n - 1;
9         while (len < _n) len <= 1;
10        a = (ll*) calloc(len, sizeof(ll));
11    }
12    Poly(int l, int d, int *b) {
13        len = l;
14        deg = d;
15        a = b;
16    }
17    void resize(int _n) {
18        int len1 = 1;
19        while (len1 < _n) len1 <= 1;
20        int *res = (ll*) calloc(len1, sizeof(ll));
21        for (int i = 0; i < min(len, _n); i++) {
22            res[i] = a[i];
23        }
24        len = len1;
25        deg = _n - 1;
26        free(a);
27        a = res;
28    }
29    Poly& operator=(const Poly rhs) {
30        this->len = rhs.len;
31        this->deg = rhs.deg;
32        this->a = (ll*)realloc(this->a, sizeof(ll) * len);
33        copy(rhs.a, rhs.a + len, this->a);
34        return *this;
35    }
36    Poly operator*(Poly rhs) {
37        int l1 = this->len, l2 = rhs.len;
38        int d1 = this->deg, d2 = rhs.deg;
39        while (l1 > 0 and this->a[l1 - 1] == 0) l1--;
40        while (l2 > 0 and rhs.a[l2 - 1] == 0) l2--;
41        int l = 1;
42        while (l < max(l1 + l2 - 1, d1 + d2 + 1)) l <= 1;
43        int *x, *y, *res;
44        x = (ll*) calloc(l, sizeof(ll));
45        y = (ll*) calloc(l, sizeof(ll));
46        res = (ll*) calloc(l, sizeof(ll));

```

```

47        copy(this->a, this->a + l1, x);
48        copy(rhs.a, rhs.a + l2, y);
49        ntt.tran(l, x); ntt.tran(l, y);
50        FOR (i, 0, l - 1)
51            res[i] = x[i] * y[i] % mod;
52        ntt.tran(l, res, true);
53        free(x); free(y);
54        return Poly(l, d1 + d2, res);
55    }
56    Poly operator+(Poly rhs) {
57        int l1 = this->len, l2 = rhs.len;
58        int l = max(l1, l2);
59        Poly res;
60        res.len = l;
61        res.deg = max(this->deg, rhs.deg);
62        res.a = (ll*) calloc(l, sizeof(ll));
63        FOR (i, 0, l1 - 1) {
64            res.a[i] += this->a[i];
65            if (res.a[i] >= mod) res.a[i] -= mod;
66        }
67        FOR (i, 0, l2 - 1) {
68            res.a[i] += rhs.a[i];
69            if (res.a[i] >= mod) res.a[i] -= mod;
70        }
71        return res;
72    }
73    Poly operator-(Poly rhs) {
74        int l1 = this->len, l2 = rhs.len;
75        int l = max(l1, l2);
76        Poly res;
77        res.len = l;
78        res.deg = max(this->deg, rhs.deg);
79        res.a = (ll*) calloc(l, sizeof(ll));
80        FOR (i, 0, l1 - 1) {
81            res.a[i] += this->a[i];
82            if (res.a[i] >= mod) res.a[i] -= mod;
83        }
84        FOR (i, 0, l2 - 1) {
85            res.a[i] -= rhs.a[i];
86            if (res.a[i] < 0) res.a[i] += mod;
87        }
88        return res;
89    }
90    Poly operator*(const int rhs) {
91        Poly res;
92        res = *this;
93        FOR (i, 0, res.len - 1) {
94            res.a[i] = res.a[i] * rhs % mod;
95            if (res.a[i] < 0) res.a[i] += mod;
96        }
97        return res;
98    }
99    Poly(vector<int> f) {
100        int _n = f.size();
101        len = 1;
102        deg = _n - 1;
103        while (len < _n) len <= 1;
104        a = (ll*) calloc(len, sizeof(ll));
105        FOR (i, 0, deg) a[i] = f[i];
106    }
107    Poly derivative() {
108        Poly g(this->deg);
109        FOR (i, 1, this->deg) {
110            g.a[i - 1] = this->a[i] * i % mod;
111        }
112        return g;

```

```

113    }
114    Poly integral() {
115        Poly g(this->deg + 2);
116        FOR (i, 0, this->deg) {
117            g.a[i + 1] = this->a[i] * ::inv(i + 1) % mod;
118        }
119        return g;
120    }
121    Poly inv(int len1 = -1) {
122        if (len1 == -1) len1 = this->len;
123        Poly g(1); g.a[0] = ::inv(a[0]);
124        for (int l = 1; l < len1; l <= 1) {
125            Poly t; t = *this;
126            t.resize(l < 1);
127            t = g * t;
128            t.resize(l < 1);
129            Poly g1 = g * 2 - t;
130            swap(g, g1);
131        }
132        return g;
133    }
134    Poly ln(int len1 = -1) {
135        if (len1 == -1) len1 = this->len;
136        auto g = *this;
137        auto x = g.derivative() * g.inv(len1);
138        x.resize(len1);
139        x = x.integral();
140        x.resize(len1);
141        return x;
142    }
143    Poly exp() {
144        Poly g(1);
145        g.a[0] = 1;
146        for (int l = 1; l < len; l <= 1) {
147            Poly t, g1; t = *this;
148            t.resize(l < 1); t.a[0]++;
149            g1 = (t - g.ln(l < 1)) * g;
150            g1.resize(l < 1);
151            swap(g, g1);
152        }
153        return g;
154    }
155    Poly pow(ll n) {
156        Poly &a = *this;
157        int i = 0;
158        while (i <= a.deg and a.a[i] == 0) i++;
159        if (i and (n > a.deg or n * i > a.deg)) return Poly(a.deg + 1);
160        if (i == a.deg + 1) {
161            Poly res(a.deg + 1);
162            res.a[0] = 1;
163            return res;
164        }
165        Poly b(a.deg - i + 1);
166        int inv1 = ::inv(a.a[i]);
167        FOR (j, 0, b.deg)
168            b.a[j] = a.a[j + i] * inv1 % mod;
169        Poly res1 = (b.ln()) * (n % mod).exp() * (::power(a.a[i], n));
170        Poly res2(a.deg + 1);
171        FOR (j, 0, min((ll)(res1.deg), (ll)(a.deg - n * i)))
172            res2.a[j + n * i] = res1.a[j];
173        return res2;
174    }
175 };

```

7.16 Stirling's formula

$$n! \approx \sqrt{2\pi n} \left(\frac{n}{e}\right)^n$$

7.17 Theorem

1. $1 \sim x$ 質數的數量 $\approx \frac{x}{\ln x}$
2. x 的因數的數量 $\approx x^{\frac{1}{3}}$
3. x 的質因數的數量 $\approx \log \log x$
4. p is a prime number $\Leftrightarrow (p-1)! \equiv -1 \pmod{p}$
5. 每個正整數都可以表示成四個整數的平方和
6. 任何大於 2 的整數都可以表示成兩個質數的和
7. $n^{k-2} \cdot \prod_{i=1}^k s_i$ n 個點、 k 的連通塊、加上 $k-1$ 條邊使得變成一個連通圖的方法數、其中每個連通塊有 s_i 個點

7.18 josephus [0be067]

```
1 // n 個人、每 k 個人就刪除的約瑟夫遊戲
2 int josephus(int n, int k) {
3     if (n == 1)
4         return 0;
5     if (k == 1)
6         return n-1;
7     if (k > n)
8         return (josephus(n-1, k) + k) % n;
9     int cnt = n / k;
10    int res = josephus(n - cnt, k);
11    res -= n % k;
12    if (res < 0)
13        res += n;
14    else
15        res += res / (k - 1);
16    return res;
17 }
```

7.19 二元一次方程式

$$\begin{cases} ax + by = e \\ cx + dy = f \end{cases} = \begin{cases} x = \frac{ed-bf}{ad-bc} \\ y = \frac{af-ec}{ad-bc} \end{cases}$$

若 $x = \frac{0}{0}$ 且 $y = \frac{0}{0}$ ，則代表無限多組解。若 $x = \frac{*}{0}$ 且 $y = \frac{*}{0}$ ，則代表無解。

7.20 數論分塊 [8ccab5]

```
1 // 時間複雜度為 O(sqrt(n))
2 // 區間為 [l, r]
3 for(int i=1 ; i<=n ; i++){
4     int l = i, r = n/(n/i);
5     i = r;
6     ans.push_back(r);
7 }
```

7.21 最大質因數 [ca5e52]

```
1 void max_fac(int n, int &ret){
2     if (n<=ret || n<2) return;
3     if (isprime(n)){
4         ret = max(ret, n);
5         return;
6     }
7
8     int p = Pollard_Rho(n);
9     max_fac(p, ret), max_fac(n/p, ret);
10 }
```

7.22 歐拉公式 [85f3b1]

```
1 // phi(n) = 小於 n 並與 n 互質的正整數數量。
2 // O(sqrt(n)) · 回傳 phi(n)
3 int phi(int n){
4     int ret = n;
5
6     for (int i=2 ; i<=n ; i++){
7         if (n%i==0){
8             while (n%i==0) n /= i;
9             ret = ret*(i-1)/i;
10        }
11    }
12    if (n>1) ret = ret*(n-1)/n;
13    return ret;
14 }
15
16 // O(n Log n) · 回傳 1~n 的 phi 值
17 vector<int> phi_1_to_n(int n){
18     vector<int> phi(n+1);
19     phi[0]=0;
20     phi[1]=1;
21
22     for (int i=2 ; i<=n ; i++){
23         phi[i]=i-1;
24     }
25
26     for (int i=2 ; i<=n ; i++){
27         for (int j=2*i ; j<=n ; j+=i){ // 枚舉所有倍數
28             phi[j]-=phi[i];
29         }
30     }
31
32     return phi;
33 }
34 }
```

7.23 歐拉定理

若 a, m 互質，則：

$$a^n \equiv a^{n \bmod \varphi(m)} \pmod{m}$$

若 a, m 不互質，則：

$$a^n \equiv a^{\varphi(m) + [n \bmod \varphi(m)]} \pmod{m}$$

7.24 錯排公式

錯排公式：(n 個人中，每個人皆不再原來位置的組合數)

$$dp_i = \begin{cases} 1 & i = 0 \\ 0 & i = 1 \\ (i-1)(dp_{i-1} + dp_{i-2}) & \text{otherwise} \end{cases}$$

8 String

8.1 AC automation [018290]

```
1 struct ACAutomation{
2     vector<vector<int>> go;
3     vector<int> fail, match, pos;
4     int sz = 0; // 有效節點為 [0, sz] · 開陣列的時候要小心!!!
5
6     ACAutomation(int n) : go(n, vector<int>(26)), fail(n),
7         match(n) {}
8
9     void add(string s){
10        int now = 0;
11        for (char c : s){
12            if (!go[now][c-'a']) go[now][c-'a'] = ++sz;
13            now = go[now][c-'a'];
14        }
15        pos.push_back(now);
16    }
17
18    void build(){
19        queue<int> que;
20        for (int i=0 ; i<26 ; i++){
21            if (go[0][i]) que.push(go[0][i]);
22        }
23        while (que.size()){
24            int u = que.front();
25            que.pop();
26            for (int i=0 ; i<26 ; i++){
27                if (go[u][i]){
28                    fail[go[u][i]] = go[fail[u]][i];
29                    que.push(go[u][i]);
30                }else go[u][i] = go[fail[u]][i];
31            }
32        }
33
34        // counting pattern
35        void buildMatch(string &s){
36            int now = 0;
37            for (char c : s){
38                now = go[now][c-'a'];
39                match[now]++;
40            }
41
42            vector<int> in(sz+1), que;
43            for (int i=1 ; i<=sz ; i++) in[fail[i]]++;
44            for (int i=1 ; i<=sz ; i++) if (in[i]==0) que.push_back(i);
45
46            for (int i=0 ; i<que.size() ; i++){
47                int now = que[i];
48                match[fail[now]] += match[now];
49                if (--in[fail[now]]==0) que.push_back(fail[now]);
50            }
51        }
```

51 | };

8.2 Enumerate Runs [94ca46]

```

1 vector<array<int, 3>> enumerate_run(string s){
2
3
4     int n = s.size();
5     SuffixArray sa(s), saBar(string(s.rbegin(), s.rend()));
6     sa.init_lcp(), saBar.init_lcp();
7
8     set<pair<int, int>> ss;
9     vector<array<int, 3>> runs;
10
11     for (int len=1 ; len<=n ; len++){
12         vector<int> lcp;
13         for (int i=0 ; i+len<n ; i+=len){
14             int pos1 = sa.pos[i];
15             int pos2 = sa.pos[i+len];
16             lcp.push_back(sa.get_lcp(pos1, pos2));
17         }
18
19         for (int ll=0, rr=0 ; ll<lcp.size() ; rr++, ll=rr){
20             while (rr<lcp.size() && lcp[rr]>=len) rr++;
21
22             int preLen = 0;
23             if (ll!=0){
24                 int p = n-1;
25                 int pos1 = saBar.pos[p-(ll*len-1)];
26                 int pos2 = saBar.pos[p-((ll+1)*len-1)];
27                 preLen = saBar.get_lcp(pos1, pos2);
28             }
29             int sufLen = rr<lcp.size() ? lcp[rr] : 0;
30
31             int ansL = ll*len-preLen, ansR = (rr+1)*len-1+
                sufLen;
32             if (ansL!=ansR && ansR-ansL+1>=2*len && ss.find({
                ansL, ansR+1})==ss.end()){
33                 ss.insert({ansL, ansR+1});
34                 runs.push_back({len, ansL, ansR+1});
35             }
36         }
37     }
38
39     return runs;
40 }

```

8.3 Hash [942f42]

```

1 mt19937 seed(chrono::steady_clock::now().time_since_epoch().
2   count());
3 int rng(int l, int r){
4     return uniform_int_distribution<int>(l, r)(seed);
5 }
6 int A = rng(1e5, 8e8);
7 const int B = 1e9+7;
8
9 // 2f6192
10 struct RollingHash{
11     vector<int> Pow, Pre;
12     RollingHash(string s = ""){
13         Pow.resize(s.size());
14         Pre.resize(s.size());
15
16         for (int i=0 ; i<s.size() ; i++){

```

```

16         if (i==0){
17             Pow[i] = 1;
18             Pre[i] = s[i];
19         }else{
20             Pow[i] = Pow[i-1]*A%B;
21             Pre[i] = (Pre[i-1]*A+s[i])%B;
22         }
23     }
24
25     return;
26 }
27
28 int get(int l, int r){ // 取得 [l, r] 的數值
29     if (l==0) return Pre[r];
30     int res = (Pre[r]-Pre[l-1]*Pow[r-l+1])%B;
31     if (res<0) res += B;
32     return res;
33 }
34 };

```

8.4 KMP [7b95d6]

```

1 // KMP[i] = s[0...i] 的最長共同前後綴長度 · KMP[KMP[i]-1] 可以
2   跳 fail Link
3 // e5b7ce
4 vector<int> KMP(string &s){
5     vector<int> ret(n);
6     for (int i=1 ; i<s.size() ; i++){
7         int j = ret[i-1];
8         while (j && s[i]!=s[j]) j = ret[j-1];
9         ret[i] = j + (s[i]==s[j]);
10    }
11    return ret;
12 }

```

8.5 Manacher [9a4b4d]

```

1 string Manacher(string str) {
2     string tmp = "$#";
3     for(char i : str) {
4         tmp += i;
5         tmp += '#';
6     }
7
8     vector<int> p(tmp.size(), 0);
9     int mx = 0, id = 0, len = 0, center = 0;
10    for(int i=1 ; i<(int)tmp.size() ; i++) {
11        p[i] = mx > i ? min(p[id*2-i], mx-i) : 1;
12
13        while(tmp[i+p[i]] == tmp[i-p[i]]) p[i]++;
14        if(mx<i+p[i]) mx = i+p[i], id = i;
15        if(len<p[i]) len = p[i], center = i;
16    }
17    return str.substr((center-len)/2, len-1);
18 }

```

8.6 Min Rotation [b24786]

```

1 int minRotation(string s) {
2     int a = 0, n = s.size();
3     s += s;
4
5     for (int b=0 ; b<n ; b++){
6         for (int k=0 ; k<n ; k++){

```

```

7         if (a+k==b || s[a+k]<s[b+k]){
8             b += max(0LL, k-1);
9             break;
10        }
11        if (s[a+k]>s[b+k]){
12            a = b;
13            break;
14        }
15    }
16 }
17
18 return a;
19 }

```

8.7 Suffix Array [96d6fc]

```

1 // 注意 · 當 |s|=1 時 · lcp 不會有值 · 務必測試 |s|=1 的 case
2 struct SuffixArray {
3     string s;
4     vector<int> sa, lcp;
5
6     // 0eea96
7     template<typename T>
8     void sais(const T s, int n, int *sa, int *lar, int *p,
9              int *t, int A) {
10        int *rnk = p + n, *q = p + n / 2, *bkt = lar + A;
11        int m = 0, i, j, x = t[n - 1] = 1, y = rnk[0] = -1,
12            cnt = -1;
13
14        for (i=n-2 ; ~i ; i--) t[i] = (s[i] == s[i + 1] ? t[i
15            + 1] : s[i] < s[i + 1]);
16        for (i=1 ; i<n ; i++) rnk[i] = t[i] && !t[i-1] ? (p[m
17            ]=i, m++) : -1;
18        fill_n(lar, A, 0);
19        for (i=0 ; i<n ; i++) ++lar[s[i]];
20        for (i=1 ; i<A ; i++) lar[i] += lar[i-1];
21        auto pushS = [&](int x) { sa[--bkt[s[x]]] = x; };
22        auto pushL = [&](int x) { sa[bkt[s[x]]++] = x; };
23        auto induce_sort = [&](int* v) {
24            fill_n(sa, n, 0);
25            copy_n(lar, A, bkt);
26            for (i=m-1 ; ~i ; i--) pushS(v[i]);
27            copy_n(lar, A - 1, bkt + 1);
28            for (i=0 ; i<n ; i++) if (sa[i] && !t[sa[i] - 1])
29                pushL(sa[i] - 1);
30            copy_n(lar, A, bkt);
31            for (i=n-1 ; ~i ; i--) if (sa[i] && t[sa[i] - 1])
32                pushS(sa[i] - 1);
33        };
34        induce_sort(p);
35        for (i=0 ; i<n ; i++){
36            if (~(x=rnk[sa[i]])){
37                j = y < 0 || memcmp(s + p[x], s + p[y], (p[x
38                    + 1] - p[x]) * sizeof(s[0]));
39                q[y = x] = cnt += j;
40            }
41        }
42        if (cnt+1<m) sais(q, m, sa, bkt, rnk, t + n, cnt + 1)
43            ;
44        else for (i=0 ; i<m ; i++) sa[q[i]] = i;
45        for (i=0 ; i<m ; i++) q[i] = p[sa[i]];
46        induce_sort(q);
47    }
48 }
49
50 // 8c731c, Lim 要調整成字元集大小 · _s 不可以有 0

```

```

42 template<typename T>
43 SuffixArray(const T& _s, int lim = 256) : s(_s) {
44     s.push_back(0);
45     int n = s.length();
46     sa.resize(n);
47     lcp.resize(n);
48     vector<int> bkt(n + lim * 2), p(n * 2), t(n * 2),
49         rank(n);
50     sais(&s[0], n, &sa[0], &bkt[0], &p[0], &t[0], lim);
51
52     for (int i=1 ; i<n ; i++) rank[sa[i]] = i;
53     for (int i=0, j, k=0 ; i<n-1 ; lcp[rank[i++]]=k){
54         for (k && k--, j=sa[rank[i]-1] ; i+k<s.size() &&
55             j+k<s.size() && s[i+k]==s[j+k] ; k++);
56     }
57     sa.erase(sa.begin());
58     lcp.erase(lcp.begin(), lcp.begin()+2);
59     s.pop_back();
60 }
61
62 // f49583
63 vector<int> pos; // pos[i] = i 這個值在 pos 的哪個地方
64 SparseTable st;
65 void init_lcp(){
66     pos.resize(sa.size());
67     for (int i=0 ; i<sa.size() ; i++){
68         pos[sa[i]] = i;
69     }
70     if (lcp.size()){
71         st.build(lcp);
72     }
73 }
74
75 // 用之前記得 init
76 // 查詢「sa 上的位置」的 x 跟 y 的 lcp
77 int get_lcp(int x, int y){
78     if (x==y) return s.size()-x;
79     if (x>y) swap(x, y);
80     return st.query(x, y);
81 }
82
83 // 回傳 [l1, r1] 跟 [l2, r2] 的 lcp · 0-based
84 int get_lcp(int l1, int r1, int l2, int r2){
85     int pos_1 = pos[l1], len_1 = r1-l1+1;
86     int pos_2 = pos[l2], len_2 = r2-l2+1;
87     if (pos_1>pos_2){
88         swap(pos_1, pos_2);
89         swap(len_1, len_2);
90     }
91
92     if (l1==l2){
93         return min(len_1, len_2);
94     }else{
95         return min({st.query(pos_1, pos_2), len_1, len_2
96             });
97     }
98 }
99
100 // 檢查 [l1, r1] 跟 [l2, r2] 的大小關係 · 0-based
101 // 如果前者小於後者 · 就回傳 <0 · 相等就回傳 =0 · 否則回傳
102 // >0
103 // 5b8db0
104 int substring_cmp(int l1, int r1, int l2, int r2){
105     int len_1 = r1-l1+1;

```

```

103 int len_2 = r2-l2+1;
104 int res = get_lcp(l1, r1, l2, r2);
105
106 if (res<len_1 && res<len_2){
107     return s[l1+res]-s[l2+res];
108 }else if (len_1==res && len_2==res){
109     return 0;
110 }else{
111     return len_1==res ? -1 : 1;
112 }
113 }
114
115 // 對於位置在 <=p 的後綴 · 找離他左邊/右邊最接近位置 >p 的
116 // 後綴的 lcp · 0-based
117 // pre[i] = s[i] 離他左邊最接近位置 >p 的後綴的 lcp · 0-
118 // based
119 // suf[i] = s[i] 離他右邊最接近位置 >p 的後綴的 lcp · 0-
120 // based
121 // da12fa
122 pair<vector<int>, vector<int>> get_left_and_right_lcp(int
123     p){
124     vector<int> pre(p+1);
125     vector<int> suf(p+1);
126
127     { // build pre
128         int now = 0;
129         for (int i=0 ; i<s.size() ; i++){
130             if (sa[i]<=p){
131                 pre[sa[i]] = now;
132                 if (i<lcp.size()) now = min(now, lcp[i]);
133             }else{
134                 if (i<lcp.size()) now = lcp[i];
135             }
136         }
137     }
138     { // build suf
139         int now = 0;
140         for (int i=s.size()-1 ; i>=0 ; i--){
141             if (sa[i]<=p){
142                 suf[sa[i]] = now;
143                 if (i-1>=0) now = min(now, lcp[i-1]);
144             }else{
145                 if (i-1>=0) now = lcp[i-1];
146             }
147         }
148     }
149
150     return {pre, suf};
151 }
152 };

```

8.8 Wildcard Matching [e93074]

```

1 const int B = 27;
2 string p;
3 for (int i=0 ; i<B ; i++) p += ('a'+i);
4 p += '*';
5 vector<vector<double>> res(B);
6 for (int i=0 ; i<B ; i++){
7     vector<double> ss, tt;
8     for (auto x : s) ss.push_back(x==p[i] || x=='*');
9     for (auto x : t) tt.push_back(x==p[i] || x=='*');
10    reverse(tt.begin(), tt.end());
11    res[i] = PolyMul(ss, tt);

```

```

13 }
14 for (int i=t.size()-1 ; i+t.size()-1<res[0].size() ; i++){
15     int total = 0;
16     for (int j=0 ; j<B-1 ; j++) total += (int)abs(round(res[j
17         ][i]));
18     total -= 25*(int)abs(round(res[26][i]));
19     cout << (total==t.size());

```

8.9 Z Algorithm [9d559a]

```

1 // z[i] 回傳 s[0...] 跟 s[i...] 的 lcp, z[0] = 0
2 vector<int> z_function(string s){
3     vector<int> z(s.size());
4     int l = -1, r = -1;
5     for (int i=1 ; i<s.size() ; i++){
6         z[i] = i>=r ? 0 : min(r-i, z[i-l]);
7         while (i+z[i]<s.size() && s[i+z[i]]==s[z[i]]) z[i]++;
8         if (i+z[i]>r) l=i, r=i+z[i];
9     }
10    return z;
11 }

```

8.10 k-th Substring [61f66b]

```

1 // 回傳 s 所有子字串 (完全不同) 中 · 第 k 大的
2 string k_th_substring(string &s, int k){
3     int n = s.size();
4     SuffixArray sa(s);
5     sa.init_lcp();
6
7     int prePrefix = 0, nowRank = 0;
8     for (int i=0 ; i<n ; i++){
9         int len = n-sa[i];
10        int add = len-prePrefix;
11
12        if (nowRank+add>=k){
13            return s.substr(sa[i], prePrefix+k-nowRank);
14        }
15
16        prePrefix = sa.lcp[i];
17        nowRank += add;
18    }
19 }

```