

Contents

1 Misc	2	5 Geometry	9	6.15 Tarjan Find AP	16
1.1 Default Code	2	5.1 misc	9	6.16 Theorem	16
1.2 Run	2	5.2 struct point	9	6.17 Tree Isomorphism	17
1.3 Custom Set PQ Sort	2	5.3 point / basic operation	9	6.18 圖方樹	17
1.4 Dynamic Bitset	2	5.4 point / operators	9	6.19 最大權閉合圖	18
1.5 Enumerate Subset	2	5.5 point / banana	9	7 Math	18
1.6 Fast Input	2	5.6 point / rayHitSeg	9	7.1 Burnside's Lemma	18
1.7 OEIS	2	5.7 point / else	9	7.2 CRT	18
1.8 OEIS	2	5.8 struct line	9	7.3 Catalan Number	19
1.9 Pragma	3	5.9 line / else	9	7.4 Josephus Problem	19
1.10 Python	3	5.10 struct polygon	9	7.5 Lagrange any x	19
1.11 Xor Basis	3	5.11 polygon / make convex hull	9	7.6 Lagrange continuous x	19
1.12 diff	3	5.12 polygon / in polygon	9	7.7 Linear Mod Inverse	19
1.13 disable ASLR	3	5.13 polygon / in convex	9	7.8 Lucas's Theorem	20
1.14 hash command	3	5.14 polygon / cycle search	10	7.9 Matrix	20
1.15 hash windows	3	5.15 polygon / line cut convex	10	7.10 Matrix 01	20
1.16 random int	3	5.16 polygon / segment across convex	10	7.11 Matrix Tree Theorem	20
2 Convolution	3	5.17 polygon / segment pass convex interior	10	7.12 Miller Rabin	20
2.1 FFT	3	5.18 polygon / convex tangent point	10	7.13 Pollard Rho	20
2.2 FFT any mod	4	5.19 polygon / halfplane intersection	10	7.14 Polynomial	21
2.3 FWT	4	5.20 polygon / minkowski sum	11	7.15 Stirling's formula	22
2.4 Min Convolution Concave Concave	4	5.21 struct Cir	11	7.16 Theorem	22
2.5 NTT mod 998244353	4	5.22 Cir / Cir intersect	11	7.17 josephus	22
3 Data-Structure	5	5.23 Cir / point tangent	11	7.18 二元一次方程式	22
3.1 BIT	5	5.24 Geometry Struct 3D	11	7.19 數論分塊	22
3.2 Disjoint Set Persistent	5	5.25 Pick's Theorem	11	7.20 最大質因數	22
3.3 PBDS GP Hash Table	5	6 Graph	11	7.21 歐拉公式	22
3.4 PBDS Order Set	5	6.1 SAT	11	7.22 歐拉定理	22
3.5 Segment Tree Add Set	5	6.2 Augment Path	12	7.23 錯排公式	22
3.6 Segment Tree Li Chao Line	6	6.3 C3C4	12	8 String	22
3.7 Segment Tree Li Chao Segment	6	6.4 Cut BCC	12	8.1 AC automation	22
3.8 Segment Tree Persistent	6	6.5 Dinic	13	8.2 Enumerate Runs	23
3.9 Sparse Table	7	6.6 Dominator Tree	13	8.3 Hash	23
3.10 Treap2	7	6.7 EdgeBCC	14	8.4 KMP	23
3.11 Trie	8	6.8 EnumeratePlanarFace	14	8.5 Manacher	23
4 Dynamic-Programming	8	6.9 HLD	14	8.6 Min Rotation	23
4.1 Digit DP	8	6.10 Kosaraju	15	8.7 Suffix Array	23
4.2 Integer Partition	8	6.11 Kuhn Munkres	15	8.8 Wildcard Matching	24
4.3 Knapsack On Tree	8	6.12 LCA	15	8.9 Z Algorithm	24
		6.13 MCMF	16	8.10 k-th Substring1	24
		6.14 Tarjan	16		

1 Misc

1.1 Default Code [24a798]

```
1 #include <bits/stdc++.h>
2 using namespace std;
3 #define int long long
4 #define debug(a...) cerr << #a << " = ", dout(a)
5 void dout() { cerr << "\n"; }
6 template <typename A, typename... B>
7 void dout(A a, B... b) { cerr << a << ' ', dout(b...); }
8
9 void solve(){
10
11 }
12
13 signed main(){
14     ios::sync_with_stdio(0), cin.tie(0);
15
16     int t = 1;
17     while (t--){
18         solve();
19     }
20
21     return 0;
22 }
```

1.2 Run

```
1 from os import *
2
3 f = "pA"
4
5 while 1:
6     i = input("input: ")
7     system("clear")
8     p = listdir(".")
9     if i != "":
10         f = i
11         print(f"file = {f}")
12         if system(f"g++ {f}.cpp -std=c++17 -Wall -Wextra -Wshadow
13             -O2 -D LOCAL -g -fsanitize=undefined,address -o {f}
14             "):
15             print("CE")
16             continue
17
18     for x in sorted(p):
19         if f in x and ".in" in x:
20             print(x)
21             if system(f"./{f} < {x}"):
22                 print("RE")
23             print()
```

1.3 Custom Set PQ Sort [d4df55]

```
1 // 所有自訂的結構體，務必檢查相等的 case，給所有元素一個排序
2 // 的依據
3 struct my_struct{
4     int val;
5     my_struct(int _val) : val(_val) {}
6 };
7
8 auto cmp = [](my_struct a, my_struct b) {
9     return a.val > b.val;
10 };
```

```
10
11 set<my_struct, decltype(cmp)> ss({1, 2, 3}, cmp);
12 priority_queue<my_struct, vector<my_struct>, decltype(cmp)>
13     pq(cmp, {1, 2, 3});
14 map<my_struct, my_struct, decltype(cmp)> mp({{1, 4}, {2, 5},
15     {3, 6}}, cmp);
```

1.4 Dynamic Bitset [c78aa8]

```
1 const int MAXN = 2e5 + 5;
2 template <int len = 1>
3 void solve(int n) {
4     if (n > len) {
5         solve<min(len*2, MAXN)>(n);
6         return;
7     }
8     bitset<len> a;
9 }
```

1.5 Enumerate Subset [a13e46]

```
1 // 時間複雜度  $O(3^n)$ 
2 // 枚舉每個 mask 的子集
3 for (int mask=0; mask<(1<<n); mask++){
4     for (int s=mask; s>=0; s=(s-1)&m){
5         // s 是 mask 的子集
6         if (s==0) break;
7     }
8 }
```

1.6 Fast Input [6f8879]

```
1 // fast IO
2 // 6f8879
3 inline char readchar(){
4     static char buffer[BUFSIZ], *now = buffer + BUFSIZ, *
5     end = buffer + BUFSIZ;
6     if (now == end)
7     {
8         if (end < buffer + BUFSIZ)
9             return EOF;
10        end = (buffer + fread(buffer, 1, BUFSIZ, stdin));
11        now = buffer;
12    }
13    return *now++;
14 }
15 inline int nextint(){
16     int x = 0, c = readchar(), neg = false;
17     while(('0' > c || c > '9') && c!='-' && c!=EOF) c =
18         readchar();
19     if(c == '-') neg = true, c = readchar();
20     while('0' <= c && c <= '9') x = (x<<3) + (x<<1) + (c-'0');
21     c = readchar();
22     if(neg) x = -x;
23     return x; // returns 0 if EOF
24 }
```

1.7 OEIS [25cf74]

```
1
2 // 若一個線性遞迴有 k 項，給他恰好 2*k 個項可以求出線性遞迴
3 // s = 1 1 3 7 17, 則它會回傳 1 2
4 vector<int> BerlekampMassey(vector<int> s) {
```

```
5     if (s.empty()) return vector<int>();
6     int n = s.size(), L = 0, m = 0;
7     vector<int> C(n), B(n), T;
8     C[0] = B[0] = 1;
9
10    int b = 1;
11    for (int i=0; i<n; i++) {
12        ++m; int d = s[i]%MOD;
13        for (int j=1; j<L+1; j++) d = (d+C[j]*s[i-j])%MOD;
14        if (!d) continue;
15        T = C; int coef = d*qp(b, MOD-2, MOD)%MOD;
16        for (int j=m; j<n; j++) C[j] = (C[j]-coef*B[j-m])%
17            MOD;
18        if (2*L>i) continue;
19        L = i+1-L; B=T; b=d; m=0;
20    }
21    C.resize(L+1); C.erase(C.begin());
22    for (int &x : C) x = (MOD-x)%MOD;
23    reverse(C.begin(), C.end());
24    return C;
25 }
```

1.8 OEIS

```
1 from fractions import Fraction
2
3 def BerlekampMassey(a: list[Fraction]) -> list[Fraction]:
4     def scale(v: list[Fraction], c: Fraction) -> list[
5         Fraction]:
6         return [x * c for x in v]
7
8     s: list[Fraction] = []
9     best: list[Fraction] = []
10    bestPos = 0
11
12    for i in range(len(a)):
13        error: Fraction = a[i]
14        for j in range(len(s)):
15            error -= s[j] * a[i - 1 - j]
16        if error == 0:
17            continue
18
19        if not s:
20            s = [Fraction(0)] * (i + 1)
21            bestPos = i
22            best = [Fraction(1, error)]
23            continue
24
25        fix = scale(best, error)
26        fix = [Fraction(0)] * (i - bestPos - 1) + fix
27
28        if len(fix) >= len(s):
29            best = scale(s, Fraction(-1, error))
30            best.insert(0, Fraction(1, error))
31            bestPos = i
32            if len(s) < len(fix):
33                s += [Fraction(0)] * (len(fix) - len(s))
34
35        for j in range(len(fix)):
36            s[j] += fix[j]
37
38    return list(reversed(s))
39
40 n = int(input())
41 l = list(map(Fraction, input().split()))
```

```

41 for i in range(len(l)):
42     coeffs = BerlekampMassey(l[:i+1])
43     for x in coeffs:
44         print(x, end=" ")
45     print()

```

1.9 Pragma [09d13e]

```

1 #pragma GCC optimize("O3,unroll-loops")
2 #pragma GCC target("avx,avx2,sse,sse2,sse3,sse4,popcnt")

```

1.10 Python

```

1 # Decimal
2 from decimal import *
3 getcontext().prec = 6
4
5 # system setting
6 sys.setrecursionlimit(100000)
7 sys.set_int_max_str_digits(10000)
8
9 # turtle
10 from turtle import *
11
12 N = 3000000010
13 setworldcoordinates(-N, -N, N, N)
14 hideturtle()
15 speed(100)
16
17 def draw_line(a, b, c, d):
18     teleport(a, b)
19     goto(c, d)
20
21 def write_dot(x, y, text, diff=1): # diff = 文字的偏移
22     teleport(x, y)
23     dot(5, "red")
24
25     teleport(x+N/100*diff, y+N/100*diff)
26     write(text, font=("Arial", 5, "bold"))
27
28 # usage
29 draw_line(*a[i], *(a[i-1]))
30 write_dot(*a[i], str(a[i]))
31 # 以自己左方 100 單位為圓心向前畫一個 90 度的弧 / 正五邊形
   ( 參數可以是負的 )
32 circle(100, extent = 90)
33 circle(100, steps = 5)
34 left(90) # 左轉 90 度
35 fd(-100) # 倒退 100 單位
36 penup()
37 pendown()
38
39 tracer(0, 0) # IO 優化 · 必須在程式碼最後手動 update()
40 pos() # 回傳目前座標
41 heading() # 回傳目前方向：0 是右方、90 是上方
42 color("red") # 改變顏色 · 可以用文字或是 #000000 的格式
43
44 # OOP
45 class Point:
46     def __init__(self, x, y):
47         self.x = x
48         self.y = y
49

```

```

50     def __add__(self, o): # use dir(int) to know operator
51         name
52         return Point(self.x+o.x, self.y+o.y)
53
54     @property
55     def distance(self):
56         return (self.x**2 + self.y**2)**(0.5)
57
58 a = Point(3, 4)
59 print(a.distance)
60
61 # Fraction
62 from fractions import Fraction
63 a = Fraction(Decimal(1.1))
64 a.numerator # 分子
65 a.denominator # 分母

```

1.11 Xor Basis [840136]

```

1 vector<int> basis;
2 void add_vector(int x){
3     for (auto v : basis){
4         x=min(x, x^v);
5     }
6     if (x) basis.push_back(x);
7 }
8
9 // 給一數字集合 S · 求能不能 XOR 出 x
10 bool check(int x){
11     for (auto v : basis){
12         x=min(x, x^v);
13     }
14     return 0;
15 }
16
17 // 給一數字集合 S · 求能 XOR 出多少數字
18 // 答案等於 2^{basis 的大小}
19
20 // 給一數字集合 S · 求 XOR 出最大的數字
21 int get_max(){
22     int ans=0;
23     for (auto v : basis){
24         ans=max(ans, ans^v);
25     }
26     return ans;
27 }

```

1.12 diff

```

1 set -e
2 g++ ac.cpp -o ac
3 g++ wa.cpp -o wa
4 for ((i=0;;i++))
5 do
6     echo "$i"
7     python3 gen.py > input
8     ./ac < input > ac.out
9     ./wa < input > wa.out
10    diff ac.out wa.out || break
11 done

```

1.13 disable ASLR

```

1 # Disable randomization of memory addresses
2 setarch `uname -m` -R ./yourProgram
3 setarch $(uname -m) -R

```

1.14 hash command

```

1 cat file.cpp | cpp -dD -P -fpreprocessed | tr -d "[:space:]"
   | md5sum | cut -c-6

```

1.15 hash windows

```

1 def get_hash(path):
2     from subprocess import run, PIPE
3     from hashlib import md5
4
5     p = run(
6         ["cpp", "-dD", "-P", "-fpreprocessed", path],
7         stdout = PIPE,
8         stderr = PIPE,
9         text = True
10    )
11
12    if p.returncode != 0:
13        raise RuntimeError(p.stderr)
14
15    s = ''.join(p.stdout.split())
16    ret = md5(s.encode()).hexdigest()
17    return ret[:6]
18
19 print(get_hash("Suffix_Array.cpp"))

```

1.16 random int [9cc603]

```

1 mt19937 seed(chrono::steady_clock::now().time_since_epoch().
   count());
2 int rng(int l, int r){
3     return uniform_int_distribution<int>(l, r)(seed);
4 }

```

2 Convolution

2.1 FFT [16591a]

```

1 typedef complex<double> cd;
2
3 // 778272
4 void FFT(vector<cd> &a) {
5     int n = a.size(), L = 31-__builtin_clz(n);
6     vector<complex<long double>> R(2, 1);
7     vector<cd> rt(2, 1);
8     for (int k=2 ; k<n ; k*=2){
9         R.resize(n), rt.resize(n);
10        auto x = polar(1.0L, acos(-1.0L) / k);
11        for (int i=k ; i<2*k ; i++) rt[i] = R[i] = (i&1 ? R[i/2]*x : R[i/2]);
12    }
13
14    vector<int> rev(n);
15    for (int i=0 ; i<n ; i++) rev[i] = (rev[i/2] | (i&1)<<L) /2;
16    for (int i=0 ; i<n ; i++) if (i<rev[i]) swap(a[i], a[rev[i]]);
17    for (int k=1 ; k<n ; k*=2){
18        for (int i=0 ; i<n ; i+=2*k){

```

```

19     for (int j=0 ; j<k ; j++){
20         // cd z = rt[j+k] * a[i+j+k];
21         auto x = (double *)&rt[j+k], y = (double *)&a
            [i+j+k];
22         cd z(x[0]*y[0] - x[1]*y[1], x[0]*y[1] + x[1]*
            y[0]);
23         a[i+j+k] = a[i+j]-z;
24         a[i+j] += z;
25     }
26 }
27 }
28 }
29
30 // 192528
31 vector<double> PolyMul(const vector<double> a, const vector<
    double> b){
32     if (a.empty() || b.empty()) return {};
33     vector<double> res(a.size()+b.size()-1);
34     int L = 32 - __builtin_clz(res.size()), n = 1<<L;
35     vector<cd> in(n), out(n);
36     copy(a.begin(), a.end(), in.begin());
37     for (int i=0 ; i<b.size() ; i++) in[i].imag(b[i]);
38     FFT(in);
39     for (cd& x : in) x *= x;
40     for (int i=0 ; i<n ; i++) out[i] = in[-i & (n - 1)] -
        conj(in[i]);
41     FFT(out);
42     for (int i=0 ; i<res.size() ; i++) res[i] = imag(out[i])
        / (4 * n);
43     return res;
44 }

```

2.2 FFT any mod [412000]

```

1 // n=524288, ~=400ms
2 const int MOD = 998244353;
3 typedef complex<double> cd;
4
5 // bb6d94
6 void FFT(vector<cd> &a) {
7     int n = a.size(), L = 31-__builtin_clz(n);
8     vector<complex<long double>> R(2, 1);
9     vector<cd> rt(2, 1);
10    for (int k=2 ; k<n ; k*=2){
11        R.resize(n);
12        rt.resize(n);
13        auto x = polar(1.0L, acos(-1.0L) / k);
14        for (int i=k ; i<2*k ; i++){
15            rt[i] = R[i] = (i&1 ? R[i/2]*x : R[i/2]);
16        }
17    }
18 }
19
20 vector<int> rev(n);
21 for (int i=0 ; i<n ; i++) rev[i] = (rev[i/2] | (i&1)<<L)
    /2;
22 for (int i=0 ; i<n ; i++) if (i<rev[i]) swap(a[i], a[rev[
    i]]);
23 for (int k=1 ; k<n ; k*=2){
24     for (int i=0 ; i<n ; i+=2*k){
25         for (int j=0 ; j<k ; j++){
26             auto x = (double *)&rt[j+k];
27             auto y = (double *)&a[i+j+k];
28             cd z(x[0]*y[0] - x[1]*y[1], x[0]*y[1] + x[1]*
                y[0]);

```

```

29         a[i+j+k] = a[i+j]-z;
30         a[i+j] += z;
31     }
32 }
33 }
34 }
35
36 // c3dcf6
37 vector<int> PolyMul(vector<int> a, vector<int> b){
38     if (a.empty() || b.empty()) return {};
39     vector<int> res(a.size()+b.size()-1);
40     int B = 32-__builtin_clz(res.size()), n = (1<<B), cut = (
        int)(sqrt(MOD));
41     vector<cd> L(n), R(n), outs(n), outl(n);
42
43     for (int i=0 ; i<a.size() ; i++) L[i] = cd((int) a[i]/cut
        , (int)a[i]%cut);
44     for (int i=0 ; i<b.size() ; i++) R[i] = cd((int) b[i]/cut
        , (int)b[i]%cut);
45     FFT(L), FFT(R);
46     for (int i=0 ; i<n ; i++){
47         int j = -i&(n-1);
48         outl[j] = (L[i]+conj(L[j])) * R[i]/(2.0*n);
49         outs[j] = (L[i]-conj(L[j])) * R[i]/(2.0*n)/1i;
50     }
51     FFT(outl), FFT(outs);
52     for (int i=0 ; i<res.size() ; i++){
53         int av = (int)(real(outl[i])+0.5), cv = (int)(imag(
            outs[i])+0.5);
54         int bv = (int)(imag(outl[i])+0.5) + (int)(real(outs[
            i])+0.5);
55         res[i] = ((av%MOD*cut+bv) % MOD*cut+cv) % MOD;
56     }
57     return res;
58 }

```

2.3 FWT [e50788]

```

1 // 已經把 mint 刪掉 · 需要增加註解
2 vector<int> xor_convolution(vector<int> a, vector<int> b, int
    k) {
3     if (k==0) return vector<int>{a[0]*b[0]};
4     vector<int> aa(1 << (k - 1)), bb(1 << (k - 1));
5     for (int i=0 ; i<(1<<(k-1)) ; i++){
6         aa[i] = a[i] + a[i + (1 << (k - 1))];
7         bb[i] = b[i] + b[i + (1 << (k - 1))];
8     }
9     vector<int> X = xor_convolution(aa, bb, k - 1);
10    for (int i=0 ; i<(1<<(k-1)) ; i++){
11        aa[i] = a[i] - a[i + (1 << (k - 1))];
12        bb[i] = b[i] - b[i + (1 << (k - 1))];
13    }
14    vector<int> Y = xor_convolution(aa, bb, k - 1);
15    vector<int> c(1 << k);
16    for (int i=0 ; i<(1<<(k-1)) ; i++){
17        c[i] = (X[i] + Y[i]) / 2;
18        c[i + (1 << (k - 1))] = (X[i] - Y[i]) / 2;
19    }
20    return c;
21 };

```

2.4 Min Convolution Concave Concave [ffb28d]

```

1 // 需要增加註解
2 // min convolution

```

```

3 vector<int> mkk(vector<int> a, vector<int> b) {
4     vector<int> slope;
5     FOR (i, 1, ssize(a) - 1) slope.pb(a[i] - a[i - 1]);
6     FOR (i, 1, ssize(b) - 1) slope.pb(b[i] - b[i - 1]);
7     sort(all(slope));
8     slope.insert(begin(slope), a[0] + b[0]);
9     partial_sum(all(slope), begin(slope));
10    return slope;
11 }

```

2.5 NTT mod 998244353 [f9fed4]

```

1 const int MOD = (119 << 23) + 1, ROOT = 62; // = 998244353
2 // For p < 2^30 there is also e.g. 5 << 25, 7 << 26, 479 <<
3 // 21
4 // and 483 << 21 (same root). The last two are > 10^9.
5
6 // e169db
7 void NTT(vector<int> &a) {
8     int n = a.size();
9     int L = 31-__builtin_clz(n);
10    vector<int> rt(2, 1);
11    for (int k=2, s=2 ; k<n ; k*=2, s++){
12        rt.resize(n);
13        int z[] = {1, qp(ROOT, MOD>>s)};
14        for (int i=k ; i<2*k ; i++) rt[i] = rt[i/2]*z[i&1]%
            MOD;
15    }
16
17    vector<int> rev(n);
18    for (int i=0 ; i<n ; i++) rev[i] = (rev[i/2] | (i&1)<<L)/2;
19    for (int i=0 ; i<n ; i++){
20        if (i<rev[i]) swap(a[i], a[rev[i]]);
21    }
22
23    for (int k=1 ; k<n ; k*=2){
24        for (int i=0 ; i<n ; i+=2*k){
25            for (int j=0 ; j<k ; j++){
26                int z = rt[j+k]*a[i+j+k]%MOD, &ai = a[i+j];
27                a[i+j+k] = ai-z+(z>ai ? MOD : 0);
28                ai += (ai+z)>MOD ? z-MOD : z;
29            }
30        }
31    }
32 }
33
34 // 290957
35 vector<int> polyMul(vector<int> &a, vector<int> &b){
36     if (a.empty() || b.empty()) return {};
37     int s = a.size()+b.size()-1, B = 32-__builtin_clz(s), n =
        1<<B;
38     int inv = qp(n, MOD-2);
39     vector<int> L(a), R(b), out(n);
40     L.resize(n), R.resize(n);
41     NTT(L), NTT(R);
42     for (int i=0 ; i<n ; i++) out[-i&(n-1)] = L[i]*R[i]%MOD*
        inv%MOD;
43     NTT(out);
44     out.resize(s);
45     return out;
46 }

```

3 Data-Structure

3.1 BIT [7ef3a9]

```

1 vector<int> BIT(MAX_SIZE);
2
3 // const int MAX_N = (1<<20)
4 int k_th(int k){ // 回傳 BIT 中第 k 小的元素 (based-1)
5     int res = 0;
6     for (int i=MAX_N>>1; i>=1; i>>=1)
7         if (BIT[res+i]<k)
8             k -= BIT[res+=i];
9     return res+1;
10 }

```

3.2 Disjoint Set Persistent [447002]

```

1 struct Persistent_Disjoint_Set{
2     Persistent_Segment_Tree arr, sz;
3
4     void init(int n){
5         arr.init(n);
6         vector<int> v1;
7         for (int i=0; i<n; i++){
8             v1.push_back(i);
9         }
10        arr.build(v1, 0);
11
12        sz.init(n);
13        vector<int> v2;
14        for (int i=0; i<n; i++){
15            v2.push_back(1);
16        }
17        sz.build(v2, 0);
18    }
19
20    int find(int a){
21        int res = arr.query_version(a, a+1, arr.version.size()
22        (-1).val;
23        if (res==a) return a;
24        return find(res);
25    }
26
27    bool unite(int a, int b){
28        a = find(a);
29        b = find(b);
30
31        if (a!=b){
32
33            int sz1 = sz.query_version(a, a+1, arr.version.
34            size()-1).val;
35            int sz2 = sz.query_version(b, b+1, arr.version.
36            size()-1).val;
37
38            if (sz1<sz2){
39                arr.update_version(a, b, arr.version.size()
40                -1);
41                sz.update_version(b, sz1+sz2, arr.version.
42                size()-1);
43            }else{
44                arr.update_version(b, a, arr.version.size()
45                -1);
46                sz.update_version(a, sz1+sz2, arr.version.
47                size()-1);
48            }
49        }
50    }

```

```

42         return true;
43     }
44     return false;
45 }
46 };

```

3.3 PBDS GP Hash Table [866cf6]

```

1 #include <ext/pb_ds/assoc_container.hpp>
2 using namespace __gnu_pbds;
3 typedef tree<int, null_type, less<int>, rb_tree_tag,
4     tree_order_statistics_node_update> order_set;
5 struct custom_hash {
6     static uint64_t splitmix64(uint64_t x) {
7         // http://xorshift.di.unimi.it/splitmix64.c
8         x += 0x9e3779b97f4a7c15;
9         x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
10        x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
11        return x ^ (x >> 31);
12    }
13
14    size_t operator()(uint64_t x) const {
15        static const uint64_t FIXED_RANDOM = chrono::
16        steady_clock::now().time_since_epoch().count();
17        return splitmix64(x + FIXED_RANDOM);
18    }
19 };
20 gp_hash_table<int, int, custom_hash> ss;

```

3.4 PBDS Order Set [231774]

```

1 // .find_by_order(k) 回傳第 k 小的值 (based-0)
2 // .order_of_key(k) 回傳有多少元素比 k 小
3 // 不能在 #define int long long 後 #include 檔案
4 #include <ext/pb_ds/assoc_container.hpp>
5 #include <ext/pb_ds/tree_policy.hpp>
6 using namespace __gnu_pbds;
7 typedef tree<int, null_type, less<int>, rb_tree_tag,
8     tree_order_statistics_node_update> order_set;

```

3.5 Segment Tree Add Set [bb1898]

```

1 // [ll, rr), based-0
2 // 使用前記得 init(陣列大小), build(陣列名稱)
3 // add(LL, rr): 區間修改
4 // set(LL, rr): 區間賦值
5 // query(LL, rr): 區間求和 / 求最大值
6 struct SegmentTree{
7     struct node{
8         int add_tag = 0;
9         int set_tag = 0;
10        int sum = 0;
11        int ma = 0;
12    };
13
14    vector<node> arr;
15
16    SegmentTree(int n){
17        arr.resize(n<<2);
18    }
19
20    node pull(node A, node B){

```

```

21    node C;
22    C.sum = A.sum+B.sum;
23    C.ma = max(A.ma, B.ma);
24    return C;
25 }
26
27 // cce0c8
28 void push(int idx, int ll, int rr){
29     if (arr[idx].set_tag!=0){
30         arr[idx].sum = (rr-ll)*arr[idx].set_tag;
31         arr[idx].ma = arr[idx].set_tag;
32         if (rr-ll>1){
33             arr[idx*2+1].add_tag = 0;
34             arr[idx*2+1].set_tag = arr[idx].set_tag;
35             arr[idx*2+2].add_tag = 0;
36             arr[idx*2+2].set_tag = arr[idx].set_tag;
37         }
38         arr[idx].set_tag = 0;
39     }
40     if (arr[idx].add_tag!=0){
41         arr[idx].sum += (rr-ll)*arr[idx].add_tag;
42         arr[idx].ma += arr[idx].add_tag;
43         if (rr-ll>1){
44             arr[idx*2+1].add_tag += arr[idx].add_tag;
45             arr[idx*2+2].add_tag += arr[idx].add_tag;
46         }
47         arr[idx].add_tag = 0;
48     }
49 }
50
51 void build(vector<int> &v, int idx = 0, int ll = 0, int
52 rr = n){
53     if (rr-ll==1){
54         arr[idx].sum = v[ll];
55         arr[idx].ma = v[ll];
56     }else{
57         int mid = (ll+rr)/2;
58         build(v, idx*2+1, ll, mid);
59         build(v, idx*2+2, mid, rr);
60         arr[idx] = pull(arr[idx*2+1], arr[idx*2+2]);
61     }
62 }
63
64 void add(int ql, int qr, int val, int idx = 0, int ll =
65 0, int rr = n){
66     push(idx, ll, rr);
67     if (rr<=ql || qr<=ll) return;
68     if (ql<=ll && rr<=qr){
69         arr[idx].add_tag += val;
70         push(idx, ll, rr);
71         return;
72     }
73     int mid = (ll+rr)/2;
74     add(ql, qr, val, idx*2+1, ll, mid);
75     add(ql, qr, val, idx*2+2, mid, rr);
76     arr[idx]=pull(arr[idx*2+1], arr[idx*2+2]);
77 }
78
79 void set(int ql, int qr, int val, int idx=0, int ll=0,
80 int rr=n){
81     push(idx, ll, rr);
82     if (rr<=ql || qr<=ll) return;
83     if (ql<=ll && rr<=qr){
84         arr[idx].add_tag = 0;
85         arr[idx].set_tag = val;
86         push(idx, ll, rr);
87     }

```

```

84         return;
85     }
86     int mid = (ll+rr)/2;
87     set(q1, qr, val, idx*2+1, ll, mid);
88     set(q1, qr, val, idx*2+2, mid, rr);
89     arr[idx] = pull(arr[idx*2+1], arr[idx*2+2]);
90 }
91
92 node query(int q1, int qr, int idx = 0, int ll = 0, int
93           rr = n){
94     push(idx, ll, rr);
95     if (rr<=q1 || qr<=ll) return node();
96     if (q1<=ll && rr<=qr) return arr[idx];
97
98     int mid = (ll+rr)/2;
99     return pull(query(q1, qr, idx*2+1, ll, mid), query(q1
100   , qr, idx*2+2, mid, rr));

```

3.6 Segment Tree Li Chao Line [45b8ba]

```

1 // 全部都是 0-based
2 // 宣告：LC_Segment_Tree st(n);
3 // 函式：
4 // update({a, b})：插入一條  $y=ax+b$  的全域直線
5 // query(x)：查詢所有直線在位置  $x$  的最小值
6 const int MAX_V = 1e6+10; // 值域最大值
7
8 struct LC_Segment_Tree{
9     struct Node{ //  $y = ax+b$ 
10         int a = 0;
11         int b = INF;
12
13         int y(int x){
14             return a*x+b;
15         }
16     };
17     vector<Node> arr;
18
19     LC_Segment_Tree(int n = 0){
20         arr.resize(4*n);
21     }
22
23     void update(Node val, int idx = 0, int ll = 0, int rr =
24           MAX_V){
25         if (rr-ll==0) return;
26         if (rr-ll==1){
27             if (val.y(ll)<arr[idx].y(ll)){
28                 arr[idx] = val;
29             }
30             return;
31         }
32
33         int mid = (ll+rr)/2;
34         if (arr[idx].a > val.a) swap(arr[idx], val); // 原本
35           的線斜率要比較小
36         if (arr[idx].y(mid) < val.y(mid)){ // 交點在左邊
37             update(val, idx*2+1, ll, mid);
38         }else{ // 交點在右邊
39             swap(arr[idx], val); // 在左子樹中，新線比舊線還
           要好
           update(val, idx*2+2, mid, rr);

```

```

40         return;
41     }
42
43     int query(int x, int idx = 0, int ll = 0, int rr = MAX_V)
44     {
45         if (rr-ll==0) return INF;
46         if (rr-ll==1){
47             return arr[idx].y(ll);
48         }
49
50         int mid = (ll+rr)/2;
51         if (x<mid){
52             return min(arr[idx].y(x), query(x, idx*2+1, ll,
53           mid));
54         }else{
55             return min(arr[idx].y(x), query(x, idx*2+2, mid,
56           rr));
57         }
58     }
59 }
60 };

```

3.7 Segment Tree Li Chao Segment [2cb0a4]

```

1 // 全部都是 0-based
2 // 宣告：LC_Segment_Tree st(n);
3 // 函式：
4 // update_segment({a, b}, ql, qr)：在 [ql, qr] 插入一條  $y=ax+b$ 
5 // 的線段
6 // query(x)：查詢所有直線在位置  $x$  的最小值
7 const int MAX_V = 1e6+10; // 值域最大值
8
9 struct LC_Segment_Tree{
10     struct Node{ //  $y = ax+b$ 
11         int a = 0;
12         int b = INF;
13
14         int y(int x){
15             return a*x+b;
16         }
17     };
18     vector<Node> arr;
19
20     LC_Segment_Tree(int n = 0){
21         arr.resize(4*n);
22     }
23
24     void update(Node val, int idx = 0, int ll = 0, int rr =
25           MAX_V){
26         if (rr-ll==0) return;
27         if (rr-ll<=1){
28             if (val.y(ll)<arr[idx].y(ll)){
29                 arr[idx] = val;
30             }
31             return;
32         }
33
34         int mid = (ll+rr)/2;
35         if (arr[idx].a > val.a) swap(arr[idx], val); // 原本
36           的線斜率要比較小
37         if (arr[idx].y(mid) < val.y(mid)){ // 交點在左邊
38             update(val, idx*2+1, ll, mid);
39         }else{ // 交點在右邊
40             swap(arr[idx], val); // 在左子樹中，新線比舊線還
           要好

```

```

38         update(val, idx*2+2, mid, rr);
39     }
40     return;
41 }
42
43 // 在 [ql, qr] 加上一條 val 的線段
44 void update_segment(Node val, int ql, int qr, int idx =
45   0, int ll = 0, int rr = MAX_V){
46     if (rr-ll==0) return;
47     if (rr<=ql || qr<=ll) return;
48     if (ql<=ll && rr<=qr){
49         update(val, idx, ll, rr);
50         return;
51     }
52
53     int mid = (ll+rr)/2;
54     update_segment(val, ql, qr, idx*2+1, ll, mid);
55     update_segment(val, ql, qr, idx*2+2, mid, rr);
56     return;
57 }
58
59 int query(int x, int idx = 0, int ll = 0, int rr = MAX_V)
60 {
61     if (rr-ll==0) return INF;
62     if (rr-ll==1){
63         return arr[idx].y(ll);
64     }
65
66     int mid = (ll+rr)/2;
67     if (x<mid){
68         return min(arr[idx].y(x), query(x, idx*2+1, ll,
69           mid));
70     }else{
71         return min(arr[idx].y(x), query(x, idx*2+2, mid,
72           rr));
73     }
74 }
75 };

```

3.8 Segment Tree Persistent [3b5aa9]

```

1 // 全部都是 0-based
2 // Persistent_Segment_Tree st(n+q);
3 // st.build(v, 0);
4 // 函式：
5 // update_version(pos, val, ver)：對版本 ver 的 pos 位置改成
6 // val
7 // query_version(ql, qr, ver)：對版本 ver 查詢 [ql, qr] 的區
8 // 間和
9 // clone_version(ver)：複製版本 ver 到最新的版本
10 struct Persistent_Segment_Tree{
11     int node_cnt = 0;
12     struct Node{
13         int lc = -1;
14         int rc = -1;
15         int val = 0;
16     };
17     vector<Node> arr;
18     vector<int> version;
19
20     Persistent_Segment_Tree(int sz){
21         arr.resize(32*sz);
22         version.push_back(node_cnt++);
23         return;

```



```

22 }
23
24 void pull(Node &c, Node a, Node b){
25     c.val = a.val+b.val;
26     return;
27 }
28
29 void build(vector<int> &v, int idx, int ll = 0, int rr =
30     n){
31     auto &now = arr[idx];
32
33     if (rr-ll==1){
34         now.val = v[ll];
35         return;
36     }
37
38     int mid = (ll+rr)/2;
39     now.lc = node_cnt++;
40     now.rc = node_cnt++;
41     build(v, now.lc, ll, mid);
42     build(v, now.rc, mid, rr);
43     pull(now, arr[now.lc], arr[now.rc]);
44     return;
45 }
46
47 void update(int pos, int val, int idx, int ll = 0, int rr
48     = n){
49     auto &now = arr[idx];
50
51     if (rr-ll==1){
52         now.val = val;
53         return;
54     }
55
56     int mid = (ll+rr)/2;
57     if (pos<mid){
58         arr[node_cnt] = arr[now.lc];
59         now.lc = node_cnt;
60         node_cnt++;
61         update(pos, val, now.lc, ll, mid);
62     }else{
63         arr[node_cnt] = arr[now.rc];
64         now.rc = node_cnt;
65         node_cnt++;
66         update(pos, val, now.rc, mid, rr);
67     }
68
69     pull(now, arr[now.lc], arr[now.rc]);
70     return;
71 }
72
73 void update_version(int pos, int val, int ver){
74     update(pos, val, version[ver]);
75 }
76
77 Node query(int ql, int qr, int idx, int ll = 0, int rr =
78     n){
79     auto &now = arr[idx];
80
81     if (ql<=ll && rr<=qr) return now;
82     if (rr<=ql || qr<=ll) return Node();
83
84     int mid = (ll+rr)/2;
85
86     Node ret;
87     pull(ret, query(ql, qr, now.lc, ll, mid), query(ql,
88         qr, now.rc, mid, rr));

```

```

84     return ret;
85 }
86
87 Node query_version(int ql, int qr, int ver){
88     return query(ql, qr, version[ver]);
89 }
90
91 void clone_version(int ver){
92     version.push_back(node_cnt);
93     arr[node_cnt] = arr[version[ver]];
94     node_cnt++;
95 }
96 };

```

3.9 Sparse Table [31f22a]

```

1 struct SparseTable{
2     vector<vector<int>> st;
3     void build(vector<int> v){
4         int h = __lg(v.size());
5         st.resize(h+1);
6         st[0] = v;
7
8         for (int i=1 ; i<=h ; i++){
9             int gap = (1<<(i-1));
10            for (int j=0 ; j+gap<st[i-1].size() ; j++){
11                st[i].push_back(min(st[i-1][j], st[i-1][j+gap
12                    ]));
13            }
14        }
15
16        // 回傳 [ll, rr) 的最小值
17        int query(int ll, int rr){
18            int h = __lg(rr-ll);
19            return min(st[h][ll], st[h][rr-(1<<h)]);
20        }
21    };

```

3.10 Treap2 [3b0cca]

```

1 // 1-based · 請注意 MAX_N 是否足夠大
2 int root = 0;
3 int lc[MAX_N], rc[MAX_N];
4 int pri[MAX_N], val[MAX_N];
5 int sz[MAX_N], tag[MAX_N], fa[MAX_N], total[MAX_N];
6 // tag 為不包含自己 (僅要給子樹) 的資訊
7 int nodeCnt = 0;
8 int& new_node(int v){
9     nodeCnt++;
10    val[nodeCnt] = v;
11    total[nodeCnt] = v;
12    sz[nodeCnt] = 1;
13    pri[nodeCnt] = rand();
14    return nodeCnt;
15 }
16
17 void apply(int x, int V){
18     val[x] += V;
19     tag[x] += V;
20     total[x] += V*sz[x];
21 }
22
23 void push(int x){

```

```

24     if (tag[x]){
25         if (lc[x]) apply(lc[x], tag[x]);
26         if (rc[x]) apply(rc[x], tag[x]);
27     }
28     tag[x] = 0;
29 }
30 int pull(int x){
31     if (x){
32         fa[x] = 0;
33         sz[x] = 1+sz[lc[x]]+sz[rc[x]];
34         total[x] = val[x]+total[lc[x]]+total[rc[x]];
35         if (lc[x]) fa[lc[x]] = x;
36         if (rc[x]) fa[rc[x]] = x;
37     }
38     return x;
39 }
40
41 int merge(int a, int b){
42     if (!a || !b) return a|b;
43     push(a), push(b);
44
45     if (pri[a]>pri[b]){
46         rc[a] = merge(rc[a], b);
47         return pull(a);
48     }else{
49         lc[b] = merge(a, lc[b]);
50         return pull(b);
51     }
52 }
53
54 // [1, k] [k+1, n]
55 void split(int x, int k, int &a, int &b) {
56     if (!x) return a = b = 0, void();
57     push(x);
58     if (sz[lc[x]] >= k) {
59         split(lc[x], k, a, lc[x]);
60         b = x;
61         pull(a); pull(b);
62     }else{
63         split(rc[x], k - sz[lc[x]] - 1, rc[x], b);
64         a = x;
65         pull(a); pull(b);
66     }
67 }
68
69 // functions
70 // 回傳 x 在 Treap 中的位置
71 int get_pos(int x){
72     vector<int> sta;
73     while (fa[x]){
74         sta.push_back(x);
75         x = fa[x];
76     }
77     while (sta.size()){
78         push(x);
79         x = sta.back();
80         sta.pop_back();
81     }
82     push(x);
83
84     int res = sz[x] - sz[rc[x]];
85     while (fa[x]){
86         if (rc[fa[x]]==x){
87             res += sz[fa[x]]-sz[x];
88         }

```

```

89     x = fa[x];
90 }
91 return res;
92 }
93
94 // 1-based <前 [1, l-1] 個元素, [l, r] 個元素, [r+1, n] 個元素>
95 array<int, 3> cut(int x, int l, int r){
96     array<int, 3> ret;
97     split(x, r, ret[1], ret[2]);
98     split(ret[1], l-1, ret[0], ret[1]);
99     return ret;
100 }
101
102 void print(int x){
103     push(x);
104     if (lc[x]) print(lc[x]);
105     cerr << val[x] << " ";
106     if (rc[x]) print(rc[x]);
107 }

```

3.11 Trie [b6475c]

```

1 struct Trie{
2     struct Data{
3         int nxt[2]={0, 0};
4     };
5
6     int sz=0;
7     vector<Data> arr;
8
9     void init(int n){
10         arr.resize(n);
11     }
12
13     void insert(int n){
14         int now=0;
15         for (int i=N; i>=0; i--){
16             int v=(n>>i)&1;
17             if (!arr[now].nxt[v]){
18                 arr[now].nxt[v]=++sz;
19             }
20             now=arr[now].nxt[v];
21         }
22     }
23
24     int query(int n){
25         int now=0, ret=0;
26         for (int i=N; i>=0; i--){
27             int v=(n>>i)&1;
28             if (arr[now].nxt[1-v]){
29                 ret+=(1<<i);
30                 now=arr[now].nxt[1-v];
31             }else if (arr[now].nxt[v]){
32                 now=arr[now].nxt[v];
33             }else{
34                 return ret;
35             }
36         }
37         return ret;
38     }
39 }
40 } tr;

```

4 Dynamic-Programming

4.1 Digit DP [133f00]

```

1 #include <bits/stdc++.h>
2 using namespace std;
3
4 long long l, r;
5 long long dp[20][10][2][2]; // dp[pos][pre][limit] = 後 pos
6 // 位 · pos 前一位是 pre · (是/否) 有上界 · (是/否) 有前綴零
7 // 的答案數量
8
9 long long memorize_search(string &s, int pos, int pre, bool
10 limit, bool lead){
11
12     // 已經被找過了 · 直接回傳值
13     if (dp[pos][pre][limit][lead]!=-1) return dp[pos][pre][
14 limit][lead];
15
16     // 已經搜尋完畢 · 紀錄答案並回傳
17     if (pos==(int)s.size()){
18         return dp[pos][pre][limit][lead] = 1;
19     }
20
21     // 枚舉目前的位數數字是多少
22     long long ans = 0;
23     for (int now=0; now<=(limit ? s[pos]-'0' : 9); now++){
24         if (now==pre){
25
26             // 1~9 絕對不能連續出現
27             if (pre!=0) continue;
28
29             // 如果已經不在前綴零的範圍內 · 0 不能連續出現
30             if (lead==false) continue;
31         }
32
33         ans += memorize_search(s, pos+1, now, limit&(now==(s[
34 pos]-'0')), lead&(now==0));
35     }
36
37     // 已經搜尋完畢 · 紀錄答案並回傳
38     return dp[pos][pre][limit][lead] = ans;
39 }
40
41 // 回傳 [0, n] 有多少數字符合條件
42 long long find_answer(long long n){
43     memset(dp, -1, sizeof(dp));
44     string tmp = to_string(n);
45
46     return memorize_search(tmp, 0, 0, true, true);
47 }
48
49 int main(){
50     // input
51     cin >> l >> r;
52
53     // output - 計算 [l, r] 有多少數字任意兩個位數都不相同
54     cout << find_answer(r)-find_answer(l-1) << "\n";
55
56     return 0;
57 }

```

4.2 Integer Partition

$dp[i][x]$ = 要將整數 x 拆成 i 堆的「組合數」

$dp[i+1][x+1] += dp[i][x]$ (創造新的一堆)
 $dp[i][x+i] += dp[i][x]$ (把每一堆都增加 1)

4.3 Knapsack On Tree [df69b1]

```

1 // 需要重構 · 需要增加註解
2 #include <bits/stdc++.h>
3 #define F first
4 #define S second
5 #define all(x) begin(x), end(x)
6 using namespace std;
7
8 #define chmax(a, b) (a) = (a) < (b) ? (b) : (a)
9 #define chmin(a, b) (a) = (a) < (b) ? (a) : (b)
10
11 #define ll long long
12
13 #define FOR(i, a, b) for (int i = a; i <= b; i++)
14
15 int N, W, cur;
16 vector<int> w, v, sz;
17 vector<vector<int>> adj, dp;
18
19 void dfs(int x) {
20     sz[x] = 1;
21     for (int i : adj[x]) dfs(i), sz[x] += sz[i];
22     cur++;
23     // choose x
24     for (int i=w[x]; i<=W; i++){
25         dp[cur][i] = dp[cur-1][i-w[x]] + v[x];
26     }
27     // not choose x
28     for (int i=0; i<=W; i++){
29         chmax(dp[cur][i], dp[cur-1][i]);
30     }
31 }
32
33 signed main() {
34     cin >> N >> W;
35     adj.resize(N+1);
36     w.assign(N+1, 0);
37     v.assign(N+1, 0);
38     sz.assign(N+1, 0);
39     dp.assign(N+2, vector<int>(W+1, 0));
40     for (int i=1; i<=N; i++){
41         int p; cin >> p;
42         adj[p].push_back(i);
43     }
44
45     for (int i=1; i<=N; i++) cin >> w[i];
46     for (int i=1; i<=N; i++) cin >> v[i];
47     dfs(0);
48     cout << dp[N+1][W] << "\n";
49 }

```

4.4 SOS DP [8dfa8b]

```

1 // 總時間複雜度為  $O(n \cdot 2^n)$ 
2 // 計算  $dp[i]$  =  $i$  所有 bit mask 子集的和
3 for (int i=0; i<n; i++){
4     for (int mask=0; mask<(1<<n); mask++){
5         if ((mask>>i)&1){

```



```

6         dp[mask] += dp[mask^(1<<i)];
7     }
8 }
9 }

```

5 Geometry

5.1 misc [3ef351]

```

1 using ld = double;
2
3 // 判斷數值正負：{1:正數,0:零,-1:負數}
4 int sign(long long x) {return (x >= 0) ? ((bool)x) : -1; }
5 int sign(ld x) {return (abs(x) < 1e-9) ? 0 : (x>0 ? 1 : -1);}

```

5.2 struct point [5cc4af]

```

1 template<typename T>
2 struct point {
3     T x, y;
4     point() {}
5     point(const T &x, const T &y) : x(x), y(y) {}
6     explicit operator point<ld>() {return point<ld>(x, y); }
7 };

```

5.3 point / basic operation [c415da]

```

1 point operator+(point b) {return {x+b.x, y+b.y}; }
2 point operator-(point b) {return {x-b.x, y-b.y}; }
3 point operator*(T b) {return {x*b, y*b}; }
4 point operator/(T b) {return {x/b, y/b}; }
5 bool operator==(point b) {return x==b.x && y==b.y; }
6
7 T operator*(point b) {return x * b.x + y * b.y; }
8 T operator^(point b) {return x * b.y - y * b.x; }

```

5.4 point / operators [fc43e4]

```

1 // 逆時針極角排序
2 bool side() const{return (y == 0) ? (x > 0) : (y < 0); }
3 bool operator<(const point &b) const {
4     return side() == b.side() ?
5         (x*b.y > b.x*y) : side() < b.side();
6 }
7 friend ostream& operator<<(ostream& os, point p) {
8     return os << "(" << p.x << ", " << p.y << ")";
9 }
10 // 判斷 ab 到 ac 的方向：{1:逆時鐘,0:重疊,-1:順時鐘}
11 friend int ori(point a, point b, point c) {
12     return sign((b-a)^(c-a));
13 }
14 friend bool btw(point a, point b, point c) {
15     return ori(a, b, c) == 0 && sign((a-c)*(b-c)) <= 0;
16 }

```

5.5 point / banana [09fd7c]

```

1 // 判斷線段 ab, cd 是否相交
2 friend bool banana(point a, point b, point c, point d) {
3     if (btw(a, b, c) || btw(a, b, d)
4         || btw(c, d, a) || btw(c, d, b)) return true;
5     int u = ori(a, b, c) * ori(a, b, d);
6     int v = ori(c, d, a) * ori(c, d, b);

```

```

7     return u < 0 && v < 0;
8 }

```

5.6 point / rayHitSeg [db541a]

```

1 // 判斷 "射線 ab" 與 "線段 cd" 是否相交
2 friend bool rayHitSeg(point a, point b, point c, point d) {
3     if (a == b) return btw(c, d, a); // Special case
4     if (((a - b) ^ (c - d)) == 0) {
5         return btw(a, c, b) || btw(a, d, b) || banana(a, b, c, d);
6     }
7     point u = b - a, v = d - c, s = c - a;
8     return sign(s ^ v) * sign(u ^ v) >= 0 && sign(s ^ u)
9         * sign(u ^ v) >= 0 && abs(s ^ u) <= abs(u ^ v);
10 }

```

5.7 point / else [f46547]

```

1 // 旋轉 Arg(b) 的角度 (小心溢位)
2 point rotate(point b){return {x*b.x-y*b.y, x*b.y+y*b.x};}
3 // 回傳極座標角度·值域：[-π, +π]
4 friend ld Arg(point b) {
5     return (b.x != 0 || b.y != 0) ? atan2(b.y, b.x) : 0;
6 }
7 friend T abs2(point b) {return b * b; }

```

5.8 struct line [210dc8]

```

1 template<typename T>
2 struct line {
3     point<T> p1, p2;
4     // ax + by + c = 0
5     T a, b, c; // |a|, |b| ≤ 2C, |c| ≤ 8C²
6     line() {}
7     line(const point<T> &x, const point<T> &y) : p1(x), p2(y){
8         build();
9     }
10    void build() {
11        a = p1.y - p2.y;
12        b = p2.x - p1.x;
13        c = (-a*p1.x)-b*p1.y;
14    }
15 };

```

5.9 line / else [09bcc9]

```

1 // 判斷點和有向直線的關係：{1:左邊,0:在線上,-1:右邊}
2 int ori(point<T> &p) {
3     return sign((p2-p1) ^ (p-p1));
4 }
5 // 判斷直線斜率是否相同
6 bool parallel(line &l) {
7     return ((p1-p2) ^ (l.p1-l.p2)) == 0;
8 }
9 // 兩直線交點
10 point<ld> line_intersection(line &l) {
11     using P = point<ld>;
12     point<T> u = p2-p1, v = l.p2-l.p1, s = l.p1-p1;
13     return P(p1) + P(u) * ((ld(s^v)) / (u^v));
14 }

```

5.10 struct polygon [171a85]

```

1 template<typename T>
2 struct polygon {
3     vector<point<T>> v;
4     polygon() {}
5     polygon(const vector<point<T>> &u) : v(u) {}
6 };

```

5.11 polygon / make convex hull [2bb3ef]

```

1 // simple 為 true 的時候會回傳任意三點不共線的凸包
2 void make_convex_hull(int simple) {
3     auto cmp = [&](point<T> &p, point<T> &q) {
4         return (p.x == q.x) ? (p.y < q.y) : (p.x < q.x);
5     };
6     simple = (bool)simple;
7     sort(v.begin(), v.end(), cmp);
8     v.resize(unique(v.begin(), v.end()) - v.begin());
9     if (v.size() <= 1) return;
10    vector<point<T>> hull;
11    for (int t = 0; t < 2; ++t){
12        int sz = hull.size();
13        for (auto &i:v) {
14            while (hull.size() >= sz+2 && ori(hull[hull.size()-2], hull.back(), i) < simple) {
15                hull.pop_back();
16            }
17            hull.push_back(i);
18        }
19        hull.pop_back();
20        reverse(v.begin(), v.end());
21    }
22    swap(hull, v);
23 }

```

5.12 polygon / in polygon [f11340]

```

1 // 可以在有 n 個點的簡單多邊形內·用 O(n) 判斷一個點：
2 // {1：在多邊形內，0：在多邊形上，-1：在多邊形外}
3 int in_polygon(point<T> a){
4     const T MAX_POS = 1e9 + 5; // [記得修改] 座標的最大值
5     point<T> pre = v.back(), b(MAX_POS, a.y + 1);
6     int cnt = 0;
7
8     for (auto &i:v) {
9         if (btw(pre, i, a)) return 0;
10        if (banana(a, b, pre, i)) cnt++;
11        pre = i;
12    }
13
14    return cnt%2 ? 1 : -1;
15 }

```

5.13 polygon / in convex [e64f1e]

```

1 /// 警告：以下所有凸包專用的函式都只接受逆時針排序且任三點不
2 /// 共線的凸包 ///
3 // 可以在有 n 個點的凸包內·用 O(Log n) 判斷一個點：
4 // {1：在凸包內，0：在凸包邊上，-1：在凸包外}
5 int in_convex(point<T> p) {
6     int n = v.size();
7     int a = ori(v[0], v[1], p), b = ori(v[0], v[n-1], p);

```

```

7 | if (a < 0 || b > 0) return -1;
8 | if (btw(v[0], v[1], p)) return 0;
9 | if (btw(v[0], v[n - 1], p)) return 0;
10 | int l = 1, r = n - 1, mid;
11 | while (l + 1 < r) {
12 |     mid = (l + r) >> 1;
13 |     if (ori(v[0], v[mid], p) >= 0) l = mid;
14 |     else r = mid;
15 | }
16 | int k = ori(v[l], v[r], p);
17 | if (k <= 0) return k;
18 | return 1;
19 | }

```

5.14 polygon / cycle search [fe2f51]

```

1 | // 凸包專用的環狀二分搜 · 回傳  $\theta$ -based index
2 | int cycle_search(auto &f) {
3 |     int n = v.size(), l = 0, r = n;
4 |     if (n == 1) return 0;
5 |     bool rv = f(1, 0);
6 |     while (r - l > 1) {
7 |         int m = (l + r) / 2;
8 |         if (f(0, m) ? rv : f(m, (m + 1) % n)) r = m;
9 |         else l = m;
10 |     }
11 |     return f(1, r % n) ? 1 : r % n;
12 | }

```

5.15 polygon / line cut convex [b6a4c8]

```

1 | // 可以在有  $n$  個點的凸包內 · 用  $O(\log n)$  判斷一條直線：
2 | // {1 : 穿過凸包, 0 : 剛好切過凸包, -1 : 沒碰到凸包}
3 | int line_cut_convex(line<T> L) {
4 |     L.build();
5 |     point<T> p(L.a, L.b);
6 |     auto gt = [&](int neg) {
7 |         auto f = [&](int x, int y) {
8 |             return sign((v[x] - v[y]) * p) == neg;
9 |         };
10 |         return -(v[cycle_search(f)] * p);
11 |     };
12 |     T x = gt(1), y = gt(-1);
13 |     if (L.c < x || y < L.c) return -1;
14 |     return not (L.c == x || L.c == y);
15 | }

```

5.16 polygon / segment across convex [b4f073]

```

1 | // 可以在有  $n$  個點的凸包內 · 用  $O(\log n)$  判斷一個線段：
2 | // {1 : 存在一個凸包上的邊可以把這個線段切成兩半,
3 | // 0 : 有碰到凸包但沒有任何凸包上的邊可以把它切成兩半,
4 | // -1 : 沒碰到凸包}
5 | /// 除非線段兩端點都不在凸包邊上 · 否則此函數回傳 0 的時候不一
6 | 定表示線段沒有通過凸包內部 ///
7 | int segment_across_convex(line<T> L) {
8 |     L.build();
9 |     point<T> p(L.a, L.b);
10 |    auto gt = [&](int neg) {
11 |        auto f = [&](int x, int y) {
12 |            return sign((v[x] - v[y]) * p) == neg;
13 |        };
14 |        return cycle_search(f);
15 |    };

```

```

14 | };
15 | int i = gt(1), j = gt(-1), n = v.size();
16 | T x = -(v[i] * p), y = -(v[j] * p);
17 | if (L.c < x || y < L.c) return -1;
18 | if (L.c == x || L.c == y) return 0;
19 |
20 | if (i > j) swap(i, j);
21 | auto g = [&](int x, int lim) {
22 |     int now = 0, nxt;
23 |     for (int i = 1 << __lg(lim); i > 0; i /= 2) {
24 |         if (now + i > lim) continue;
25 |         nxt = (x + i) % n;
26 |         if (L.ori(v[x]) * L.ori(v[nxt]) >= 0) {
27 |             x = nxt;
28 |             now += i;
29 |         }
30 |     } // ↓ BE CAREFUL
31 |     return -(ori(v[x], v[(x + 1) % n], L.p1) * ori(v[x],
32 |         v[(x + 1) % n], L.p2));
33 | };
34 | return max(g(i, j - i), g(j, n - (j - i)));

```

5.17 polygon / segment pass convex interior [5f45ca]

```

1 | // 可以在有  $n$  個點的凸包內 · 用  $O(\log n)$  判斷一個線段：
2 | // {1 : 線段上存在某一點位於凸包內部 (邊上不算),
3 | // 0 : 線段上存在某一點碰到凸包的邊但線段上任一點均不在凸包
4 | // 內部,
5 | // -1 : 線段完全在凸包外面}
6 | int segment_pass_convex_interior(line<T> L) {
7 |     if (in_convex(L.p1) == 1 || in_convex(L.p2) == 1) return
8 |         1;
9 |     L.build();
10 |    point<T> p(L.a, L.b);
11 |    auto gt = [&](int neg) {
12 |        auto f = [&](int x, int y) {
13 |            return sign((v[x] - v[y]) * p) == neg;
14 |        };
15 |        return cycle_search(f);
16 |    };
17 |    int i = gt(1), j = gt(-1), n = v.size();
18 |    T x = -(v[i] * p), y = -(v[j] * p);
19 |    if (L.c < x || y < L.c) return -1;
20 |    if (L.c == x || L.c == y) return 0;
21 |
22 |    if (i > j) swap(i, j);
23 |    auto g = [&](int x, int lim) {
24 |        int now = 0, nxt;
25 |        for (int i = 1 << __lg(lim); i > 0; i /= 2) {
26 |            if (now + i > lim) continue;
27 |            nxt = (x + i) % n;
28 |            if (L.ori(v[x]) * L.ori(v[nxt]) > 0) {
29 |                x = nxt;
30 |                now += i;
31 |            }
32 |        } // ↓ BE CAREFUL
33 |        return -(ori(v[x], v[(x + 1) % n], L.p1) * ori(v[x],
34 |            v[(x + 1) % n], L.p2));
35 |    };
36 |    int ret = max(g(i, j - i), g(j, n - (j - i)));
37 |    return (ret == 0) ? (in_convex(L.p1) == 0 && in_convex(L.
38 |        p2) == 0) : ret;

```

5.18 polygon / convex tangent point [a6f66b]

```

1 | // 回傳點過凸包的兩條切線的切點的  $\theta$ -based index (不保證兩條
2 | 切線的順逆時針關係)
3 | pair<int, int> convex_tangent_point(point<T> p) {
4 |     int n = v.size(), z = -1, edg = -1;
5 |     auto gt = [&](int neg) {
6 |         auto check = [&](int x) {
7 |             if (v[x] == p) z = x;
8 |             if (btw(v[x], v[(x + 1) % n], p)) edg = x;
9 |             if (btw(v[(x + n - 1) % n], v[x], p)) edg = (x +
10 |                 n - 1) % n;
11 |         };
12 |         auto f = [&](int x, int y) {
13 |             check(x); check(y);
14 |             return ori(p, v[x], v[y]) == neg;
15 |         };
16 |         return cycle_search(f);
17 |     };
18 |     int x = gt(1), y = gt(-1);
19 |     if (z != -1) {
20 |         return {(z + n - 1) % n, (z + 1) % n};
21 |     }
22 |     else if (edg != -1) {
23 |         return {edg, (edg + 1) % n};
24 |     }
25 |     else {
26 |         return {x, y};
27 |     }

```

5.19 polygon / halfplane intersection [102d48]

```

1 | friend int halfplane_intersection(vector<line<T>> &s, polygon
2 | <T> &P) {
3 |     auto angle_cmp = [&](line<T> &A, line<T> &B) {
4 |         point<T> a = A.p2 - A.p1, b = B.p2 - B.p1;
5 |         return (a < b);
6 |     };
7 |     sort(s.begin(), s.end(), angle_cmp); // 線段左側為該線段
8 |     // 半平面
9 |     int L, R, n = s.size();
10 |    vector<point<T>> px(n);
11 |    vector<line<T>> q(n);
12 |    q[L = R = 0] = s[0];
13 |    for (int i = 1; i < n; ++i) {
14 |        while (L < R && s[i].ori(px[R-1]) <= 0) --R;
15 |        while (L < R && s[i].ori(px[L]) <= 0) ++L;
16 |        q[++R] = s[i];
17 |        if (q[R].parallel(q[R-1])) {
18 |            --R;
19 |            if (q[R].ori(s[i].p1) > 0) q[R] = s[i];
20 |        }
21 |        if (L < R) px[R-1] = q[R-1].line_intersection(q[R]);
22 |    }
23 |    while (L < R && q[L].ori(px[R-1]) <= 0) --R;
24 |    P.v.clear();
25 |    if (R - L <= 1) return 0;
26 |    px[R] = q[R].line_intersection(q[L]);
27 |    for (int i = L; i <= R; ++i) P.v.push_back(px[i]);
28 |    return R - L + 1;

```

5.20 polygon / minkowski sum [aba519]

```

1 void minkowski(vector<point<T>> a, vector<point<T>> b) {
2     // a, b: convex polygon's inside vector, CCW order
3     auto cmp = [&](auto &a, auto &b) {
4         return tie(a.y, a.x) < tie(b.y, b.x);
5     };
6     auto reorder = [&](auto &u) {
7         auto it = min_element(u.begin(), u.end(), cmp);
8         rotate(u.begin(), it, u.end());
9     };
10    reorder(a); reorder(b);
11    a.push_back(a[0]); a.push_back(a[1]);
12    b.push_back(b[0]); b.push_back(b[1]);
13    v.clear();
14    for (int i = 0, j = 0; i+2<a.size()||j+2<b.size(); ) {
15        v.push_back(a[i] + b[j]);
16        auto val = (a[i + 1] - a[i]) ^ (b[j + 1] - b[j]);
17        if (val >= 0) i++;
18        if (val <= 0) j++;
19    }
20 }

```

5.21 struct Cir [87198d]

```

1 struct Cir {
2     point<ld> o; ld r;
3     friend ostream& operator<<(ostream& os, Cir c) {
4         return os << "(" << "x" << "+-" [c.o.x >= 0] << abs(c.o.x)
5             << ")^2 + (y" << "+-" [c.o.y >= 0] << abs(c.o.y)
6             << ")^2 = " << c.r * c.r;
7     }
8     bool covers(Cir b) {
9         return sqrt((ld)abs2(o - b.o)) + b.r <= r;
10    }
11 };

```

5.22 Cir / Cir intersect [330a1c]

```

1 vector<point<ld>> Cir_intersect(Cir c) {
2     ld d2 = abs2(o - c.o), d = sqrt(d2);
3     if (d < max(r, c.r) - min(r, c.r) || d > r + c.r) return {};
4     auto sqdf = [&](ld x, ld y) { return x*x - y*y; };
5     point<ld> u = (o + c.o) / 2 + (o - c.o) * (sqdf(c.r, r) / (2 * d2));
6     ld A = sqrt(sqdf(r + d, c.r) * sqdf(c.r, d - r));
7     point<ld> v = (c.o - o).rotate({0,1}) * A / (2 * d2);
8     if (sign(v.x) == 0 && sign(v.y) == 0) return {u};
9     return {u - v, u + v};
10 }

```

5.23 Cir / point tangent [0067e6]

```

1 auto point_tangent(point<ld> p) {
2     vector<point<ld>> res;
3     ld d_sq = abs2(p - o);
4     if (sign(d_sq - r * r) <= 0) {
5         res.pb(p + (p - o).rotate({0, 1}));
6     } else if (d_sq > r * r) {
7         ld s = d_sq - r * r;
8         point<ld> v = p + (o - p) * s / d_sq;
9         point<ld> u = (o - p).rotate({0, 1}) * sqrt(s) * r / d_sq;
10    }

```

```

10    res.pb(v + u);
11    res.pb(v - u);
12 }
13 return res;
14 }

```

5.24 Geometry Struct 3D [4a50c9]

```

1 using ld = long double;
2
3 // 判斷數值正負：{1:正數,0:零,-1:負數}
4 int sign(long long x) {return (x >= 0) ? ((bool)x) : -1; }
5 int sign(ld x) {return (abs(x) < 1e-9) ? 0 : (x>0 ? 1 : -1); }
6
7 template<typename T>
8 struct pt3 {
9     T x, y, z;
10    pt3(){}
11    pt3(const T &x, const T &y, const T &z):x(x),y(y),z(z){}
12    explicit operator pt3<ld>() {return pt3<ld>(x, y, z); }
13
14    pt3 operator+(pt3 b) {return {x+b.x, y+b.y, z+b.z}; }
15    pt3 operator-(pt3 b) {return {x-b.x, y-b.y, z-b.z}; }
16    pt3 operator*(T b) {return {x * b, y * b, z * b}; }
17    pt3 operator/(T b) {return {x / b, y / b, z / b}; }
18    bool operator==(pt3 b){return x==b.x&&y==b.y&&z==b.z; }
19
20    T operator*(pt3 b) {return x*b.x+y*b.y+z*b.z; }
21    pt3 operator^(pt3 b) {
22        return pt3(y * b.z - z * b.y,
23            z * b.x - x * b.z,
24            x * b.y - y * b.x);
25    }
26    friend T abs2(pt3 b) {return b * b; }
27    friend T len (pt3 b) {return sqrt(abs2(b)); }
28    friend ostream& operator<<(ostream& os, pt3 p) {
29        return os << "(" << p.x << ", " <<
30            p.y << ", " << p.z << ")";
31    }
32 };
33
34 template<typename T>
35 struct face {
36     int a, b, c; // 三角形在 vector 裡面的 index
37     pt3<T> q; // 面積向量 (朝外)
38 };
39
40 /// 警告；v 在過程中可能被修改，回傳的 face 以修改後的為準
41 /// O(n^2) · 最多只有 2n-4 個面
42 /// 當凸包退化時會回傳空的凸包，否則回傳凸包上的每個面
43 template<typename T>
44 vector<face<T>> hull3(vector<pt3<T>> &v) {
45     int n = v.size();
46     if (n < 3) return {};
47     // don't use "==" when you use ld
48     sort(all(v), [&](pt3<T> &p, pt3<T> &q) {
49         return sign(p.x - q.x) ? (p.x < q.x) :
50             (sign(p.y - q.y) ? p.y < q.y : p.z < q.z);
51     });
52     v.resize(unique(v.begin(), v.end()) - v.begin());
53     for (int i = 2; i <= n; ++i) {
54         if (i == n) return {};
55         if (sign(len(((v[1] - v[0]) ^ (v[i] - v[0]))))) {
56             swap(v[2], v[i]);

```

```

57         break;
58     }
59 }
60 pt3<T> tmp_q = (v[1] - v[0]) ^ (v[2] - v[0]);
61 for (int i = 3; i <= n; ++i) {
62     if (i == n) return {};
63     if (sign((v[i] - v[0]) * tmp_q)) {
64         swap(v[3], v[i]);
65         break;
66     }
67 }
68
69 vector<face<T>> f;
70 vector<vector<int>> dead(n, vector<int>(n, true));
71 auto add_face = [&](int a, int b, int c) {
72     f.emplace_back(a, b, c, (v[b] - v[a]) ^ (v[c] - v[a]));
73     dead[a][b] = dead[b][c] = dead[c][a] = false;
74 };
75 add_face(0, 1, 2);
76 add_face(0, 2, 1);
77
78 for (int i = 3; i < n; ++i) {
79     vector<face<T>> f2;
80     for (auto &[a, b, c, q] : f) {
81         if (sign((v[i] - v[a]) * q) > 0)
82             dead[a][b] = dead[b][c] = dead[c][a] = true;
83         else f2.emplace_back(a, b, c, q);
84     }
85     f.clear();
86     for (face<T> &f : f2) {
87         int arr[3] = {f.a, f.b, f.c};
88         for (int j = 0; j < 3; ++j) {
89             int a = arr[j], b = arr[(j + 1) % 3];
90             if (dead[b][a]) add_face(b, a, i);
91         }
92     }
93     f.insert(f.end(), all(f2));
94 }
95 return f;
96 } // 15ef50

```

5.25 Pick's Theorem

給定頂點坐標均是整點的簡單多邊形 · 面積 = 內部格點數 + 邊上格點數/2 - 1

6 Graph

6.1 SAT [5a6317]

```

1 struct TWO_SAT {
2     int n, N;
3     vector<vector<int>> G, rev_G;
4     deque<bool> used;
5     vector<int> order, comp;
6     deque<bool> assignment;
7     void init(int _n) {
8         n = _n;
9         N = _n * 2;
10        G.resize(N + 5);
11        rev_G.resize(N + 5);
12    }
13    void dfs1(int v) {
14        used[v] = true;
15        for (int u : G[v]) {
16            if (!used[u])

```

```

17         dfs1(u);
18     }
19     order.push_back(v);
20 }
21 void dfs2(int v, int c1) {
22     comp[v] = c1;
23     for (int u : rev_G[v]) {
24         if (comp[u] == -1)
25             dfs2(u, c1);
26     }
27 }
28 bool solve() {
29     order.clear();
30     used.assign(N, false);
31     for (int i = 0; i < N; ++i) {
32         if (!used[i])
33             dfs1(i);
34     }
35     comp.assign(N, -1);
36     for (int i = 0, j = 0; i < N; ++i) {
37         int v = order[N - i - 1];
38         if (comp[v] == -1)
39             dfs2(v, j++);
40     }
41     assignment.assign(n, false);
42     for (int i = 0; i < N; i += 2) {
43         if (comp[i] == comp[i + 1])
44             return false;
45         assignment[i / 2] = (comp[i] > comp[i + 1]);
46     }
47     return true;
48 }
49 // A or B 都是 0-based
50 void add_disjunction(int a, bool na, int b, bool nb) {
51     // na is true => ~a, na is false => a
52     // nb is true => ~b, nb is false => b
53     a = 2 * a ^ na;
54     b = 2 * b ^ nb;
55     int neg_a = a ^ 1;
56     int neg_b = b ^ 1;
57     G[neg_a].push_back(b);
58     G[neg_b].push_back(a);
59     rev_G[b].push_back(neg_a);
60     rev_G[a].push_back(neg_b);
61     return;
62 }
63 void get_result(vector<int>& res) {
64     res.clear();
65     for (int i = 0; i < n; i++)
66         res.push_back(assignment[i]);
67 }
68 };

```

6.2 Augment Path [f8a5dd]

```

1 struct AugmentPath{
2     int n, m;
3     vector<vector<int>> G;
4     vector<int> mx, my;
5     vector<int> visx, visy;
6     int stamp;
7
8     AugmentPath(int _n, int _m) : n(_n), m(_m), G(n), mx(n,
9         -1), my(m, -1), visx(n), visy(n){
10         stamp = 0;

```

```

10     }
11
12     void add(int x, int y){
13         G[x].push_back(y);
14     }
15
16     // bb03e2
17     bool dfs1(int now){
18         visx[now] = stamp;
19
20         for (auto x : G[now]){
21             if (my[x]==-1){
22                 mx[now] = x;
23                 my[x] = now;
24                 return true;
25             }
26         }
27         for (auto x : G[now]){
28             if (visx[my[x]]!=stamp && dfs1(my[x])){
29                 mx[now] = x;
30                 my[x] = now;
31                 return true;
32             }
33         }
34         return false;
35     }
36
37     vector<pair<int, int>> find_max_matching(){
38         vector<pair<int, int>> ret;
39
40         while (true){
41             stamp++;
42             int tmp = 0;
43             for (int i=0; i<n; i++){
44                 if (mx[i]==-1 && dfs1(i)) tmp++;
45             }
46             if (tmp==0) break;
47         }
48
49         for (int i=0; i<n; i++){
50             if (mx[i]!=-1){
51                 ret.push_back({i, mx[i]});
52             }
53         }
54         return ret;
55     }
56
57     // 645577
58     void dfs2(int now){
59         visx[now] = true;
60
61         for (auto x : G[now]){
62             if (my[x]!=-1 && visy[x]==false){
63                 visy[x] = true;
64                 dfs2(my[x]);
65             }
66         }
67     }
68
69     // 要先執行 find_max_matching 一次
70     vector<pair<int, int>> find_min_vertex_cover(){
71         fill(visx.begin(), visx.end(), false);
72         fill(visy.begin(), visy.end(), false);
73
74         vector<pair<int, int>> ret;

```

```

75         for (int i=0; i<n; i++){
76             if (mx[i]==-1) dfs2(i);
77         }
78
79         for (int i=0; i<n; i++){
80             if (visx[i]==false) ret.push_back({1, i});
81         }
82         for (int i=0; i<m; i++){
83             if (visy[i]==true) ret.push_back({2, i});
84         }
85         return ret;
86     }
87 }
88 };

```

6.3 C3C4 [d00465]

```

1 // 0-based
2 void C3C4(vector<int> deg, vector<array<int, 2>> edges){
3     int N = deg.size();
4     int M = edges.size();
5
6     vector<int> ord(N), rk(N);
7     iota(ord.begin(), ord.end(), 0);
8     sort(ord.begin(), ord.end(), [&](int x, int y) { return
9         deg[x] > deg[y]; });
10    for (int i=0; i<N; i++) rk[ord[i]] = i;
11
12    vector<vector<int>> D(N), adj(N);
13    for (auto [u, v] : e) {
14        if (rk[u] > rk[v]) swap(u, v);
15        D[u].emplace_back(v);
16        adj[u].emplace_back(v);
17        adj[v].emplace_back(u);
18    }
19
20    vector<int> vis(N);
21
22    int c3 = 0, c4 = 0;
23    for (int x : ord) { // c3
24        for (int y : D[x]) vis[y] = 1;
25        for (int y : D[x]) for (int z : D[y]){
26            c3 += vis[z]; // xyz is C3
27        }
28        for (int y : D[x]) vis[y] = 0;
29    }
30    for (int x : ord) { // c4
31        for (int y : D[x]) for (int z : adj[y])
32            if (rk[z] > rk[x]) c4 += vis[z]++;
33        for (int y : D[x]) for (int z : adj[y])
34            if (rk[z] > rk[x]) --vis[z];
35    } // both are O(M*sqrt(M)), test @ 2022 CCPC guangzhou
36    cout << c4 << "\n";

```

6.4 Cut BCC [2af809]

```

1 #include <bits/stdc++.h>
2 using namespace std;
3
4 const int N = 200005;
5 vector<int> G[N];
6 int low[N], depth[N];
7 bool vis[N];
8 vector<vector<int>> bcc;

```

```

9 stack <int> stk;
10
11 void dfs(int v, int p) {
12     stk.push(v);
13     vis[v] = true;
14     low[v] = depth[v] = (p == -1 ? 1 : depth[p] + 1);
15     for (int u : G[v]) {
16         if (u == p) continue;
17         if (!vis[u]) {
18             /// (v, u) 是樹邊
19             dfs(u, v);
20             low[v] = min(low[v], low[u]);
21             /// u 無法在不經過父邊的情況走到 v 的祖先
22             if (low[u] >= depth[v]) {
23                 bcc.emplace_back();
24                 while (stk.top() != u) {
25                     bcc.back().push_back(stk.top());
26                     stk.pop();
27                 }
28                 bcc.back().push_back(stk.top());
29                 stk.pop();
30                 bcc.back().push_back(v);
31             }
32         } else {
33             /// (v, u) 是回邊
34             low[v] = min(low[v], depth[u]);
35         }
36     }
37 }

```

6.5 Dinic [961b34]

```

1 /// 一般圖 : O(EV^2)
2 /// 二分圖 : O(EV)
3 struct Flow{
4     using T = int; /// 可以換成別的类型別
5     struct Edge{
6         int v; T rc; int rid;
7     };
8     vector<vector<Edge>> G;
9     void add(int u, int v, T c){
10         G[u].push_back({v, c, G[v].size()});
11         G[v].push_back({u, 0, G[u].size()-1});
12     }
13     vector<int> dis, it;
14
15     Flow(int n){
16         G.resize(n);
17         dis.resize(n);
18         it.resize(n);
19     }
20
21     /// ce56d6
22     T dfs(int u, int t, T f){
23         if (u == t || f == 0) return f;
24         for (int &i=it[u] ; i<G[u].size() ; i++){
25             auto &[v, rc, rid] = G[u][i];
26             if (dis[v]!=dis[u]+1) continue;
27             T df = dfs(v, t, min(f, rc));
28             if (df <= 0) continue;
29             rc -= df;
30             G[v][rid].rc += df;
31             return df;
32         }
33         return 0;

```

```

34 }
35
36 /// e22e39
37 T flow(int s, int t){
38     T ans = 0;
39     while (true){
40         fill(dis.begin(), dis.end(), INF);
41         queue<int> q;
42         q.push(s);
43         dis[s] = 0;
44
45         while (q.size()){
46             int u = q.front(); q.pop();
47             for (auto [v, rc, rid] : G[u]){
48                 if (rc <= 0 || dis[v] < INF) continue;
49                 dis[v] = dis[u] + 1;
50                 q.push(v);
51             }
52         }
53         if (dis[t]==INF) break;
54
55         fill(it.begin(), it.end(), 0);
56         while (true){
57             T df = dfs(s, t, INF);
58             if (df <= 0) break;
59             ans += df;
60         }
61     }
62     return ans;
63 }
64
65 /// the code below constructs minimum cut
66 void dfs_mincut(int now, vector<bool> &vis){
67     vis[now] = true;
68     for (auto &[v, rc, rid] : G[now]){
69         if (vis[v] == false && rc > 0){
70             dfs_mincut(v, vis);
71         }
72     }
73 }
74
75 vector<pair<int, int>> construct(int n, int s, vector<
76     pair<int, int>> &E){
77     /// E is G without capacity
78     vector<bool> vis(n);
79     dfs_mincut(s, vis);
80     vector<pair<int, int>> ret;
81     for (auto &[u, v] : E){
82         if (vis[u] == true && vis[v] == false){
83             ret.emplace_back(u, v);
84         }
85     }
86     return ret;
87 };

```

6.6 Dominator Tree [52b249]

```

1 /// 全部都是 0-based
2 /// G 要是是有向無權圖
3 /// 一開始要初始化 G(N, root)
4 /// 用完之後要 build
5 /// G[i] = 從 root 走到 i 時，一定要走到的點且離 i 最近
6 struct DominatorTree{
7     int N;

```

```

8     vector<vector<int>> G;
9     vector<vector<int>> buckets, rg;
10     /// dfn[x] = the DFS order of x
11     /// rev[x] = the vertex with DFS order x
12     /// par[x] = the parent of x
13     vector<int> dfn, rev, par;
14     vector<int> sdom, dom, idom;
15     vector<int> fa, val;
16     int stamp;
17     int root;
18
19     int operator [] (int x){
20         return idom[x];
21     }
22
23     DominatorTree(int _N, int _root) :
24         N(_N),
25         G(N), buckets(N), rg(N),
26         dfn(N, -1), rev(N, -1), par(N, -1),
27         sdom(N, -1), dom(N, -1), idom(N, -1),
28         fa(N, -1), val(N, -1)
29     {
30         stamp = 0;
31         root = _root;
32     }
33
34     void add_edge(int u, int v){
35         G[u].push_back(v);
36     }
37
38     void dfs(int x){
39         rev[dfn[x] = stamp] = x;
40         fa[stamp] = sdom[stamp] = val[stamp] = stamp;
41         stamp++;
42
43         for (int u : G[x]){
44             if (dfn[u]==-1){
45                 dfs(u);
46                 par[dfn[u]] = dfn[x];
47             }
48             rg[dfn[u]].push_back(dfn[x]);
49         }
50     }
51
52     int eval(int x, bool first){
53         if (fa[x]==x) return !first ? -1 : x;
54         int p = eval(fa[x], false);
55
56         if (p==-1) return x;
57         if (sdom[val[x]]>sdom[val[fa[x]]]) val[x] = val[fa[x]];
58         fa[x] = p;
59
60         return !first ? p : val[x];
61     }
62
63     void link(int x, int y){
64         fa[x] = y;
65     }
66
67     void build(){
68         dfs(root);
69
70         for (int x=stamp-1 ; x>=0 ; x--){
71             for (int y : rg[x]){
72                 sdom[x] = min(sdom[x], sdom[eval(y, true)]);

```



```

73     }
74     if (x>0) buckets[sdom[x]].push_back(x);
75     for (int u : buckets[x]){
76         int p = eval(u, true);
77         if (sdom[p]==x) dom[u] = x;
78         else dom[u] = p;
79     }
80     if (x>0) link(x, par[x]);
81 }
82
83 idom[root] = root;
84 for (int x=1 ; x<stamp ; x++){
85     if (sdom[x]!=dom[x]) dom[x] = dom[dom[x]];
86 }
87 for (int i=1 ; i<stamp ; i++) idom[rev[i]] = rev[dom[
88     i]];
89 }
};

```

6.7 EdgeBCC [d09eb1]

```

1 // d09eb1
2 // 0-based · 支援重邊
3 struct EdgeBCC{
4     int n, m, dep, sz;
5     vector<vector<pair<int, int>>> G;
6     vector<vector<int>>> bcc;
7     vector<int> dfn, low, stk, isBridge, bccId;
8     vector<pair<int, int>> edge, bridge;
9
10    EdgeBCC(int _n) : n(_n), m(0), sz(0), dfn(n), low(n), G(n
11        ), bcc(n), bccId(n) {}
12
13    void add_edge(int u, int v) {
14        edge.push_back({u, v});
15        G[u].push_back({v, m});
16        G[v].push_back({u, m++});
17    }
18
19    void dfs(int now, int pre) {
20        dfn[now] = low[now] = ++dep;
21        stk.push_back(now);
22
23        for (auto [x, id] : G[now]){
24            if (!dfn[x]){
25                dfs(x, id);
26                low[now] = min(low[now], low[x]);
27            } else if (id!=pre){
28                low[now] = min(low[now], dfn[x]);
29            }
30        }
31
32        if (low[now]==dfn[now]){
33            if (pre!=-1) isBridge[pre] = true;
34            int u;
35            do{
36                u = stk.back();
37                stk.pop_back();
38                bcc[sz].push_back(u);
39                bccId[u] = sz;
40            } while (u!=now);
41            sz++;
42        }
43    }
};

```

```

44 void get_bcc() {
45     isBridge.assign(m, 0);
46     dep = 0;
47     for (int i=0 ; i<n ; i++){
48         if (!dfn[i]) dfs(i, -1);
49     }
50
51     for (int i=0 ; i<m ; i++){
52         if (isBridge[i]){
53             bridge.push_back({edge[i].first , edge[i].
54                 second});
55         }
56     }
57 }
};

```

6.8 EnumeratePlanarFace [e70ee1]

```

1 // 0-based
2 struct PlanarGraph{
3     int n, m, id;
4     vector<point<int>>> v;
5     vector<vector<pair<int, int>>> G;
6     vector<int> conv, nxt, vis;
7
8     PlanarGraph(int n, int m, vector<point<int>>> _v) :
9         n(n), m(m), id(0),
10         v(_v), G(n),
11         conv(2*m), nxt(2*m), vis(2*m) {}
12
13    void add_edge(int x, int y){
14        G[x].push_back({y, 2*id});
15        G[y].push_back({x, 2*id+1});
16        conv[2*id] = x;
17        conv[2*id+1] = y;
18        id++;
19    }
20
21    vector<int> enumerate_face(){
22        for (int i=0 ; i<n ; i++){
23            sort(G[i].begin(), G[i].end(), [&](pair<int, int>
24                a, pair<int, int> b){
25                return (v[a.first]-v[i])<(v[b.first]-v[i]);
26            });
27
28            int sz = G[i].size(), pre = sz-1;
29            for (int j=0 ; j<sz ; j++){
30                nxt[G[i][pre].second] = G[i][j].second^1;
31                pre = j;
32            }
33        }
34
35        vector<int> ret;
36        for (int i=0 ; i<2*m ; i++){
37            if (vis[i]==false){
38                int area = 0, now = i;
39                vector<int> pt;
40
41                while (!vis[now]){
42                    vis[now] = true;
43                    pt.push_back(conv[now]);
44                    now = nxt[now];
45                }
46                pt.push_back(pt.front());

```

```

47         for (int i=0 ; i+1<pt.size() ; i++){
48             area -= (v[pt[i]]^v[pt[i+1]]);
49         }
50
51         // pt = face boundary
52         if (area>0){
53             ret.push_back(area);
54         } else{
55             // pt is outer face
56         }
57     }
58 }
59 return ret;
60 }
61 };

```

6.9 HLD [f57ec6]

```

1 #include <bits/stdc++.h>
2 #define int long long
3 using namespace std;
4
5 const int N = 100005;
6 vector<int> G[N];
7 struct HLD {
8     vector<int> pa, sz, depth, mxson, topf, id;
9     int n, idcnt = 0;
10    HLD(int _n) : n(_n), pa(_n + 1), sz(_n + 1), depth(_n +
11        1), mxson(_n + 1), topf(_n + 1), id(_n + 1) {}
12
13    void dfs1(int v = 1, int p = -1) {
14        pa[v] = p; sz[v] = 1; mxson[v] = 0;
15        depth[v] = (p == -1 ? 0 : depth[p] + 1);
16        for (int u : G[v]) {
17            if (u == p) continue;
18            dfs1(u, v);
19            sz[v] += sz[u];
20            if (sz[u] > sz[mxson[v]]) mxson[v] = u;
21        }
22    }
23
24    void dfs2(int v = 1, int top = 1) {
25        id[v] = ++idcnt;
26        topf[v] = top;
27        if (mxson[v]) dfs2(mxson[v], top);
28        for (int u : G[v]) {
29            if (u == mxson[v] || u == pa[v]) continue;
30            dfs2(u, u);
31        }
32    }
33
34    // query 為區間資料結構
35    int path_query(int a, int b) {
36        int res = 0;
37        while (topf[a] != topf[b]) { /// 若不在同一條鍊上
38            if (depth[topf[a]] < depth[topf[b]]) swap(a, b);
39            res = max(res, 011); // query : l = id[topf[a]],
40                r = id[a]
41            a = pa[topf[a]];
42        }
43        /// 此時已在同一條鍊上
44        if (depth[a] < depth[b]) swap(a, b);
45        res = max(res, 011); // query : l = id[b], r = id[a]
46        return res;
47    }
};

```


6.10 Kosaraju [c7d5aa]

```

1 // 給定一個有向圖，迴傳傳縮點後的圖、SCC 的資訊
2 // 所有點都以 based-0 編號
3 // 函式：
4 // .compress:  $O(n \log n)$  計算  $G3$ 、SCC、SCC_id 的資訊，並把縮
  點後的結果存在 result 裡
5 // SCC[i] = 某個 SCC 中的所有點
6 // SCC_id[i] = 第 i 個點在第幾個 SCC
7 struct SCC_compress{
8     int N, M, sz;
9     vector<vector<int>> G, inv_G, result;
10    vector<pair<int, int>> edges;
11    vector<bool> vis;
12    vector<int> order;
13
14    vector<vector<int>> SCC;
15    vector<int> SCC_id;
16
17    SCC_compress(int _N) :
18        N(_N), M(0), sz(0),
19        G(N), inv_G(N),
20        vis(N), SCC_id(N)
21    {}
22
23    vector<int> operator [] (int x){
24        return result[x];
25    }
26
27    void add_edge(int u, int v){
28        G[u].push_back(v);
29        inv_G[v].push_back(u);
30        edges.push_back({u, v});
31        M++;
32    }
33
34    void dfs1(vector<vector<int>> &G, int now){
35        vis[now] = 1;
36        for (auto x : G[now]) if (!vis[x]) dfs1(G, x);
37        order.push_back(now);
38    }
39
40    void dfs2(vector<vector<int>> &G, int now){
41        SCC_id[now] = SCC.size()-1;
42        SCC.back().push_back(now);
43        vis[now] = 1;
44        for (auto x : G[now]) if (!vis[x]) dfs2(G, x);
45    }
46
47    void compress(){
48        fill(vis.begin(), vis.end(), 0);
49        for (int i=0 ; i<N ; i++) if (!vis[i]) dfs1(G, i);
50
51        fill(vis.begin(), vis.end(), 0);
52        reverse(order.begin(), order.end());
53        for (int i=0 ; i<N ; i++){
54            if (!vis[order[i]]){
55                SCC.push_back(vector<int>());
56                dfs2(inv_G, order[i]);
57            }
58        }
59
60        result.resize(SCC.size());
61        sz = SCC.size();
62        for (auto [u, v] : edges){

```

```

63            if (SCC_id[u]!=SCC_id[v]) result[SCC_id[u]].
        push_back(SCC_id[v]);
64        }
65        for (int i=0 ; i<SCC.size() ; i++){
66            sort(result[i].begin(), result[i].end());
67            result[i].resize(unique(result[i].begin(), result
        [i].end())-result[i].begin());
68        }
69    }
70 };

```

6.11 Kuhn Munkres [e66c35]

```

1 //  $O(n^3)$  找到最大權匹配
2 struct KuhnMunkres{
3     int n; // max(n, m)
4     vector<vector<int>> G;
5     vector<int> match, lx, ly, visx, visy;
6     vector<int> slack;
7     int stamp = 0;
8
9     KuhnMunkres(int n) : n(n), G(n, vector<int>(n)), lx(n),
        ly(n), slack(n), match(n), visx(n), visy(n) {}
10
11    void add(int x, int y, int w){
12        G[x][y] = max(G[x][y], w);
13    }
14
15    bool dfs(int i, bool aug){ // aug = true 表示要更新 match
16        if (visx[i]==stamp) return false;
17        visx[i] = stamp;
18
19        for (int j=0 ; j<n ; j++){
20            if (visy[j]==stamp) continue;
21            int d = lx[i]+ly[j]-G[i][j];
22
23            if (d==0){
24                visy[j] = stamp;
25                if (match[j]==-1 || dfs(match[j], aug)){
26                    if (aug){
27                        match[j] = i;
28                    }
29                    return true;
30                }
31            }else{
32                slack[j] = min(slack[j], d);
33            }
34        }
35        return false;
36    }
37
38    bool augment(){
39        for (int j=0 ; j<n ; j++){
40            if (visy[j]!=stamp && slack[j]==0){
41                visy[j] = stamp;
42                if (match[j]==-1 || dfs(match[j], false)){
43                    return true;
44                }
45            }
46        }
47        return false;
48    }
49
50    void relabel(){
51        int delta = INF;

```

```

52        for (int j=0 ; j<n ; j++){
53            if (visy[j]!=stamp) delta = min(delta, slack[j]);
54        }
55        for (int i=0 ; i<n ; i++){
56            if (visx[i]==stamp) lx[i] -= delta;
57        }
58        for (int j=0 ; j<n ; j++){
59            if (visy[j]==stamp) ly[j] += delta;
60            else slack[j] -= delta;
61        }
62    }
63
64    int solve(){
65
66        for (int i=0 ; i<n ; i++){
67            lx[i] = 0;
68            for (int j=0 ; j<n ; j++){
69                lx[i] = max(lx[i], G[i][j]);
70            }
71        }
72
73        fill(ly.begin(), ly.end(), 0);
74        fill(match.begin(), match.end(), -1);
75
76        for(int i = 0; i < n; i++) {
77            fill(slack.begin(), slack.end(), INF);
78            stamp++;
79            if(dfs(i, true)) continue;
80
81            while(augment()==false) relabel();
82            stamp++;
83            dfs(i, true);
84        }
85
86        int ans = 0;
87        for (int j=0 ; j<n ; j++){
88            if (match[j]!=-1){
89                ans += G[match[j]][j];
90            }
91        }
92        return ans;
93    }
94 };

```

6.12 LCA [5b6a5b]

```

1 // 1-based，可以支援森林，0 是超級源點，所有樹都要跟他建邊
2 struct Tree{
3     int N, M = 0, H;
4     vector<int> parent, dep;
5     vector<vector<int>> G, LCA;
6
7     Tree(int _N) : N(_N+1), H(__lg(N)+1), parent(N, -1), dep(
        N), G(N){
8         LCA.resize(H, vector<int>(N, 0));
9     }
10
11    void add_edge(int u, int v){
12        M++;
13        G[u].push_back(v);
14        G[v].push_back(u);
15    }
16
17    void dfs(int now = 0, int pre = 0){
18        dep[now] = dep[pre]+1;

```

```

19     parent[now] = pre;
20     for (auto x : G[now]){
21         if (x==pre) continue;
22         dfs(x, now);
23     }
24 }
25
26 void build_LCA(int root = 0){
27     dfs();
28     for (int i=0; i<N; i++) LCA[0][i] = parent[i];
29     for (int i=1; i<H; i++){
30         for (int j=0; j<N; j++){
31             LCA[i][j] = LCA[i-1][LCA[i-1][j]];
32         }
33     }
34 }
35
36 int jump(int u, int step){
37     for (int i=0; i<H; i++){
38         if (step&(1<<i)) u = LCA[i][u];
39     }
40     return u;
41 }
42
43 int get_LCA(int u, int v){
44     if (dep[u]<dep[v]) swap(u, v);
45     u = jump(u, dep[u]-dep[v]);
46     if (u==v) return u;
47     for (int i=H-1; i>=0; i--){
48         if (LCA[i][u]!=LCA[i][v]){
49             u = LCA[i][u];
50             v = LCA[i][v];
51         }
52     }
53     return parent[u];
54 }
55 };

```

6.13 MCMF [0d5244]

```

1 struct Flow {
2     struct Edge {
3         int u, rc, k, rv;
4     };
5
6     vector<vector<Edge>> G;
7     vector<int> par, par_eid;
8     Flow(int n) : G(n+1), par(n+1), par_eid(n+1) {}
9
10    // v->u, capacity: c, cost: k
11    void add(int v, int u, int c, int k){
12        G[v].push_back({u, c, k, G[u].size()});
13        G[u].push_back({v, 0, -k, G[v].size()-1});
14    }
15
16    // 6d1140
17    int spfa(int s, int t){
18        fill(par.begin(), par.end(), -1);
19        vector<int> dis(par.size(), INF);
20        vector<bool> in_q(par.size(), false);
21        queue<int> Q;
22        dis[s] = 0;
23        in_q[s] = true;
24        Q.push(s);
25

```

```

26 while (!Q.empty()){
27     int v = Q.front();
28     Q.pop();
29     in_q[v] = false;
30
31     for (int i=0; i<G[v].size(); i++){
32         auto [u, rc, k, rv] = G[v][i];
33         if (rc>0 && dis[v]+k<dis[u]){
34             dis[u] = dis[v]+k;
35             par[u] = v;
36             par_eid[u] = i;
37             if (!in_q[u]) Q.push(u);
38             in_q[u] = true;
39         }
40     }
41 }
42
43 return dis[t];
44 }
45
46 // return <max flow, min cost>, d7e7ad
47 pair<int, int> flow(int s, int t){
48     int fl = 0, cost = 0, d;
49     while ((d = spfa(s, t))<INF){
50         int cur = INF;
51         for (int v=t; v!=s; v=par[v])
52             cur = min(cur, G[par[v]][par_eid[v]].rc);
53         fl += cur;
54         cost += d*cur;
55         for (int v=t; v!=s; v=par[v]){
56             G[par[v]][par_eid[v]].rc -= cur;
57             G[v][G[par[v]][par_eid[v]].rv].rc += cur;
58         }
59     }
60     return {fl, cost};
61 }
62 };

```

6.14 Tarjan [8b2350]

```

1 struct tarjan_SCC {
2     int now_T, now_SCCs;
3     vector<int> dfn, low, SCC;
4     stack<int> S;
5     vector<vector<int>> E;
6     vector<bool> vis, in_stack;
7
8     tarjan_SCC(int n) {
9         init(n);
10    }
11
12    void init(int n) {
13        now_T = now_SCCs = 0;
14        dfn = low = SCC = vector<int>(n);
15        E = vector<vector<int>>(n);
16        S = stack<int>();
17        vis = in_stack = vector<bool>(n);
18    }
19
20    void add(int u, int v) {
21        E[u].push_back(v);
22    }
23
24    void build() {
25        for (int i = 0; i < dfn.size(); ++i) {
26            if (!dfn[i]) dfs(i);
27        }
28    }
29

```

```

26 void dfs(int v) {
27     now_T++;
28     vis[v] = in_stack[v] = true;
29     dfn[v] = low[v] = now_T;
30     S.push(v);
31     for (auto &i:E[v]) {
32         if (!vis[i]) {
33             vis[i] = true;
34             dfs(i);
35             low[v] = min(low[v], low[i]);
36         }
37         else if (in_stack[i]) {
38             low[v] = min(low[v], dfn[i]);
39         }
40     }
41     if (low[v] == dfn[v]) {
42         int tmp;
43         do {
44             tmp = S.top();
45             S.pop();
46             SCC[tmp] = now_SCCs;
47             in_stack[tmp] = false;
48         } while (tmp != v);
49         now_SCCs += 1;
50     }
51 }
52 };

```

6.15 Tarjan Find AP [1daed6]

```

1 vector<int> dep(MAX_N), low(MAX_N), AP;
2 bitset<MAX_N> vis;
3
4 void dfs(int now, int pre){
5     int cnt = 0;
6     bool ap = 0;
7     vis[now] = 1;
8     low[now] = dep[now] = (now==1 ? 0 : dep[pre]+1);
9
10    for (auto x : G[now]){
11        if (x==pre){
12            continue;
13        } else if (vis[x]==0){
14            cnt++;
15            dfs(x, now);
16            low[now] = min(low[now], low[x]);
17            if (low[x]>=dep[now]) ap=1;
18        } else {
19            low[now] = min(low[now], dep[x]);
20        }
21    }
22
23    if ((now==pre && cnt==2) || (now!=pre && ap)){
24        AP.push_back(now);
25    }
26 }

```

6.16 Theorem

• 任意圖

- 最大匹配 + 最小邊覆蓋 = n (不能有孤點)
- 點覆蓋的補集是獨立集。最小點覆蓋 + 最大獨立集 = n
- w (最小權點覆蓋) + w (最大權獨立集) = $\sum w_v$

- (帶點權的二分圖可以用最小割解·構造請參考 Augment Path.cpp)
- 二分圖
 - 最小點覆蓋 = 最大匹配 = n - 最大獨立集
- 只有邊帶權的二分圖
 - w-vertex-cover (帶權點覆蓋): 每條邊的兩個連接點被選中的次數總和至少要是 w_e 。
 - w-weight matching (帶權匹配)
 - minimum vertex count of w-vertex-cover = maximum weight count of w-weight matching (一個點可以被選很多次·但邊不行)
- 點、邊都帶權的二分圖的定理
 - b-matching: 假設 v 的點權是 b_v ·那所有 v 的匹配邊 e 的權重都要滿足 $\sum w_e \leq b_v$ 。
 - The maximum w-weight of a b-matching equals the minimum b-weight of vertices in a w-vertex-cover.

6.17 Tree Isomorphism [cd2bbc]

```

1 #include <bits/stdc++.h>
2 #pragma GCC optimize("O3,unroll-loops")
3 #define fastio ios::sync_with_stdio(0), cin.tie(0), cout.tie
4 (0)
5 #define dbg(x) cerr << #x << " = " << x << endl
6 #define int long long
7 using namespace std;
8 // declare
9 const int MAX_SIZE = 2e5+5;
10 const int INF = 9e18;
11 const int MOD = 1e9+7;
12 const double EPS = 1e-6;
13 typedef vector<vector<int>> Graph;
14 typedef map<vector<int>, int> Hash;
15
16 int n, a, b;
17 int id1, id2;
18 pair<int, int> c1, c2;
19 vector<int> sz1(MAX_SIZE), sz2(MAX_SIZE);
20 vector<int> we1(MAX_SIZE), we2(MAX_SIZE);
21 Graph g1(MAX_SIZE), g2(MAX_SIZE);
22 Hash m1, m2;
23 int testcase=0;
24
25 void centroid(Graph &g, vector<int> &s, vector<int> &w, pair<
26 int, int> &rec, int now, int pre){
27   s[now]=1;
28   w[now]=0;
29   for (auto x : g[now]){
30     if (x!=pre){
31       centroid(g, s, w, rec, x, now);
32       s[now]+=s[x];
33       w[now]=max(w[now], s[x]);
34     }
35   }
36   w[now]=max(w[now], n-s[now]);
37   if (w[now]<=n/2){
38     if (rec.first==0) rec.first=now;
39     else rec.second=now;

```

```

40   }
41 }
42
43 int dfs(Graph &g, Hash &m, int &id, int now, int pre){
44   vector<int> v;
45   for (auto x : g[now]){
46     if (x!=pre){
47       int add=dfs(g, m, id, x, now);
48       v.push_back(add);
49     }
50   }
51   sort(v.begin(), v.end());
52
53   if (m.find(v)!=m.end()){
54     return m[v];
55   }else{
56     m[v]++;id;
57     return id;
58   }
59 }
60
61 void solve1(){
62
63   // init
64   id1=0;
65   id2=0;
66   c1={0, 0};
67   c2={0, 0};
68   fill(sz1.begin(), sz1.begin()+n+1, 0);
69   fill(sz2.begin(), sz2.begin()+n+1, 0);
70   fill(we1.begin(), we1.begin()+n+1, 0);
71   fill(we2.begin(), we2.begin()+n+1, 0);
72   for (int i=1; i<=n; i++){
73     g1[i].clear();
74     g2[i].clear();
75   }
76   m1.clear();
77   m2.clear();
78
79   // input
80   cin >> n;
81   for (int i=0; i<n-1; i++){
82     cin >> a >> b;
83     g1[a].push_back(b);
84     g1[b].push_back(a);
85   }
86   for (int i=0; i<n-1; i++){
87     cin >> a >> b;
88     g2[a].push_back(b);
89     g2[b].push_back(a);
90   }
91
92   // get tree centroid
93   centroid(g1, sz1, we1, c1, 1, 0);
94   centroid(g2, sz2, we2, c2, 1, 0);
95
96   // process
97   int res1=0, res2=0, res3=0;
98   if (c2.second!=0){
99     res1=dfs(g1, m1, id1, c1.first, 0);
100     m2=m1;
101     id2=id1;
102     res2=dfs(g2, m1, id1, c2.first, 0);
103     res3=dfs(g2, m2, id2, c2.second, 0);
104   }else if (c1.second!=0){

```

```

106     res1=dfs(g2, m1, id1, c2.first, 0);
107     m2=m1;
108     id2=id1;
109     res2=dfs(g1, m1, id1, c1.first, 0);
110     res3=dfs(g1, m2, id2, c1.second, 0);
111   }else{
112     res1=dfs(g1, m1, id1, c1.first, 0);
113     res2=dfs(g2, m1, id1, c2.first, 0);
114   }
115
116   // output
117   cout << (res1==res2 || res1==res3 ? "YES" : "NO") << endl;
118   ;
119   return;
120 }
121
122 signed main(void){
123   fastio;
124
125   int t=1;
126   cin >> t;
127   while (t--){
128     solve1();
129   }
130   return 0;
131 }

```

6.18 圓方樹 [675aec]

```

1 #include <bits/stdc++.h>
2 #define lp(i,a,b) for(int i=(a);i<(b);i++)
3 #define pii pair<int,int>
4 #define pb push_back
5 #define ins insert
6 #define ff first
7 #define ss second
8 #define opa(x) cerr << #x << " = " << x << ", ";
9 #define op(x) cerr << #x << " = " << x << endl;
10 #define ops(x) cerr << x;
11 #define etr cerr << endl;
12 #define spc cerr << ' ';
13 #define BAE(x) (x).begin(), (x).end()
14 #define STL(x) cerr << #x << " : "; for(auto &qwe:x) cerr <<
15 qwe << ' '; cerr << endl;
16 #define deb1 cerr << "deb1" << endl;
17 #define deb2 cerr << "deb2" << endl;
18 #define deb3 cerr << "deb3" << endl;
19 #define deb4 cerr << "deb4" << endl;
20 #define deb5 cerr << "deb5" << endl;
21 #define bye exit(0);
22 using namespace std;
23
24 const int mxn = (int)(2e5) + 10;
25 const int mxlg = 17;
26 int last_special_node = (int)(1e5) + 1;
27 vector<int> E[mxn], F[mxn];
28
29 struct edg{
30   int fr, to;
31   edg(int _fr, int _to){
32     fr = _fr;
33     to = _to;
34   }
35 };

```

```

35 ostream& operator<<(ostream& os, edg x){os << x.fr << "--" << 99
    x.to;}
36 vector<edg> EV;
37
38 void tarjan(int v, int par, stack<int>& S){
39     static vector<int> dfn(mxn), low(mxn);
40     static vector<bool> to_add(mxn);
41     static int nowT = 0;
42
43     int child = 0;
44     nowT += 1;
45     dfn[v] = low[v] = nowT;
46     for(auto &ne:E[v]){
47         int i = EV[ne].to;
48         if(i == par) continue;
49         if(!dfn[i]){
50             S.push(ne);
51             tarjan(i, v, S);
52             child += 1;
53             low[v] = min(low[v], low[i]);
54
55             if(par >= 0 && low[i] >= dfn[v]){
56                 vector<int> bcc;
57                 int tmp;
58                 do{
59                     tmp = S.top(); S.pop();
60                     if(!to_add[EV[tmp].fr]){
61                         to_add[EV[tmp].fr] = true;
62                         bcc.pb(EV[tmp].fr);
63                     }
64                     if(!to_add[EV[tmp].to]){
65                         to_add[EV[tmp].to] = true;
66                         bcc.pb(EV[tmp].to);
67                     }
68                 }while(tmp != ne);
69                 for(auto &j:bcc){
70                     to_add[j] = false;
71                     F[last_special_node].pb(j);
72                     F[j].pb(last_special_node);
73                 }
74                 last_special_node += 1;
75             }
76         }
77         else{
78             low[v] = min(low[v], dfn[i]);
79             if(dfn[i] < dfn[v]){ // edge i--v will be visited
80                 twice at here, but we only need one.
81                 S.push(ne);
82             }
83         }
84     }
85
86     int dep[mxn], jmp[mxn][mxlg];
87     void dfs_lca(int v, int par, int depth){
88         dep[v] = depth;
89         for(auto &i:F[v]){
90             if(i == par) continue;
91             jmp[i][0] = v;
92             dfs_lca(i, v, depth + 1);
93         }
94     }
95
96     inline void build_lca(){
97         jmp[1][0] = 1;
98         dfs_lca(1, -1, 1);

```

```

    lp(j,1,mxlg){
        lp(i,1,mxn){
            jmp[i][j] = jmp[jmp[i][j-1]][j-1];
        }
    }
}

inline int lca(int x, int y){
    if(dep[x] < dep[y]){ swap(x, y); }

    int diff = dep[x] - dep[y];
    lp(j,0,mxlg){
        if((diff >> j) & 1){
            x = jmp[x][j];
        }
    }
    if(x == y) return x;

    for(int j = mxlg - 1; j >= 0; j--){
        if(jmp[x][j] != jmp[y][j]){
            x = jmp[x][j];
            y = jmp[y][j];
        }
    }
    return jmp[x][0];
}

inline bool can_reach(int fr, int to){
    if(dep[to] > dep[fr]) return false;

    int diff = dep[fr] - dep[to];
    lp(j,0,mxlg){
        if((diff >> j) & 1){
            fr = jmp[fr][j];
        }
    }
    return fr == to;
}

int main(){
    ios::sync_with_stdio(false); cin.tie(0);
    // freopen("test_input.txt", "r", stdin);
    int n, m, q; cin >> n >> m >> q;
    lp(i,0,m){
        int u, v; cin >> u >> v;
        E[u].pb(EV.size());
        EV.pb(edg(u, v));
        E[v].pb(EV.size());
        EV.pb(edg(v, u));
    }
    E[0].pb(EV.size());
    EV.pb(edg(0, 1));
    stack<int> S;
    tarjan(0, -1, S);
    build_lca();

    lp(queries,0,q){
        int fr, to, relay; cin >> fr >> to >> relay;
        if(fr == relay || to == relay){
            cout << "NO\n";
            continue;
        }
        if((can_reach(fr, relay) || can_reach(to, relay)) &&
            dep[relay] >= dep[lca(fr, to)]){
            cout << "NO\n";
            continue;
        }
    }
}

```

```

164     }
165     cout << "YES\n";
166 }
167 }

```

6.19 最大權閉合圖 [6ca663]

```

1 // 邊 u → v 表示選 u 就要選 v (0-based)
2 // 保證回傳值非負
3 // 構造：從 S 開始 dfs，不走最小割的邊。
4 // 所有經過的點就是要選的那些點。
5 // 一般圖：O(n²m) / 二分圖：O(m√n)
6 template<typename U>
7 U maximum_closure(vector<U> w, vector<pair<int,int>>& EV) {
8     int n = w.size(), S = n + 1, T = n + 2;
9     Flow G(T + 5); // Graph/Dinic.cpp
10    U sum = 0;
11    for (int i = 0; i < n; ++i) {
12        if (w[i] > 0) {
13            G.add(S, i, w[i]);
14            sum += w[i];
15        }
16        else if (w[i] < 0) {
17            G.add(i, T, abs(w[i]));
18        }
19    }
20    for (auto &[u, v] : EV) { // 請務必確保 INF > Σw_i
21        G.add(u, v, INF);
22    }
23    U cut = G.flow(S, T);
24    return sum - cut;
25 }

```

7 Math

7.1 Burnside's Lemma

$$\sum_{k=1}^n \frac{c(k)}{n}$$

- n : 有多少種置換方式 (例如：旋轉方式)
- $c(k)$: 所有可能中，經過 k 次旋轉後，仍不會和別人相同的方式的數量

7.2 CRT [682ac6]

```

1 // 求出 d = gcd(a,b) 並找出 x, y 使 ax + by = d
2 tuple<int, int, int> extgcd(int a, int b){
3     if (!b) return {a, 1, 0};
4     auto [d, x, y] = extgcd(b, a%b);
5     return {d, y, x-a/b*y};
6 }
7
8 // CRT maybe need use int128
9 int CRT_m_coprime(vector<int> &a, vector<int> &m) {
10    int n = a.size(), p = 1, ans = 0;
11    vector<int> M(n), invM(n);
12
13    for (int i=0; i<n; i++) p *= m[i];
14    for (int i=0; i<n; i++){
15        M[i] = p/m[i];
16        auto [d, x, y] = extgcd(M[i], m[i]);
17        invM[i] = x;

```

```

18     ans += a[i]*invM[i]*M[i];
19     ans %= p;
20 }
21 return (ans%p+p)%p;
22 }
23
24 // CRT maybe need use int128
25 int CRT_m_not_coprime(vector<int> &a, vector<int> &m) {
26     int n = a.size();
27
28     for (int i=1 ; i<n ; i++){
29         int g = __gcd(m[0], m[i]);
30         if ((a[i]-a[0])%g!=0) return -1;
31
32         auto [d, x, y] = extgcd(m[0], m[i]);
33         x = (a[i]-a[0])*x/g;
34
35         a[0] = x*m[0]+a[0];
36         m[0] = m[0]*m[i]/g;
37         a[0] = (a[0]%m[0]+m[0])%m[0];
38     }
39
40     if (a[0]<0) return a[0]+m[0];
41     return a[0];
42 }
43
44 // ans = a / b (mod m)
45 // ans = ret.F + k * ret.S, k is integer
46 pair<int, int> div(int a, int b, int m) {
47     int flag = 1;
48     if (a < 0) { a = -a; flag *= -1; }
49     if (b < 0) { b = -b; flag *= -1; }
50     int t = -1, k = -1;
51     int res = extgcd_abc(b, m, a, t, k);
52     if (res == INF) return {INF, INF};
53     m = abs(m / res);
54     t = t * flag;
55     t = (t % m + m) % m;
56     return {t, m};
57 }

```

7.3 Catalan Number

任意括號序列: $C_n = \frac{1}{n+1} \binom{2n}{n}$

7.4 Josephus Problem [e0ed50]

```

1 // 有 n 個人，第偶數個報數的人被刪掉，問第 k 個被踢掉的是誰
2 int solve(int n, int k){
3     if (n==1) return 1;
4     if (k<=(n+1)/2){
5         if (2*k>n) return 2*k%n;
6         else return 2*k;
7     }else{
8         int res=solve(n/2, k-(n+1)/2);
9         if (n&1) return 2*res+1;
10        else return 2*res-1;
11    }
12 }

```

7.5 Lagrange any x [1f2c26]

```

1 // init: (x1, y1), (x2, y2) in a vector
2 struct Lagrange{
3     int n;

```

```

4     vector<pair<int, int>> v;
5
6     Lagrange(vector<pair<int, int>> &v){
7         n = _v.size();
8         v = _v;
9     }
10
11     // O(n^2 Log MAX_A)
12     int solve(int x){
13         int ret = 0;
14         for (int i=0 ; i<n ; i++){
15             int now = v[i].second;
16             for (int j=0 ; j<n ; j++){
17                 if (i==j) continue;
18                 now *= ((x-v[j].first+MOD)%MOD);
19                 now %= MOD;
20                 now *= (qp((v[i].first-v[j].first+MOD)%MOD,
21                     MOD-2)+MOD)%MOD;
22                 now %= MOD;
23             }
24             ret = (ret+now)%MOD;
25         }
26         return ret;
27     }
28 };

```

7.6 Lagrange continuous x [57536a]

```

1 #include <bits/stdc++.h>
2 using namespace std;
3
4 const int MAX_N = 5e5 + 10;
5 const int mod = 1e9 + 7;
6
7 long long inv_fac[MAX_N];
8
9 inline int fp(long long x, int y) {
10     int ret = 1;
11     for (; y; y >>= 1) {
12         ret = (y & 1) ? (ret * x % mod) : ret;
13         x = x * x % mod;
14     }
15     return ret;
16 }
17
18 // TO USE THIS TEMPLATE, YOU MUST MAKE SURE THAT THE MOD
19 // NUMBER IS A PRIME.
20 struct Lagrange {
21     /*
22      * Initialize a polynomial with f(x_0), f(x_0 + 1), ..., f(
23      * x_0 + n).
24      * This determines a polynomial f(x) whose degree is at most
25      * n.
26      * Then you can call sample(x) and you get the value of f(x)
27      * .
28      * Complexity of init() and sample() are both O(n).
29      */
30     int m, shift; // m = n + 1
31     vector<int> v, mul;
32     // You can use this function if you don't have inv_fac array
33     // already.
34     void construct_inv_fac() {
35         long long fac = 1;
36         for (int i = 2; i < MAX_N; ++i) {

```

```

37         fac = fac * i % mod;
38     }
39     inv_fac[MAX_N - 1] = fp(fac, mod - 2);
40     for (int i = MAX_N - 1; i >= 1; --i) {
41         inv_fac[i - 1] = inv_fac[i] * i % mod;
42     }
43 }
44 // You call init() many times without having a second
45 // instance of this struct.
46 void init(int X_0, vector<int> &u) {
47     v = u;
48     shift = ((1 - X_0) % mod + mod) % mod;
49     if (v.size() == 1) v.push_back(v[0]);
50     m = v.size();
51     mul.resize(m);
52 }
53 // You can use sample(x) instead of sample(x % mod).
54 int sample(int x) {
55     x = ((long long)x + shift) % mod;
56     x = (x < 0) ? (x + mod) : x;
57     long long now = 1;
58     for (int i = m; i >= 1; --i) {
59         mul[i - 1] = now;
60         now = now * (x - i) % mod;
61     }
62     int ret = 0;
63     bool neg = (m - 1) & 1;
64     now = 1;
65     for (int i = 1; i <= m; ++i) {
66         int up = now * mul[i - 1] % mod;
67         int down = inv_fac[m - i] * inv_fac[i - 1] % mod;
68         int tmp = ((long long)v[i - 1] * up % mod) * down
69             % mod;
70         ret += (neg && tmp) ? (mod - tmp) : (tmp);
71         ret = (ret >= mod) ? (ret - mod) : ret;
72         now = now * (x - i) % mod;
73         neg ^= 1;
74     }
75     return ret;
76 }
77
78 int main() {
79     int n; cin >> n;
80     vector<int> v(n);
81     for (int i = 0; i < n; ++i) {
82         cin >> v[i];
83     }
84     Lagrange L;
85     L.construct_inv_fac();
86     L.init(0, v);
87     int x; cin >> x;
88     cout << L.sample(x);
89 }

```

7.7 Linear Mod Inverse [ecf71e]

```

1 // 線性求 1-based a[i] 對 p 的乘法反元素
2 vector<int> s(n+1, 1), invS(n+1), invA(n+1);
3 for (int i=1 ; i<=n ; i++) s[i] = s[i-1]*a[i]%p;
4 invS[n] = qp(s[n], p-2, p);
5 for (int i=n ; i>=1 ; i--) invS[i-1] = invS[i]*a[i]%p;
6 for (int i=1 ; i<=n ; i++) invA[i] = invS[i]*s[i-1]%p;

```

7.8 Lucas's Theorem [b37dcf]

```
1 // 對於很大的  $C^n_{m}$  對質數  $p$  取模，只要  $p$  不大就可以用。
2 int Lucas(int n, int m, int p){
3     if (m==0) return 1;
4     return (C(n%p, m%p, p)*Lucas(n/p, m/p, p)%p);
5 }
```

7.9 Matrix [8d1a23]

```
1 struct Matrix{
2     int n, m;
3     vector<vector<int>> arr;
4
5     Matrix(int _n, int _m){
6         n = _n;
7         m = _m;
8         arr.assign(n, vector<int>(m));
9     }
10
11     vector<int> & operator [] (int i){
12         return arr[i];
13     }
14
15     Matrix operator * (Matrix b){
16         Matrix ret(n, b.m);
17         for (int i=0 ; i<n ; i++){
18             for (int j=0 ; j<b.m ; j++){
19                 for (int k=0 ; k<m ; k++){
20                     ret.arr[i][j] += arr[i][k]*b.arr[k][j]%
21                         MOD;
22                     ret.arr[i][j] %= MOD;
23                 }
24             }
25             return ret;
26         }
27
28     Matrix pow(int p){
29         Matrix ret(n, n), mul = *this;
30         for (int i=0 ; i<n ; i++){
31             ret.arr[i][i] = 1;
32         }
33
34         for ( ; p ; p>=1){
35             if (p&1) ret = ret*mul;
36             mul = mul*mul;
37         }
38         return ret;
39     }
40 }
41
42 int det(){
43     vector<vector<int>> arr = this->arr;
44     bool flag = false;
45     for (int i=0 ; i<n ; i++){
46         int target = -1;
47         for (int j=i ; j<n ; j++){
48             if (arr[j][i]){
49                 target = j;
50                 break;
51             }
52         }
53         if (target==-1) return 0;
54     }
```

```
55     if (i!=target){
56         swap(arr[i], arr[target]);
57         flag = !flag;
58     }
59
60     for (int j=i+1 ; j<n ; j++){
61         if (!arr[j][i]) continue;
62         int freq = arr[j][i]*qp(arr[i][i], MOD-2)%MOD;
63
64         for (int k=i ; k<n ; k++){
65             arr[j][k] -= freq*arr[i][k];
66             arr[j][k] = (arr[j][k]%MOD+MOD)%MOD;
67         }
68     }
69
70     int ret = !flag ? 1 : MOD-1;
71     for (int i=0 ; i<n ; i++){
72         ret *= arr[i][i];
73         ret %= MOD;
74     }
75     return ret;
76 }
77 };
```

7.10 Matrix 01 [8d542a]

```
1 const int MAX_N = (1LL<<12);
2 struct Matrix{
3     int n, m;
4     vector<bitset<MAX_N>> arr;
5
6     Matrix(int _n, int _m){
7         n = _n;
8         m = _m;
9         arr.resize(n);
10    }
11
12    Matrix operator * (Matrix b){
13        Matrix b_t(b.m, b.n);
14        for (int i=0 ; i<b.n ; i++){
15            for (int j=0 ; j<b.m ; j++){
16                b_t.arr[j][i] = b.arr[i][j];
17            }
18        }
19
20        Matrix ret(n, b.m);
21        for (int i=0 ; i<n ; i++){
22            for (int j=0 ; j<b.m ; j++){
23                ret.arr[i][j] = ((arr[i]&b_t.arr[j]).count()
24                    &1);
25            }
26        }
27        return ret;
28    }
29 };
```

7.11 Matrix Tree Theorem

目標：給定一張無向圖，問他的生成樹數量。
方法：先把所有自環刪掉，定義 Q 為以下矩陣

$$Q_{i,j} = \begin{cases} \deg(v_i) & \text{if } i = j \\ -(邊v_i v_j \text{ 的數量}) & \text{otherwise} \end{cases}$$

接著刪掉 Q 的第一個 row 跟 column，它的 determinant 就是答案。
目標：給定一張有向圖，問他的以 r 為根，可以走到所有點生成樹數量。

方法：先把所有自環刪掉，定義 Q 為以下矩陣

$$Q_{i,j} = \begin{cases} \deg_{in}(v_i) & \text{if } i = j \\ -(邊v_i v_j \text{ 的數量}) & \text{otherwise} \end{cases}$$

接著刪掉 Q 的第 r 個 row 跟 column，它的 determinant 就是答案。

7.12 Miller Rabin [24bd0d]

```
1 //  $O(k \log^3 n)$ ,  $k = llsprr.size()$ 
2 typedef Uint unsigned long long;
3 Uint modmul(Uint a, Uint b, Uint m) {
4     int ret = a*b - m*(Uint)((long double)a*b/m);
5     return ret + m*(ret < 0) - m*(ret >= (int)m);
6 }
7
8 int qp(int b, int p, int m){
9     int ret = 1;
10    for ( ; p ; p>=1){
11        if (p&1) ret = modmul(ret, b, m);
12        b = modmul(b, b, m);
13    }
14    return ret;
15 }
16
17 // ed23aa
18 vector<int> llsprr = {2, 325, 9375, 28178, 450775, 9780504,
19     1795265022};
20 bool is_prime(int n, vector<int> sprp = llsprr){
21     if (n==2) return 1;
22     if (n<2 || n%2==0) return 0;
23
24     int t = 0;
25     int u = n-1;
26     for ( ; u%2==0 ; t++) u>>=1;
27
28     for (int i=0 ; i<sprp.size() ; i++){
29         int a = sprp[i]%n;
30         if (a==0 || a==1 || a==n-1) continue;
31         int x = qp(a, u, n);
32         if (x==1 || x==n-1) continue;
33         for (int j=0 ; j<t ; j++){
34             x = modmul(x, x, n);
35             if (x==1) return 0;
36             if (x==n-1) break;
37         }
38         if (x==n-1) continue;
39         return false;
40     }
41
42     return true;
43 }
```

7.13 Pollard Rho [a5dae]

```
1 mt19937 seed(chrono::steady_clock::now().time_since_epoch().
2     count());
3 int rnd(int l, int r){
4     return uniform_int_distribution<int>(l, r)(seed);
5 }
```



```

5
6 //  $O(n^{1/4})$  回傳 1 或自己的因數、記得先判斷  $n$  是不是質數
  (用 Miller-Rabin)
7 // c1670c
8 int Pollard_Rho(int n){
9     int s = 0, t = 0;
10    int c = rnd(1, n-1);
11
12    int step = 0, goal = 1;
13    int val = 1;
14
15    for (goal=1 ; ; goal<=1, s=t, val=1){
16        for (step=1 ; step<=goal ; step++){
17
18            t = ((__int128)t*t+c)%n;
19            val = (__int128)val*abs(t-s)%n;
20
21            if ((step % 127) == 0){
22                int d = __gcd(val, n);
23                if (d>1) return d;
24            }
25        }
26
27        int d = __gcd(val, n);
28        if (d>1) return d;
29    }
30 }

```

7.14 Polynomial [51ca3b]

```

1 struct Poly {
2     int len, deg;
3     int *a;
4     //  $len = 2^k \geq$  the original length
5     Poly(): len(0), deg(0), a(nullptr) {}
6     Poly(int _n) {
7         len = 1;
8         deg = _n - 1;
9         while (len < _n) len <= 1;
10        a = (ll*) calloc(len, sizeof(ll));
11    }
12    Poly(int l, int d, int *b) {
13        len = l;
14        deg = d;
15        a = b;
16    }
17    void resize(int _n) {
18        int len1 = 1;
19        while (len1 < _n) len1 <= 1;
20        int *res = (ll*) calloc(len1, sizeof(ll));
21        for (int i = 0; i < min(len, _n); i++) {
22            res[i] = a[i];
23        }
24        len = len1;
25        deg = _n - 1;
26        free(a);
27        a = res;
28    }
29    Poly& operator=(const Poly rhs) {
30        this->len = rhs.len;
31        this->deg = rhs.deg;
32        this->a = (ll*)realloc(this->a, sizeof(ll) * len);
33        copy(rhs.a, rhs.a + len, this->a);
34        return *this;
35    }

```

```

36 Poly operator*(Poly rhs) {
37     int l1 = this->len, l2 = rhs.len;
38     int d1 = this->deg, d2 = rhs.deg;
39     while (l1 > 0 and this->a[l1 - 1] == 0) l1--;
40     while (l2 > 0 and rhs.a[l2 - 1] == 0) l2--;
41     int l = 1;
42     while (l < max(l1 + l2 - 1, d1 + d2 + 1)) l <= 1;
43     int *x, *y, *res;
44     x = (ll*) calloc(l, sizeof(ll));
45     y = (ll*) calloc(l, sizeof(ll));
46     res = (ll*) calloc(l, sizeof(ll));
47     copy(this->a, this->a + l1, x);
48     copy(rhs.a, rhs.a + l2, y);
49     ntt.tran(l, x); ntt.tran(l, y);
50     FOR (i, 0, l - 1)
51         res[i] = x[i] * y[i] % mod;
52     ntt.tran(l, res, true);
53     free(x); free(y);
54     return Poly(l, d1 + d2, res);
55 }
56 Poly operator+(Poly rhs) {
57     int l1 = this->len, l2 = rhs.len;
58     int l = max(l1, l2);
59     Poly res;
60     res.len = l;
61     res.deg = max(this->deg, rhs.deg);
62     res.a = (ll*) calloc(l, sizeof(ll));
63     FOR (i, 0, l1 - 1) {
64         res.a[i] += this->a[i];
65         if (res.a[i] >= mod) res.a[i] -= mod;
66     }
67     FOR (i, 0, l2 - 1) {
68         res.a[i] += rhs.a[i];
69         if (res.a[i] >= mod) res.a[i] -= mod;
70     }
71     return res;
72 }
73 Poly operator-(Poly rhs) {
74     int l1 = this->len, l2 = rhs.len;
75     int l = max(l1, l2);
76     Poly res;
77     res.len = l;
78     res.deg = max(this->deg, rhs.deg);
79     res.a = (ll*) calloc(l, sizeof(ll));
80     FOR (i, 0, l1 - 1) {
81         res.a[i] += this->a[i];
82         if (res.a[i] >= mod) res.a[i] -= mod;
83     }
84     FOR (i, 0, l2 - 1) {
85         res.a[i] -= rhs.a[i];
86         if (res.a[i] < 0) res.a[i] += mod;
87     }
88     return res;
89 }
90 Poly operator*(const int rhs) {
91     Poly res;
92     res = *this;
93     FOR (i, 0, res.len - 1) {
94         res.a[i] = res.a[i] * rhs % mod;
95         if (res.a[i] < 0) res.a[i] += mod;
96     }
97     return res;
98 }
99 Poly(vector<int> f) {
100    int _n = f.size();
101    len = 1;

```

```

102    deg = _n - 1;
103    while (len < _n) len <= 1;
104    a = (ll*) calloc(len, sizeof(ll));
105    FOR (i, 0, deg) a[i] = f[i];
106 }
107 Poly derivative() {
108     Poly g(this->deg);
109     FOR (i, 1, this->deg) {
110         g.a[i - 1] = this->a[i] * i % mod;
111     }
112     return g;
113 }
114 Poly integral() {
115     Poly g(this->deg + 2);
116     FOR (i, 0, this->deg) {
117         g.a[i + 1] = this->a[i] * ::inv(i + 1) % mod;
118     }
119     return g;
120 }
121 Poly inv(int len1 = -1) {
122     if (len1 == -1) len1 = this->len;
123     Poly g(1); g.a[0] = ::inv(a[0]);
124     for (int l = 1; l < len1; l <= 1) {
125         Poly t; t = *this;
126         t.resize(l < 1);
127         t = g * t;
128         t.resize(l < 1);
129         Poly g1 = g * 2 - t;
130         swap(g, g1);
131     }
132     return g;
133 }
134 Poly ln(int len1 = -1) {
135     if (len1 == -1) len1 = this->len;
136     auto g = *this;
137     auto x = g.derivative() * g.inv(len1);
138     x.resize(len1);
139     x = x.integral();
140     x.resize(len1);
141     return x;
142 }
143 Poly exp() {
144     Poly g(1);
145     g.a[0] = 1;
146     for (int l = 1; l < len; l <= 1) {
147         Poly t, g1; t = *this;
148         t.resize(l < 1); t.a[0]++;
149         g1 = (t - g.ln(l < 1)) * g;
150         g1.resize(l < 1);
151         swap(g, g1);
152     }
153     return g;
154 }
155 Poly pow(ll n) {
156     Poly &a = *this;
157     int i = 0;
158     while (i <= a.deg and a.a[i] == 0) i++;
159     if (i and (n > a.deg or n * i > a.deg)) return Poly(a.deg + 1);
160     if (i == a.deg + 1) {
161         Poly res(a.deg + 1);
162         res.a[0] = 1;
163         return res;
164     }
165     Poly b(a.deg - i + 1);
166     int inv1 = ::inv(a.a[i]);

```

```

167     FOR (j, 0, b.deg)
168         b.a[j] = a.a[j + i] * inv1 % mod;
169     Poly res1 = (b.ln() * (n % mod)).exp() * (::power(a.a
    [i], n));
170     Poly res2(a.deg + 1);
171     FOR (j, 0, min((11)(res1.deg), (11)(a.deg - n * i)))
172         res2.a[j + n * i] = res1.a[j];
173     return res2;
174 }
175 };

```

7.15 Stirling's formula

$$n! \approx \sqrt{2\pi n} \left(\frac{n}{e}\right)^n$$

7.16 Theorem

1. $1 \sim x$ 質數的數量 $\approx \frac{x}{\ln x}$
2. x 的因數的數量 $\approx x^{\frac{1}{3}}$
3. x 的質因數的數量 $\approx \log \log x$
4. p is a prime number $\Leftrightarrow (p-1)! \equiv -1 \pmod{p}$
5. 每個正整數都可以表示成四個整數的平方和
6. 任何大於 2 的整數都可以表示成兩個質數的和
7. $n^{k-2} \cdot \prod_{i=1}^k s_i$ n 個點、 k 的連通塊，加上 $k-1$ 條邊使得變成一個連通圖的方法數，其中每個連通塊有 s_i 個點

7.17 josephus [0be067]

```

1 // n 個人，每 k 個人就刪除的約瑟夫遊戲
2 int josephus(int n, int k) {
3     if (n == 1)
4         return 0;
5     if (k == 1)
6         return n-1;
7     if (k > n)
8         return (josephus(n-1, k) + k) % n;
9     int cnt = n / k;
10    int res = josephus(n - cnt, k);
11    res -= n % k;
12    if (res < 0)
13        res += n;
14    else
15        res += res / (k - 1);
16    return res;
17 }

```

7.18 二元一次方程式

$$\begin{cases} ax + by = e \\ cx + dy = f \end{cases} = \begin{cases} x = \frac{ed-bf}{ad-bc} \\ y = \frac{af-ec}{ad-bc} \end{cases}$$

若 $x = \frac{0}{0}$ 且 $y = \frac{0}{0}$ ，則代表無限多組解。若 $x = \frac{*}{0}$ 且 $y = \frac{*}{0}$ ，則代表無解。

7.19 數論分塊 [8ccab5]

```

1 // 時間複雜度為 O(sqrt(n))
2 // 區間為 [L, r]
3 for(int i=1; i<=n; i++){
4     int l = i, r = n/(n/i);
5     i = r;
6     ans.push_back(r);
7 }

```

7.20 最大質因數 [ca5e52]

```

1 void max_fac(int n, int &ret){
2     if (n<=ret || n<2) return;
3     if (isprime(n)){
4         ret = max(ret, n);
5         return;
6     }
7
8     int p = Pollard_Rho(n);
9     max_fac(p, ret), max_fac(n/p, ret);
10 }

```

7.21 歐拉公式 [85f3b1]

```

1 // phi(n) = 小於 n 並與 n 互質的正整數數量。
2 // O(sqrt(n)) · 回傳 phi(n)
3 int phi(int n){
4     int ret = n;
5
6     for (int i=2; i*i<=n; i++){
7         if (n%i==0){
8             while (n%i==0) n /= i;
9             ret = ret*(i-1)/i;
10        }
11    }
12    if (n>1) ret = ret*(n-1)/n;
13
14    return ret;
15 }
16
17 // O(n log n) · 回傳 1~n 的 phi 值
18 vector<int> phi_1_to_n(int n){
19     vector<int> phi(n+1);
20     phi[0]=0;
21     phi[1]=1;
22
23     for (int i=2; i<=n; i++){
24         phi[i]=i-1;
25     }
26
27     for (int i=2; i<=n; i++){
28         for (int j=2*i; j<=n; j+=i){ // 枚舉所有倍數
29             phi[j]-=phi[i];
30         }
31     }
32
33     return phi;
34 }

```

7.22 歐拉定理

若 a, m 互質，則：

$$a^n \equiv a^{n \bmod \varphi(m)} \pmod{m}$$

若 a, m 不互質，則：

$$a^n \equiv a^{\varphi(m) + [n \bmod \varphi(m)]} \pmod{m}$$

7.23 錯排公式

錯排公式： $(n$ 個人中，每個人皆不再原來位置的組合數)

$$dp_i = \begin{cases} 1 & i = 0 \\ 0 & i = 1 \\ (i-1)(dp_{i-1} + dp_{i-2}) & \text{otherwise} \end{cases}$$

8 String

8.1 AC automation [018290]

```

1 struct ACAutomation{
2     vector<vector<int>> go;
3     vector<int> fail, match, pos;
4     int sz = 0; // 有效節點為 [0, sz] · 開陣列的時候要小心 !!!
5
6     ACAutomation(int n) : go(n, vector<int>(26)), fail(n),
7         match(n) {}
8
9     void add(string s){
10        int now = 0;
11        for (char c : s){
12            if (!go[now][c-'a']) go[now][c-'a'] = ++sz;
13            now = go[now][c-'a'];
14        }
15        pos.push_back(now);
16    }
17
18    void build(){
19        queue<int> que;
20        for (int i=0; i<26; i++){
21            if (go[0][i]) que.push(go[0][i]);
22        }
23        while (que.size()){
24            int u = que.front();
25            que.pop();
26            for (int i=0; i<26; i++){
27                if (go[u][i]){
28                    fail[go[u][i]] = go[fail[u]][i];
29                    que.push(go[u][i]);
30                }else go[u][i] = go[fail[u]][i];
31            }
32        }
33    }
34
35    // counting pattern
36    void buildMatch(string &s){
37        int now = 0;
38        for (char c : s){
39            now = go[now][c-'a'];
40            match[now]++;
41        }
42
43        vector<int> in(sz+1), que;
44        for (int i=1; i<=sz; i++) in[fail[i]]++;
45        for (int i=1; i<=sz; i++) if (in[i]==0) que.
46            push_back(i);

```

```

45     for (int i=0 ; i<que.size() ; i++){
46         int now = que[i];
47         match[fail[now]] += match[now];
48         if (--in[fail[now]]==0) que.push_back(fail[now]);
49     }
50 }
51 };

```

8.2 Enumerate Runs [94ca46]

```

1 vector<array<int, 3>> enumerate_run(string s){
2
3
4     int n = s.size();
5     SuffixArray sa(s), saBar(string(s.rbegin(), s.rend()));
6     sa.init_lcp(), saBar.init_lcp();
7
8     set<pair<int, int>> ss;
9     vector<array<int, 3>> runs;
10
11     for (int len=1 ; len<=n ; len++){
12         vector<int> lcp;
13         for (int i=0 ; i<len ; i++){
14             int pos1 = sa.pos[i];
15             int pos2 = sa.pos[i+len];
16             lcp.push_back(sa.get_lcp(pos1, pos2));
17         }
18
19         for (int ll=0, rr=0 ; ll<lcp.size() ; rr++, ll=rr){
20             while (rr<lcp.size() && lcp[rr]>=len) rr++;
21
22             int preLen = 0;
23             if (ll!=0){
24                 int p = n-1;
25                 int pos1 = saBar.pos[p-(ll*len-1)];
26                 int pos2 = saBar.pos[p-((ll+1)*len-1)];
27                 preLen = saBar.get_lcp(pos1, pos2);
28             }
29             int sufLen = rr<lcp.size() ? lcp[rr] : 0;
30
31             int ansL = ll*len-preLen, ansR = (rr+1)*len-1+
32                 sufLen;
33             if (ansL!=ansR && ansR-ansL+1==2*len && ss.find({
34                 ansL, ansR+1})==ss.end()){
35                 ss.insert({ansL, ansR+1});
36                 runs.push_back({len, ansL, ansR+1});
37             }
38         }
39     }
40 }

```

8.3 Hash [942f42]

```

1 mt19937 seed(chrono::steady_clock::now().time_since_epoch().
2     count());
3 int rng(int l, int r){
4     return uniform_int_distribution<int>(l, r)(seed);
5 }
6 int A = rng(1e5, 8e8);
7 const int B = 1e9+7;
8 // 2f6192
9 struct RollingHash{

```

```

10     vector<int> Pow, Pre;
11     RollingHash(string s = ""){
12         Pow.resize(s.size());
13         Pre.resize(s.size());
14
15         for (int i=0 ; i<s.size() ; i++){
16             if (i==0){
17                 Pow[i] = 1;
18                 Pre[i] = s[i];
19             }else{
20                 Pow[i] = Pow[i-1]*A%B;
21                 Pre[i] = (Pre[i-1]*A+s[i])%B;
22             }
23         }
24
25         return;
26     }
27
28     int get(int l, int r){ // 取得 [l, r] 的數值
29         if (l==0) return Pre[r];
30         int res = (Pre[r]-Pre[l-1]*Pow[r-l+1])%B;
31         if (res<0) res += B;
32         return res;
33     }
34 };

```

8.4 KMP [7b95d6]

```

1 // KMP[i] = s[0...i] 的最長共同前後綴長度 · KMP[KMP[i]-1] 可以
2 // 跳 fail link
3 // e5b7ce
4 vector<int> KMP(string &s){
5     vector<int> ret(n);
6     for (int i=1 ; i<s.size() ; i++){
7         int j = ret[i-1];
8         while (j && s[i]!=s[j]) j = ret[j-1];
9         ret[i] = j + (s[i]==s[j]);
10    }
11    return ret;

```

8.5 Manacher [9a4b4d]

```

1 string Manacher(string str) {
2     string tmp = "$#";
3     for(char i : str) {
4         tmp += i;
5         tmp += '#';
6     }
7
8     vector<int> p(tmp.size(), 0);
9     int mx = 0, id = 0, len = 0, center = 0;
10    for(int i=1 ; i<(int)tmp.size() ; i++) {
11        p[i] = mx > i ? min(p[id*2-i], mx-i) : 1;
12
13        while(tmp[i+p[i]] == tmp[i-p[i]]) p[i]++;
14        if(mx<i+p[i]) mx = i+p[i], id = i;
15        if(len<p[i]) len = p[i], center = i;
16    }
17    return str.substr((center-len)/2, len-1);
18 }

```

8.6 Min Rotation [b24786]

```

1 int minRotation(string s) {
2     int a = 0, n = s.size();
3     s += s;
4
5     for (int b=0 ; b<n ; b++){
6         for (int k=0 ; k<n ; k++){
7             if (a+k==b || s[a+k]<s[b+k]){
8                 b += max(0LL, k-1);
9                 break;
10            }
11            if (s[a+k]>s[b+k]){
12                a = b;
13                break;
14            }
15        }
16    }
17    return a;
18 }

```

8.7 Suffix Array [f66629]

```

1 // 注意 · 當 |s|=1 時 · lcp 不會有值 · 務必測試 |s|=1 的 case
2 struct SuffixArray {
3     string s;
4     vector<int> sa, lcp;
5
6     // 69ced9
7     // lim 要調整成字元集大小 · _s 不可以有 0
8     SuffixArray(string _s, int lim = 256) {
9         s = _s;
10        int n = s.size()+1, k = 0, a, b;
11        vector<int> x(s.begin(), s.end()), y(n), ws(max(n,
12            lim)), rank(n);
13        x.push_back(0);
14        sa = lcp = y;
15        iota(sa.begin(), sa.end(), 0);
16        for (int j=0, p=0 ; p<n ; j=max(1LL, j*2), lim=p) {
17            p = j;
18            iota(y.begin(), y.end(), n-j);
19            for (int i=0 ; i<n ; i++) if (sa[i] >= j) y[p++]
20                = sa[i] - j;
21            fill(ws.begin(), ws.end(), 0);
22            for (int i=0 ; i<n ; i++) ws[x[i]]++;
23            for (int i=1 ; i<lim ; i++) ws[i] += ws[i-1];
24            for (int i = n; i--;) sa[--ws[x[i]]] = i;
25            swap(x, y), p = 1, x[sa[0]] = 0;
26            for (int i=1 ; i<n ; i++){
27                a = sa[i-1];
28                b = sa[i];
29                x[b] = (y[a] == y[b] && y[a+j] == y[b+j])
30                    ? p-1 : p++;
31            }
32        }
33
34        for (int i=1 ; i<n ; i++) rank[sa[i]] = i;
35        for (int i=0, j ; i<n-1 ; lcp[rank[i++]]=(k
36            for (k && k--, j=sa[rank[i]-1] ; i+k<s.size() &&
37                j+k<s.size() && s[i+k]==s[j+k] ; k++);
38        sa.erase(sa.begin());
39        lcp.erase(lcp.begin(), lcp.begin()+2);
40    }
41
42    // f49583
43    vector<int> pos; // pos[i] = i 這個值在 pos 的哪個地方

```

```

40 SparseTable st;
41 void init_lcp(){
42     pos.resize(sa.size());
43     for (int i=0 ; i<sa.size() ; i++){
44         pos[sa[i]] = i;
45     }
46     if (lcp.size()){
47         st.build(lcp);
48     }
49 }
50
51 // 用之前記得 init
52 // 查詢「sa 上的位置」的 x 跟 y 的 lcp
53 int get_lcp(int x, int y){
54     if (x==y) return s.size()-x;
55     if (x>y) swap(x, y);
56     return st.query(x, y);
57 }
58
59 // 回傳 [l1, r1] 跟 [l2, r2] 的 lcp · 0-based
60 int get_lcp(int l1, int r1, int l2, int r2){
61     int pos_1 = pos[l1], len_1 = r1-l1+1;
62     int pos_2 = pos[l2], len_2 = r2-l2+1;
63     if (pos_1>pos_2){
64         swap(pos_1, pos_2);
65         swap(len_1, len_2);
66     }
67
68     if (l1==l2){
69         return min(len_1, len_2);
70     }else{
71         return min({st.query(pos_1, pos_2), len_1, len_2
72             });
73     }
74
75 // 檢查 [l1, r1] 跟 [l2, r2] 的大小關係 · 0-based
76 // 如果前者小於後者 · 就回傳 <0 · 相等就回傳 =0 · 否則回傳
77 // >0
78 // 5b8db0
79 int substring_cmp(int l1, int r1, int l2, int r2){
80     int len_1 = r1-l1+1;
81     int len_2 = r2-l2+1;
82     int res = get_lcp(l1, r1, l2, r2);
83
84     if (res<len_1 && res<len_2){
85         return s[l1+res]-s[l2+res];
86     }else if (len_1==res && len_2==res){
87         return 0;
88     }else{
89         return len_1==res ? -1 : 1;
90     }
91 }
92
93 // 對於位置在 <=p 的後綴 · 找離他左邊/右邊最接近位置 >p 的
94 // 後綴的 lcp · 0-based
95 // pre[i] = s[i] 離他左邊最接近位置 >p 的後綴的 lcp · 0-
96 // based
97 // suf[i] = s[i] 離他右邊最接近位置 >p 的後綴的 lcp · 0-
98 // based
99 // da12fa
100 pair<vector<int>, vector<int>> get_left_and_right_lcp(int
101     p){
102     vector<int> pre(p+1);

```

```

98     vector<int> suf(p+1);
99
100     { // build pre
101         int now = 0;
102         for (int i=0 ; i<s.size() ; i++){
103             if (sa[i]<=p){
104                 pre[sa[i]] = now;
105                 if (i<lcp.size()) now = min(now, lcp[i]);
106             }else{
107                 if (i<lcp.size()) now = lcp[i];
108             }
109         }
110     }
111     { // build suf
112         int now = 0;
113         for (int i=s.size()-1 ; i>=0 ; i--){
114             if (sa[i]<=p){
115                 suf[sa[i]] = now;
116                 if (i-1>=0) now = min(now, lcp[i-1]);
117             }else{
118                 if (i-1>=0) now = lcp[i-1];
119             }
120         }
121     }
122     return {pre, suf};
123 }
124
125 };

```

8.8 Wildcard Matching [e93074]

```

1 const int B = 27;
2 string p;
3 for (int i=0 ; i<B ; i++) p += ('a'+i);
4 p += '*';
5 vector<vector<double>> res(B);
6 for (int i=0 ; i<B ; i++){
7     vector<double> ss, tt;
8     for (auto x : s) ss.push_back(x==p[i] || x=='*');
9     for (auto x : t) tt.push_back(x==p[i] || x=='*');
10    reverse(tt.begin(), tt.end());
11    res[i] = PolyMul(ss, tt);
12 }
13 for (int i=t.size()-1 ; i+t.size()-1<res[0].size() ; i++){
14     int total = 0;
15     for (int j=0 ; j<B-1 ; j++) total += (int)abs(round(res[j
16         ][i]));
17     total -= 25*(int)abs(round(res[26][i]));
18     cout << (total==t.size());
19 }

```

8.9 Z Algorithm [9d559a]

```

1 // z[i] 回傳 s[0...] 跟 s[i...] 的 lcp, z[0] = 0
2 vector<int> z_function(string s){
3     vector<int> z(s.size());
4     int l = -1, r = -1;
5     for (int i=1 ; i<s.size() ; i++){
6         z[i] = i>=r ? 0 : min(r-i, z[i-l]);
7         while (i+z[i]<s.size() && s[i+z[i]]==s[z[i]]) z[i]++;
8         if (i+z[i]>r) l=i, r=i+z[i];
9     }
10    return z;
11 }

```

8.10 k-th Substring [61f66b]

```

1 // 回傳 s 所有子字串 (完全不同) 中 · 第 k 大的
2 string k_th_substring(string &s, int k){
3     int n = s.size();
4     SuffixArray sa(s);
5     sa.init_lcp();
6
7     int prePrefix = 0, nowRank = 0;
8     for (int i=0 ; i<n ; i++){
9         int len = n-sa[i];
10        int add = len-prePrefix;
11
12        if (nowRank+add>=k){
13            return s.substr(sa[i], prePrefix+k-nowRank);
14        }
15
16        prePrefix = sa.lcp[i];
17        nowRank += add;
18    }
19 }

```