

PRIVESC Security Report

Host: DESKTOP-OTS2610 . .

Generated: 2026-05-09 04:05 UTC

Executive Summary

Risk Level	Risk Score	Total Findings	Critical	High	Medium	Low
CRITICAL	98	22	0	0	0	0

System Information

Property	Value
Hostname	DESKTOP-OTS2610
Architecture	64-bit
Is Root	True

Findings (22 total)

CRITICAL	1. Dangerous Privilege: SeDebugPrivilege	Windows Token Privileges
SeDebugPrivilege is Enabled. Allows opening any process (including SYSTEM processes) for read/write. Can be used to dump lsass credentials or inject shellcode into SYSTEM processes.		
Mitigation: Remove SeDebugPrivilege from this account if not required. Use the principle of least privilege – assign only necessary rights via Local Security Policy → User Rights Assignment.		
CRITICAL	2. SAM/SYSTEM Hive Readable	Windows Credentials
The file C:\Windows\System32\config\SAM is readable by the current user. The SAM hive contains NTLM hashes of local accounts. Combined with the SYSTEM hive, offline password cracking or pass-the-hash attacks are possible.		
Mitigation: Ensure only SYSTEM and Administrators have read access to SAM/SYSTEM hives. Check for backup copies in C:\Windows\repair\ and restrict them.		
CRITICAL	3. Writable Task Executable	Windows Scheduled Tasks
Scheduled task 'BraveSoftwareUpdateTaskMachineCore{AC73359C-BE7B-4A45-A746-2C9FD1CCD413}' runs as 'SYSTEM' and its executable 'C:\Program Files (x86)\BraveSoftware\Update\BraveUpdate.exe' is writable by the current user. Overwriting this binary will execute arbitrary code at the next task trigger.		
Mitigation: Fix permissions on 'C:\Program Files (x86)\BraveSoftware\Update\BraveUpdate.exe': icaccls "C:\Program Files (x86)\BraveSoftware\Update\BraveUpdate.exe" /inheritance:d /grant:r "Administrators:(F)" /remove "Users"		
HIGH	4. Dangerous Privilege: SeImpersonatePrivilege	Windows Token Privileges
SeImpersonatePrivilege is Enabled. Allows impersonation of any user token. Exploitable via Juicy Potato, Rogue Potato, or PrintSpoofer to escalate to SYSTEM.		
Mitigation: Remove SeImpersonatePrivilege from this account if not required. Use the principle of least privilege – assign only necessary rights via Local Security Policy → User Rights Assignment.		

HIGH	5. Dangerous Privilege: SeBackupPrivilege	Windows Token Privileges
SeBackupPrivilege is Enabled. Allows reading any file regardless of ACLs (backup bypass). Can be used to extract SAM, SYSTEM, and NTDS.dit hive files for offline cracking.		
Mitigation: Remove SeBackupPrivilege from this account if not required. Use the principle of least privilege – assign only necessary rights via Local Security Policy → User Rights Assignment.		
HIGH	6. Dangerous Privilege: SeRestorePrivilege	Windows Token Privileges
SeRestorePrivilege is Enabled. Allows writing any file regardless of ACLs (restore bypass). Can overwrite system binaries or add a backdoor DLL.		
Mitigation: Remove SeRestorePrivilege from this account if not required. Use the principle of least privilege – assign only necessary rights via Local Security Policy → User Rights Assignment.		
HIGH	7. Stored Credential (cmdkey)	Windows Credentials
Stored Windows credential found for target 'MicrosoftAccount:target=SSO_POP_User:user=ghimirenitesh8@gmail.com' (User: ghimirenitesh8@gmail.com, Type: Generic). These credentials can be extracted with tools like Mimikatz or used directly via runas /savedcred to escalate privileges or move laterally.		
Mitigation: Remove the stored credential: cmdkey /delete:MicrosoftAccount:target=SSO_POP_User:user=ghimirenitesh8@gmail.com Avoid storing credentials unless absolutely necessary.		
HIGH	8. Writable Service Executable	Windows Service
The executable for service 'Aggregated Data Platform Service' (ADPSvc) is writable by the current user: C:\WINDOWS\system32\svchost.exe. Overwriting it and restarting the service will execute arbitrary code as 'NT AUTHORITY\LocalService'.		
Mitigation: Fix permissions: icacls "C:\WINDOWS\system32\svchost.exe" /inheritance:d /grant:r "Administrators:(F)" /remove "Users"		
HIGH	9. Writable Service Directory	Windows Service
The directory containing the 'ADPSvc' service binary is writable: C:\WINDOWS\system32. A malicious DLL or replacement executable can be planted here.		
Mitigation: Restrict directory permissions: icacls "C:\WINDOWS\system32" /grant:r "Administrators:(OI)(CI)F" /remove "Users"		
HIGH	10. Writable AutoRun Binary	Windows Registry
AutoRun entry 'RtkAudUService' in HKLM\SOFTWARE\Microsoft\Windows\CurrentVersion\Run points to a writable binary: C:\WINDOWS\System32\DriverStore\FileRepository\realtekservice.inf_amd64_9971779a1c712866\RtkAudUService64.exe. Replacing this binary will execute arbitrary code at login.		
Mitigation: Fix permissions on C:\WINDOWS\System32\DriverStore\FileRepository\realtekservice.inf_amd64_9971779a1c712866\RtkAudUService64.exe or remove the AutoRun entry if it is not required.		
HIGH	11. Writable Directory in %PATH%	Windows PATH Hijacking
The directory 'C:\Program Files\Git\mingw64\bin' in %PATH% is writable by the current user and appears before system directories. A malicious executable placed here may be loaded instead of a legitimate system binary.		
Mitigation: Remove write permissions from 'C:\Program Files\Git\mingw64\bin' for non-admin users: icacls "C:\Program Files\Git\mingw64\bin" /remove "Users" /T		

HIGH	12. Writable Task Binary Directory	Windows Scheduled Tasks
Scheduled task 'BraveSoftwareUpdateTaskMachineCore{AC73359C-BE7B-4A45-A746-2C9FD1CCD413}' runs as 'SYSTEM'. Its binary directory 'C:\Program Files (x86)\BraveSoftware\Update' is writable. A malicious DLL can be planted here to hijack the task's DLL search order.		
Mitigation: Restrict write access to 'C:\Program Files (x86)\BraveSoftware\Update' for non-admin users.		
HIGH	13. Missing Task Executable	Windows Scheduled Tasks
Scheduled task 'UninstallDeviceTask' runs as 'SYSTEM' but its executable 'BthUdTask.exe' does not exist. If the directory is writable, a malicious binary can be planted at that path.		
Mitigation: Remove or update the scheduled task 'UninstallDeviceTask' to point to a valid executable, or disable the task if it is no longer needed.		
HIGH	14. Standard Users Auto-Elevated Without Prompt	Windows UAC
ConsentPromptBehaviorUser=3 means standard user elevation requests are automatically approved without a consent prompt, weakening UAC.		
Mitigation: Set ConsentPromptBehaviorUser to 0 (auto-deny) or 1 (credential prompt).		
MEDIUM	15. Dangerous Privilege: SeLoadDriverPrivilege	Windows Token Privileges
SeLoadDriverPrivilege is Disabled. Allows loading arbitrary kernel drivers. A malicious signed (or test-mode) driver can disable security controls or escalate privileges at kernel level.		
Mitigation: Remove SeLoadDriverPrivilege from this account if not required. Use the principle of least privilege – assign only necessary rights via Local Security Policy → User Rights Assignment.		
MEDIUM	16. Unquoted Service Path	Windows Service
Service 'Aggregated Data Platform Service' (ADPSvc) has an unquoted path with spaces. A binary can be planted at 'C:\WINDOWS.exe' to hijack execution.		
Mitigation: Wrap the ImagePath value in quotes: sc config ADPSvc binpath= \"C:\WINDOWS\system32\svchost.exe\"		
MEDIUM	17. Print Spooler Running	Windows Kernel / Services
The Windows Print Spooler service is running. If the system is not fully patched against CVE-2021-1675 / CVE-2021-34527 (PrintNightmare), this service can be exploited for SYSTEM-level code execution.		
Mitigation: Disable if not needed: Stop-Service Spooler; Set-Service Spooler -StartupType Disabled. Ensure KB5004945 or later is installed.		
MEDIUM	18. Missing PATH Directory (Phantom Dir Attack)	Windows PATH Hijacking
The PATH directory 'C:\Users\Administrator\bin' does not exist, but its parent 'C:\Users\Administrator' is writable. An attacker can create this directory and plant malicious executables that will be found before legitimate ones.		
Mitigation: Create the missing directory 'C:\Users\Administrator\bin' with correct permissions, or remove it from the PATH.		

MEDIUM	19. Writable Working Directory (DLL Hijacking)	Windows PATH Hijacking
The current working directory 'D:\menotr project\Linux Privilege Escalation Automation Toolkit' is writable. Windows searches the current directory before System32 for DLLs. Planting a malicious DLL here may be loaded by privileged applications that execute from this directory. Mitigation: Avoid running privileged processes from user-writable directories. Use the SafeDllSearchMode registry setting: HKLM\SYSTEM\CurrentControlSet\Control\Session Manager\SafeDllSearchMode = 1		
LOW	20. Dangerous Privilege: SeTakeOwnershipPrivilege	Windows Token Privileges
SeTakeOwnershipPrivilege is Disabled. Allows taking ownership of any securable object (file, registry key, service). Can be combined with SeRestorePrivilege to overwrite protected resources. Mitigation: Remove SeTakeOwnershipPrivilege from this account if not required. Use the principle of least privilege – assign only necessary rights via Local Security Policy → User Rights Assignment.		
LOW	21. Dangerous Privilege: SeManageVolumePrivilege	Windows Token Privileges
SeManageVolumePrivilege is Disabled. Allows direct low-level writes to volumes, bypassing filesystem ACLs. Can be used to overwrite protected system files at the raw disk level. Mitigation: Remove SeManageVolumePrivilege from this account if not required. Use the principle of least privilege – assign only necessary rights via Local Security Policy → User Rights Assignment.		
LOW	22. Dangerous Privilege: SeCreateSymbolicLinkPrivilege	Windows Token Privileges
SeCreateSymbolicLinkPrivilege is Disabled. Allows creating symbolic links, which can be used in link-following attacks to redirect file operations of privileged processes. Mitigation: Remove SeCreateSymbolicLinkPrivilege from this account if not required. Use the principle of least privilege – assign only necessary rights via Local Security Policy → User Rights Assignment.		