

```
In [1]: # NETWORK TRAFFIC & SECURITY INSIGHTS DASHBOARD
```

```
import pandas as pd
import matplotlib.pyplot as plt
import seaborn as sns
```

```
In [2]: rf = pd.read_csv("logs.csv")
rf.columns = rf.columns.str.strip()
print(rf.columns)

print(rf.head())
```

```
Index(['timestamp', 'source_ip', 'dest_ip', 'protocol', 'action',
       'threat_label', 'log_type', 'bytes_transferred', 'user_agent',
       'request_path'],
      dtype='object')

   timestamp      source_ip      dest_ip protocol  action \
0  2024-05-01T00:00:00  192.168.1.125  192.168.1.124    TCP  blocked
1  2024-07-18T00:00:00  192.168.1.201  192.168.1.201    ICMP  blocked
2  2024-04-07T00:00:00  192.168.1.248  192.168.1.15    HTTP  allowed
3  2024-10-26T00:00:00  192.168.1.236  192.168.1.219    HTTP  allowed
4  2024-10-31T00:00:00  192.168.1.221  192.168.1.61    ICMP  allowed

   threat_label  log_type  bytes_transferred \
0      benign    firewall             10889
1      benign  application             36522
2      benign  application             20652
3      benign  application              5350
4      benign  application             40691

   user_agent request_path
0      Nmap Scripting Engine      /
1      Nmap Scripting Engine      /
2  Mozilla/5.0 (Windows NT 10.0; Win64; x64) Appl...  /login
3  Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7...  /login
4  Mozilla/5.0 (Windows NT 10.0; Win64; x64) Appl...
```

```
In [3]: print("\n DATASET INFORMATION")
print(rf.info())
```

```
DATASET INFORMATION
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 6000000 entries, 0 to 5999999
Data columns (total 10 columns):
 #   Column          Dtype
---  -
 0   timestamp       object
 1   source_ip       object
 2   dest_ip        object
 3   protocol       object
 4   action         object
 5   threat_label   object
 6   log_type       object
 7   bytes_transferred  int64
 8   user_agent     object
 9   request_path   object
dtypes: int64(1), object(9)
memory usage: 457.8+ MB
None
```

```
In [4]: #remove duplicates and handle missing value
rf = rf.drop_duplicates()
rf = rf.dropna()
```

```
In [5]: #Rows and column
print("\n Rows and Columns")
print(rf.shape)
```

```
Rows and Columns
(6000000, 10)
```

```
In [6]: #Function for Finding Suspicious IPS

def find_suspicious_ips(data):
    blocked = data[data["action"] == "blocked"]
    suspicious = blocked["source_ip"].value_counts()
    return suspicious
```

```
In [7]: #Function to show protocol usage

def show_protocols(data):
    protocols = data["protocol"].value_counts()
    return protocols
```

In [8]: *# Threat Level count*

```
print("\nThreat Label Count")
print(rf["threat_label"].value_counts())
```

```
Threat Label Count
benign      5517611
suspicious  360883
malicious   121506
Name: threat_label, dtype: int64
```

In [9]: *#Blocked Requests*

```
blocked_requests = rf[rf["action"] == "blocked"]
print("\nTotal Block Requests")
print(len(blocked_requests))
```

```
Total Block Requests
2999354
```

In [10]: *#Suspicious Ip Analysis*

```
suspicious_ips = find_suspicious_ips(rf)
print("\nTop Suspicious source IPS")
print(suspicious_ips.head(10))
```

```
Top Suspicious source IPS
88.72.40.56      9222
25.169.111.91    9213
59.211.9.207     9195
44.137.187.63    9195
109.9.8.24       9158
55.139.34.186    9151
144.138.68.192   9143
193.69.197.165   9139
207.79.62.15     9137
187.14.173.168   9128
Name: source_ip, dtype: int64
```

```
In [11]: rf.head(10)
```

Out[11]:

	timestamp	source_ip	dest_ip	protocol	action	threat_label	log_type	bytes_trar
0	2024-05-01T00:00:00	192.168.1.125	192.168.1.124	TCP	blocked	benign	firewall	
1	2024-07-18T00:00:00	192.168.1.201	192.168.1.201	ICMP	blocked	benign	application	
2	2024-04-07T00:00:00	192.168.1.248	192.168.1.15	HTTP	allowed	benign	application	
3	2024-10-26T00:00:00	192.168.1.236	192.168.1.219	HTTP	allowed	benign	application	
4	2024-10-31T00:00:00	192.168.1.221	192.168.1.61	ICMP	allowed	benign	application	
5	2024-12-02T00:00:00	192.168.1.134	192.168.1.81	FTP	allowed	benign	application	
6	2024-03-08T00:00:00	192.168.1.77	192.168.1.118	UDP	allowed	benign	firewall	
7	2024-02-07T00:00:00	192.168.1.130	192.168.1.68	TCP	blocked	benign	firewall	
8	2024-03-21T00:00:00	192.168.1.140	192.168.1.181	UDP	allowed	benign	application	
9	2024-03-09T00:00:00	192.168.1.228	192.168.1.28	HTTPS	allowed	benign	ids	

```
In [12]: #Protocol Usage

print("\nProtocol Usage")
print(show_protocols(rf))
```

```
Protocol Usage
TCP      1497493
HTTP     1201528
HTTPS    1199970
UDP       900422
ICMP      599903
SSH       300464
FTP       300220
Name: protocol, dtype: int64
```

In [13]: *#Top request paths*

```
print("\nTop Request Paths")
print(rf["request_path"].value_counts().head())
```

```
Top Request Paths
/                2741075
/login          414760
/admin/config   226796
/secure        226412
/auth          225761
Name: request_path, dtype: int64
```

In [14]: *#Most Targeted Destination Ips*

```
print("\nTop Destination Ips")
print(rf["dest_ip"].value_counts().head())
```

```
Top Destination Ips
192.168.1.5      24140
192.168.1.135    24121
192.168.1.193    24091
192.168.1.226    24042
192.168.1.237    23972
Name: dest_ip, dtype: int64
```

In [15]: *#Total Bytes Transferred*

```
print("\nTotal Bytes Transferred")
print(rf["bytes_transferred"].value_counts().head())
```

```
Total Bytes Transferred
22906      170
26654      166
25391      166
40000      163
25367      162
Name: bytes_transferred, dtype: int64
```

```
In [16]: # VISUALIZATION 1
# THREAT LABEL DISTRIBUTION


plt.figure(figsize=(6,5))
sns.countplot(
    x="threat_label",
    data=rf
)

plt.title("Threat Label Distribution")

plt.xlabel("Threat Label")


plt.ylabel("Count")

plt.show()
```



```
In [17]: # VISUALIZATION 2  
# ALLOWED VS BLOCKED REQUESTS
```

```
plt.figure(figsize=(6,5))  
  
sns.countplot(  
    x = "action",  
    data = rf  
)  
  
plt.title("Allowed vs Blocked Request")  
plt.xlabel("Action")  
plt.ylabel("Count")  
plt.show()
```



```

In [18]: # VISUALIZATION 3
# TOP SUSPICIOUS IPS


top_ips = suspicious_ips.head(20)

plt.figure(figsize = (10,5))

sns.barplot(
    x = top_ips.index,
    y = top_ips.values
)

plt.title("Top Suspicious Source Ips")
plt.xlabel("Source IP")
plt.ylabel("Blocked Requests")
plt.xticks(rotation=45)
plt.show()

```




```
In [19]: # VISUALIZATION 4
# PROTOCOL DISTRIBUTION


protocol_count = rf["protocol"].value_counts()

plt.figure(figsize=(7,7))

protocol_count.plot(
    kind = "pie",
    autopct = "%1.1f%"
)

plt.title("Protocol Distribution")
plt.ylabel("")
plt.show
```

```
Out[19]: <function matplotlib.pyplot.show(close=None, block=None)>
```




```
In [20]: # VISUALIZATION 5
# TOP REQUEST PATHS

top_paths = rf["request_path"].value_counts().head(5)

plt.figure(figsize=(8,5))

sns.barplot(
    x = top_paths.index,
    y = top_paths.values
)

plt.title("Top Request Paths")
plt.xlabel("Request Path")
plt.ylabel("Count")
plt.xticks(rotation=20)
plt.show()
```



```
In [ ]: suspicious_ips.to_csv("suspicious_ips_report.csv")

print("\nSUSPICIOUS IP REPORT SAVED SUCCESSFULLY")

print("\nNETWORKING CONCEPTS USED IN PROJECT")

print("""
1. IP Address:
    Identifies devices in the network.
2. Protocol:
    Rules used for communication such as HTTP, TCP, HTTPS.

3. Blocked Requests:
    Requests denied due to suspicious behavior.

4. Traffic Analysis:
    Monitoring data movement in the network.

5. Threat Detection:
    Identifying suspicious or malicious activities.
""")
```