

Ex. No : 03**Classes and Objects in Kotlin Aim**

To understand the concept of classes and objects in Kotlin by creating a class with properties and methods, and accessing them using an object in an Android application.

Procedure

1. Open Android Studio and your project.
2. Open activity_main.xml and add a **TextView** and **Button**.
3. Create a new Kotlin class named Student.
4. Define properties and a method inside the class.
5. Open MainActivity.kt.
6. Create an object of the class inside onCreate().
7. Call the class method using the object.
8. Display the result in the TextView.
9. Run the app and observe output.

Code Student.kt

```
package com.example.kotlinbasics
class Student(val name: String, val rollNo: Int)

{ fun displayDetails(): String {

    return "Name: $name\nRoll No: $rollNo"
}}
```

activity_main.xml

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:layout_width="match_parent"    android:layout_height="match_parent"
    android:gravity="center"
    android:orientation="vertical">

    <Button
        android:id="@+id/btnShow"
        android:layout_width="wrap_content"
        android:layout_height="wrap_content"
        android:text="Show Details"/>

    <TextView
        android:id="@+id/txtOutput"
        android:layout_width="wrap_content"
```

```
android:layout_height="wrap_content"  
android:textSize="18sp"/> </LinearLayout>
```

MainActivity.kt

```
package com.example.kotlinbasics
```

```
import android.os.Bundle  
import android.widget.Button  
import android.widget.TextView  
import androidx.appcompat.app.AppCompatActivity
```

```
class MainActivity : AppCompatActivity() {  
  
    override fun onCreate(savedInstanceState: Bundle?)  
    { super.onCreate(savedInstanceState)  
      setContentView(R.layout.activity_main)  
  
      val btn = findViewById<Button>(R.id.btnShow)  
      val txt = findViewById<TextView>(R.id.txtOutput)  
  
      btn.setOnClickListener {  
  
          // Creating object  
          val student = Student("Ravi", 101)  
  
          // Display output  
          txt.text = student.displayDetails()  
      }  
    }  
}
```

Result

The application successfully demonstrates classes and objects by displaying:

