

Ex. No :08**App Architecture – UI Layer Aim**

To understand the UI layer in Android architecture by handling user interaction and updating UI using Activity and ViewModel.

Procedure

1. Open Android Studio.
2. Create a new project (Empty Activity, Kotlin).
3. Design UI in activity_main.xml using:
 - TextView (to display message) ○
 - Button (to trigger action)
4. Create a

ViewModel class to manage data.

5. Open MainActivity.kt.
6. Connect UI components using findViewById.
7. Use ViewModel to fetch data.
8. Handle button click and update UI.
9. Run the app and observe output.

Code activity_main.xml

```
<?xml version="1.0" encoding="utf-8"?>
<LinearLayout xmlns:android="http://schemas.android.com/apk/res/android"
    android:orientation="vertical"    android:padding="20dp"
    android:layout_width="match_parent"
    android:layout_height="match_parent">

    <TextView
        android:id="@+id/tvTitle"
        android:text="UI Layer Demo"
        android:textSize="22sp"
        android:gravity="center"
        android:layout_width="match_parent" android:layout_height="wrap_content"/>

    <TextView
        android:id="@+id/tvMessage"
        android:text="Message will appear here"
        android:textSize="18sp"    android:paddingTop="20dp"
        android:layout_width="match_parent"
        android:layout_height="wrap_content"/>
```

```
<Button      android:id="@+id/btnLoad"
android:text="Load Data"
android:layout_width="match_parent"
android:layout_height="wrap_content"/>
</LinearLayout>
```

MainViewModel.kt

```
package com.example.uilayerdemo

import androidx.lifecycle.ViewModel

class MainViewModel : ViewModel() {
```

```
    fun getMessage(): String {
        return "Hello from ViewModel"
    }
}
```

MainActivity.kt

```
package com.example.uilayerdemo

import android.os.Bundle
import android.widget.Button
import android.widget.TextView
import androidx.activity.viewModels
import androidx.appcompat.app.AppCompatActivity

class MainActivity : AppCompatActivity() {

    private val viewModel: MainViewModel by viewModels()

    override fun onCreate(savedInstanceState: Bundle?) {
        super.onCreate(savedInstanceState)
        setContentView(R.layout.activity_main)

        val tvMessage = findViewById<TextView>(R.id.tvMessage)
        val btnLoad = findViewById<Button>(R.id.btnLoad)

        btnLoad.setOnClickListener {
            tvMessage.text = viewModel.getMessage()
        }
    }
}
```

Result

The application successfully:

- Handles user interaction through UI layer
- Uses ViewModel to provide data
- Displays dynamic message on button click



MADL Lab Flutter

Welcome to MADL Lab

Enter your name

TONY

Submit

Hello TONY, Welcome to MADL Lab!