

■ *agribase/manage.py*

```
#!/usr/bin/env python
"""Django's command-line utility for administrative tasks."""
import os
import sys

def main():
    """Run administrative tasks."""
    os.environ.setdefault('DJANGO_SETTINGS_MODULE', 'agribase.settings')
    try:
        from django.core.management import execute_from_command_line
    except ImportError as exc:
        raise ImportError(
            "Couldn't import Django. Are you sure it's installed and "
            "available on your PYTHONPATH environment variable? Did you "
            "forget to activate a virtual environment?"
        ) from exc
    execute_from_command_line(sys.argv)

if __name__ == '__main__':
    main()
```

■ *agribase/users/__init__.py*

■ *agribase/users/admin.py*

```
from django.contrib import admin

# Register your models here.
```

■ *agribase/users/apps.py*

```
from django.apps import AppConfig

class UsersConfig(AppConfig):
    default_auto_field = 'django.db.models.BigAutoField'
    name = 'users'
```

■ *agribase/users/models.py*

```
from django.db import models
```

```
# Create your models here.
from django.db import models
from django.contrib.auth.models import User

class UserProfile(models.Model):
    user = models.OneToOneField(User, on_delete=models.CASCADE)
    phone = models.CharField(max_length=20, blank=True)
    address = models.TextField(blank=True)
    state = models.CharField(max_length=100, blank=True)
    farm_size = models.CharField(max_length=50, blank=True)

    profile_image = models.ImageField(upload_to="profiles/", blank=True, null=True)

    def __str__(self):
        return self.user.username
```

■ **agribase/users/tests.py**

```
from django.test import TestCase

# Create your tests here.
```

■ **agribase/users/urls.py**

```
from django.urls import path
from .views import register, login, profile, check_email, reset_password

urlpatterns = [
    path("register/", register),
    path("login/", login),
    path("profile/", profile),
    path("check-email/", check_email),
    path("reset-password/", reset_password),
]
```

■ **agribase/users/views.py**

```
from django.contrib.auth.models import User
from rest_framework.decorators import api_view, permission_classes
from rest_framework.permissions import IsAuthenticated
from rest_framework.response import Response
from rest_framework_simplejwt.tokens import RefreshToken

from django.contrib.auth import authenticate
from .models import UserProfile
from order.models import Order

# REGISTER
```

```

@api_view(['POST'])
def register(request):
    username = request.data.get('username')
    email = request.data.get('email')
    password = request.data.get('password')

    if User.objects.filter(username=username).exists():
        return Response({"error": "User already exists"}, status=400)

    user = User.objects.create_user(
        username=username,
        email=email,
        password=password
    )

    # create profile automatically
    UserProfile.objects.create(user=user)

    return Response({"message": "User created"})


# LOGIN
@api_view(['POST'])
def login(request):
    user = authenticate(
        username=request.data.get('username'),
        password=request.data.get('password')
    )

    if user is None:
        return Response({"error": "Invalid credentials"}, status=401)

    refresh = RefreshToken.for_user(user)

    return Response({
        "access": str(refresh.access_token),
        "refresh": str(refresh)
    })


# PROFILE (GET + PATCH)
@api_view(['GET', 'PATCH'])
@permission_classes([IsAuthenticated])
def profile(request):
    user = request.user

    # ensure profile exists
    profile, created = UserProfile.objects.get_or_create(user=user)

    # GET PROFILE
    if request.method == "GET":
        return Response({
            "id": user.id,
            "username": user.username,
            "email": user.email,
            "first_name": user.first_name,

```

```
"last_name": user.last_name,  
"phone": profile.phone,  
"address": profile.address,  
"state": profile.state,  
"farm_size": profile.farm_size,  
"profile_image": profile.profile_image.url if profile.profile_image else None,  
"date_joined": user.date_joined,
```

```
}}
```

```
# UPDATE PROFILE
```

```
data = request.data
```

```
if 'username' in data and data['username']:
```

```
if User.objects.exclude(pk=user.pk).filter(username=data['username']).exists():
```

```
return Response({"error": "Username already taken"}, status=400)
```

```
user.username = data['username']
```

```
if 'first_name' in data:
```

```
user.first_name = data['first_name']
```

```
if 'last_name' in data:
```

```
user.last_name = data['last_name']
```

```
if 'email' in data:
```

```
user.email = data['email']
```

```
user.save()
```

```
# update extra profile fields
```

```
if 'phone' in data:
```

```
profile.phone = data['phone']
```

```
if 'address' in data:
```

```
profile.address = data['address']
```

```
if 'state' in data:
```

```
profile.state = data['state']
```

```
if 'farm_size' in data:
```

```
profile.farm_size = data['farm_size']
```

```
# profile image upload
```

```
if 'avatar' in request.FILES:
```

```
profile.profile_image = request.FILES['avatar']
```

```
profile.save()
```

```
return Response({
```

```
"id": user.id,
```

```
"username": user.username,
```

```
"email": user.email,
```

```
"first_name": user.first_name,
```

```
"last_name": user.last_name,
```

```
"phone": profile.phone,
```

```

"address": profile.address,
"state": profile.state,
"farm_size": profile.farm_size,
"profile_image": profile.profile_image.url if profile.profile_image else None,
"date_joined": user.date_joined,

})

# CHECK EMAIL
@api_view(['POST'])
def check_email(request):
    email = request.data.get('email', "").strip()

    if not email:
        return Response({"error": "Email is required"}, status=400)

    if User.objects.filter(email=email).exists():
        return Response({"message": "Email found"})

    return Response({"error": "No account found with this email"}, status=404)

# RESET PASSWORD
@api_view(['POST'])
def reset_password(request):
    email = request.data.get('email', "").strip()
    new_password = request.data.get('new_password', "")

    if not email or not new_password:
        return Response({"error": "Email and password required"}, status=400)

    if len(new_password) < 6:
        return Response({"error": "Password must be at least 6 characters"}, status=400)

    try:
        user = User.objects.get(email=email)
    except User.DoesNotExist:
        return Response({"error": "No account found"}, status=404)

    user.set_password(new_password)
    user.save()

    return Response({"message": "Password reset successfully"})

```

■ *agribase/users/migrations/0001_initial.py*

Generated by Django 5.2.11 on 2026-03-12 19:24

```

import django.db.models.deletion
from django.conf import settings
from django.db import migrations, models

```

```

class Migration(migrations.Migration):

    initial = True

    dependencies = [
        migrations.swappable_dependency(settings.AUTH_USER_MODEL),
    ]

    operations = [
        migrations.CreateModel(
            name='UserProfile',
            fields=[
                ('id', models.BigAutoField(auto_created=True, primary_key=True, serialize=False, verbose_name='ID')),
                ('phone', models.CharField(blank=True, max_length=20)),
                ('address', models.TextField(blank=True)),
                ('state', models.CharField(blank=True, max_length=100)),
                ('farm_size', models.CharField(blank=True, max_length=50)),
                ('profile_image', models.ImageField(blank=True, null=True, upload_to='profiles/')),
                ('user', models.OneToOneField(on_delete=django.db.models.deletion.CASCADE, to=settings.AUTH_USER_MODEL)),
            ],
        ),
    ]

```

■ *agribase/users/migrations/__init__.py*

■ *agribase/guide/__init__.py*

■ *agribase/guide/admin.py*

```

from django.contrib import admin

```

```

# Register your models here.

```

■ *agribase/guide/apps.py*

```

from django.apps import AppConfig

```

```

class GuideConfig(AppConfig):
    default_auto_field = 'django.db.models.BigAutoField'
    name = 'guide'

```

■ ***agribase/guide/models.py***

```
from django.db import models
```

■ ***agribase/guide/tests.py***

```
from django.test import TestCase
```

```
# Create your tests here.
```

■ ***agribase/guide/views.py***

```
from django.shortcuts import render
```

```
# Create your views here.
```

■ ***agribase/guide/migrations/__init__.py***

■ ***agribase/order/__init__.py***

■ ***agribase/order/admin.py***

```
from django.contrib import admin
```

```
# Register your models here.
```

■ ***agribase/order/apps.py***

```
from django.apps import AppConfig
```

```
class OrderConfig(AppConfig):  
    default_auto_field = 'django.db.models.BigAutoField'  
    name = 'order'
```

■ ***agribase/order/models.py***

```

from django.db import models
from django.contrib.auth.models import User
from product.models import Product

class Order(models.Model):

    STATUS = [
        ("orderplaced", "Order Placed"),
        ("shipped", "Shipped"),
        ("out_for_delivery", "Out for Delivery"),
        ("delivered", "Delivered"),
    ]

    user = models.ForeignKey(User, on_delete=models.CASCADE, related_name="user_orders")
    product = models.ForeignKey(Product, on_delete=models.CASCADE)

    quantity = models.IntegerField()
    payment_type = models.CharField(max_length=50)
    name = models.CharField(max_length=100, null=True, blank=True)
    email = models.EmailField(null=True, blank=True)
    phone = models.CharField(max_length=20, null=True, blank=True)
    address = models.TextField(null=True, blank=True)

    status = models.CharField(max_length=50, choices=STATUS, default="orderplaced")

    created_at = models.DateTimeField(auto_now_add=True)

    def __str__(self):
        return self.product.title

```

■ *agribase/order/serializers.py*

```

from rest_framework import serializers
from .models import Order
from product.models import Product

class ProductSerializer(serializers.ModelSerializer):
    class Meta:
        model = Product
        fields = ["id", "title", "price", "image"]

class OrderSerializer(serializers.ModelSerializer):

    product = ProductSerializer(read_only=True)

    class Meta:
        model = Order
        fields = "__all__"

```


■ *agribase/order/tests.py*

```
from django.test import TestCase
```

```
# Create your tests here.
```

■ *agribase/order/urls.py*

```
from django.urls import path
from .views import orders_api, my_orders, delete_order, order_count
```

```
urlpatterns = [
    path("", my_orders), # GET /api/orders/
    path("create/", orders_api), # POST /api/orders/create/
    path("<int:pk>/delete/", delete_order), # DELETE /api/orders/<pk>/delete/
    path("order-count/", order_count),
]
```

■ *agribase/order/views.py*

```
from django.shortcuts import get_object_or_404
from rest_framework.decorators import api_view, permission_classes
from rest_framework.permissions import IsAuthenticated
from rest_framework.response import Response
from rest_framework import status
```

```
from .models import Order
from .serializers import OrderSerializer
from product.models import Product
```

```
# CREATE ORDER
@api_view(["POST"])
@permission_classes([IsAuthenticated])
def orders_api(request):
```

```
    product_id = request.data.get("product")
    quantity = request.data.get("quantity")
    payment_type = request.data.get("payment_type")
```

```
    name = request.data.get("name")
    email = request.data.get("email")
    phone = request.data.get("phone")
    address = request.data.get("address")
```

```
    try:
        product = Product.objects.get(id=product_id)
```

```
    order = Order.objects.create(
        user=request.user,
        product=product,
        quantity=quantity,
```

```

payment_type=payment_type,
name=name,
email=email,
phone=phone,
address=address
)

serializer = OrderSerializer(order)

return Response(serializer.data, status=status.HTTP_201_CREATED)

except Product.DoesNotExist:
    return Response({"error": "Product not found"}, status=404)

# GET USER ORDERS
@api_view(["GET"])
@permission_classes([IsAuthenticated])
def my_orders(request):

    orders = Order.objects.filter(user=request.user)
    serializer = OrderSerializer(orders, many=True)

    return Response(serializer.data)

# DELETE ORDER
@api_view(["DELETE"])
@permission_classes([IsAuthenticated])
def delete_order(request, pk):

    order = get_object_or_404(Order, id=pk, user=request.user)
    order.delete()

    return Response({"message": "Order deleted"})

#order count
@api_view(["GET"])
@permission_classes([IsAuthenticated])
def order_count(request):

    count = Order.objects.filter(user=request.user).count()

    return Response({
        "order_count": count
    })

```

■ *agribase/order/migrations/0001_initial.py*

Generated by Django 5.2.11 on 2026-02-25 21:00

```

import django.db.models.deletion
from django.conf import settings

```

```
from django.db import migrations, models
```

```
class Migration(migrations.Migration):
```

```
    initial = True
```

```
    dependencies = [
        ('product', '__first__'),
        migrations.swappable_dependency(settings.AUTH_USER_MODEL),
    ]
```

```
    operations = [
        migrations.CreateModel(
            name='Order',
            fields=[
                ('id', models.BigAutoField(auto_created=True, primary_key=True, serialize=False, verbose_name='ID')),
                ('quantity', models.IntegerField()),
                ('payment_type', models.CharField(max_length=50)),
                ('status', models.CharField(choices=[('processing', 'Processing'), ('shipped', 'Shipped'), ('out_for_delivery', 'Out for Delivery'), ('delivered', 'Delivered')], default='processing', max_length=50)),
                ('created_at', models.DateTimeField(auto_now_add=True)),
                ('product', models.ForeignKey(on_delete=django.db.models.deletion.CASCADE, to='product.product')),
                ('user', models.ForeignKey(on_delete=django.db.models.deletion.CASCADE, related_name='user_orders', to=settings.AUTH_USER_MODEL)),
            ],
        ),
    ]
```

■ **agribase/order/migrations/0002_order_address_order_email_order_name_order_phone.py**

```
# Generated by Django 5.2.11 on 2026-03-02 12:56
```

```
from django.db import migrations, models
```

```
class Migration(migrations.Migration):
```

```
    dependencies = [
        ('order', '0001_initial'),
    ]
```

```
    operations = [
        migrations.AddField(
            model_name='order',
            name='address',
            field=models.TextField(blank=True, null=True),
        ),
        migrations.AddField(
            model_name='order',
            name='email',
            field=models.EmailField(blank=True, max_length=254, null=True),
        ),
    ]
```

```

),
migrations.AddField(
    model_name='order',
    name='name',
    field=models.CharField(blank=True, max_length=100, null=True),
),
migrations.AddField(
    model_name='order',
    name='phone',
    field=models.CharField(blank=True, max_length=20, null=True),
),
]

```

■ *agribase/order/migrations/__init__.py*

■ *agribase/product/__init__.py*

■ *agribase/product/admin.py*

```

from django.contrib import admin
from .models import Product

admin.site.register(Product)
# Register your models here.

```

■ *agribase/product/apps.py*

```

from django.apps import AppConfig

class ProductConfig(AppConfig):
    default_auto_field = 'django.db.models.BigAutoField'
    name = 'product'

```

■ *agribase/product/models.py*

```

from django.db import models
from django.contrib.auth.models import User

class Product(models.Model):
    user = models.ForeignKey(User, on_delete=models.CASCADE)

```

```
title = models.CharField(max_length=100)
category = models.CharField(max_length=50)
image = models.ImageField(upload_to="products/")
price = models.IntegerField()
created = models.DateTimeField(auto_now_add=True)
```

```
def __str__(self):
    return self.title
```

■ *agribase/product/serializers.py*

```
from rest_framework import serializers
from .models import Product

class ProductSerializer(serializers.ModelSerializer):
    user = serializers.ReadOnlyField(source="user.username")

class Meta:
    model = Product
    fields = "__all__"
```

■ *agribase/product/tests.py*

```
from django.test import TestCase

# Create your tests here.
```

■ *agribase/product/urls.py*

```
from django.urls import path
from .views import products_api, product_detail, my_products, delete_product

urlpatterns = [
    path("", products_api), # IT IS CALLING GET all products AND POST add product
    path("my/", my_products), # IT IS CALLING GET my products
    path("<int:pk>/", delete_product), # IT'S CALLING GET single / DELETE product
    path("detail/<int:pk>/", product_detail), # IT IS CALLING product detail
]
```

■ *agribase/product/views.py*

```
from urllib import request

from rest_framework.decorators import api_view, permission_classes
from rest_framework.permissions import IsAuthenticated
from rest_framework.response import Response
```

```

from .models import Product
from .serializers import ProductSerializer

@api_view(["GET", "POST"])
@permission_classes([IsAuthenticated])
def products_api(request):
    if request.method == "GET":
        products = Product.objects.all()
        serializer = ProductSerializer(products, many=True)
        return Response(serializer.data)

    if request.method == "POST":
        serializer = ProductSerializer(data=request.data)
        if serializer.is_valid():
            serializer.save(user=request.user)
            return Response(serializer.data)
        return Response(serializer.errors, status=400)

@api_view(["GET"])
@permission_classes([IsAuthenticated])
def my_products(request):
    products = Product.objects.filter(user=request.user).order_by("-id")
    serializer = ProductSerializer(products, many=True)
    return Response(serializer.data)

@api_view(["GET", "DELETE"])
@permission_classes([IsAuthenticated])
def delete_product(request, pk):
    try:
        product = Product.objects.get(id=pk)
    except Product.DoesNotExist:
        return Response({"error": "Not found"}, status=404)

    # GET single product
    if request.method == "GET":
        serializer = ProductSerializer(product)
        return Response(serializer.data)

    # DELETE product
    if request.method == "DELETE":
        if product.user != request.user:
            return Response({"error": "Not allowed"}, status=403)

        product.delete()
        return Response({"message": "Deleted"}, status=204)

    @api_view(["GET"])
    def product_detail(request, pk):
        product = Product.objects.get(id=pk)
        serializer = ProductSerializer(product)
        return Response(serializer.data)

```

■ **agribase/agribase/___init___py**

■ *agribase/agribase/asgi.py*

.....

ASGI config for agribase project.

It exposes the ASGI callable as a module-level variable named ``application``.

For more information on this file, see

<https://docs.djangoproject.com/en/5.2/howto/deployment/asgi/>

.....

```
import os
```

```
from django.core.asgi import get_asgi_application
```

```
os.environ.setdefault('DJANGO_SETTINGS_MODULE', 'agribase.settings')
```

```
application = get_asgi_application()
```

■ *agribase/agribase/settings.py*

.....

Django settings for agribase project.

Generated by 'django-admin startproject' using Django 5.2.11.

For more information on this file, see

<https://docs.djangoproject.com/en/5.2/topics/settings/>

For the full list of settings and their values, see

<https://docs.djangoproject.com/en/5.2/ref/settings/>

.....

```
from pathlib import Path
```

```
from datetime import timedelta
```

```
# Build paths inside the project like this: BASE_DIR / 'subdir'.
```

```
BASE_DIR = Path(__file__).resolve().parent.parent
```

```
# Quick-start development settings - unsuitable for production
```

```
# See https://docs.djangoproject.com/en/5.2/howto/deployment/checklist/
```

```
# SECURITY WARNING: keep the secret key used in production secret!
```

```
SECRET_KEY = 'django-insecure-6b_huc4)c80%%m9#(j-#)f9#u5nqr0&k$^bwdi^j8dh_vpb7*s'
```

```
# SECURITY WARNING: don't run with debug turned on in production!
```

```
DEBUG = True
```

```
ALLOWED_HOSTS = []
```

Application definition

```
INSTALLED_APPS = [  
    'django.contrib.admin',  
    'django.contrib.auth',  
    'django.contrib.contenttypes',  
    'django.contrib.sessions',  
    'django.contrib.messages',  
    'django.contrib.staticfiles',  
    'rest_framework', # import rest_framework is use to acess the react.js file  
    'rest_framework_simplejwt', # it is used for generate jwt token to access,  
    'corsheaders', # it is Allow frontend to access backend API  
    'product', # this is product App is used store the product DB  
    'users', # this is user App is used store the user DB  
    'paymentapi', # this is patment App is used store the payment DB  
    'order', # this is order App is used store the order DB
```

]

```
MIDDLEWARE = [  
    'django.middleware.security.SecurityMiddleware',  
    'django.contrib.sessions.middleware.SessionMiddleware',  
    'django.middleware.common.CommonMiddleware',  
    'django.middleware.csrf.CsrfViewMiddleware',  
    'django.contrib.auth.middleware.AuthenticationMiddleware',  
    'django.contrib.messages.middleware.MessageMiddleware',  
    'django.middleware.clickjacking.XFrameOptionsMiddleware',  
    'corsheaders.middleware.CorsMiddleware',  
]
```

```
CORS_ALLOW_ALL_ORIGINS = True  
ROOT_URLCONF = 'agribase.urls'
```

```
TEMPLATES = [  
    {  
        'BACKEND': 'django.template.backends.django.DjangoTemplates',  
        'DIRS': [],  
        'APP_DIRS': True,  
        'OPTIONS': {  
            'context_processors': [  
                'django.template.context_processors.request',  
                'django.contrib.auth.context_processors.auth',  
                'django.contrib.messages.context_processors.messages',  
            ],  
        },  
    },  
]
```

```
WSGI_APPLICATION = 'agribase.wsgi.application'
```


Database

<https://docs.djangoproject.com/en/5.2/ref/settings/#databases>

```
DATABASES = {  
    'default': {  
        'ENGINE': 'django.db.backends.mysql',  
        'NAME': 'agribase',  
        'USER': 'agriuser',  
        'PASSWORD': 'nk09',  
        'HOST': 'localhost',  
        'PORT': '3306',  
    }  
}
```

Password validation

<https://docs.djangoproject.com/en/5.2/ref/settings/#auth-password-validators>

```
AUTH_PASSWORD_VALIDATORS = [  
    {  
        'NAME': 'django.contrib.auth.password_validation.UserAttributeSimilarityValidator',  
    },  
    {  
        'NAME': 'django.contrib.auth.password_validation.MinimumLengthValidator',  
    },  
    {  
        'NAME': 'django.contrib.auth.password_validation.CommonPasswordValidator',  
    },  
    {  
        'NAME': 'django.contrib.auth.password_validation.NumericPasswordValidator',  
    },  
]
```

Internationalization

<https://docs.djangoproject.com/en/5.2/topics/i18n/>

LANGUAGE_CODE = 'en-us'

TIME_ZONE = 'UTC'

USE_I18N = True

USE_TZ = True

Static files (CSS, JavaScript, Images)

<https://docs.djangoproject.com/en/5.2/howto/static-files/>

STATIC_URL = 'static/'

Default primary key field type

<https://docs.djangoproject.com/en/5.2/ref/settings/#default-auto-field>

DEFAULT_AUTO_FIELD = 'django.db.models.BigAutoField'

```

import os

MEDIA_URL = '/media/'
MEDIA_ROOT = os.path.join(BASE_DIR, 'media')

MEDIA_ROOT = BASE_DIR / "media"

SIMPLE_JWT = {
    "ACCESS_TOKEN_LIFETIME": timedelta(hours=5),
    "REFRESH_TOKEN_LIFETIME": timedelta(days=1),
    "AUTH_HEADER_TYPES": ("Bearer",),
}

REST_FRAMEWORK = {
    'DEFAULT_AUTHENTICATION_CLASSES': (
        'rest_framework_simplejwt.authentication.JWTAuthentication',
    ),
}
RAZORPAY_KEY_ID = "your_public_key"
RAZORPAY_KEY_SECRET = "your_secret_key"

```

■ *agribase/agribase/urls.py*

```

from django.contrib import admin
from django.urls import path, include
from django.conf import settings
from django.conf.urls.static import static
from rest_framework_simplejwt.views import TokenObtainPairView, TokenRefreshView
from paymentapi import views

urlpatterns = [
    path('admin/', admin.site.urls),
    path('api/', include('users.urls')),
    path('api/products/', include('product.urls')),
    path('api/login/', TokenObtainPairView.as_view()),
    path('api/refresh/', TokenRefreshView.as_view()),
    path("create-payment/", views.create_payment),
    path("api/orders/", include("order.urls")),

]

if settings.DEBUG:
    urlpatterns += static(settings.MEDIA_URL, document_root=settings.MEDIA_ROOT)

```

■ *agribase/agribase/wsgi.py*

```
"""
```

WSGI config for agribase project.

It exposes the WSGI callable as a module-level variable named ``application``.

For more information on this file, see

<https://docs.djangoproject.com/en/5.2/howto/deployment/wsgi/>

```
"""
```

```
import os
```

```
from django.core.wsgi import get_wsgi_application
```

```
os.environ.setdefault('DJANGO_SETTINGS_MODULE', 'agribase.settings')
```

```
application = get_wsgi_application()
```

■ *agribase/paymentapi/__init__.py*

■ *agribase/paymentapi/admin.py*

```
from django.contrib import admin
```

```
# Register your models here.
```

■ *agribase/paymentapi/apps.py*

```
from django.apps import AppConfig
```

```
class PaymentapiConfig(AppConfig):
```

```
    default_auto_field = 'django.db.models.BigAutoField'
```

```
    name = 'paymentapi'
```

■ *agribase/paymentapi/models.py*

```
from django.db import models
```

```
# Create your models here.
```

```
from django.db import models
```

```
from django.contrib.auth.models import User
```

```
class Order(models.Model):
```

```
    user = models.ForeignKey(User, on_delete=models.CASCADE)
```

```

product_id = models.IntegerField()

quantity = models.IntegerField()

phone = models.CharField(max_length=20)

email = models.EmailField()

address = models.TextField()

payment_type = models.CharField(max_length=20)

created_at = models.DateTimeField(auto_now_add=True)

def __str__(self):
    return str(self.product_id)

```

■ *agribase/paymentapi/tests.py*

```

from django.test import TestCase

# Create your tests here.

```

■ *agribase/paymentapi/views.py*

```

from django.shortcuts import render

# Create your views here.
import razorpay
from django.conf import settings
from rest_framework.response import Response
from rest_framework.decorators import api_view, permission_classes
from rest_framework.permissions import IsAuthenticated
from .models import Order

@api_view(["POST"])
def create_payment(request):
    client = razorpay.Client(
        auth=(settings.RAZORPAY_KEY_ID, settings.RAZORPAY_KEY_SECRET)
    )

    amount = int(request.data.get("amount")) * 100 # paise

    payment = client.order.create({
        "amount": amount,
        "currency": "INR",
        "payment_capture": 1
    })

    return Response(payment)

```

```

@api_view(["POST"])
@permission_classes([IsAuthenticated])
def orders_api(request):

    order = Order.objects.create(
        user=request.user,
        product_id=request.data["product"],
        quantity=request.data["quantity"],
        phone=request.data["phone"],
        email=request.data["email"],
        address=request.data["address"],
        payment_type=request.data["payment_type"]
    )

    return Response({"message": "Order created"})

```

■ *agribase/paymentapi/migrations/0001_initial.py*

Generated by Django 5.2.11 on 2026-02-21 10:16

```

import django.db.models.deletion
from django.conf import settings
from django.db import migrations, models

```

```

class Migration(migrations.Migration):

```

```

    initial = True

```

```

    dependencies = [
        migrations.swappable_dependency(settings.AUTH_USER_MODEL),
    ]

```

```

    operations = [
        migrations.CreateModel(
            name='Order',
            fields=[
                ('id', models.BigAutoField(auto_created=True, primary_key=True, serialize=False, verbose_name='ID')),
                ('product_id', models.IntegerField()),
                ('quantity', models.IntegerField()),
                ('phone', models.CharField(max_length=20)),
                ('email', models.EmailField(max_length=254)),
                ('address', models.TextField()),
                ('payment_type', models.CharField(max_length=20)),
                ('created_at', models.DateTimeField(auto_now_add=True)),
                ('user', models.ForeignKey(on_delete=django.db.models.deletion.CASCADE, to=settings.AUTH_USER_MODEL)),
            ],
        ),
    ]

```

■ *agribase/paymentapi/migrations/__init__.py*

