Server Tools Scripting Help

Query 1 SQL File 3* SQL File 4* SQL File 7*

Don't Limit

```sql
-- Q1: customer names and their order amounts using INNER joins
select c.customer_name, o.order_amount
from customers c
inner join orders o on c.customer_id = o.customer_id;
```

Result Grid Filter Rows: Export: Wrap Cell Content:

customer_name	order_amount
Aarav	500
Sophia	1200
Liam	800
Meera	1500
Ethan	700
Aisha	900
Daniel	1100
Kavya	600
Noah	2000
Riya	1300
Zayn	400
Aria	950
Kyra	300
Jace	1700

Result 9

Output

Action Output

Query 1 | SQL File 3* | SQL File 4* | SQL File 7*

Don't Limit

```sql
SELECT * FROM customers;
SELECT * FROM orders;

-- Q2: ALL customers and their order amounts
select c.customer_name, o.order_amount
from customers c
left join orders o on c.customer_id = o.customer_id;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

customer_name	order_amount
Arjun	600
Arjun	1200
Sneha	890
Varun	1340
Divya	1500
Divya	760
Karthik	1450
Harini	1990
Oliver	NULL
Grace	NULL
Benjamin	NULL
Chloe	NULL
Lucas	NULL
Madison	NULL
Henry	NULL
Scarlett	NULL
Jack	NULL
Natalie	NULL
Elio	NULL
Soren	NULL
[illegible]	NULL

Result 10

Output

Query 1 | SQL File 3* | SQL File 4* | SQL File 7*

Don't Limit

```sql
SELECT * FROM customers;
SELECT * FROM orders;

-- Q3: Show ALL orders with customer names
select o.order_amount, c.customer_name
from customers c
right join orders o on c.customer_id = o.customer_id;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

order_amount	customer_name
1200	Arjun
890	Sneha
1340	Varun
760	Divya
1450	Karthik
1990	Harini
500	NULL
800	NULL
900	NULL
1200	NULL
300	Aarav
450	Ethan
700	Riya
950	Mira
1100	Finn
600	Arjun
750	Sophia
820	Liam
910	Meera
660	Aisha

Result 11

Output

Query 1 | SQL File 3* | SQL File 4* | SQL File 7*

Don't Limit

```sql
SELECT * FROM orders;

-- Q4: Find customers who have NOT placed any orders
select  c.customer_name, o.customer_id as `Order`
from customers c
left join orders o on c.customer_id = o.customer_id
where o.customer_id is null
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

customer_name	Order
Oliver	NULL
Grace	NULL
Benjamin	NULL
Chloe	NULL
Lucas	NULL
Madison	NULL
Henry	NULL
Scarlett	NULL
Jack	NULL
Natalie	NULL
Elio	NULL
Soren	NULL
Amara	NULL
Kael	NULL
Liora	NULL
Zora	NULL
Renan	NULL
Selene	NULL
Thane	NULL
Elara	NULL

Result 17

Query 1 | SQL File 3* | SQL File 4* | SQL File 7*

Don't Limit

```sql
-- Q5: Find orders that do NOT have a valid customer
-- (Includes NULL customer_id and invalid IDs like 60, 70
select o.order_id, o.customer_id, o.order_amount
from orders o
left join customers c
on o.customer_id = c.customer_id
where c.customer_id IS NULL;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

order_id	customer_id	order_amount
31	NULL	500
32	NULL	800
33	60	900
34	70	1200

Result 28

Output

Action Output

#	Time	Action	Me
118	21:07:43	select c.customer_name, sum(o.order_amount) as total_amount from orders o join customers c on o.customer_i	1 r

base Server Tools Scripting Help

Query 1 SQL File 3* SQL File 4* SQL File 7*

Don't Limit

```sql
-- Q6: Show customer name and order amount
-- But only for orders greater than 1000
select c.customer_name, o.order_amount
from orders o
join customers c on o.customer_id = c.customer_id
where o.order_amount > 1000;
```

Result Grid Filter Rows: Export: Wrap Cell Content:

customer_name	order_amount
Sophia	1200
Meera	1500
Daniel	1100
Noah	2000
Riya	1300
Jace	1700
Mira	2200
Zara	1400
Nyla	1800
Finn	2100
Ishita	1600
Arjun	1200
Varun	1340
Karthik	1450
Harini	1990
Finn	1100

Result 20

Output

Query 1 | SQL File 3* | SQL File 4* | SQL File 7*

Don't Limit

```sql
-- Q7: Show all customers from 'Chennai' and their orders
-- Even if they have no orders
select c.customer_name, c.city, o.order_amount
from orders o
left join customers c on o.customer_id = c.customer_id
where c.city = "chennai" ;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

customer_name	city	order_amount
Aarav	Chennai	500
Aisha	Chennai	900
Zayn	Chennai	400
Kian	Chennai	750
Nithin	Chennai	650
Sneha	Chennai	890
Aarav	Chennai	300
Aisha	Chennai	660

Result 22

Output

abase Server Tools Scripting Help

Query 1 | SQL File 3* | SQL File 4* | SQL File 7*

Don't Limit

```sql
-- Q8: Count how many orders each customer has placed
select c.customer_name, count(o.order_id) as `order`
from orders o
join customers c on o.customer_id = c.customer_id
group by c.customer_name ;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

customer_name	order
Aarav	2
Sophia	2
Liam	2
Meera	2
Ethan	2
Aisha	2
Daniel	1
Kavya	2
Noah	2
Riya	2
Zayn	1
Aria	2
Kyra	1
Jace	1
Mira	2
Kian	1
Zara	1
Leo	2

Result 23

Output

Action Output

#	Time	Action	Message
112	20:54:18	select c.customer_name, c.city, o.order_amount from orders o left join customers c on o.customer_id = c.custo...	8 row(s) retume
113	20:57:28	select c.customer_name, count(o.order_id) as `order` from orders o join customers c on o.customer_id = c.custo...	30 row(s) return

Query 1 | SQL File 3* | SQL File 4* | SQL File 7*

Don't Limit

```sql
-- Q9: Calculate total amount spent by each customer
select c.customer_name, sum(o.order_amount) as total_spent
from orders o
join customers c on o.customer_id = c.customer_id
group by c.customer_name ;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

customer_name	total_spent
Aarav	800
Sophia	1950
Liam	1620
Meera	2410
Ethan	1150
Aisha	1560
Daniel	1100
Kavya	1140
Noah	3320
Riya	2000
Zayn	400
Aria	1420
Kyra	300
Jace	1700
Mira	3150
Kian	750
Zara	1400
Leo	1380

Result 25

Output

Action Output

#	Time	Action
114	20:58:54	SELECT * FROM orders

Query 1 | SQL File 3* | SQL File 4* | SQL File 7*

Don't Limit

```sql
-- Q10: Find the customer who spent the HIGHEST total amount
select c.customer_name, sum(o.order_amount) as total_amount
from orders o
join customers c on o.customer_id = c.customer_id
group by c.customer_name order by total_amount DESC
limit 1 ;
```

Result Grid | Filter Rows: | Export: | Wrap Cell Content:

customer_name	total_amount
Noah	3320

Result 29

Output

Action Output