Experiment-3

Design a simple network topology using Cisco Packet tracer.

Aim:

To design and configure the simple network topology with one router, two switches and multiple PCs using Cisco packet tracer.

Requirements:

Cisco Packet Tracer 8.x.1, Router (2811 or 1841) 2 switches (2960), 4-6 PCs Ethernet cables.

Procedure:

1) Open Cisco Packet tracer and create new Project.

2) Drag, routers, 2 switches and 4 PC onto the workshop.

3) connect PC0 and PC1 with switch0 using copper straight-through cable.

4) Connect PC2 and PC3 with switch using copper straight-through cable.

Commands:

Router > enable
Router # config terminal
Router (config) # hostname main router.
main router (config) # interface fa
ethernet 0/1
main router (config) # ip address 192.168.
main router (config-if) # exit
main router # copy running-config
startup-config:

5) Connect switch, to router via ethernet 0/1

6) Config PC2: IP=192.168.22 mask: 255.253.255.0 GW=192.168.21

7) Config PC3: IP=192.168.2, mask=255.255.255 GW=192.168.2.2

8) Config Router int g0/1: IP address 192.168.2.1 255.255.255.0) no shutdown.

Result: 8/10

A network topology with 1 router, 2 switch and 4 PC's was successfully created in Cisco packet tracer.