R-PROGRAMMING

6. MEAN, MEDIAN, ADN MODE

```
> names <- c("siri", "mahi", "chiru")
> age <- c(23, 24, 25)
> marks <- c(88, 78, 25)
>
> df <- data.frame(names, age, marks)
>
> # Mean
> mean(df$age)
[1] 24
>
> # Median
> median(df$age)
[1] 24
>
> # Mode
> get_mode <- function(x) {
+     values <- unique(x)
+     values[which.max(tabulate(match(x, values)))]
+ }
> get_mode(df$age)
[1] 23
>
> write.csv(df, "datafr.csv", row.names = FALSE)
>
```

7. SUMMARY

```
> names <- c("siri", "mahi", "chiru")
> age <- c(23, 24, 25)
> marks <- c(88, 78, 25)
>
> df <- data.frame(names, age, marks)
>
> summary(df$age)
   Min. 1st Qu.  Median    Mean 3rd Qu.    Max.
   23.0    23.5    24.0    24.0    24.5    25.0
> write.csv(df, "datafr.csv", row.names = FALSE)
```

8.GREATEST AMONG THREE NUMBERS

```
> x <- as.integer(readline(prompt = "Enter first number:
"))
Enter first number: 2
> y <- as.integer(readline(prompt = "Enter second number:
"))
Enter second number: 3
>
> z <- as.integer(readline(prompt = "Enter third number:
"))
Enter third number: 4
>
>
> if (x >= y && x >= z) {
+     print(paste("Greatest is:", x))
+ } else if (y >= x && y >= z) {
+     print(paste("Greatest is:", y))
+ } else {
+     print(paste("Greatest is:", z))
+ }
[1] "Greatest is: 4"
```

9. INTERQUARTLE RANGE (IQR)

```
> names <- c("siri", "mahi", "chiru")
> age <- c(23, 24, 25)
> marks <- c(88, 78, 25)
>
> df <- data.frame(names, age, marks)
>
> IQR(df$age)
[1] 1
> write.csv(df, "datafr.csv", row.names = FALSE)
>
```

10. QUANTILE

```
> names <- c("siri", "mahi", "chiru")
> age <- c(23, 24, 25)
> marks <- c(88, 78, 25)
>
> df <- data.frame(names, age, marks)
>
> quantile(df$age)
  0%  25%  50%  75% 100%
23.0 23.5 24.0 24.5 25.0
> write.csv(df, "datafr.csv", row.names = FALSE)
>
```