


Java Full Stack Development-LAB08

ID.NO:2000030185

Name: Suprith Ch

application.properties




The screenshot shows the Eclipse IDE with the 'application.properties' file open. The file contains the following configuration:

```
1 server.port=2040
2
3 #spring.datasource.properties
4
5
6 spring.datasource.driver-class-name=com.mysql.cj.jdbc.Driver
7 spring.datasource.url=jdbc:mysql://localhost:3306/springjparestapi?useSSL=false&allowPublicKeyRetrieval=true
8 spring.datasource.username=root
9 spring.datasource.password=0906
10
11 #spring.hibernate.jpa.properties
12
13 spring.jpa.hibernate.ddl-auto=update
14 spring.jpa.show-sql=true
15 spring.jpa.properties.hibernate.dialect=org.hibernate.dialect.MySQL55Dialect
```

com.klef.jfsd.springboot

SpringBootJparestapiDemoApplication.java




The screenshot shows the Eclipse IDE with the 'SpringBootJparestapiDemoApplication.java' file open. The file contains the following code:

```
1 package com.klef.jfsd.springboot;
2
3 import org.springframework.boot.SpringApplication;
4
5 @SpringBootApplication
6 @ComponentScan(basePackages = "com.klef.jfsd.springboot")
7 public class SpringBootJparestapiDemoApplication
8 {
9
10     public static void main(String[] args)
11     {
12         SpringApplication.run(SpringBootJparestapiDemoApplication.class, args);
13         System.out.println("Spring Boot Application to Implement RESTful Web Services with JPA");
14     }
15 }
16
17
18
19
```


com.klef.jfsd.springboot.controller


ClientController.java



com.klef.jfsd.springboot.model


Employee.java






com.klef.jfsd.springboot.repository

EmployeeRepository.java



com.klef.jfsd.springboot.service

EmployeeService.java



EmployeeServiceImpl.java

