Rajalakshmi Engineering College

Name: Nitin Aakash

Email: 240701370@rajalakshmi.edu.in

Roll no: 240701370 Phone: 9498349045

Branch: REC

Department: I CSE FD

Batch: 2028

Degree: B.E - CSE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 5

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

Input Format

The first line contains an integer n, representing the number of items to be initially entered into the inventory.

The second line contains n integers, each representing the unique identification number of an item separated by spaces.

The third line contains an integer p, representing the position of the item to be deleted from the inventory.

Output Format

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If p is an invalid position, the output prints "Invalid position. Try again."

If p is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

Sample Test Case

```
Input: 4
1 2 3 4
5
Output: Data entered in the list:
node 1 : 1
node 2 : 2
node 3 : 3
node 4 : 4
Invalid position. Try again.

Answer
class Node:
```

def __init__(self, data);

```
self.data = data
        self.prev = None
        self.next = None
    class DoublyLinkedList:
      def __init__(self):
         self.head = None
        self.tail = None
      def append(self, data):
        new_node = Node(data)
        if not self.head:
          self.head = new_node
           self.tail = new_node
        else:
          self.tail.next = new_node
          new_node.prev = self.tail
           self.tail = new_node
      def delete_at_position(self, position):
        if position < 1:
          return False
```

```
for in
         for _ in range(position - 1):
           if current is None:
              return False
           current = current.next
         if current is None:
           return False
         if current.prev:
           current.prev.next = current.next
         if current.next:
           current.next.prev = current.prev
         if current == self.head:
           self.head = current.next
         if current == self.tail:
           self.tail = current.prev
```

24010131 return True

2,40701370

240701370

```
def display(self):
    current = self.head
    index = 1
    while current:
       print(f" node {index} : {current.data}")
       current = current.next
       index += 1
n = int(input())
elements = list(map(int, input().split()))
p = int(input())
dll = DoublyLinkedList()
for element in elements:
dll.append(element)
print("Data entered in the list:")
dll.display()
if p < 1 or p > n:
  print("Invalid position. Try again.")
  dll.delete_at_position(p)
else:
```

print("\nAfter deletion the new list:")
dll.display()

240701370

240701370

Status: Correct Marks: 10/10

240701370

240701370

2,0701370

040701370

240701370

2,0701370

2,40701370

0,0701370

240701370

040101310

2,40701370

240701370