

# Rajalakshmi Engineering College

Name: Nitin Aakash  
Email: 240701370@rajalakshmi.edu.in  
Roll no: 240701370  
Phone: 9498349045  
Branch: REC  
Department: I CSE FD  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 6\_COD\_Question 1

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem Statement

John and Mary are collaborating on a project that involves data analysis. They each have a set of age data, one sorted in ascending order and the other in descending order. However, their analysis requires the data to be in ascending order.

Write a program to help them merge the two sets of age data into a single sorted array in ascending order using merge sort.

##### ***Input Format***

The first line of input consists of an integer N, representing the number of age values in each dataset.

The second line consists of N space-separated integers, representing the ages of participants in John's dataset (in ascending order).

The third line consists of N space-separated integers, representing the ages of participants in Mary's dataset (in descending order).

### **Output Format**

The output prints a single line containing space-separated integers, which represents the merged dataset of ages sorted in ascending order.

Refer to the sample output for formatting specifications.

### **Sample Test Case**

Input: 5

1 3 5 7 9

10 8 6 4 2

Output: 1 2 3 4 5 6 7 8 9 10

### **Answer**

```
#include <stdio.h>
```

```
void merge(int arr[], int left[], int right[], int left_size, int right_size) {
```

```
    int i = 0, j = 0, k = 0;
```

```
    while (i < left_size && j < right_size) {
```

```
        if (left[i] <= right[j]) {
```

```
            arr[k++] = left[i++];
```

```
        } else {
```

```
            arr[k++] = right[j++];
```

```
        }
```

```
    }
```

```
    while (i < left_size) {
```

```
        arr[k++] = left[i++];
```

```
    }
```

```
    while (j < right_size) {
```

```
        arr[k++] = right[j++];
```

```
    }
```

```
}
```

```
void mergeSort(int arr[], int size) {
```

```
    if (size < 2) {
```

```
        return;
```

```
    }
```

```

int mid = size / 2;
int left[mid];
int right[size - mid];
for (int i = 0; i < mid; i++) {
    left[i] = arr[i];
}
for (int i = mid; i < size; i++) {
    right[i - mid] = arr[i];
}
mergeSort(left, mid);
mergeSort(right, size - mid);
merge(arr, left, right, mid, size - mid);
}

int main() {
int n, m;
scanf("%d", &n);
int arr1[n], arr2[n];
for (int i = 0; i < n; i++) {
    scanf("%d", &arr1[i]);
}
for (int i = 0; i < n; i++) {
    scanf("%d", &arr2[i]);
}
int merged[n + n];
mergeSort(arr1, n);
mergeSort(arr2, n);
merge(merged, arr1, arr2, n, n);
for (int i = 0; i < n + n; i++) {
    printf("%d ", merged[i]);
}
return 0;
}

```

**Status :** Correct

**Marks : 10/10**