

## Chapter 7

# STRING, CONVERSION, AND MISCELLANEOUS FUNCTIONS

- ❑ String functions
- ❑ Conversion functions
- ❑ Miscellaneous functions

In the last chapter we have seen how to use arithmetic and date functions. In this chapter let us see how to use string, conversion and miscellaneous functions.

## String Functions

String functions are functions that manipulate a set of characters. A set of characters is a string. For example, the name of the company, the address of a person all these are examples of a string. CHAR and VARCHAR data types contain strings. Let us first see how to concatenate strings in Oracle.

## Concatenating Strings

Two strings can be concatenated (added one after another) to form a single string using the string concatenation operator, which is `||` (two pipe symbols).

The following example concatenates name of the faculty with qualification. We also put two spaces between these two values to provide required space.

```
select name || ' ' || qual from faculty
```

```
NAME||' '||QUAL
```

```
-----  
George Koch  MS Computer Science  
Dan Appleman CS and EE graduate  
Herbert Schildt MS Computer Science  
David Hunter  MS Electronics  
Stephen Walther Ph.D. in Philosophy  
Kevin Loney   MS Eletronics  
Jamie Jaworski Bachlors of Electrical  
Jason Couchman OCP DBA
```

Table 1 shows the list of string functions. These functions generally take a string as parameter and also return a string as return value.

Function	Description
<b>LENGTH (string)</b>	Returns the number of characters in the <i>string</i> .
<b>LOWER (string)</b>	Returns the string after converting the string to lowercase.
<b>UPPER (string)</b>	Returns the string after converting the string to uppercase.
<b>INITCAP (string)</b>	Converts first character of every word to uppercase and remaining to lower case.
<b>LPAD (string, length [, fillstring])</b>	Makes the <i>string</i> of the given <i>length</i> by padding the string on the left either with space or with <i>fillstring</i> .
<b>RPAD (string, length [, fillstring])</b>	Same as LPAD but pads on the right.
<b>LTRIM (string [, charset])</b>	Removes all left most characters of string up to the first character that is not in the <i>charset</i> . if <i>charset</i> is not given then it defaults to blank.
<b>RTRIM (string [, charset])</b>	Same as LTRIM, but trims on the right.
<b>TRIM (string)</b>	Trims space on both sides.
<b>SUBSTR (string, pos , length)</b>	Extracts <i>length</i> number of characters from position <i>pos</i> in the string. If <i>length</i> is not given then extracts everything from <i>pos</i> .
<b>INSTR (s1,s2 [,pos [,occurrence]])</b>	Finds the starting position of <i>s2</i> in <i>s1</i> . If <i>occurrence</i> is not given then it finds first occurrence. Search starts at <i>pos</i> , if given, otherwise at the first character in <i>s1</i> .
<b>ASCII (string)</b>	Returns ASCII code of the first character in the given string
<b>CHR (number)</b>	Returns ASCII character for the given ASCII code.
<b>TRANSLATE (string, from, to)</b>	Replaces characters in <i>from</i> with <i>to</i> in string.
<b>REPLACE (string, source, replace)</b>	Replaces <i>source</i> in <i>string</i> with <i>replace</i> .

**Table 1:** String functions.

## Converting Case

Functions LOWER and UPPER are straightforward. And they play a very important role in string comparison. As string comparison is case sensitive, LOWER or UPPER can be used to convert strings to uniform case before they are compared.

The following query tries to retrieve details of courses related to programming.

```
select name,duration from courses
where name like '%programming%'
```

NAME	DURATION
-----	-----
C programming	20

The above query retrieves only one row whereas there are two rows that contain the word programming. It is because of the difference in the case. So the following query is converting the name to lowercase before comparison.

```
select name,duration from courses
where LOWER(name) like '%programming%'
```

NAME	DURATION
-----	-----
C programming	20
XML Programming	15

As NAME is converted to lowercase during comparison and compared with programming, which is in lowercase, the difference in case is ignored. The same result can be achieved even by using UPPER function. But in that case the string must be given in uppercase – PROGRAMMING.

INITCAP converts first letter of each word to capital and remaining letters to lowercase.

```
select initcap('this IS to Test INITCAP') Result
from dual;
```

RESULT
-----
This Is To Test Initcap

## INSTR function

INSTR returns the position in the first string where the second string starts in the first string. If second string is not found in first string, it returns 0.

The default is to return the position of first occurrence by starting the search at the very first character in first string. However, INSTR has options using which we can specify from where the search should start and which occurrence is to be considered.

The following examples illustrate the usage of two optional parameters; *start* and *occurrence*.

```
select instr('How do you do','do') Postion
from dual;
```

```
      POSTION
-----
          5
```

Though string "do" occurs for twice, the position of first occurrence is be returned. It is possible to specify to INSTR that it should start looking for *do* starting from the given position as follows.

```
select instr('How do you do','do',8) Postion
from dual
```

```
      POSTION
-----
         12
```

It is possible to specify that the position of the specified occurrence is to be returned as follows:

```
select instr('How do you do','do',1,2) Postion
from dual
```

```
      POSTION
-----
         12
```

---

**Note:** When occurrence is specified then starting position must also be specified, as third parameter cannot be omitted while fourth parameter is given.

---

The following example displays the details of courses where the letter p exists in the name of the course after 6<sup>th</sup> position.

```
select ccode,name
from courses
where instr(name,'n') > 6
```

```
CCODE NAME
-----
c      C programming
java   Java Language
xml    XML Programming
```

The same query can also be written as follows using LIKE operator and six underscores to indicate that first six letters may be anything but **n** must exists after that. But INSTR version will be more flexible.

```
select ccode,name
from courses
where name like '_____n%'
```

```
CCODE NAME
-----
c      C programming
java   Java Language
xml    XML Programming
```

We will see some more applications of INSTR at a later stage.

### SUBSTR function

SUBSTR is used to extract a sub string from the given string. It takes the position from where extraction starts and the number of characters to be extracted.

The following example displays the first 2 character from the code of the course.

```
select ccode, substr(ccode,1,2) sn from courses
```

```
CCODE SN
-----
ora    or
vbnet  vb
c       c
asp     as
java   ja
xml     xm
```

It is possible to omit third parameter – length of the sub string. The following example illustrates it.

```
select substr('Srikanth Technologies',10) Result from dual
```

```
RESULT
-----
Technologies
```

The result of one function can be passed to another function as input. We have already seen nesting functions in the previous chapter. Now let us see how we can combine SUBSTR and INSTR to get the first name of each faculty. First name is the name before space.

```
select name, substr( name, 1, instr(name,' ') - 1) Firstname from faculty;
```

NAME	FIRSTNAME
George Koch	George
Dan Appleman	Dan
Herbert Schildt	Herbert
David Hunter	David
Stephen Walther	Stephen
Kevin Loney	Kevin
Jamie Jaworski	Jamie
Jason Couchman	Jason

INSTR function is used to find out the position of first space. Then that position is used to specify the number of character to be taken from name. We subtracted one from position because position indicates the position of space but we have to take up to the character before the space.

The following is another example of these two functions. It take last name of the faculty.

```
select name, substr(name,instr(name,' ') + 1) Lastname from faculty
```

NAME	LASTNAME
George Koch	Koch
Dan Appleman	Appleman
Herbert Schildt	Schildt
David Hunter	Hunter
Stephen Walther	Walther
Kevin Loney	Loney
Jamie Jaworski	Jaworski
Jason Couchman	Couchman

The following is the sequence of steps in the above query.

- ❑ INSTR returns the position of first space in NAME
- ❑ The return value of the INSTR, after 1 is added, is passed to SUBSTR as the starting position.
- ❑ Everything on the right of the given position is taken by SUBSTR

Since Oracle converts the given values to required data type automatically, INSTR and SUBSTR can also be used with numbers and dates. The following query displays payments made in the month of April.

```
select * from payments
where instr(dp, 'APR') <> 0
```

ROLLNO	DP	AMOUNT
9	07-APR-01	3000
10	10-APR-01	4500
11	07-APR-01	1000
11	10-APR-01	3500

## Trimming Strings

LTRIM and RTRIM are used to trim off unwanted characters from the left and right ends of the string respectively. Leftmost spaces are called as **leading spaces** and rightmost spaces are called as **trailing spaces**.

They trim spaces by default. Optionally, you can specify which set of characters you want to trim.

The following example is used to trim spaces on the left using LEFT. The length of the string will show the result.

```
select length(' abc xyz ') Before,
       length( ltrim(' abc xyz ')) After
from dual
```

BEFORE	AFTER
13	11

You can also trim a specified set of characters as shown below.

```
select ltrim( 'aabcbadxyabc','abc') Result from dual
```

```
RESULT
-----
dxyabc
```

In the above example, trimming stopped at 'd' because 'd' is the first character that doesn't fall in the character set of 'abc'.

While trimming, each character from left or right is taken and checked against the characters in the set. If character is same as any character in the character set, then character is trimmed otherwise trimming ends at that character. The same is true with RTRIM function, but it trims on the right.

TRIM function, which was introduced in Oracle8i, is used to trim both leading and trailing spaces.

```
select length(' abc xyz ') Before,
       length(trim(' abc xyz ')) After
from dual
```

```
      BEFORE      AFTER
-----
          12          8
```

## Padding Strings

A string can be made of a given length by padding either on the left using LPAD or on the right using RPAD. By default Oracle uses space to pad strings. However, it is possible to specify which character(s) should be used for padding.

The following example course to 12 characters it specifies that dot is to be used for padding.

```
select rpad(name,12,'.') Name from courses
```



---

```
NAME
-----
Oracle datab
VB.NET.....
C programmin
ASP.NET.....
Java Languag
XML Programm
```

The above example is padding strings that are shorter than 12 characters and truncating strings that are larger than 12 characters. Names like *VB.NET* and *ASP.NET* are padded on the right using dots. Whereas names like *Oracle database* and *C programming* are truncated to 12 characters.

---

**Note:** *RPAD* and *LAPD* truncate the given string if string has more number of characters than the given length.

---

### TRANSLATE and REPLACE functions

These two functions return the string after modifying the given string. *TRANSLATE* works on individual characters, whereas *REPLACE* replaces a string with another string.

The following two examples will make the difference clear.

```
select replace('ABC ABAC XYZ DABC','ABC','PQR') Result from dual

RESULT
-----
PQR ABAC XYZ DPQR
```

*REPLACE* replaces every occurrence of string 'ABC' with string 'PRQ'.

```
select translate('ABC ABAC XYZ DABC','ABC','PQR') Result
from dual

RESULT
-----
PQR PQPR XYZ DPQR
```

*TRANSLATE* changes every occurrence of letter A with P, B with Q and C with R.

## Conversion Functions

Conversion functions are used to convert a value from one data type into another. These functions are not required if Oracle can automatically convert the value. But there are cases where these conversion functions are required to convert the value to the required data type. The following table lists conversion functions.

FUNCTION	DESCRIPTION
TO_CHAR (value [, format])	Converts <i>value</i> , which is of DATE or NUMBER type, to CHAR type.
TO_DATE (char [, format])	Converts the given CHAR type value to DATE type.
TO_NUMBER (char)	Converts given CHAR type value to NUMBER type.

**Table 2:** Conversion Functions.

Before we understand how and where we use conversion functions, let us see how Oracle tries to convert the given data to the required data type.

## Automatic Type Conversion

Oracle automatically converts the value to the required data type if it is possible. For example, if a number is used with string function, number is converted to string and then the function is executed.

In the same way, if a DATE type value is required but if a CHAR type value is given in the format DD-MON-YY or DD-MON-YYYY then Oracle converts it to DATE type.

But this automatic data type conversion is not always possible. To convert the value to the required data type, the given value must already look like the data type it is being converted to. The following are guidelines that describe automatic type conversion.

**GUIDELINES FOR AUTOMATIC CONVERSION OF DATA TYPE**

- ❑ Any NUMBER or DATE will be converted to a CHAR.
- ❑ If DATE is a literal enclose it in quotes.
- ❑ CHAR type will be converted to NUMBER if it contains only digits, decimal point, or minus sign on the left.
- ❑ CHAR will be converted to DATE type if it is in DD-MON-YY or DD-MON-YYYY format.
- ❑ A DATE will NOT be converted to NUMBER.
- ❑ A NUMBER will NOT be converted to DATE.

The following few examples will give you better idea about automatic conversion of data type:

In the following example NUMBER is automatically converted to CHAR before LENGTH function is used.

```
select length(1133) from dual;
```

```
LENGTH(1133)
-----
              4
```

In the example below, a DATE given in CHAR format is converted to DATE before LAST\_DAY function is applied.

```
select last_day('20-aug-2001') from dual;
```

```
LAST_DAY(
-----
31-AUG-01
```

Similarly it is possible to use a CHAR value where a NUMBER is required, as shown below.

```
select 5 * '20' from dual;
```

```
5*'20'
-----
      100
```

Here are a few examples where Oracle cannot automatically convert the value.

```
SQL> select next_day('12-1-2001', 'Fri') from dual;
select next_day('12-1-2001', 'Fri') from dual
*
```

ERROR at line 1:  
ORA-01843: not a valid month

Oracle returns an error saying the date is not having valid month because Oracle expects months to be of first three letters of the month name. As we have given only month number, it is not acceptable to Oracle. In this case we need to explicitly convert the value to DATE type using TO\_DATE function.

The following sections will show how to use conversion functions.

### TO\_CHAR Function

This function is used to convert the given DATE or NUMBER to CHAR type. TO\_CHAR function may also be used to format the given date or number while converting the value to CHAR type. For example, to display date in DD-MM-YYYY format instead of standard format - DD-MON-YY, enter the following:

```
select to_char(sysdate,'dd-mm-yyyy') Result from dual

RESULT
-----
15-08-2000
```

In fact, TO\_CHAR is one of the most frequently used functions. Here in the example, below it is used to display both date and time of SYSDATE. Remember this operation needs explicit usage of TO\_CHAR as by default Oracle displays only date.

```
select to_char(sysdate,'dd Month yyyy hh24:mi:ss')
from dual

TO_CHAR(SYSDATE,'DDMONTHYY
-----
15 August      2000 02:18:56
```

In the above example **Month** is standing for complete month name, **yyyy** stands for four digits year, **hh24** for 24 hours based hour, **mi** minutes and **ss** for seconds.

Format in TO\_CHAR function is a collection of more than 40 formatting options. Please see Table 3 for more options. For complete list, please see on-line help for *Date Format Elements*.

All options in the format are replaced with the corresponding values and remaining characters are returned as they are. In the above example, ':' between HH24 and MI is returned as it is but HH24 and MI are replaced with the corresponding values.

Format Option	Description
MM	Number of the month: 10
MON	First three letters of month name: OCT
MONTH	Complete month name: OCTOBER
DDD	Day of the year since January 1st: 340
DD	Day of the month: 16
D	Day of the week: 5
Day	Day fully spelled: Wednesday
YYYY	Four digits year: 1996
YY	Two digits year: 96
YEAR	Year spelled out: NINETEEN-NINTY-SIX
HH or HH12	Hour of the day: 5
HH24	Hour of the day: 20
MI	Minute of hour: 30
SS	Second of minute: 30
A.M. or P.M.	Displays A.M. or P.M. depending on the time.
Fm	Removes trailing spaces. 'May ' becomes 'May'
TH	Suffix to number: DDTH will produce 16 <sup>th</sup>
SP	Number Spelled out: DDSP will produce THIRD for day 3.

**Table 3:** TO\_CHAR and TO\_DATE formats.

The following query retrieves details of the students who have joined in the month of April in year 2001.

```
select bcode, name from students
where to_char(dj,'mmyyyy') = '042001';
```

```
BCODE NAME
-----
b5      Richard Marx
b5      Tina Turner
b5      Jody Foster
```

In the following example TO\_CHAR is used to display month name of the year. However, as you can see in the output, there are trailing spaces after month name. This is because Oracle pads the name to 9 characters. Months that have smaller name than that will have trailing spaces.

```
select bcode, name, to_char(dj,'dd-Month-yyyy') dj from students
```

BCODE	NAME	DJ
b1	George Micheal	10-January -2001
b1	Micheal Douglas	11-January -2001
b2	Andy Roberts	11-January -2001
b2	Malcom Marshall	16-January -2001
b2	Vivan Richards	16-January -2001
b3	Chirs Evert	14-January -2001
b3	Ivan Lendal	15-January -2001
b4	George Micheal	01-March -2001
b5	Richard Marx	06-April -2001
b5	Tina Turner	06-April -2001
b5	Jody Foster	07-April -2001

Format fm can be used to remove these trailing spaces in months name. Here is revised version of the above query.

```
select bcode, name, to_char(dj,'dd-fmMonth-yyyy') dj from students
```

BCODE	NAME	DJ
b1	George Micheal	10-January-2001
b1	Micheal Douglas	11-January-2001
b2	Andy Roberts	11-January-2001
b2	Malcom Marshall	16-January-2001
b2	Vivan Richards	16-January-2001
b3	Chirs Evert	14-January-2001
b3	Ivan Lendal	15-January-2001
b4	George Micheal	01-March-2001
b5	Richard Marx	06-April-2001
b5	Tina Turner	06-April-2001
b5	Jody Foster	07-April-2001

---

**Note:** The output of TO\_CHAR will be in the same case as the format. For example, if Month is given then output will be April; if MONTH is given then output will be APRIL.

---

## TO\_DATE function

TO\_DATE is used to convert a CHAR type value to DATE type. If the value is in DD-MON-YY or DD-MM-YYYY format then TO\_DATE is not needed because Oracle implicitly converts the value to DATE type.

When you insert a record with only date in DD-MON-YY format, time portion of the date is set to 00:00:00. The following INSERT inserts a new row into PAYMETS table with date as well as time.

```
insert into payments
values ( 10,to_date('14-04-2001 10:20:00',
                  'dd-mm-yyyy hh24:mi:ss'), 2000);
```

It is important to make sure the values given are matching with the format. That means, in the above example, as we gave *dd-mm-yyyy hh24:mi:ss* as the formation even the data is to given in the same format. The format informs to Oracle how to interpret the given values. If there is any mismatch, the values may be misinterpreted.

The *format options* are same as TO\_CHAR function format options. See **Table 3** for available format options.

### TO\_NUMBER function

This function is required in only two occasions. The following are the two cases.

- ❑ To convert formatted number to number.
- ❑ To sort CHAR data in numeric order.

The first application of TO\_NUMBER is to convert formatted number to number. The following example is trying to multiply \$333 by 20. But as the number with currency symbol is not taken as a number by Oracle, it results in error.

```
SQL> select $333 * 20 from dual;
select $333 * 20 from dual
      *
ERROR at line 1:
ORA-00911: invalid character
```

TO\_NUMBER function can be used to convert \$333 to a number so that it is treated as a number by Oracle. The format in TO\_NUMBER specified that the first character is to be taken as currency symbol and remaining as digits.

```
SQL> select to_number('$333','$999') * 20 from dual

TO_NUMBER('$333','$999')*20
-----
                        6660
```

### Sorting strings in numeric order

Another usage of TO\_NUMBER is to sort a column that contains numbers but stored in the form of CHAR type.

Assume the following data is existing in VNO column of VEHICLES table. Column VNO is defined as VARCHAR2(10).

```
SQL> select vno from vehicles;
```

```
VNO
-----
1133
1583
2502
5657
9
234
45
```

The following SELECT sorts the data but sorts the column VNO as a collection of strings. That means the numeric values are not taken into account and numbers are taken as a collection of characters (each digits is a character).

```
select vno from vehicles order by vno;
```

```
VNO
-----
1133
1583
234
2502
45
5657
9
```

The output show that number 9 is at the bottom. It is because of the way strings are compared in sorting – first character first and then second character and so on.

To sort the data using numeric value, issue the following command where VNO column is converted to a number before it is sorted using TO\_NUMBER function.

```
select vno from vehicles order by to_number(vno);
```



```
VNO
-----
9
45
234
1133
1583
2502
5657
```

We will see a lot of usage of conversion function TO\_CHAR throughout the rest of the book.

## Miscellaneous Functions

Miscellaneous functions are the functions that can be used with any data type. See table 4 for the list of miscellaneous functions.

Function	Description
DECODE(expression,cond,value, cond,value,...,elsevalue)	If <i>expression</i> is equivalent to first <i>cond</i> then first <i>value</i> is returned otherwise Oracle checks whether the <i>expression</i> is equivalent to second <i>cond</i> then second value is returned. If <i>expression</i> doesn't match with any of the values then <i>elsevalue</i> is returned.
GREATEST(value1,value2,...)	Returns the greatest of the given values.
LEAST( value1, value2, ...)	Returns the least value of the given values.
NVL(value1,value2)	Return <i>value2</i> if <i>value1</i> is null otherwise returns <i>value1</i> .

**Table 4:** Miscellaneous Functions.

The following examples will show you how to use miscellaneous functions.

### DECODE function

This function works like a multiple IF statement or a CASE/SWITCH statement in a typical programming language.

It takes a value and compares it with the given values one by one. Wherever the value is equivalent to the given value it returns the corresponding value.

The following example shows how to decode the GRADE of COURSE\_FACULTY table.

```
select fcode, ccode, decode(grade, 'A', 'Very Good',
                             'B', 'Good',
                             'C', 'Average',
                             'Unknown') Grade
from course_faculty
```

FCODE	CCODE	GRADE
-----	-----	-----
gk	ora	Very Good
kl	ora	Very Good
jc	ora	Very Good
da	vbnet	Very Good
sw	asp	Very Good
da	asp	Good
hs	c	Very Good
dh	xml	Very Good
jj	java	Very Good
hs	java	Good
jj	c	Very Good
jj	vbnet	Good

The function is used to display meaningful text for column GRADE, which contains only A,B or C.

The following example shows another usage of DECODE where we display the total remuneration paid to faculty. Assuming the payment is based on the time of the batch and no. of days of the batch.

```
select bcode, ccode, fcode, stdate, enddate,
       decode(timing, 1, 200, 2, 150, 175) * (enddate-stdate) Amount from batches
where enddate is not null
```

BCODE	CCODE	FCODE	STDATE	ENDDATE	AMOUNT
-----	-----	-----	-----	-----	-----
b1	ora	gk	12-JAN-01	20-FEB-01	7800
b2	asp	da	15-JAN-01	05-MAR-01	7350
b3	c	hs	20-JAN-01	27-FEB-01	6650
b4	xml	dh	02-MAR-01	30-MAR-01	4900
b5	java	hs	05-APR-01	10-MAY-01	7000

---

**GREATEST and LEAST functions**

These functions take a collection of values and return a single value which is either the least or greatest of the given values as the case may be.

GREATEST is used to return the largest of the given values and LEAST the smallest of the given values.

The following example shows the discount to be given to each course. The scheme is to given discount of 10% on the course fee or 500 whichever is higher. The following query with GREATEST function will achieve the result.

```
select ccode, name, greatest( fee * 0.10,500) Discount from courses;
```

CCODE	NAME	DISCOUNT
ora	Oracle database	500
vbnet	VB.NET	550
c	C programming	500
asp	ASP.NET	500
java	Java Language	500
xml	XML Programming	500

LEAST Function can be used in the same manner but it sets the upper limit. In the following query the discount is either 10% of the course fee or 500 whichever is lower.

```
select ccode,name, least( fee * 0.10,500) Discount from courses
```

CCODE	NAME	DISCOUNT
ora	Oracle database	450
vbnet	VB.NET	500
c	C programming	350
asp	ASP.NET	500
java	Java Language	450
xml	XML Programming	400

---

**Note:** GREATEST and LEAST will not treat string literal that is in date format as date. Instead these dates are taken as strings.

---

The following example shows how these two functions treat dates that are given in date format but as strings.

```
select greatest ( '12-jun-2001','17-mar-2001')
from dual
```

```
GREATEST('1
-----
17-mar-2001
```

The above command returns '17-mar-2001' instead of '12-jun-2001' because when these two are treated as strings, value in second position in first string (7) is greater than it corresponding value in first string (2), so 17-mar-2001 is returned as the greatest value.

### NVL function

It is used to return the second value if first value is null. This function has a lot of significance since Oracle returns a null value from any expression containing a null value.

---

**Note:** Any expression involving a null value will result in a null value.

---

The following query is to display the details of all batches. But we get nothing – actually null value – for NODAYS of batches b6 and b7 as they have null value in ENDDATE. Since Oracle results in null value for any expression having a null value the result of ENDDATE-STDDATE is a null value.

```
select bcode, stdate, enddate - stdate nodays from batches;
```

BCODE	STDATE	NODAYS
-----	-----	-----
b1	12-JAN-01	39
b2	15-JAN-01	49
b3	20-JAN-01	38
b4	02-MAR-01	28
b5	05-APR-01	35
b6	12-JUL-01	
b7	15-AUG-01	

However, now we want to take ending date if batch is completed otherwise we want to take system date as ending date.

```
select bcode, stdate, nvl(enddate,sysdate) - stdate nodays from batches;
```

BCODE	STDATE	NODAYS
-----	-----	-----
b1	12-JAN-01	39
b2	15-JAN-01	49
b3	20-JAN-01	38

b4	02-MAR-01	28
b5	05-APR-01	35
b6	12-JUL-01	50.17985
b7	15-AUG-01	16.17985

Now we want to include even the status of the batch, which will be COMPLETED if ENDDATE is not null otherwise RUNNING.

```
select bcode, stdate, nvl(enddate,sysdate) - stdate nodays,  
       decode(enddate,null,'Running','Completed') Status from batches;
```

BCODE	STDATE	NODAYS	STATUS
b1	12-JAN-01	39	Completed
b2	15-JAN-01	49	Completed
b3	20-JAN-01	38	Completed
b4	02-MAR-01	28	Completed
b5	05-APR-01	35	Completed
b6	12-JUL-01	50.1811	Running
b7	15-AUG-01	16.1811	Running

## Summary

String functions manipulate strings. Conversion functions are used to convert the data type of a value from one to another. In fact, Oracle always tries to convert the given value to the required data type. But in some cases as Oracle cannot convert implicitly, conversion functions are to be used to convert the value to the required data type.

Miscellaneous functions like DECODE and NVL can be used with any data type. DECODE is an if-elseif-else structure. NVL returns either the first value if it is not null or second value if first value is null.

## Exercises

1. \_\_\_\_\_ function performs one to one character substitution.
2. \_\_\_\_\_ format option is used to get complete year spelled out in TO\_CHAR function.
3. \_\_\_\_\_ symbol is used to concatenate strings.
4. What happens if 'replace string' is not given for REPLACE functions.

5. Can a NUMBER be converted to DATE? [Yes/No] \_\_\_\_.
6. How do you change the name of each student to uppercase in STUDENTS table.
7. Display the names of the students who have more than 15 characters in the name.
8. Display students 'first name' second and 'second name' first.  
For example, Louis Figo should be displayed as Figo Louis.
9. Display the details of the students who have more than 10 characters in the first name.
10. What is the result of AMOUNT – DISCOUNT if column DISCOUNT is null.
11. How do you get the position of 5<sup>th</sup> occurrence of letter 'o' in student's name.
12. What will be the result of select '10' \* '20' from dual;