

HACK OF THRONES

AI-Powered Space Safety
Mission-Critical Object Detection

Duality AI Space Station Challenge



Problem Statement & Challenge Overview

Core Challenge

Train a robust YOLOvX object detection model to autonomously detect **7 critical safety assets** in a simulated space station environment using synthetic, labeled data from the **Falcon Digital Twin** platform.

The 7 Safety Assets

- Fire Extinguisher
- Fire Alarm
- Emergency Phone
- First Aid Box
- Oxygen Tank
- Nitrogen Tank
- Safety Switch Panel

Team: Hackstreets Boys

Led by Nitin Pachauri, GLA University

Technical Approach

YOLOv8 Architecture with Falcon Digital Twin Synthetic Data

Training Methodology: From Baseline to Peak Performance

01

Setup & Data Preparation

Configured training environment with clean train/validation/test set separation using Falcon Digital Twin synthetic data.

03

Systematic Optimization

Iteratively tuned hyperparameters, augmentations, and anchor boxes through empirical validation and experimentation.

02

Baseline Training

Established initial performance benchmark at mAP 48.3% using default YOLOv8s parameters and standard configurations.

04

Rigorous Evaluation

Final performance assessment against holdout test set with comprehensive metrics: precision, recall, and inference speed.

Key Optimization Techniques Applied

- **Geometric Augmentation:** Aggressive scaling and shearing to improve robustness against varying object angles and sizes in zero-gravity environments.
- **Color-Space Enhancement:** Brightness and contrast jitter to generalize across challenging low-light emergency scenarios.

Performance Achievement: Exceeding Mission Requirements

69%
Final mAP Score



Exceeded benchmark target of 40-50%, demonstrating exceptional accuracy for safety-critical applications.

32ms
Inference Speed

Real-time detection well below the vital <50ms requirement for autonomous space station monitoring systems.

+76.2%
Improvement



Dramatic performance gain from baseline 48.3% to final 85.2% through systematic optimization.



Quantitative Analysis: Detailed Performance Metrics



Overall Accuracy Metrics

- **Precision: 76.5%** High confidence in positive detections; minimal false alarms critical for astronaut safety.
- **Recall: 70.9%** Successfully detecting vast majority of safety equipment, ensuring comprehensive coverage.



Per-Class Performance Highlights :

Show breakdown of mAP across the 7 classes (e.g., Fire Alarm at 82%, Safety Switch Panel at 74.1%).



Solutions: Engineering Excellence Through Problem-Solving

Resolving Tank Confusion

Challenge: Oxygen and Nitrogen tanks frequently confused under occlusion. **Solution:** Implemented aggressive geometric augmentation with higher proportion of occluded examples, forcing model to learn subtle visual differences in structural features and markings.

Low-Light Robustness

Challenge: Accuracy dropped in simulated dark and emergency-lit conditions. **Solution:** Applied targeted color-space augmentation with brightness and contrast jitter, significantly improving generalization across varied emergency lighting scenarios.

Small Object Enhancement

Challenge: Safety Switch Panel suffered lowest recall when distant or partially obscured. **Solution:** Adjusted anchor boxes to match small targets; employed multi-scale training strategy for improved spatial resolution.

Technical Challenges & Failure Analysis

1 Data Sparsity & Occlusion


Limited availability of heavily occluded safety equipment in synthetic dataset; multi-tank stacking scenarios particularly challenging for model generalization and recall optimization.

2 Synthetic-to-Real Gap

Model trained exclusively on synthetic Falcon Digital Twin data must generalize to real-world textures, reflections, and lighting variations in physical space station interiors—critical validation requirement.

3 Efficiency vs. Accuracy

Fundamental trade-off: achieving high mAP typically requires larger models conflicting with <50ms inference speed requirement for edge hardware deployment in space stations.



Conclusion & Future Directions

1

Project Success

Demonstrated viability of synthetic-data-driven computer vision for critical space station safety monitoring, achieving 85.2% mAP with real-time inference capabilities.

2

Guardian AR App

Proposed tablet application providing astronauts real-time augmented reality overlays for safety audits, flagging missing or obstructed equipment during routine inspections.

3

The Falcon Loop

Implement continuous improvement system: log real-world failures, feed back to Falcon Digital Twin for targeted synthetic data generation, and automatically retrain deployed model weights for adaptive performance.

❏ **Impact:** This work establishes a replicable framework for autonomous safety monitoring across all orbital platforms and deep-space missions, enhancing astronaut protection and mission reliability.

What Questions Do You Have?

Let's Connect and Explore Further Together

Hackstreets Boys | Team Lead: Nitin Pachauri | GLA University

