

Authentication and Access Control Pending

1. Create a simple login form for a mock Zomato admin panel that asks for username and password, then displays 'Access Granted' only if both fields match hardcoded admin credentials.

ANS :

- **Python Code**

```
username = input("Enter Username: ")  
password = input("Enter Password: ")
```

```
admin_username = "admin"  
admin_password = "zomato123"
```

```
if username == admin_username and password == admin_password:  
    print("Access Granted")  
else:  
    print("Access Denied")
```

- **Sample Output**

```
Enter Username: admin  
Enter Password: zomato123  
Access Granted
```

2. Write a Python function `check_access(user_role, resource)` that returns `True` if the `user_role` is allowed to access the resource, otherwise `False`. Test it with roles like 'customer', 'restaurant_owner', and resources like 'menu_edit', 'order_history', 'admin_dashboard'. Hint : Use a dictionary to map roles to allowed resources.

ANS :

- **Python Code**

```
def check_access(user_role, resource):  
    permissions = {  
        "customer": ["order_history"],  
        "restaurant_owner": ["menu_edit", "order_history"],  
        "admin": ["menu_edit", "order_history", "admin_dashboard"]  
    }  
  
    return resource in permissions.get(user_role, [])  
  
# Test Cases  
print(check_access("customer", "order_history"))  
print(check_access("customer", "menu_edit"))  
print(check_access("restaurant_owner", "menu_edit"))  
print(check_access("restaurant_owner", "admin_dashboard"))  
print(check_access("admin", "admin_dashboard"))
```

- **Output**

True
False
True
False
True

3. Simulate a two-factor authentication flow like Paytm: after a user enters the correct password, generate a 6-digit OTP and display it in the console. Ask the user to input the OTP and display 'Login Successful' only if it matches.

ANS :

- **Python Code**

```
import random

correct_password = "paytm123"

password = input("Enter Password: ")

if password == correct_password:

    otp = random.randint(100000, 999999)

    print("Generated OTP:", otp)

    user_otp = int(input("Enter OTP: "))

    if user_otp == otp:

        print("Login Successful")

    else:

        print("Invalid OTP")

else:

    print("Incorrect Password")
```

- **Sample Output**

```
Enter Password: paytm123

Generated OTP: 456789

Enter OTP: 456789

Login Successful
```

4. Given an array of user objects with properties: username, isPremium, and lastLogin, write a function that returns only those users who are premium and have logged in within the last 7 days.

Constraint: Assume lastLogin is a date string in 'YYYY-MM-DD' format, and today is '2024-06-10'.

ANS :

- **Python Code**

```
from datetime import datetime, timedelta

def get_active_premium_users(users):
    today = datetime.strptime("2024-06-10", "%Y-%m-%d")
    seven_days_ago = today - timedelta(days=7)
    result = []
    for user in users:
        login_date = datetime.strptime(user["lastLogin"], "%Y-%m-%d")
        if user["isPremium"] and login_date >= seven_days_ago:
            result.append(user)
    return result

users = [
    {"username": "harsh", "isPremium": True, "lastLogin": "2024-06-08"},
    {"username": "rahul", "isPremium": False, "lastLogin": "2024-06-09"},
    {"username": "priya", "isPremium": True, "lastLogin": "2024-05-30"},
    {"username": "neha", "isPremium": True, "lastLogin": "2024-06-05"}
]

print(get_active_premium_users(users))
```

- **Output**

```
{'username': 'harsh', 'isPremium': True, 'lastLogin': '2024-06-08'},
{'username': 'neha', 'isPremium': True, 'lastLogin': '2024-06-05'}
```

5. Use ChatGPT to generate a list of 5 common access control mistakes developers make in real-world apps like Instagram or Flipkart, and for each, write a one-line fix or prevention tip.

ANS :

Mistake	Fix / Prevention
1. Using weak passwords	Enforce strong password policies and complexity rules.
2. Not implementing role-based permissions	Use RBAC (Role-Based Access Control) for every resource.
3. Exposing admin pages through direct URLs	Verify user authorization on every request.
4. Storing passwords in plain text	Store passwords using secure hashing algorithms like bcrypt.
5. Not enabling Multi-Factor Authentication (MFA)	Require OTP or authenticator app verification for sensitive actions.