

# Learning Distributed Document Representations for Multi-Label Document Categorization

**Nitish Gupta**

B.Tech - M.Tech Dual Degree

Thesis Defense

Electrical Engineering

IIT Kanpur

May 16, 2015



- ➊ Multi-Label Document Categorization
- ➋ Related Work
  - Text Representations
  - Learning Algorithms
- ➌ Distributed Word Representations
- ➍ Learning Distributed Document Representations
- ➎ Document Categorization Algorithm
- ➏ Results
- ➐ Conclusion and Future Work

# Intoduction to Multi-Label Document Categorization

- Text Documents usually belong to more than one conceptual class.  
For E.g. an article on Music Piracy

# Intoduction to Multi-Label Document Categorization

- Text Documents usually belong to more than one conceptual class.  
For E.g. an article on Music Piracy
- Task of assigning documents to one or more predefined categories is called *Multi-Label Document Categorization*

# Introduction to Multi-Label Document Categorization

- Text Documents usually belong to more than one conceptual class.  
For E.g. an article on Music Piracy
- Task of assigning documents to one or more predefined categories is called *Multi-Label Document Categorization*
- Wide range real-world applications :
  - Web-page tagging
  - Medical Patient Record Management
  - Wikipedia Article Management
  - Document Recommendation etc.

# Introduction to Multi-Label Document Categorization

- Text Documents usually belong to more than one conceptual class.  
For E.g. an article on Music Piracy
- Task of assigning documents to one or more predefined categories is called *Multi-Label Document Categorization*
- Wide range real-world applications :
  - Web-page tagging
  - Medical Patient Record Management
  - Wikipedia Article Management
  - Document Recommendation etc.
- Multi-label classification belongs to a general class of supervised learning algorithms where :

# Introduction to Multi-Label Document Categorization

- Text Documents usually belong to more than one conceptual class.  
For E.g. an article on Music Piracy
- Task of assigning documents to one or more predefined categories is called *Multi-Label Document Categorization*
- Wide range real-world applications :
  - Web-page tagging
  - Medical Patient Record Management
  - Wikipedia Article Management
  - Document Recommendation etc.
- Multi-label classification belongs to a general class of supervised learning algorithms where :
  - Training instances in the form of document-category pairs are used to learn a classifier  $\mathcal{H}$

# Introduction to Multi-Label Document Categorization

- Text Documents usually belong to more than one conceptual class.  
For E.g. an article on Music Piracy
- Task of assigning documents to one or more predefined categories is called *Multi-Label Document Categorization*
- Wide range real-world applications :
  - Web-page tagging
  - Medical Patient Record Management
  - Wikipedia Article Management
  - Document Recommendation etc.
- Multi-label classification belongs to a general class of supervised learning algorithms where :
  - Training instances in the form of document-category pairs are used to learn a classifier  $\mathcal{H}$
  - Learned classifier  $\mathcal{H}$  is used to assign categories to new test documents



# Introduction to Multi-Label Document Categorization

Given,

- A set of documents  $D = \{d_1, \dots, d_{|D|}\}$

# Introduction to Multi-Label Document Categorization

Given,

- A set of documents  $D = \{d_1, \dots, d_{|D|}\}$
- A set of categories  $C = \{c_1, \dots, c_{|C|}\}$

# Introduction to Multi-Label Document Categorization

Given,

- A set of documents  $D = \{d_1, \dots, d_{|D|}\}$
- A set of categories  $C = \{c_1, \dots, c_{|C|}\}$
- Training data for  $n$  ( $n < |D|$ ) documents,  $\mathcal{T} = \{l_{d_1}, \dots, l_{d_n}\}$

# Introduction to Multi-Label Document Categorization

Given,

- A set of documents  $D = \{d_1, \dots, d_{|D|}\}$
- A set of categories  $C = \{c_1, \dots, c_{|C|}\}$
- Training data for  $n$  ( $n < |D|$ ) documents,  $\mathcal{T} = \{l_{d_1}, \dots, l_{d_n}\}$   
Each label vector  $l_{d_i} \in \{0, 1\}^{|C|}$  denotes relevance of categories to the document  $d_i$

# Introduction to Multi-Label Document Categorization

Given,

- A set of documents  $D = \{d_1, \dots, d_{|D|}\}$
- A set of categories  $C = \{c_1, \dots, c_{|C|}\}$
- Training data for  $n$  ( $n < |D|$ ) documents,  $\mathcal{T} = \{l_{d_1}, \dots, l_{d_n}\}$   
Each label vector  $l_{d_i} \in \{0, 1\}^{|C|}$  denotes relevance of categories to the document  $d_i$

Example :

Documents	Sports	Music	Arts	Technology	Literature	Politics
$d_1$	0	0	1	0	1	0
$d_2$	0	1	1	0	0	1
$d_3$	1	0	0	1	0	1
$d_4$	x	x	x	x	x	x
$d_5$	x	x	x	x	x	x

# Introduction to Multi-Label Document Categorization

Given,

- A set of documents  $D = \{d_1, \dots, d_{|D|}\}$
- A set of categories  $C = \{c_1, \dots, c_{|C|}\}$
- Training data for  $n$  ( $n < |D|$ ) documents,  $\mathcal{T} = \{l_{d_1}, \dots, l_{d_n}\}$   
Each label vector  $l_{d_i} \in \{0, 1\}^{|C|}$  denotes relevance of categories to the document  $d_i$

Example :

Documents	Sports	Music	Arts	Technology	Literature	Politics
$d_1$	0	0	1	0	1	0
$d_2$	0	1	1	0	0	1
$d_3$	1	0	0	1	0	1
$d_4$	x	x	x	x	x	x
$d_5$	x	x	x	x	x	x

Using  $\mathcal{T}$ ,  $D$  and  $C$  the learning algorithm learns a multi-label classifier  $\mathcal{H}$  to estimate category label vectors,  $l_{d_j}$  ( $j > n$ ) for the test documents.

# Introduction to Multi-Label Document Categorization

Document Categorization task has the following two components :

# Introduction to Multi-Label Document Categorization

Document Categorization task has the following two components :

- 1 *Learning Document Representations* : Representing text documents using numerical vectors that are inputs to the multi-label classifier  $\mathcal{H}$



# Introduction to Multi-Label Document Categorization

Document Categorization task has the following two components :

- 1 *Learning Document Representations* : Representing text documents using numerical vectors that are inputs to the multi-label classifier  $\mathcal{H}$ 
  - Each document  $d_i \in D$  is represented using a vector  $v_{d_i} \in \mathbb{R}^k$

# Introduction to Multi-Label Document Categorization

Document Categorization task has the following two components :

- 1 *Learning Document Representations* : Representing text documents using numerical vectors that are inputs to the multi-label classifier  $\mathcal{H}$ 
  - Each document  $d_i \in D$  is represented using a vector  $v_{d_i} \in \mathbb{R}^k$
  - Vectors  $(v_{d_i})$  should encode the semantic content of the documents

# Introduction to Multi-Label Document Categorization

Document Categorization task has the following two components :

- 1 *Learning Document Representations* : Representing text documents using numerical vectors that are inputs to the multi-label classifier  $\mathcal{H}$ 
  - Each document  $d_i \in D$  is represented using a vector  $v_{d_i} \in \mathbb{R}^k$
  - Vectors ( $v_{d_i}$ ) should encode the semantic content of the documents
  - Encoding documents in a  $k$ -dimensional space using such representation is called the *Vector Space Model*

# Introduction to Multi-Label Document Categorization

Document Categorization task has the following two components :

- 1 *Learning Document Representations* : Representing text documents using numerical vectors that are inputs to the multi-label classifier  $\mathcal{H}$ 
  - Each document  $d_i \in D$  is represented using a vector  $v_{d_i} \in \mathbb{R}^k$
  - Vectors ( $v_{d_i}$ ) should encode the semantic content of the documents
  - Encoding documents in a  $k$ -dimensional space using such representation is called the *Vector Space Model*
  - The complete document set  $D$  can be represented by a document representation matrix  $D \in \mathbb{R}^{k \times |D|}$

# Introduction to Multi-Label Document Categorization

Document Categorization task has the following two components :

- 1 *Learning Document Representations* : Representing text documents using numerical vectors that are inputs to the multi-label classifier  $\mathcal{H}$ 
  - Each document  $d_i \in D$  is represented using a vector  $v_{d_i} \in \mathbb{R}^k$
  - Vectors ( $v_{d_i}$ ) should encode the semantic content of the documents
  - Encoding documents in a  $k$ -dimensional space using such representation is called the *Vector Space Model*
  - The complete document set  $D$  can be represented by a document representation matrix  $D \in \mathbb{R}^{k \times |D|}$

*In this thesis, we focus on learning efficient document representations,  $D$*

# Introduction to Multi-Label Document Categorization

Document Categorization task has the following two components :

- 1 *Learning Document Representations* : Representing text documents using numerical vectors that are inputs to the multi-label classifier  $\mathcal{H}$ 
  - Each document  $d_i \in D$  is represented using a vector  $v_{d_i} \in \mathbb{R}^k$
  - Vectors ( $v_{d_i}$ ) should encode the semantic content of the documents
  - Encoding documents in a  $k$ -dimensional space using such representation is called the *Vector Space Model*
  - The complete document set  $D$  can be represented by a document representation matrix  $D \in \mathbb{R}^{k \times |D|}$

*In this thesis, we focus on learning efficient document representations,  $D$*

- 2 *Learning Algorithm* : Algorithm to learn the multi-label classifier  $\mathcal{H}$

# Background on Learning Algorithms

## ① *Learning Multiple Binary Classifiers :*



# Background on Learning Algorithms

## ① *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

## 1 *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

- Logistic Regression

## ① *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

- Logistic Regression
- Support Vector Machines (SVM)

## ① *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

- Logistic Regression
- Support Vector Machines (SVM)
- Neural Networks

## ① *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

- Logistic Regression
- Support Vector Machines (SVM)
- Neural Networks
- Naive Bayes

# Background on Learning Algorithms

## ① *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

- Logistic Regression
- Support Vector Machines (SVM)
- Neural Networks
- Naive Bayes

## ② *Learning Single Joint Classifier :*

# Background on Learning Algorithms

## ① *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

- Logistic Regression
- Support Vector Machines (SVM)
- Neural Networks
- Naive Bayes

## ② *Learning Single Joint Classifier :*

Algorithms that jointly assign all the categories to a document  $d_i$ , i.e. estimate the complete label vector  $l_{d_i}$  using a single classifier

# Background on Learning Algorithms

## ① *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

- Logistic Regression
- Support Vector Machines (SVM)
- Neural Networks
- Naive Bayes

## ② *Learning Single Joint Classifier :*

Algorithms that jointly assign all the categories to a document  $d_i$ , i.e. estimate the complete label vector  $l_{d_i}$  using a single classifier

- k-Nearest Neighbor (k-NN)



# Background on Learning Algorithms

## ① *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

- Logistic Regression
- Support Vector Machines (SVM)
- Neural Networks
- Naive Bayes

## ② *Learning Single Joint Classifier :*

Algorithms that jointly assign all the categories to a document  $d_i$ , i.e. estimate the complete label vector  $l_{d_i}$  using a single classifier

- k-Nearest Neighbor (k-NN)
- Linear Least Square Fit

# Background on Learning Algorithms

## ① *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

- Logistic Regression
- Support Vector Machines (SVM)
- Neural Networks
- Naive Bayes

## ② *Learning Single Joint Classifier :*

Algorithms that jointly assign all the categories to a document  $d_i$ , i.e. estimate the complete label vector  $l_{d_i}$  using a single classifier

- k-Nearest Neighbor (k-NN)
- Linear Least Square Fit
- Decision Trees

# Background on Learning Algorithms

## ① *Learning Multiple Binary Classifiers :*

Algorithms that treat each category assignment independently and learn multiple binary classifiers, one for each category, to make the category assignments

- Logistic Regression
- Support Vector Machines (SVM)
- Neural Networks
- Naive Bayes

## ② *Learning Single Joint Classifier :*

Algorithms that jointly assign all the categories to a document  $d_i$ , i.e. estimate the complete label vector  $l_{d_i}$  using a single classifier

- k-Nearest Neighbor (k-NN)
- Linear Least Square Fit
- Decision Trees
- Generative Probabilistic Models

# Background on Text Representation

## Bag of Words Model

# Background on Text Representation

## Bag of Words Model

- Document  $d_i$  represented by  $v_{d_i} \in \mathbb{R}^{|V|}$

# Background on Text Representation

## Bag of Words Model

- Document  $d_i$  represented by  $v_{d_i} \in \mathbb{R}^{|V|}$
- Each element in  $v_{d_i}$  denotes presence/absence of each word

# Background on Text Representation

## Bag of Words Model

- Document  $d_i$  represented by  $v_{d_i} \in \mathbb{R}^{|V|}$
- Each element in  $v_{d_i}$  denotes presence/absence of each word
- Weighing techniques employed to give importance to important terms

# Background on Text Representation

## Bag of Words Model

- Document  $d_i$  represented by  $v_{d_i} \in \mathbb{R}^{|V|}$
- Each element in  $v_{d_i}$  denotes presence/absence of each word
- Weighing techniques employed to give importance to important terms
  - Term Frequency ( $tf$ )
  - Inverse Document Frequency ( $idf$ )
  - Term Frequency - Inverse Document Frequency ( $tf-idf$ ) :  $tf \times idf$



# Background on Text Representation

## Bag of Words Model

- Document  $d_i$  represented by  $v_{d_i} \in \mathbb{R}^{|V|}$
- Each element in  $v_{d_i}$  denotes presence/absence of each word
- Weighing techniques employed to give importance to important terms
  - Term Frequency ( $tf$ )
  - Inverse Document Frequency ( $idf$ )
  - Term Frequency - Inverse Document Frequency ( $tf-idf$ ) :  $tf \times idf$

## Drawbacks of the Bag-of-Words model

# Background on Text Representation

## Bag of Words Model

- Document  $d_i$  represented by  $v_{d_i} \in \mathbb{R}^{|V|}$
- Each element in  $v_{d_i}$  denotes presence/absence of each word
- Weighing techniques employed to give importance to important terms
  - Term Frequency ( $tf$ )
  - Inverse Document Frequency ( $idf$ )
  - Term Frequency - Inverse Document Frequency ( $tf-idf$ ) :  $tf \times idf$

## Drawbacks of the Bag-of-Words model

- High-dimensionality

# Background on Text Representation

## Bag of Words Model

- Document  $d_i$  represented by  $v_{d_i} \in \mathbb{R}^{|V|}$
- Each element in  $v_{d_i}$  denotes presence/absence of each word
- Weighing techniques employed to give importance to important terms
  - Term Frequency ( $tf$ )
  - Inverse Document Frequency ( $idf$ )
  - Term Frequency - Inverse Document Frequency ( $tf-idf$ ) :  $tf \times idf$

## Drawbacks of the Bag-of-Words model

- High-dimensionality
- Sparsity

# Background on Text Representation

## Bag of Words Model

- Document  $d_i$  represented by  $v_{d_i} \in \mathbb{R}^{|V|}$
- Each element in  $v_{d_i}$  denotes presence/absence of each word
- Weighing techniques employed to give importance to important terms
  - Term Frequency ( $tf$ )
  - Inverse Document Frequency ( $idf$ )
  - Term Frequency - Inverse Document Frequency ( $tf-idf$ ) :  $tf \times idf$

## Drawbacks of the Bag-of-Words model

- High-dimensionality
- Sparsity
- Inability to encode word contexts

# Background on Text Representation

## Bag of Words Model

- Document  $d_i$  represented by  $v_{d_i} \in \mathbb{R}^{|V|}$
- Each element in  $v_{d_i}$  denotes presence/absence of each word
- Weighing techniques employed to give importance to important terms
  - Term Frequency ( $tf$ )
  - Inverse Document Frequency ( $idf$ )
  - Term Frequency - Inverse Document Frequency ( $tf-idf$ ) :  $tf \times idf$

## Drawbacks of the Bag-of-Words model

- High-dimensionality
- Sparsity
- Inability to encode word contexts
- Ignores word order

# Background on Feature Selection / Dimensionality Reduction

Techniques to deal with sparsity and high-dimensionality in BOW

# Background on Feature Selection / Dimensionality Reduction

Techniques to deal with sparsity and high-dimensionality in BOW

- Information Gain

$$G(t) = - \sum_{i=1}^{|C|} P(c_i) \log P(c_i) + P(t) \sum_{i=1}^{|C|} P(c_i|t) \log P(c_i|t) + P(\sim t) \sum_{i=1}^{|C|} P(c_i|\sim t) \log P(c_i|\sim t) \quad (1)$$

# Background on Feature Selection / Dimensionality Reduction

## Techniques to deal with sparsity and high-dimensionality in BOW

- Information Gain

$$G(t) = - \sum_{i=1}^{|C|} P(c_i) \log P(c_i) + P(t) \sum_{i=1}^{|C|} P(c_i|t) \log P(c_i|t) + P(\sim t) \sum_{i=1}^{|C|} P(c_i|\sim t) \log P(c_i|\sim t) \quad (1)$$

- Mutual Information

$$I(t, c) = \log \frac{P(t \wedge c)}{P(t) \times P(c)}, \quad I_{avg}(t) = \sum_{i=1}^{|C|} P(c_i) I(t, c_i) \quad (2)$$



# Background on Feature Selection / Dimensionality Reduction

## Techniques to deal with sparsity and high-dimensionality in BOW

- Information Gain

$$G(t) = - \sum_{i=1}^{|C|} P(c_i) \log P(c_i) + P(t) \sum_{i=1}^{|C|} P(c_i|t) \log P(c_i|t) + P(\sim t) \sum_{i=1}^{|C|} P(c_i|\sim t) \log P(c_i|\sim t) \quad (1)$$

- Mutual Information

$$I(t, c) = \log \frac{P(t \wedge c)}{P(t) \times P(c)}, \quad I_{avg}(t) = \sum_{i=1}^{|C|} P(c_i) I(t, c_i) \quad (2)$$

- Latent Semantic Indexing (LSI)

$$X = TSD^T \quad (3)$$

# Distributed Word Representations

Representing each word  $w_i$  using vector  $v_{w_i} \in \mathbb{R}^k$  ( $k \in [50, 300]$ )

# Distributed Word Representations

Representing each word  $w_i$  using vector  $v_{w_i} \in \mathbb{R}^k$  ( $k \in [50, 300]$ )

## Need for Distributed Word Representations

# Distributed Word Representations

Representating each word  $w_i$  using vector  $v_{w_i} \in \mathbb{R}^k$  ( $k \in [50, 300]$ )

## Need for Distributed Word Representations

- Curse of Dimensionality

# Distributed Word Representations

Representing each word  $w_i$  using vector  $v_{w_i} \in \mathbb{R}^k$  ( $k \in [50, 300]$ )

## Need for Distributed Word Representations

- Curse of Dimensionality
  - One-hot representations grow with the size of vocabulary

# Distributed Word Representations

Representing each word  $w_i$  using vector  $v_{w_i} \in \mathbb{R}^k$  ( $k \in [50, 300]$ )

## Need for Distributed Word Representations

- Curse of Dimensionality
  - One-hot representations grow with the size of vocabulary
  - Parameters in language modelling grow exponentially with the size of vocabulary

# Distributed Word Representations

Representating each word  $w_i$  using vector  $v_{w_i} \in \mathbb{R}^k$  ( $k \in [50, 300]$ )

## Need for Distributed Word Representations

- Curse of Dimensionality
  - One-hot representations grow with the size of vocabulary
  - Parameters in language modelling grow exponentially with the size of vocabulary
- No Word Similarity Measure

# Distributed Word Representations

Representing each word  $w_i$  using vector  $v_{w_i} \in \mathbb{R}^k$  ( $k \in [50, 300]$ )

## Need for Distributed Word Representations

- Curse of Dimensionality
  - One-hot representations grow with the size of vocabulary
  - Parameters in language modelling grow exponentially with the size of vocabulary
- No Word Similarity Measure
  - One-hot representations are orthogonal representations



# Distributed Word Representations

Representating each word  $w_i$  using vector  $v_{w_i} \in \mathbb{R}^k$  ( $k \in [50, 300]$ )

## Need for Distributed Word Representations

- Curse of Dimensionality
  - One-hot representations grow with the size of vocabulary
  - Parameters in language modelling grow exponentially with the size of vocabulary
- No Word Similarity Measure
  - One-hot representations are orthogonal representations
  - Cannot capture semantic similarity between words

# Neural Probabilistic Language Model

Bengio et al. [1] developed *Neural Probabilistic Language Model (NPLM)* to learn

# Neural Probabilistic Language Model

Bengio et al. [1] developed *Neural Probabilistic Language Model (NPLM)* to learn

- 1 Distributed word vectors

# Neural Probabilistic Language Model


Bengio et al. [1] developed *Neural Probabilistic Language Model (NPLM)* to learn

- 1 Distributed word vectors
- 2 A probability function that, using these word vectors, learns a statistical model of language

# Neural Probabilistic Language Model

Bengio et al. [1] developed *Neural Probabilistic Language Model (NPLM)* to learn


- 1 Distributed word vectors
- 2 A probability function that, using these word vectors, learns a statistical model of language



# Neural Probabilistic Language Model

Bengio et al. [1] developed *Neural Probabilistic Language Model (NPLM)* to learn

- 1 Distributed word vectors
- 2 A probability function that, using these word vectors, learns a statistical model of language




$$P(w_t | w_1^{t-1}) \approx P(w_t | w_{t-n+1}^{t-1}) \quad (4)$$

# Neural Probabilistic Language Model

Bengio et al. [1] developed *Neural Probabilistic Language Model (NPLM)* to learn

- ① Distributed word vectors
- ② A probability function that, using these word vectors, learns a statistical model of language




$$P(w_t | w_1^{t-1}) \approx P(w_t | w_{t-n+1}^{t-1}) \quad (4)$$

$$y = b + U \tanh(d + Hx), \quad y \in \mathbb{R}^{|V|} \quad (5)$$

# Neural Probabilistic Language Model

Bengio et al. [1] developed *Neural Probabilistic Language Model (NPLM)* to learn

- ① Distributed word vectors
- ② A probability function that, using these word vectors, learns a statistical model of language



$$P(w_t | w_1^{t-1}) \approx P(w_t | w_{t-n+1}^{t-1}) \quad (4)$$

$$y = b + \text{Utanh}(d + Hx), \quad y \in \mathbb{R}^{|V|} \quad (5)$$

$$P(w_t = i | w_{t-1}, \dots, w_{t-n+1}) = \frac{e^{y_{wt}}}{\sum_i e^{y_i}} \quad (6)$$




# Log-Linear Models

*Log-Linear Models* for learning distributed word vectors are proposed in Mikolov et al. [3]. These models use word vectors to predict other words in the context.

# Log-Linear Models

*Log-Linear Models* for learning distributed word vectors are proposed in Mikolov et al. [3]. These models use word vectors to predict other words in the context.


## 1 Continuous Bag-of-Words Model



# Log-Linear Models

*Log-Linear Models* for learning distributed word vectors are proposed in Mikolov et al. [3]. These models use word vectors to predict other words in the context.

## 1 Continuous Bag-of-Words Model




$$h = w_{t-k} + \dots + w_{t-1} + w_{t+1} + \dots + w_{t+k} \quad (7)$$

# Log-Linear Models

*Log-Linear Models* for learning distributed word vectors are proposed in Mikolov et al. [3]. These models use word vectors to predict other words in the context.

## 1 Continuous Bag-of-Words Model




$$h = w_{t-k} + \dots + w_{t-1} + w_{t+1} + \dots + w_{t+k} \quad (7)$$

$$y = b + Uh, \quad y \in \mathbb{R}^{|V|} \quad (8)$$

# Log-Linear Models

*Log-Linear Models* for learning distributed word vectors are proposed in Mikolov et al. [3]. These models use word vectors to predict other words in the context.

## 1 Continuous Bag-of-Words Model



$$h = w_{t-k} + \dots + w_{t-1} + w_{t+1} + \dots + w_{t+k} \quad (7)$$


$$y = b + Uh, \quad y \in \mathbb{R}^{|V|} \quad (8)$$

$$P(w_t | w_{t-k}, \dots, w_{t+k}) = \frac{e^{y_{w_t}}}{\sum_i e^{y_i}} \quad (9)$$

# Log-Linear Models

*Log-Linear Models* for learning distributed word vectors are proposed in Mikolov et al. [3]. These models use word vectors to predict other words in the context.

## 1 Continuous Bag-of-Words Model




$$h = w_{t-k} + \dots + w_{t-1} + w_{t+1} + \dots + w_{t+k} \quad (7)$$

$$y = b + Uh, \quad y \in \mathbb{R}^{|V|} \quad (8)$$

$$P(w_t | w_{t-k}, \dots, w_{t+k}) = \frac{e^{y_{w_t}}}{\sum_i e^{y_i}} \quad (9)$$


## 2 Skip-Gram Model



# Log-Linear Models

*Log-Linear Models* for learning distributed word vectors are proposed in Mikolov et al. [3]. These models use word vectors to predict other words in the context.

## 1 Continuous Bag-of-Words Model




$$h = w_{t-k} + \dots + w_{t-1} + w_{t+1} + \dots + w_{t+k} \quad (7)$$

$$y = b + Uh, \quad y \in \mathbb{R}^{|V|} \quad (8)$$

$$P(w_t | w_{t-k}, \dots, w_{t+k}) = \frac{e^{y_{w_t}}}{\sum_i e^{y_i}} \quad (9)$$

## 2 Skip-Gram Model



$$P(w_{t+j} | w_t) = \frac{e^{(v_{w_t} \cdot v_{w_{t+j}})}}{\sum_i e^{(v_{w_t} \cdot v_{w_i})}} \quad (10)$$

# Distributed Document Representations

## Motivation for learning distributed document representations



# Distributed Document Representations

## Motivation for learning distributed document representations

- 1 Traditional representations do not encode semantic similarity between documents. Therefore, cannot handle synonyms

# Distributed Document Representations

## Motivation for learning distributed document representations

- 1 Traditional representations do not encode semantic similarity between documents. Therefore, cannot handle synonyms
- 2 Drawbacks in BOW like sparsity, high-dimensionality, inability to encode context information and consider word ordering

## Motivation for learning distributed document representations

- 1 Traditional representations do not encode semantic similarity between documents. Therefore, cannot handle synonyms
- 2 Drawbacks in BOW like sparsity, high-dimensionality, inability to encode context information and consider word ordering
- 3 Compositionality of word vectors beyond weighted average [5, 8, 7, 2, 4] is not simple

## Motivation for learning distributed document representations

- 1 Traditional representations do not encode semantic similarity between documents. Therefore, cannot handle synonyms
- 2 Drawbacks in BOW like sparsity, high-dimensionality, inability to encode context information and consider word ordering
- 3 Compositionality of word vectors beyond weighted average  $[5, 8, 7, 2, 4]$  is not simple
- 4 Socher et al. [6] propose a Recursive Tensor Neural Network (RTNN) to compose word vectors for learning sentence representations using the parse-tree of the sentence in a bottom-up fashion

## Motivation for learning distributed document representations

- ❶ Traditional representations do not encode semantic similarity between documents. Therefore, cannot handle synonyms
- ❷ Drawbacks in BOW like sparsity, high-dimensionality, inability to encode context information and consider word ordering
- ❸ Compositionality of word vectors beyond weighted average  $[5, 8, 7, 2, 4]$  is not simple
- ❹ Socher et al. [6] propose a Recursive Tensor Neural Network (RTNN) to compose word vectors for learning sentence representations using the parse-tree of the sentence in a bottom-up fashion
  - Parsing, a computationally expensive step required for each sentence

## Motivation for learning distributed document representations

- ❶ Traditional representations do not encode semantic similarity between documents. Therefore, cannot handle synonyms
- ❷ Drawbacks in BOW like sparsity, high-dimensionality, inability to encode context information and consider word ordering
- ❸ Compositionality of word vectors beyond weighted average [5, 8, 7, 2, 4] is not simple
- ❹ Socher et al. [6] propose a Recursive Tensor Neural Network (RTNN) to compose word vectors for learning sentence representations using the parse-tree of the sentence in a bottom-up fashion
  - Parsing, a computationally expensive step required for each sentence
  - Composing sentence vectors to represent documents is not straight-forward

# Our Model for Learning Document Representations

*Inspired by the log-linear models to learn word vectors, we present model, to learn universal distributed representations for documents and words*

# Our Model for Learning Document Representations

*Inspired by the log-linear models to learn word vectors, we present model, to learn universal distributed representations for documents and words*

## Hypothesis

*Document Representations that encode semantic content of the document should be able to predict words in the document*



# Our Model for Learning Document Representations

*Inspired by the log-linear models to learn word vectors, we present model, to learn universal distributed representations for documents and words*

## Hypothesis

*Document Representations that encode semantic content of the document should be able to predict words in the document*

Our model,

# Our Model for Learning Document Representations

*Inspired by the log-linear models to learn word vectors, we present model, to learn universal distributed representations for documents and words*

## Hypothesis

*Document Representations that encode semantic content of the document should be able to predict words in the document*

Our model,

- ① Learns distributed representations for document (and words) that encode the different semantic content in the documents

# Our Model for Learning Document Representations

*Inspired by the log-linear models to learn word vectors, we present model, to learn universal distributed representations for documents and words*

## Hypothesis

*Document Representations that encode semantic content of the document should be able to predict words in the document*

Our model,

- 1 Learns distributed representations for document (and words) that encode the different semantic content in the documents
- 2 Embeds document and words in the same  $k$ -dimensional space such that semantically similar entities have similar vector representations

# References

- [1] Y. Bengio, R. Ducharme, P. Vincent, and C. Janvin. A neural probabilistic language model. *The Journal of Machine Learning Research*, 3:1137–1155, 2003.
- [2] E. Grefenstette, G. Dinu, Y.-Z. Zhang, M. Sadrzadeh, and M. Baroni. Multi-step regression learning for compositional distributional semantics. *arXiv preprint arXiv:1301.6939*, 2013.
- [3] T. Mikolov, K. Chen, G. Corrado, and J. Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013.
- [4] T. Mikolov, I. Sutskever, K. Chen, G. S. Corrado, and J. Dean. Distributed representations of words and phrases and their compositionality. In *Advances in Neural Information Processing Systems*, pages 3111–3119, 2013.
- [5] J. Mitchell and M. Lapata. Composition in distributional models of semantics. *Cognitive science*, 34(8):1388–1429, 2010.
- [6] R. Socher, A. Perelygin, J. Y. Wu, J. Chuang, C. D. Manning, A. Y. Ng, and C. Potts. Recursive deep models for semantic compositionality over a sentiment treebank. In *Proceedings of the conference on empirical methods in natural language processing (EMNLP)*, volume 1631, page 1642. Citeseer, 2013.
- [7] A. Yessenalina and C. Cardie. Compositional matrix-space models for