

The video provides an in-depth, first-principles breakdown of the Spring Bean Lifecycle within the Inversion of Control (IoC) container. It explores how Spring manages Singletons from container initialization to destruction, covering metadata parsing, instantiation, dependency injection, Aware interfaces, and initialization/destruction callbacks like `@PostConstruct` and `@PreDestroy`.

IoC Container Start & Configuration Parsing

The lifecycle begins when the IoC container boots up and immediately parses configuration metadata provided via classes annotated with `@Configuration` or `@ComponentScan`. Instead of blindly creating objects, the container first generates **Bean Definitions**. A Bean Definition is a blueprint containing vital metadata about the bean, including its name, class type, scope (e.g., Singleton or Prototype), lazy-loading status, and required dependencies. By mapping all definitions first, Spring can intelligently orchestrate the creation order.

Instantiation & Dependency Injection


Once definitions are mapped, Spring instantiates the beans. The container is dependency-aware, meaning it resolves dependencies strictly in order. If `OrderService` requires `PaymentService`, Spring will detect this dependency and construct `PaymentService` completely before constructing `OrderService`.

The timing of dependency injection shifts slightly depending on how the injection is defined:

Injection Type	Lifecycle Timing	Characteristics
Constructor	Simultaneous with object instantiation.	Safest; prevents the object from existing in a partially initialized state.
Field / Setter	Occurs sequentially right <i>after</i> the object is instantiated.	Allows the object to be built first, enabling workarounds for circular dependencies.

Aware Interfaces

Following injection, Spring checks if the bean implements any **Aware Interfaces** (such as `BeanNameAware` or `ApplicationContextAware`). If implemented, Spring triggers these specific callback methods to supply the bean with internal framework context. For example, implementing `BeanNameAware` forces Spring to pass the bean its assigned name within the container. While rarely used for standard business logic, Aware interfaces are valuable for advanced enterprise logging, dynamic context switching, or framework-level debugging.



Initialization Callbacks

Once the bean is instantiated, its dependencies are fully injected, and any Aware interfaces have been triggered, you might think the bean is ready to use. However, Spring provides one more crucial phase:

Initialization Callbacks.

Why do we need Initialization Callbacks?

You might need to perform setup tasks *before* any business logic executes. For example:

- Pre-loading an "expensive" (large) file into memory.
- Flushing or populating an internal data structure, like a `HashMap`.
- Invalidating or warming up a cache.


Why not just do this in the Constructor? The video emphasizes a vital interview question: *Why use initialization callbacks instead of the constructor?*

1. **Dependencies aren't ready:** When the constructor runs, field-based or setter-based dependencies have not been injected yet. If your initialization logic relies on those dependencies, it will fail (throw a `NullPointerException`) in the constructor.
2. **Heavy Lifting:** Constructors should ideally be lightweight. If you put heavy initialization logic (like file I/O or network calls) in the constructor, it slows down the bean creation process. It is a best practice to let the object create cleanly and lightly, and do the heavy lifting in a dedicated initialization phase.

How to Implement Initialization Callbacks

Spring offers three ways to hook into this phase. The video explains that while all three work, one is the modern industry standard.

Method	Approach	How it Works	Pros / Cons
InitializingBean Interface	Programmatic	Implement the interface and override the <code>afterPropertiesSet()</code> method.	Cons: Couples your code directly to Spring interfaces. Considered an older, legacy approach.
initMethod	Configuration-based	In your <code>@Configuration</code> class, specify <code>@Bean(initMethod="start")</code> and write a custom <code>start()</code> method in your class.	Pros: No Spring interfaces needed in your business class. Cons: Only works when manually defining beans with <code>@Bean</code> , not with <code>@ComponentScan</code> .
@PostConstruct	Annotation-based	Simply annotate any custom <code>void</code> method with <code>@PostConstruct</code> .	Pros: The modern standard. Clean, easy, and requires no interfaces. Cons: Requires the <code>jakarta.annotation-api</code> dependency if you are using bare Spring Context (Spring Boot includes it by default).



Bean is Ready for Use

After the initialization callbacks execute, the bean enters the "Ready" state. This is the phase you spend 99% of your time in as a developer. You can now freely call your business logic methods (e.g., `addToCart()`, `getValue()`, `placeOrder()`). The IoC container simply holds the bean in memory and serves it to whatever other classes request it.

Destruction Callbacks

Just as there is a setup phase, there is a teardown phase. When the Spring application shuts down, the IoC container needs to gracefully destroy the beans it manages. Before it removes them from memory, it gives you a chance to run cleanup logic via **Destruction Callbacks**.

Why do we need Destruction Callbacks?

This is the exact inverse of the initialization phase. If you opened a database connection, you need to close it. If you loaded an expensive file, you need to release it. If you populated a cache, you might want to clear it.

Note on Simulating Destruction: To see this in action, the video demonstrates casting the `ApplicationContext` to a `ConfigurableApplicationContext` so you can manually call `context.close()`. This simulates an application shutdown and triggers the destruction lifecycle.

How to Implement Destruction Callbacks

Mirroring the initialization phase, there are three ways to handle destruction:

Method	Approach	How it Works
DisposableBean Interface	Programmatic	Implement the interface and override the <code>destroy()</code> method.
destroyMethod	Configuration-based	Specify <code>@Bean(destroyMethod="stop")</code> and write a custom <code>stop()</code> method.
@PreDestroy	Annotation-based	Annotate your cleanup method with <code>@PreDestroy</code> . (This is the industry standard).

Nuances of Scopes and Loading

The lifecycle changes slightly depending on how the bean is scoped or loaded.

Lazy Initialization (@Lazy)

By default, Singleton beans are initialized **eagerly** (created as soon as the IoC container starts). If you annotate a Singleton bean with `@Lazy`, the container still reads its configuration and creates a Bean Definition, but it **stops there**.


The bean will not be instantiated, injected, or initialized until the exact moment a client requests it (e.g., via `getBean()` or when another bean requires it as a dependency). Once requested, it follows the standard lifecycle.


Prototype Scope Nuances

If a bean is annotated with `@Scope("prototype")`, two major things change in its lifecycle:

1. **Inherently Lazy:** Prototype beans are always lazy. The container will never create them on startup.
2. **Handed Over to the Client:** When a prototype bean is requested, Spring creates it, injects dependencies, calls Aware interfaces, and runs initialization callbacks. However, once it is "Ready", **Spring hands the object over to the client and forgets about it.**

Why doesn't Spring manage Prototype destruction? To avoid **Memory Leaks**. If you request a prototype bean 10,000 times, you get 10,000 distinct objects. If the IoC container kept track of all of them to trigger `@PreDestroy` later, the Garbage Collector could never clean them up (because Spring still holds a reference to them). Your Heap Memory would fill up and crash the application. Therefore, for prototype beans, `@PreDestroy` is **never called by Spring**. It is solely the Java Garbage Collector's job to destroy them.





Bonus: Resolving Circular Dependencies with @PostConstruct

The video concludes with an advanced hack. If `Class A` requires `Class B`, and `Class B` requires `Class A`, using Constructor Injection will result in a `BeanCurrentlyInCreationException` (a circular dependency failure).

While refactoring the code is the best solution, the video demonstrates how `@PostConstruct` can be used to manually resolve this:

1. Remove constructor injection and use empty constructors so both beans can be instantiated freely.
2. Add a standard setter method for the dependency (e.g., `setA(A a)` inside `Class B`).
3. Inside `Class A`, create a method annotated with `@PostConstruct`.
4. Inside that `@PostConstruct` method, manually call `b.setA(this)`.

Because `@PostConstruct` runs *after* both objects exist in memory, the circular loop is bypassed. (Note: The video instructor strictly advises fixing the architecture rather than using this hack in production).

3. Actionable Takeaways

- **Prefer Annotations:** Always use `@PostConstruct` and `@PreDestroy` for lifecycle hooks instead of legacy interfaces like `InitializingBean` or `DisposableBean`. It keeps your code decoupled from Spring-specific imports.
- **Keep Constructors Clean:** Never put heavy lifting, file loading, or complex logic in your class constructors. Use `@PostConstruct` to ensure the object is fully built and dependencies are injected before doing heavy setup.
- **Mind Your Prototypes:** Remember that Spring does not call `@PreDestroy` on `Prototype` scoped beans. If your prototype bean opens a database connection or a file stream, you must manually write logic (like a `try-with-resources` block) to close it, or you will leak resources.
- **Dependency Injection Timing Matters:** Understand that Field and Setter injections happen *after* instantiation. If you try to use an `@Autowired` field inside a constructor, it will result in a `NullPointerException`.
- **Add Jakarta API for Plain Spring:** If you are learning bare Spring Core/Context (not Spring Boot) and `@PostConstruct` isn't working, remember to add the `jakarta.annotation-api` dependency to your `pom.xml`.