

Backend API (homepage map)

One API for v1. Frontend calls it **once** on load, then keeps the JSON in memory. No body, no auth.

Full contract: [API.md](#).

API

```
GET /api/v1/homepage-map/bootstrap?audience=family
```

What the frontend sends

Query only:

Name	Example	Allowed values	Purpose
audience	family	first, family, culture, active, budget	First-paint pin order and matchline. Default if omitted: family .

Do **not** rank-only for that audience. Still return **fits** for **all five** audiences so a preference tap does not need another request.

What the backend returns

JSON. Production: all countries in the homepage slice (today 6), ≤ 8 cities each, ≤ 4 attractions, ≤ 3 products. Example below is **two countries** and **one city / one attraction / one product**.

```
{
  "audience": "family",
  "audiences": [
    { "id": "family", "label": "Family", "matchCount": 2 },
    { "id": "culture", "label": "Culture & history", "matchCount": 3 }
  ],
  "matchline": "1 best match and 1 best alternative for family.",
  "camera": { "center": { "lat": 30, "lng": 40 }, "zoom": 2.4 },
  "destinations": [
    {
      "id": "pl",
      "name": "Poland",
      "lat": 52,
      "lng": 19.4,
      "cityId": "krakow",
      "picks": 9,
      "opts": 180,
      "fits": {
        "family": [0, ["Strong family-compatible inventory"], "Compact old
```

```

towns you can walk in an hour.", "Fewer English-language departures than
western Europe."],
  "culture": [1, ["Twentieth-century depth"], "The history is recent
enough that guides can name the buildings.", "Heavier subject matter for
under-12s."]
},
],
{
  "id": "it",
  "name": "Italy",
  "lat": 42.8,
  "lng": 12.6,
  "cityId": "rome",
  "picks": 31,
  "opts": 812,
  "fits": {
    "family": [2, ["Skip-the-line ticket classes"], "Ticket class is
the difference between a great day and a queue.", "August heat pushes good
formats before 10:00."],
    "culture": [0, ["Archaeologist-led access"], "Restricted-area entry
with a specialist.", "Crowds at the icons."]
  }
},
],
"cities": {
  "krakow": {
    "id": "krakow",
    "countryId": "pl",
    "name": "Kraków",
    "lat": 50.0647,
    "lng": 19.945,
    "picks": 9,
    "attractions": [
      {
        "name": "Wawel Castle",
        "category": "Castles & royal sites",
        "lat": 50.054,
        "lng": 19.9354,
        "from": 14,
        "rating": 4.8,
        "reviews": 3420,
        "fits": {
          "family": [0, "Flat courtyards and a 90-minute format."],
          "culture": [0, "Royal apartments with a guide who can date each
rebuild."]
        },
        "products": [
          {
            "title": "Wawel Castle & Cathedral, 90-minute family walk",
            "rating": 4.9,
            "reviews": 1204,
            "duration": "1h 30m",
            "price": 32,
            "why": "Ninety minutes, flat ground, dragon legend before the

```

```

    tombs.",
        "trade": "Skips the Crown Treasury.",
        "snip": "Reviews from travellers with children under 12.",
        "quote": "Short enough that our seven-year-old was still
listening."
    }
  ]
}
}
}
}
}

```

Prices are numbers in **EUR** (no € in JSON). **lat** / **lng** are decimal degrees.

Purpose of each field

Field	Purpose
audiences	Preference chips. matchCount is the badge on the chip.
matchline	Sentence above the map for the requested audience .
camera	Optional first world view. Frontend can also build this from destination lat / lng .
destinations	World pins and the list. lat / lng place the pin. cityId is the default city when they open the country. picks / opts is "9 picks from 180".
fits (country)	[tier , chips , why , tradeOff]. 0 = best match, 1 = best alternative, 2 = also fits, 3 = worth considering. Frontend re-ranks from this when the chip changes. Include every audience, not only the query.
cities	Drill-in tree (country → city → attraction → products). Key = cityId .
attractions	City pins and list. from / rating / reviews show from city level. fits here is [tier , why].
products	Attraction cards: price, duration, why, trade-off, review quote.

After this response, the frontend does not call the API again for zoom or preference.