



ePost Global Shipping Api Documentation

Introduction:

- The ePost Global API uses a cloud portal to access carrier settings and rates, origin and return locations, integration settings, and assigned profile requirements. This will be set up by your ePost Global representative. Postman collections can be provided by request to accelerate development time.

Overview:

- Api Overview -
 - An API is an application programming interface - in short, it is a set of rules that lets programs talk to each other, exposing data and functionality across the internet in a consistent format.
- Type –
 - The APIs follow the principles of the REST architectural style and use HTTP as the underlying protocol. For security, requests use HTTPS. Responses include success or failure messages and any requested resources. Resource objects use JSON formatting.
 - REST stands for Representational State Transfer. This is an architectural pattern that describes how distributed systems can expose a consistent interface. When people use the term 'REST API,' they are generally referring to an API accessed via HTTP protocol at a predefined set of URLs.
 - These URLs represent various resources - any information or content accessed at that location, which can be returned as JSON, HTML, audio files, or images. Often, resources have one or more methods that can be performed on them over HTTP, like GET, POST, PUT and DELETE.



- Headers -
 - Key: Authorization, Value: Bearer {Token}
 - Key: Content-Type, Value: application/json
- Api Environments –
 - The EPG API provides Sandbox and Production environments.
 - Each environment has its own set of base URLs, as listed below. Note that the base URL is just one part of the API call:
 - Production: Base URL - **<https://api.epgparcels.com/>**
 - Sandbox: Base URL - **https://test_api.epgparcels.com/**
 - The Sandbox endpoint is a test environment that is intended for all your development and testing work prior to deployment on Production. Sandbox gives full access to all the API calls available on Production.
- HTTPS Requirement –
 - All API requests must use HTTPS. HTTPS uses Transport Layer Security (TLS) to verify the identity of the accessed API server and to encrypt communications.
- Quota –
 - Quotas are in effect for all the ePost Global APIs endpoints. Quota statistics are returned in the response headers. Quota regenerates at approximately +1/second.
 - **X-Quota-Available**
Remaining Quota after your most recent call was made.
Ex: 9
 - **X-Quota-Controller**
The Api Controller that the request was made against.
Ex: Rate



- **X-Quota-Penalty**

An indication of the amount of quota that will be deducted for each request against the endpoint.

Ex: -1

- **X-Quota-Cost**

The amount of quota that was actually deducted in the request.

Ex: 1

- **X-Quota-Quota**

Total amount of quota available for the Api controller that is tied to the specific endpoint of the request.

Ex: 10

Documentation:

- Sandbox: http://test_api.epgparcels.com/index.html
- Production: <https://api.epgparcels.com/index.html>

Error Handling:

- General-
 - 2XX - Success of some kind.
 - 4XX – An error occurred because of the data submitted in the request.
 - 5XX – An unexpected internal server error.
- Specific-

Code	Status	Description
200	Success	OK. The request was successful.
201	Success	Created. The request was successful and has resulted in a new resource being created.
204	Success	Request was successful but the server does not need to return a body in the response.
400	Failure	Bad Request. The request could not be interpreted by the server to due an issue with the submitted data. The request should not be repeated without modifications.



401	Failure	Unauthorized. The credentials submitted in the request are missing or invalid.
403	Failure	Forbidden. Token is not permitted access to the resource despite passing authentication. Usually, a result of the Api quota being exceeded.
404	Failure	Not Found. The server has not found an endpoint that matches the request URL.
500	Failure	Internal Server Error. The server ran into an unexpected condition which prevented it from processing the request.

ePost Global Carrier services:

- Domestic –

Service Code	Product Code	Service Name
EP03	10	EP03 - EPG Domestic Priority Parcel
EP05	45	EP45 – EPG Domestic eDGE

- International –

Service Code	Product Code	Service Name
EP60	29	EPG First Class Parcels International
EP80	21	EPG Expedited Parcel with DC Duties Paid
EP70	07	EPG Priority Parcel with DC
EP81	22	EPG Expedited with DC
EP71	01	EPG Priority Parcel with DC Duties Paid
EP82	08	EPG Courier Service
EP72	09	EPG Priority Parcel no DC
EP83	03	EPG Courier Service Duties Paid



EP73	05	EPG Priority Parcel no DC Duties Paid
EP84	12	EPG PMI Service
EP74	04	EPG Economy Parcel Service
EP85	24	EPG PMI DDP
EP76	11	EPG ePacket Service
EP86	13	EPG PMEI
EP77	23	EPG ePacket DDP
EP87	34	EPG PMEI DDP
EP78	25	EPG Priority Packet DDU
EP90	02	EPG IPA Service
EP92	06	EPG ISAL Service
EP50	50	EPG Canada Edge
EP46	46	EPG Canada Returns

Rating/Shipping:

- POST /api/v1/rate
- POST /api/v1/ship
- Elements –
 - **“serviceCode”**
 - **“recipient”** object
 - **“from”** object
 - **“package”** object
 - **“customs”** object
 - **“items”** array

Rating/Shipping Fields:

- **“serviceCode”**
 - String
 - maxLength: 4
 - Required



- The EPG Service Code (see above section) to be used to process the shipment.
- **“referenceld”**
 - String
 - maxLength: 60
 - Optional reference field
- **“subAccount”**
 - String
 - maxLength: 20
 - Not required unless previously set up by an ePost Global representative
- **“labelFormat”**
 - String
 - maxLength: 3
 - Should be set to “PNG” or “ZPL”
 - Required
- **“skipValueAddedTaxValidation”**
 - Boolean
 - Required for shipments to the European Union and United Kingdom if the below **“valueAddedTaxInformation”** object is not utilized.
- **“valueAddedTaxInformation”** object
 - **“vatNumber”**
 - String
 - maxLength: 30
 - Required for shipments to the European Union and United Kingdom if the above **“skipValueAddedTaxValidation”** boolean is omitted or set to False.
 - **“taxType”**
 - Numeric
 - Submit **0** for a VAT Number and **1** for an IOSS Number
 - Required for shipments to the European Union and United Kingdom if the above **“skipValueAddedTaxValidation”** boolean is omitted or set to False.



- **“issuerCountry”**
 - String
 - maxLength: 3
 - Field is for the issuer country of the respective VAT or IOSS number.
- Address Fields
 - “recipient” object
 - **“company”**
 - String
 - maxLength: 50
 - Optional
 - **“name”**
 - String
 - maxLength: 50
 - Required
 - **“address1”**
 - String
 - maxLength: 50
 - Required
 - **“address2”**
 - String
 - maxLength: 50
 - Optional
 - **“address3”**
 - String
 - maxLength: 50
 - Optional
 - **“city”**
 - String
 - maxLength: 50



- Required
- **“postalCode”**
 - String
 - maxLength: 10
 - Required
- **“stateOrProvince”**
 - String
 - maxLength: 20
 - Not required for international
 - Required for domestic
- **“countryCode”**
 - String
 - maxLength: 2
 - Required
- **“countryName”**
 - String
 - maxLength: 30
 - Optional
- **“phone”**
 - String
 - maxLength: 20
 - Not required
- **“email”**
 - String
 - maxLength: 50
 - Not required
- **“from” object**
 - **“company”**
 - String
 - maxLength: 50
 - Required




- **“address1”**
 - String
 - maxLength: 50
 - Required
- **“address2”**
 - String
 - maxLength: 50
 - Not required
- **“city”**
 - String
 - maxLength: 50
 - Required
- **“postalCode”**
 - String
 - maxLength: 10
 - Required
- **“stateOrProvince”**
 - String
 - maxLength: 20
 - Not required
- **“countryCode”**
 - String
 - maxLength: 2
 - Required
- **“countryName”**
 - String
 - maxLength: 30
 - Optional
- **“phone”**
 - String



- maxLength: 20
 - Not required
- **“email”**
 - String
 - maxLength: 50
 - Not required
- “package” fields
 - **“reference1”**
 - String
 - maxLength: 50
 - Optional
 - At least one reference is recommended as a secondary reference point on the package.
 - **Note:** Any reference1 value less than or equal to 22 characters will generate a scannable barcode on EPG labels for the following services:
 - EP03 - EPG Domestic Priority Parcel
 - EP05 - EPG Domestic eDGE
 - EP70 - EPG Priority Parcel With DC
 - EP71 - EPG Priority Parcel With DC Duties Paid
 - EP72 - EPG Priority Parcel No DC
 - EP73 - EPG Priority Parcel No DC Duties Paid
 - EP74 - EPG Economy Parcel Service
 - EP78 - EPG Priority Packet DDU
 - EP80 - EPG Expedited Parcel With DC Duties Paid
 - EP81 - EPG Expedited Parcel With DC
 - EP82 - EPG Courier Service
 - EP83 - EPG Courier Service Duties Paid
 - Ex:



Customer Reference 1



ref1BarcodeValue

- If you would like a reference printed without a barcode, then the reference1 value should be greater than or equal to 23 characters.
- Ex:

Customer Reference 1

0000000ref1BarcodeValue

- **“reference2”**
 - String
 - maxLength: 50
 - Optional
- **“reference3”**
 - String
 - maxLength: 50
 - Optional
- **“currencyCode”**
 - String
 - maxLength: 3
 - Required
- **“value”**
 - String, Numeric
 - maxLength: 29
 - Required



- **“weight”**
 - String, Numeric
 - Required
- **“dimensions” object**
 - **“length”, “width”, “height”**
 - String, Numeric
 - Optional
 - Each dimension must be less 999.99
- **“customs” object**
 - **“description”**
 - String
 - maxLength: 100
 - Required
 - **“signer”**
 - String
 - maxLength: 50
 - Optional
 - **“itemCategory”**
 - String
 - maxLength: 30
 - Optional
 - **“itemCategoryOtherDescription”**
 - String
 - Optional
 - **“consigneeTaxId”**
 - String
 - maxLength: 50
 - Optional
 - Primary purpose of this field is for shipments to Brazil.
 - **“customerPaidTaxes”**
 - String, Numeric



- maxLength: 29
- Optional
- **“customerPaidDuties”**
 - String, Numeric
 - maxLength: 29
 - Optional
- “items” array
 - **“quantity”**
 - String, Numeric
 - maxLength: 10
 - Required for Shipping
 - Optional for Rating
 - **“code”**
 - String
 - maxLength: 20
 - Required
 - **“name”**
 - String
 - maxLength: 50
 - Required for Shipping
 - Optional for Rating
 - **“value”**
 - String, Numeric
 - maxLength: 29
 - Required
 - **“hsCode”**
 - String
 - maxLength: 20
 - Required
 - **“weight”**
 - String, Numeric



- maxLength: 6
 - **“originManufactureCountry”**
 - String
 - maxLength: 2
 - Required
- Voiding:
 - GET /api/v1/Ship/{id}/Void
 - The "uniqueReferenceId" that gets returned in the POST /api/v1/Ship response should be passed into the “id”

- Closing:
 - GET /api/v1/Ship/Close
 - Returns the account number and number of active/unclosed packages
 - Sample response

```
1  {
2    {
3      "accountNumber": "12345",
4      "packageCount": 1
5    }
6  }
```

- POST /api/v1/Ship/Close?accountNumber={accountNumber}
 - Actually, processes the close for the specified account number.
 - Returns the “closeId” and “closeReports”

Change Log:

Date	Description of changes
2024-08-20	Initial File Created
2024-09-25	Service Code/Field Updates