

Signal Processing Laboratory

The **Signal Processing Laboratory** serves as a vital bridge between theoretical engineering principles and real-world technological innovation. Designed for undergraduate, postgraduate, and research students, this facility focuses on the **acquisition, analysis, manipulation, and transformation** of dynamic real-world signals. Through an optimal mix of software simulations and hardware implementations, the lab equips students with the skills needed to solve complex engineering challenges in **telecommunications, medical imaging, automation, and audio-visual technologies**.

🎯 Key Objectives

- **Bridge Theory and Practice:** Validate textbook mathematical algorithms using hands-on computational tools and physical circuits.
- **Master System Analysis:** Analyze Linear Time-Invariant (LTI) systems and evaluate spectral characteristics using Fourier and Z-transforms.
- **Design Advanced Filters:** Develop, simulate, and implement finite impulse response (FIR) and infinite impulse response (IIR) digital filters.
- **Real-Time Implementation:** Program dedicated hardware boards to process streaming audio, video, and biometric data in real time.

🔧 Lab Facilities & Infrastructure

The laboratory provides a modern computational environment featuring advanced hardware and standard industry software toolchains:

Resource Type	Available Equipment & Software	Primary Use Case
Computing Hardware	High-performance workstations & Digital Storage Oscilloscopes	System simulation, debugging, and visual signal analysis
Hardware Kits	Texas Instruments TMS320C6xxx DSP Boards & PLD systems	Real-time algorithm testing and embedded system synthesis
Software Suites	MATLAB, Code Composer Studio (CCS) IDE, and Python	Code development, windowing, filter design, and spectral analysis
Peripheral Modules	CCD Cameras, biometric sensors, and functional generators	Image acquisition, noise reduction, and signal modulation


🚀 Core Application & Research Areas

- **Telecommunications:** Waveform generation, channel equalization, and wireless modulation techniques.
- **Biomedical Engineering:** Preprocessing and feature extraction for neural (EEG) and cardiac (ECG) monitoring systems.
- **Audio & Speech Processing:** Acoustic noise cancellation, voice recognition, and digital audio effect applications.
- **Image & Video Processing:** Data compression algorithms, object recognition, and high-dynamic-range (HDR) image sharpening.

Equipment Overview


DSP Starter KIT: TMS320C6416T

The **TMS320C6416T DSP Starter Kit (DSK)** is a low-cost, all-in-one hardware and software development platform designed by Texas Instruments and Spectrum Digital. It allows engineers and researchers to prototype and evaluate high-performance digital signal processing applications based on the **TMS320C64x fixed-point DSP generation**.



DSP Starter KIT: TMS320C6748

The **TMS320C6748 DSP Development Kit**, commonly referred to as the **Low-Cost Development Kit (LCDK)**, is a high-performance evaluation platform designed by [Texas Instruments](https://www.ti.com). It serves as an accessible hardware and software sandbox for engineers, students, and researchers working on real-time signal processing, embedded analytics, biometrics, and high-fidelity audio engineering.



DSP Processor Trainer Kit: TM5320C6713

The **TMS320C6713 DSP Starter Kit (DSK)**—often referred to as the **TMS320C6713 Development Kit**—is a highly popular, low-cost evaluation platform designed by Texas Instruments and Spectrum Digital. It is built around a high-performance **floating-point digital signal processor**, making it an industry and academic standard for teaching real-time audio processing, filter design, and control systems.



Digital Signal Oscilloscope:

A **Digital Storage Oscilloscope (DSO)** is an essential electronic test instrument used to capture, visualize, analyze, and store electrical signals over time. Unlike older analog oscilloscopes that use a cathode-ray tube to display waveforms directly, a DSO converts electrical voltages into digital data using an Analog-to-Digital Converter (ADC) and displays them on a digital screen.



Mixed Signal Oscilloscope:

A **Mixed Signal Oscilloscope (MSO)** is a hybrid electronic test instrument that combines the detailed analog visualization of a Mixed Domain or Digital Storage Oscilloscope (DSO) with the multi-channel digital timing capabilities of a **logic analyzer**. It allows engineers to view and analyze both analog waveforms and digital logic signals simultaneously on a single screen, perfectly synchronized to a single timebase.




Waveform/Signal Generator:

A **Waveform Generator** (frequently called a **Signal Generator** or **Function Generator**) is an essential electronic test instrument used to inject precise, predictable electrical voltages into a circuit. While an oscilloscope *listens* to a circuit to display signals, a waveform generator *talks* to a circuit by sourcing controlled electrical stimuli to test its behavior, verify its design, or discover faults.




Thermal Printer:

A **Thermal Printer** is a digital printing instrument that uses heat instead of liquid ink or toner ribbon to produce text and images on paper. Because they contain fewer moving parts and do not require ink cartridge refills, thermal printers are highly reliable, low-maintenance, and widely used in commercial, logistics, and retail spaces.




Spectrum Analyzer:

A **Spectrum Analyzer** is a sophisticated electronic test instrument used to visualize and analyze the strength of electrical signals across a range of frequencies. While an oscilloscope displays signals in the **time domain** (Voltage vs. Time), a spectrum analyzer translates signals into the **frequency domain** (Amplitude vs. Frequency), allowing engineers to look at individual frequency components that make up a complex signal.




ARM Cortex M3 kit: LPC1768

The **LPC1768 evaluation and evaluation kit** is a popular hardware development platform built around an **ARM Cortex-M3 microcontroller** manufactured by NXP Semiconductors. It serves as a robust sandbox for engineers, embedded students, and firmware developers to prototype and evaluate real-time applications such as industrial automation, automotive electronics, and connected IoT systems.




Educational Practice board for TMS320C6748:

The **Educational Practice Board (EPB) for the TMS320C6748** is a specialized, all-in-one laboratory trainer kit designed for universities, technical institutions, and engineering labs. Built as an educational alternative to standard industrial hardware, this platform expands on the native [Texas Instruments TMS320C6748 floating-point DSP architecture](#) by populating the board with heavy-duty user interfaces, multimedia connectors, and diagnostic tools to help students master real-time signal, audio, and image processing.




Finger Print Sensor interfacing kit:

A **Fingerprint Sensor Interfacing Kit** is a hardware development bundle designed to teach developers, students, and engineers how to integrate biometric authentication into embedded applications. The kit centers around a self-contained biometric module (such as the widely used R307 Optical Sensor or [AS608 Module](#)) paired with a host microcontroller development board.



General Purpose IO Board:

A **General Purpose Input/Output (GPIO) Board** (frequently called a **GPIO Expansion Board** or **Breakout Board**) is a hardware accessory designed to extend, protect, and distribute the digital control pins of a primary computing host like a microcontroller, Single Board Computer (SBC), or automated industrial controller [sparkfun.com]. It bridges sensitive processing cores with real-world physical electronics like switches, sensors, relays, and indicators.




RFID Interfacing Kit:

An **RFID (Radio Frequency Identification) Interfacing Kit** is a hardware development bundle designed to teach engineers, students, and makers how to implement wireless tracking, access control, and asset identification systems. The kit typically pairs a popular RFID reader module—such as the low-cost **RC522 (13.56 MHz HF)** or **EM-18 (125 kHz LF)**—with a host microcontroller and a variety of transponder tags.



WIFI Module: RN174

The **RN174 WiFly GSX Super Module** (marketed under [Microchip Technology](#) following their acquisition of Roving Networks) is a field-ready, Wi-Fi Alliance-certified **802.11 b/g wireless prototyping board**. Rather than being just a bare IC, the RN174 serves as a comprehensive **development evaluation platform built around the core RN-171 Wi-Fi module**, designed specifically to add networking capabilities to low-power embedded designs without forcing engineers to rewrite extensive hardware



Zigbee interfacing kit:

A **Zigbee Interfacing Kit** is a hardware development bundle designed to teach developers, engineers, and students how to implement low-power, short-range **wireless mesh networking**. The kit typically pairs popular Zigbee modules—such as the industry-standard **Digi XBee (Series 2 or 3)** or **TI CC2530**—with interfacing breakout boards, transceivers, and host microcontrollers.

