

The ShorTeX package

Trevor Campbell, Jonathan Huggins, and Jeff Negrea

Updated April 26, 2023

Abstract

The purpose of the ShorTeX (meta)package is to make the process of typesetting typical mathematical documents in L^AT_EX more efficient, and the resulting code easier to read. It achieves this by (1) providing an extensive, internally consistent, and easy to learn set of macro shorthands and custom commands, and (2) incorporating a set of packages that are dedicated to reducing manual coding effort.

Contents

| | | |
|----------|--|-----------|
| 1 | Usage and package options | 2 |
| 2 | Shorthands for existing commands | 2 |
| 2.1 | Environments | 2 |
| 2.2 | Delimiters | 3 |
| 2.3 | Font styles and accents | 4 |
| 2.4 | Greek characters and variants | 6 |
| 2.5 | Referencing figures, equations, tables, etc. | 6 |
| 2.6 | Automatic equation numbers | 7 |
| 3 | Custom macros | 7 |
| 3.1 | Shrinking whitespace in math | 7 |
| 3.2 | Wide bar | 8 |
| 3.3 | Commenting | 8 |
| 3.4 | Sets and set operations | 9 |
| 3.5 | Linear algebra | 9 |
| 3.6 | Calculus | 10 |
| 3.7 | General mathematics | 10 |
| 3.8 | Common words and names with accents | 11 |
| 3.9 | Probability and statistics | 11 |
| 3.10 | Vector spaces and operators | 12 |
| 3.11 | Paired delimiters | 13 |
| 4 | Example Document | 14 |

1 Usage and package options

Include ShorTeX by adding `\usepackage{shortex}` to the preamble of your document. ShorTeX will include and configure many common packages for you (e.g., `graphicx`, `subcaption`, `hyperref`, `algorithm`, `algpseudocode`, `amsmath`, among others), so you do not need to explicitly include and set these up yourself. If you are writing a document that must use a specific style file (e.g., for a conference or journal) that itself includes some of these packages, we recommend editing those style files to remove the package imports.

The ShorTeX package has a few options:

manualnumbering Do not include `autonum.sty`. This disables automatic equation numbering.

blackhypersetup Switch hyperlinks, citations, references, etc. to be typeset in black font. The default is dark blue.

You must compile your document 4 times when using ShorTeX to ensure that equation numbers and references update properly.

2 Shorthands for existing commands

2.1 Environments

L^AT_EX documents often includes a lot of verbose code related to creating environments (`\begin{blah}...\end{blah}`). ShorTeX provides a set of shortened macros for common environments. Note that all theorem-like environments (theorem, lemma, proposition, etc.) are numbered by default; unnumbered versions can be obtained by appending a `u`. For example, `\bthmu...\ethmu` creates an unnumbered theorem environment, while `\blemu...\elemu` creates an unnumbered lemma environment.

| Environment | Syntax |
|--|--|
| abstract | <code>\babs...\eabs</code> |
| itemize | <code>\bitems...\eitems</code> |
| enumerate | <code>\benum...\eenum</code> |
| description | <code>\bdesc...\edesc</code> |
| algorithm | <code>\balg...\ealg</code> |
| algorithmic | <code>\balgc...\ealgc</code> |
| table | <code>\btab...\etab</code> |
| subtable | <code>\bsubtab...\esubtab</code> |
| tabular | <code>\btabr...\etabr</code> |
| figure | <code>\bfig...\efig</code> |
| figure* | <code>\bfigs...\efigs</code> |
| subfigure | <code>\bsubfig...\esubfig</code> |
| center | <code>\bcent...\ecent</code> |
| align | <code>\[...\]</code> |
| inline math | <code>\$_...\$_</code> |
| <i>Note: These are numbered theorem-like environments. For unnumbered, append a u: e.g., <code>bthmu...ethmu</code>.</i> | |
| theorem | <code>\bthm...\ethm</code> |
| lemma | <code>\blem...\elem</code> |
| proposition | <code>\bprop...\eprop</code> |
| corollary | <code>\bcor...\ecor</code> |
| conjecture | <code>\bconj...\econj</code> |
| definition | <code>\bdef...\edef</code> |
| assumption | <code>\bassump...\eassump</code> |
| example | <code>\bexa...\eexa</code> |
| remark | <code>\brmk...\ermk</code> |
| fact | <code>\bfact...\efact</code> |
| exercise | <code>\bexer...\eexer</code> |
| proof | <code>\bprf...\eprf</code> |
| proofof | <code>\bprfof{\cref{theorem_label}}...\eprfof</code> |
| matrix | <code>\bmat...\emat</code> |
| bmatrix | <code>\bbmat...\ebmat</code> |
| pmatrix | <code>\pmat...\epmat</code> |

2.2 Delimiters

Mathematics in L^AT_EX often includes quite a few delimiters (parentheses, brackets, curly brackets, etc.). A very common usage of these involves the `\left...\right` commands for automatic sizing. One can also use `\bigl...\bigr`, `\Bigl...\Bigr`, `\biggl...\biggr`, `\Biggl...\Biggr` to control sizing manually. ShorTeX cre-

ates shorthands for these.

| Description | Syntax |
|-------------|--------------------------|
| automatic | <code>\lt...\rt</code> |
| big | <code>\lb...\rb</code> |
| Big | <code>\lB...\rB</code> |
| bigg | <code>\lbg...\rbg</code> |
| Bigg | <code>\lBg...\rBg</code> |

These can be applied to all the usual delimiter characters. The following tables demonstrate usage for automatically sized delimiters.

| Description | Example | Text style | Display style |
|-----------------|--|--|--|
| parentheses | <code>\lt(\frac{x}{y}\rt)</code> | $\left(\frac{x}{y}\right)$ | $\left(\frac{x}{y}\right)$ |
| curly brackets | <code>\lt\{\frac{x}{y}\rt\}</code> | $\left\{\frac{x}{y}\right\}$ | $\left\{\frac{x}{y}\right\}$ |
| square brackets | <code>\lt[\frac{x}{y}\rt]</code> | $\left[\frac{x}{y}\right]$ | $\left[\frac{x}{y}\right]$ |
| pipes | <code>\lt \frac{x}{y}\rt </code> | $\left \frac{x}{y}\right $ | $\left \frac{x}{y}\right $ |
| double pipes | <code>\lt\ \frac{x}{y}\rt\ </code> | $\left\ \frac{x}{y}\right\ $ | $\left\ \frac{x}{y}\right\ $ |
| angle brackets | <code>\lt<\frac{x}{y}\rt></code> | $\left\langle\frac{x}{y}\right\rangle$ | $\left\langle\frac{x}{y}\right\rangle$ |

2.3 Font styles and accents

Applying accents (e.g., hats \hat{a} , tildes \tilde{a} , bars \bar{a}) and changing fonts (e.g., double-stroke \mathbb{A} , calligraphic \mathcal{A} , and bold \mathbf{A}) is quite cumbersome in standard L^AT_EX. For example, the code to make a tilde calligraphic A, $\tilde{\mathcal{A}}$ is `\widetilde{\mathcal{A}}`. By itself that code is not too bad, but many such characters in a large mathematical expression results in unreadable code.

ShorTeX defines an efficient syntax for changing fonts and applying accents to characters. The syntax takes the form `\f[modifiers]character`, where **modifiers** is a set of single characters that represent font/accent modifications to **character**. For example, the code for tilde calligraphic A is `\f[tc]A` where **t** represents “tilde,” **c** represents “calligraphic,” and **A** is the character to typeset.

Note: modifiers are applied in the reverse of the order in which they appear; the modifier furthest to the right is applied first. This matches the order that the corresponding commands would appear in TeX code.

| Style/Accent | Modifier | Example | Typeset Example |
|---------------------------------------|----------------|---------------------|-----------------|
| caligraphic (<code>\mathcal</code>) | <code>c</code> | <code>\f[c]A</code> | \mathcal{A} |
| bold (<code>\mathbf</code>) | <code>k</code> | <code>\f[k]A</code> | \mathbf{A} |
| doublestroke (<code>\mathbb</code>) | <code>d</code> | <code>\f[d]A</code> | \mathbb{A} |
| hat (<code>\widehat</code>) | <code>h</code> | <code>\f[h]A</code> | \widehat{A} |
| tilde (<code>\widetilde</code>) | <code>t</code> | <code>\f[t]A</code> | \widetilde{A} |
| bar (<code>\widebar</code>) | <code>b</code> | <code>\f[b]A</code> | \widebar{A} |

These style modifiers can be combined; the underlying code is flexible enough that it will happily produce a wide variety of combinations, including those that aren't very sensible.

| Style/Accent | Modifier | Example | Typeset Example |
|-------------------|-----------------|----------------------|---------------------------|
| caligraphic tilde | <code>ct</code> | <code>\f[ct]A</code> | $\widetilde{\mathcal{A}}$ |
| bold hat | <code>kh</code> | <code>\f[kh]A</code> | $\widehat{\mathbf{A}}$ |
| hat tilde | <code>ht</code> | <code>\f[ht]A</code> | $\widetilde{\widehat{A}}$ |
| tilde hat | <code>th</code> | <code>\f[th]A</code> | $\widehat{\widetilde{A}}$ |

We can avoid typing `[]` for commonly used patterns by parsing the font style string in advance. For example, if we use “bold hat” symbols frequently, we might want to use commands like `\fkh...` instead of `\f[kh]...`. We can accomplish this using the `\parsefontstylestrings` command, with syntax

```
\parsefontstylestrings{<fstr1>}{<fstr2>...}{<alphabet>}
```

For example, to define “bold hat” and “caligraphic hat” styles for the characters A, B, C, and D, we would use the command

```
\parsefontstylestrings{{kh}{ch}}{ABCD}
```

and then in the \LaTeX document, use the commands `\fkhA` `\fkhB` `\fkhC` `\fkhD` and `\fchA` `\fchB` `\fchC` `\fchD` to obtain the following symbols:

$$\widehat{\mathbf{A}}\widehat{\mathbf{B}}\widehat{\mathbf{C}}\widehat{\mathbf{D}}\widehat{\mathcal{A}}\widehat{\mathcal{B}}\widehat{\mathcal{C}}\widehat{\mathcal{D}}$$

As another example, for “bold hat” applied to α , β , and γ , we would use the syntax

```
\parsefontstylestrings{{kh}}{\alpha\beta\gamma}
```

and then in the \LaTeX document, use the commands `\fkhalpha` `\fkhhbeta` `\fkhhgamma` to obtain the following symbols:

$$\widehat{\mathbf{\alpha}}\widehat{\mathbf{\beta}}\widehat{\mathbf{\gamma}}$$

For convenience we also provide a few common alphabets of symbols for use in the `\parsefontstylestrings` command. Note that not every Greek character has an uppercase version (in cases where it is identical to its Roman counterpart).

| Syntax | Characters |
|------------------------------|---|
| <code>\lowercaseRoman</code> | abcdefghijklmnopqrstuvwxyz |
| <code>\uppercaseRoman</code> | ABCDEFGHIJKLMNOPQRSTUVWXYZ |
| <code>\lowercaseGreek</code> | alpha,beta,gamma,delta,epsilon,zeta,eta,theta iota,kappa,lambda,mu,nu,xi,omicron,pi,rho sigma,tau,upsilon,phi,chi,psi,omega |
| <code>\uppercaseGreek</code> | Gamma,Delta,Theta,Lambda,Xi,Pi,Sigma Upsilon,Phi,Psi,Omega |

2.4 Greek characters and variants

ShorTeX defines a number of shorthands for Greek characters and variants.

| Letter | Syntax | Symbol |
|-----------------|----------------------|---------------|
| epsilon | <code>\eps</code> | ϵ |
| upsilon | <code>\ups</code> | υ |
| variant epsilon | <code>\veps</code> | ε |
| variant theta | <code>\vtheta</code> | ϑ |
| variant pi | <code>\vpi</code> | ϖ |
| variant rho | <code>\vrho</code> | ϱ |
| variant sigma | <code>\vsigma</code> | ς |
| variant phi | <code>\vphi</code> | φ |
| variant kappa | <code>\vkappa</code> | \varkappa |

2.5 Referencing figures, equations, tables, etc.

ShorTeX includes the `cleveref` package, which simplifies the process of typesetting references. Use the `\cref` command (or `\Cref` at the beginning of a sentence) to automatically typeset the names of the objects you reference (including properly handling multiple references). For example, if `\label{fig:first}` is applied to the first figure in the document,

In `\cref{fig:first}`, you can see...

would typeset as “In Fig. 1, you can see...” Similarly, if `\label{thm:first}` references a theorem and `\label{second_result}` references a lemma,

`\cref{thm:first,lem:second}` show that...

will typeset as “Theorem 1 and Lemma 2 show that...” This works for many different reference types (Figure, Algorithm, Equation, Table, etc), and can be extended if needed. See the `cleveref` documentation at <https://ctan.org/pkg/cleveref?lang=en> and the homepage at <https://www.dr-qubit.org/cleveref.html> for more information.

2.6 Automatic equation numbers

ShorTeX includes the `autonum` package, which simplifies the process of equation numbering. Typically when you typeset equations, you have to choose between `...\$, \$...\$, \begin{align}...\end{align}, \begin{aligned}...\end{aligned}, \begin{equation}...\end{equation}`, not to mention starred versions of those environments and `\nonumber/\notag` commands, depending on whether/where you want equation numbers,

The `autonum` package automatically decides which equations to provide numbers based on *which equations you reference*. So when using ShorTeX, you only need two commands for math mode: single dollar signs `...\$` for inline math, and `align` environments (redefined in ShorTeX to be `\[...\]`) for display math.¹

For example, if you create the following display math,

```
\[
  a+b = c \label{eq:the_equation}
\]
```

then if you use the command `\cref{eq:the_equation}` somewhere in the document, that equation will automatically be assigned a number. If not, it won't get a number. See the `autonum` package documentation <https://ctan.org/pkg/autonum?lang=en> for more information.

3 Custom macros

3.1 Shrinking whitespace in math

The command `\squish{<frac>}` in math mode enables you to shrink whitespace in mathematics, where `<frac>` represents the fraction of whitespace reduction. Below, the first line is regularly spaced, the second line has `\squish{0.5}`, and the third has `\squish{0.0}`.

$$\begin{aligned} &\sqrt{\frac{1^2}{0.111222}(0.111222 \times 1.111163 + 0.066987^2 \times 0.111222) - 1} = \sqrt{0.111222} \\ &\sqrt{\frac{1^2}{0.111222}(0.111222 \times 1.111163 + 0.066987^2 \times 0.111222) - 1} = \sqrt{0.111222} \\ &\sqrt{\frac{1^2}{0.111222}(0.111222 \times 1.111163 + 0.066987^2 \times 0.111222) - 1} = \sqrt{0.111222} \end{aligned}$$

The code for `\squish` was taken from <https://tex.stackexchange.com/questions/467942/how-to-squeeze-a-long-equation>.

¹There are differences between how `align` and other math display environments typeset equations. I have not ever encountered a case where it mattered much. If you are very picky about typesetting, note that ShorTeX does not *disable* any functionality, so you can use other environments anywhere you feel it is necessary.

3.2 Wide bar

ShorTeX provides the `\widebar` command to typeset a wide bar accent on top of a character (similar to the usual `\widehat` and `\widetilde` commands). Compare to the usual `\bar` and `\overline` commands:

widebar: $\overline{\overline{A}}$ overline: \overline{A} bar: \bar{A}

The code for `\widebar` was taken from <https://tex.stackexchange.com/questions/16337/can-i-get-a-widebar-without-using-the-mathabx-package>.

3.3 Commenting

ShorTeX defines two types of comments that can be used (*remarks* and *problems*), and provides an inline and margin style for each. This is a lightweight alternative to some more common todo packages (e.g., `todonotes`).

| Comment Type | Syntax |
|----------------|--|
| remark | <code>\RMK{Example remark}</code> |
| margin remark | <code>\mRMK{Example margin remark}</code> |
| problem | <code>\PRB{Example problem}</code> |
| margin problem | <code>\mPRB{Example margin problem}</code> |

Here is an example of how these look in a typical paragraph:

Lorem ipsum dolor sit amet (!) Here is an inline remark, consectetur adipiscing elit, sed do eiusmod tempor incididunt ut labore et dolore magna aliqua. Ut enim ad minim veniam, quis nostrud exercitation (!!)

Here is an inline problem ullamco laboris nisi ut aliquip ex ea commodo consequat. Duis aute irure dolor in reprehenderit in ⁽¹⁾ voluptate velit esse cillum dolore eu fugiat nulla pariatur. Excepteur sint occaecat ⁽²⁾ cupidatat non proident, sunt...

(1) Here is a margin remark
 ((2)) Here is a margin problem

You can also disable all comments to see the clean version of the current document using the `\suppresscomments` command.

3.4 Sets and set operations

| Name | Syntax | Symbol |
|----------------------|---|-------------------------|
| reals | <code>\reals</code> | \mathbb{R} |
| extended reals | <code>\extreals</code> | $\overline{\mathbb{R}}$ |
| rational numbers | <code>\rats</code> | \mathbb{Q} |
| integers | <code>\ints</code> | \mathbb{Z} |
| natural numbers | <code>\nats</code> | \mathbb{N} |
| complex numbers | <code>\comps</code> | \mathbb{C} |
| measures | <code>\measures</code> | \mathcal{M} |
| probability measures | <code>\pmeasures</code> | \mathcal{M}_1 |
| (big) intersection | <code>\intersect</code> , <code>\Intersect</code> | \cap , \bigcap |
| (big) union | <code>\union</code> , <code>\Union</code> | \cup , \bigcup |
| (big) disjoint union | <code>\djunion</code> , <code>\djUnion</code> | \sqcup , \bigsqcup |
| volume | <code>\vol</code> | vol |
| diameter | <code>\diam</code> | diam |
| boundary | <code>\boundary</code> | ∂ |
| closure | <code>\closure</code> | cl |
| span | <code>\spann</code> | span |
| cone | <code>\cone</code> | cone |
| convex hull | <code>\conv</code> | conv |

3.5 Linear algebra

| Name | Syntax | Symbol |
|-------------------|-----------------------|------------------|
| trace | <code>\tr A</code> | $\text{tr } A$ |
| rank | <code>\rank A</code> | $\text{rank } A$ |
| transpose | <code>A\T</code> | A^\top |
| inverse transpose | <code>A\nT</code> | $A^{-\top}$ |
| diagonal | <code>\diag A</code> | $\text{diag } A$ |
| adjoint | <code>A\adj</code> | A^\dagger |
| spectrum | <code>\spec A</code> | σA |
| kronecker product | <code>A\kron B</code> | $A \otimes B$ |

3.6 Calculus

| Name | Syntax | Symbol |
|-------------------------------|------------------------------|--|
| differential symbol | <code>\dee x</code> | dx |
| gradient symbol | <code>\grad f</code> | ∇f |
| derivative | <code>\der{x}{y}</code> | $\frac{dx}{dy}$ |
| double derivative | <code>\dder{x}{y}</code> | $\frac{d^2x}{dy^2}$ |
| derivative w.r.t. | <code>\derwrt{y}</code> | $\frac{d}{dy}$ |
| partial derivative | <code>\pder{x}{y}</code> | $\frac{\partial x}{\partial y}$ |
| partial double derivative | <code>\pdder{x}{y}</code> | $\frac{\partial^2 x}{\partial y^2}$ |
| partial derivative coordinate | <code>\pderi{x}{y}{i}</code> | $\frac{\partial^i x}{\partial y^i}$ |
| partial derivative w.r.t. | <code>\pderwrt{y}</code> | $\frac{\partial}{\partial y}$ |
| Hessian | <code>\hess{a}{x}{y}</code> | $\frac{\partial^2 a}{\partial x \partial y}$ |

3.7 General mathematics

| Name | Syntax | Symbol |
|---------------------|-------------------------------------|--|
| argmax | <code>\argmax_{x \in \reals}</code> | $\arg \max_{x \in \mathbb{R}}$ |
| argmin | <code>\argmin_{x \in \reals}</code> | $\arg \min_{x \in \mathbb{R}}$ |
| esssup | <code>\esssup_{x \in \reals}</code> | $\operatorname{ess\,sup}_{x \in \mathbb{R}}$ |
| essinf | <code>\essinf_{x \in \reals}</code> | $\operatorname{ess\,inf}_{x \in \mathbb{R}}$ |
| indicator | <code>\ind[x=3]</code> | $1[x = 3]$ |
| sign | <code>\sgn x</code> | $\operatorname{sgn} x$ |
| scientific notation | <code>\scin{3}{5}</code> | 3×10^5 |
| such that | <code>\st</code> | : |
| given | <code>\given</code> | |
| defined as | <code>\defas</code> | \coloneqq |
| defines | <code>\defines</code> | \colonequals |
| half | <code>\half</code> | $1/2$ |
| third | <code>\third</code> | $1/3$ |
| quarter | <code>\quarter</code> | $1/4$ |

3.8 Common words and names with accents

| Syntax | Symbol |
|------------------------|----------|
| <code>\cadlag</code> | càdlàg |
| <code>\Frechet</code> | Fréchet |
| <code>\Gronwall</code> | Grönwall |
| <code>\Holder</code> | Hölder |
| <code>\Ito</code> | Itô |
| <code>\Levy</code> | Lévy |
| <code>\Matern</code> | Matérn |
| <code>\Nystrom</code> | Nyström |
| <code>\Renyi</code> | Rényi |
| <code>\Schatten</code> | Schatten |

3.9 Probability and statistics

| Name | Syntax | Symbol |
|-----------------------------|--|--|
| i.i.d. | <code>\iid</code> | i.i.d. |
| almost sure | <code>\as</code> | a.s. |
| almost everywhere | <code>\aev</code> | a.e. |
| convergence almost surely | <code>\convas</code> | $\xrightarrow{a.s.}$ |
| convergence in probability | <code>\convp</code> | \xrightarrow{p} |
| convergence in distribution | <code>\convd</code> | \xrightarrow{d} |
| equality in distribution | <code>\eqd</code> | $\stackrel{d}{=}$ |
| equality almost surely | <code>\eqas</code> | $\stackrel{a.s.}{=}$ |
| probability | <code>\pr</code> | \mathbb{P} |
| expectation | <code>\ex</code> | \mathbb{E} |
| variance | <code>\var</code> | Var |
| covariance | <code>\cov</code> | Cov |
| correlation | <code>\cor</code> | Corr |
| support | <code>\supp</code> | supp |
| distributed as | <code>\dist</code> | \sim |
| distributed i.i.d. | <code>\distiid</code> | $\stackrel{iid}{\sim}$ |
| distributed independently | <code>\distind</code> | $\stackrel{ind}{\sim}$ |
| independent | <code>\indep</code> | \perp |
| Entropy | <code>\ent{q}</code> | $\mathcal{H}(q)$ |
| KL divergence | <code>\kl{q}{p}, \kl[a]{q}{p}</code> | $D_{\text{KL}}(q p), D_{\text{KL}}^a(q p)$ |
| Hellinger distance | <code>\hell{q}{p}, \hell[a]{q}{p}</code> | $D_{\text{H}}(q, p), D_{\text{H}}^a(q, p)$ |
| Total variation distance | <code>\tvd{q}{p}, \tvd[a]{q}{p}</code> | $D_{\text{TV}}(q, p), D_{\text{TV}}^a(q, p)$ |

| Name | Syntax | Symbol |
|--------------------------------------|-----------------------------|----------------|
| Bernoulli | <code>\distBern</code> | Bern |
| beta | <code>\distBeta</code> | Beta |
| beta prime | <code>\distBetaPrime</code> | Beta' |
| binomial | <code>\distBinom</code> | Binom |
| categorical | <code>\distCat</code> | Categorical |
| Cauchy | <code>\distCauchy</code> | Cauchy |
| chi-squared | <code>\distChiSq</code> | χ^2 |
| Dirichlet | <code>\distDir</code> | Dir |
| exponential | <code>\distExp</code> | Exp |
| gamma | <code>\distGam</code> | Gam |
| inverse gamma | <code>\distInvGam</code> | InvGam |
| geometric | <code>\distGeom</code> | Geom |
| Gumbel | <code>\distGum</code> | Gumbel |
| generalized extreme value | <code>\distGEV</code> | GEV |
| Laplace | <code>\distLap</code> | Lap |
| multinomial | <code>\distMulti</code> | Multi |
| normal | <code>\distNorm</code> | \mathcal{N} |
| Poisson | <code>\distPoiss</code> | Poiss |
| student-t | <code>\distT</code> | \mathcal{T} |
| uniform | <code>\distUnif</code> | Unif |
| von Mises-Fisher | <code>\distVMF</code> | vMF |
| Wishart | <code>\distWish</code> | \mathcal{W} |
| inverse Wishart | <code>\distInvWish</code> | \mathcal{IW} |
| Bernoulli process | <code>\distBeP</code> | BeP |
| beta process | <code>\distBP</code> | BP |
| beta prime process | <code>\distBPP</code> | BPP |
| Dirichlet process | <code>\distDP</code> | DP |
| Chinese restaurant process | <code>\distCRP</code> | CRP |
| completely random measure | <code>\distCRM</code> | CRM |
| normalized completely random measure | <code>\distNCRM</code> | NCRM |
| gamma process | <code>\distGamP</code> | Γ P |
| normalized gamma process | <code>\distNGamP</code> | N Γ P |
| Gaussian process | <code>\distGP</code> | GP |
| Pitman-Yor process | <code>\distPYP</code> | PY |
| Poisson process | <code>\distPP</code> | PP |

3.10 Vector spaces and operators

| Description | Syntax | Symbol |
|--|--|---|
| Norm | <code>\norm{\frac{x}{y}}</code> | $\ \frac{x}{y}\ $ |
| Norm with subscript | <code>\normsub*{\frac{x}{y}}{2}</code> | $\left\ \frac{x}{y}\right\ _2$ |
| Inner product | <code>\inner{\frac{x}{y}}{\frac{y}{z}}</code> | $\langle \frac{x}{y}, \frac{y}{z} \rangle$ |
| Inner prod with subscript | <code>\innersub*{\frac{x}{y}}{z}{2}</code> | $\left\langle \frac{x}{y}, z \right\rangle_2$ |
| L^p space | <code>\Lp{2}</code> | L^2 |
| L^p space for specified measure | <code>\Lpm{2}{\mu}</code> | $L^2(\mu)$ |
| | <code>\Lpm*{2}{\mu}</code> | $L^2(\mu)$ |
| | <code>\Lpm[\Big]{2}{\mu}</code> | $L^2(\mu)$ |
| L^p norm | <code>\Lpnorm{\Gamma}{2}</code> | $\ \Gamma\ _{L^2}$ |
| | <code>\Lpnorm*{\Gamma}{2}</code> | $\ \Gamma\ _{L^2}$ |
| | <code>\Lpnorm[\Big]{\Gamma}{2}</code> | $\left\ \Gamma\right\ _{L^2}$ |
| L^p norm for specified measure | <code>\Lpmnorm{\Gamma}{2}{\mu}</code> | $\ \Gamma\ _{L^2(\mu)}$ |
| | <code>\Lpmnorm*{\Gamma}{2}{\mu}</code> | $\ \Gamma\ _{L^2(\mu)}$ |
| | <code>\Lpmnorm[\Big]{\Gamma}{2}{\mu}</code> | $\left\ \Gamma\right\ _{L^2(\mu)}$ |
| L^p inner product | <code>\Lpinner{\Gamma}{\Gamma}{2}</code> | $\langle \Gamma, \Gamma \rangle_{L^2}$ |
| | <code>\Lpinner*{\Gamma}{\Gamma}{2}</code> | $\langle \Gamma, \Gamma \rangle_{L^2}$ |
| | <code>\Lpinner[\Big]{\Gamma}{\Gamma}{2}</code> | $\left\langle \Gamma, \Gamma \right\rangle_{L^2}$ |
| L^p inner product for specified measure | <code>\Lpminner{\Gamma}{\Gamma}{2}{\mu}</code> | $\langle \Gamma, \Gamma \rangle_{L^2(\mu)}$ |
| | <code>\Lpminner*{\Gamma}{\Gamma}{2}{\mu}</code> | $\langle \Gamma, \Gamma \rangle_{L^2(\mu)}$ |
| | <code>\Lpminner[\big]{\Gamma}{\Gamma}{2}{\mu}</code> | $\langle \Gamma, \Gamma \rangle_{L^2(\mu)}$ |

3.11 Paired delimiters

| Description | Example | Text style | Display style |
|-----------------|---|--------------------------------|--------------------------------|
| Round brackets | <code>\rbra{\frac{x}{y}}</code> | $(\frac{x}{y})$ | $(\frac{x}{y})$ |
| Curly brackets | <code>\cbr{*}{\frac{x}{y}}</code> | $\{\frac{x}{y}\}$ | $\{\frac{x}{y}\}$ |
| Square brackets | <code>\sbra[\bigg]{\frac{x}{y}}</code> | $\left[\frac{x}{y}\right]$ | $\left[\frac{x}{y}\right]$ |
| Absolute value | <code>\abs{\frac{x}{y}}</code> | $ \frac{x}{y} $ | $ \frac{x}{y} $ |
| Set | <code>\set{\frac{x}{y}, \frac{y}{z}}</code> | $\{\frac{x}{y}, \frac{y}{z}\}$ | $\{\frac{x}{y}, \frac{y}{z}\}$ |
| Floor | <code>\floor{\frac{x}{y}}</code> | $\lfloor\frac{x}{y}\rfloor$ | $\lfloor\frac{x}{y}\rfloor$ |
| Ceiling | <code>\ceil{\frac{x}{y}}</code> | $\lceil\frac{x}{y}\rceil$ | $\lceil\frac{x}{y}\rceil$ |
| Cardinality | <code>\card{\mathsf{h}A}</code> | $ \hat{A} $ | $ \hat{A} $ |

4 Example Document

TODO: a full example in basic latex versus shortex