

GANs: A New Theory of Representation for **Nonlinear** Bounded Operators

William Guss

Machine Learning at Berkeley

April 22, 2016

Introduction: What's up with continuous data?

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

- **All** of the data we deal with is discrete thanks to Turing.
- But, most of it models a continuous process.
- **Examples**
 - Audio: We take $> 100k$ samples of something we could describe with $f : \mathbb{R} \rightarrow \mathbb{R}$! Trick Question: Which is easier to use? (a) $v \in \mathbb{R}^{100000}$ or (b) f .
 - Images: We take $100k \times 100k$ samples of something we could describe with $f : \mathbb{R}^2 \rightarrow \mathbb{R}$.
- Why do we use discrete data? No computer known can really store f . End of story.

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

The End

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

Jk

Introduction: Abusing continuity

General
Artificial
Neural
Networks


William Guss

Introduction

The Core Idea

Results

- f can't be *that* bad. Can it?
- If f is smooth it's easy to draw:



- I can even name f most of the time: $f : x \mapsto x^2$ or even super precisely $g : x \mapsto \sum_i^\infty a_n x^n$.
- Moral: Smooth functions are mostly very manageable.


Introduction: Abusing continuity

General
Artificial
Neural
Networks


William Guss

Introduction
The Core Idea
Results

- So why do we do this:



- To classify this:



The Core Idea: Let neural
networks abuse continuity
and smoothness.

Artificial Neural Networks

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

From CS189-ish.

Definition

We say $\mathcal{N} : \mathbb{R}^n \rightarrow \mathbb{R}^m$ is a feed-forward neural network if for an input vector \mathbf{x} ,

$$\begin{aligned} \mathcal{N} : \sigma_j^{(l+1)} &= g \left(\sum_{i \in Z^{(l)}} w_{ij}^{(l)} \sigma_i^{(l)} + \beta^{(l)} \right) \\ \sigma_i^{(0)} &= x_i \end{aligned} \tag{1}$$

where $1 \leq l \leq L - 1$. Furthermore we say $\{\mathcal{N}\}$ is the set of all neural networks.

Operator Neural Networks

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

Let's get rid of \mathbb{R}^{100000} and use f .

Definition

We call $\mathcal{O} : L^p(X) \rightarrow L^1(Y)$ an operator neural network if,

$$\begin{aligned}\mathcal{O} : \sigma^{(l+1)}(j) &= g \left(\int_{R^{(l)}} \sigma^{(l)}(i) w^{(l)}(i, j) \, di \right) \\ \sigma^{(0)}(j) &= f(j).\end{aligned}\tag{2}$$

Furthermore let $\{\mathcal{O}\}$ denote the set of all functional neural networks.

Well that was easy. In fact $\{\mathcal{O}\} \supset \{\mathcal{N}\}$

These definitions looks really similar? Is there some more general category or structure containing them.

Generalized Artificial Neural Networks

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

Definition

If A, B are (possibly distinct) Banach spaces over a field \mathbb{F} , we say $\mathcal{G} : A \rightarrow B$ is a generalized neural network if and only if

$$\begin{aligned}\mathcal{G} : \sigma^{(l+1)} &= g \left(T_l \left[\sigma^{(l)} \right] + \beta^{(l)} \right) \\ \sigma^{(0)} &= \xi\end{aligned}\tag{3}$$

for some input $\xi \in A$, and a linear form T_l .

Claim: "Neural networks" are powerful because they can move bumps anywhere!


How? T_l is a linear form. It can move $\sigma^{(l)}$ anywhere, and g is a bump of some sort.

Moving bumps around

- The sigmoid function

$$g = \frac{1}{1 + e^{-x}} \quad (4)$$

is a bump, that we can move around with weights!



T_l as the layer type.

Definition

We suggest several classes of T_l as follows

- T_l is said to be **o** operational if and only if =

$$T_l = \mathbf{o} : L^p(R^{(l)}) \rightarrow L^1(R^{(l+1)})$$
$$\sigma \mapsto \int_{R^{(l)}} \sigma(i) w^{(l)}(i, j) \, di. \quad (5)$$

- T_l is said to be **n** discrete if and only if

$$T_l = \mathbf{n} : \mathbb{R}^n \rightarrow \mathbb{R}^m$$
$$\vec{\sigma} \mapsto \sum_j^m \vec{e}_j \sum_i^n \sigma_i w_{ij}^{(l)} \quad (6)$$

where \vec{e}_j denotes the j^{th} basis vector in \mathbb{R}^m .

T_l as the layer type.

Definition

- T_l is said to be \mathfrak{n}_1 transitional if and only if

$$\begin{aligned} T_l = \mathfrak{n}_1 : \mathbb{R}^n &\rightarrow L^q(R^{(l+1)}) \\ \vec{\sigma} &\mapsto \sum_i^n \sigma_i w_i^{(l)}(j). \end{aligned} \quad (7)$$

- T_l is said to be \mathfrak{n}_2 transitional if and only if

$$\begin{aligned} T_l = \mathfrak{n}_2 : L^p(R^{(l)}) &\rightarrow \mathbb{R}^m \\ \sigma(i) &\mapsto \sum_j^m \vec{e}_j \int_{R^{(l)}} \sigma(i) w_j^{(l)}(i) \, di \end{aligned} \quad (8)$$

Neural networks as diagrams!

This generalization is nice from a creative standpoint.
I can come up with new sorts of "classifiers" on the fly.

Examples:

- A three layer neural network is just

$$\mathcal{N}_3 : \mathbb{R}^{10000} \xrightarrow{g \circ n} \mathbb{R}^{30} \xrightarrow{g \circ n} \mathbb{R}^3. \quad (9)$$

- A three layer operator network is simply

$$\mathcal{O}_3 : L^p(R) \xrightarrow{g \circ o} L^1(R) \xrightarrow{g \circ o} C(R). \quad (10)$$

- We can even classify functions!

$$\mathcal{C} : L^p(R) \xrightarrow{g \circ o} L^1(R) \xrightarrow{g \circ o} \dots \xrightarrow{g \circ o} L^1(R) \xrightarrow{g \circ n_2} \mathbb{R}^n. \quad (11)$$

Results: Did abusing continuity help?

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

For every layer l has weights

$$w^{(l)}(i, j) = \sum_b z_Y^{(l)} \sum_a z_X^{(l)} k_{a,b}^{(l)} i^a j^b. \quad (12)$$

Theorem

Let \mathcal{C} be a GANN with only one n_2 transitional layer with $O(1)$ weight polynomial. If a continuous function, say $f(t)$ is sampled uniformly from $t = 0$, to $t = N$, such that $x_n = f(n)$, and if \mathcal{G} has an input function which is piecewise linear with $O(N^2)$ weights.


$$\xi = (x_{n+1} - x_n)(z - n) + x_n \quad (13)$$

for $n \leq z < n + 1$, then there exist some discrete neural network \mathcal{N} such that $\mathcal{G}(\xi) = \mathcal{N}(\mathbf{x})$.

Results: Did abusing continuity help?

WHAT!?!? How did \mathcal{C} reduce the number of weights from $O(N^2)$ to $O(1)$?

- The infinite dimensional versions of \mathcal{N} , in particular \mathcal{O} and \mathcal{C} are invariant to input quality. Takes the idea behind Convnets to an extreme!
- This is easy to see.



Results: Representation Theory

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

How good are Continuous Classifier Networks, $\{\mathcal{C}\}$ as algorithms?

Theorem

Let X be a compact Hausdorff space. For every $\epsilon > 0$ and every continuous bounded functional on $L^q(X)$, say f , there exists a two layer continuous classifier

$$\mathcal{C} : L^q(X) \xrightarrow{g \circ n_2} \mathbb{R}^m \xrightarrow{n} \mathbb{R}^n \quad (14)$$

such that

$$\|f - \mathcal{C}\| < \epsilon. \quad (15)$$

Results: Representation Theory

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

How good are Operator Networks and GANNs as algorithms? They should be able to approximate the important operators, eg. **Fourier Transform, Laplace Transform, Derivation**, etc.

Theorem

Given a operator neural network \mathcal{O} then some layer $l \in \mathcal{O}$, the let $K : C(R^{(l)}) \rightarrow C(R^{(l)})$ be a bounded linear operator. If we denote the operation of layer l on layer $l - 1$ as $\sigma^{(l+1)} = g(\sum_{l+1} \sigma^{(l)})$, then for every $\epsilon > 0$, there exists a weight polynomial $w^{(l)}(i, j)$ such that the supremum norm over $R^{(l)}$

$$\left\| K\sigma^{(l)} - \sum_{l+1} \sigma^{(l)} \right\|_{\infty} < \epsilon \quad (16)$$

Proof.

See paper. Nice!



Did you say bounded **linear**?

Results: Not as good as they sounded in my head.

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

Theorem

*Given a operator neural network \mathcal{O} then some layer $l \in \mathcal{O}$, the let $K : C(R^{(l)}) \rightarrow C(R^{(l)})$ be a bounded **linear** operator. If we denote the operation of layer l on layer $l - 1$ as $\sigma^{(l+1)} = g(\Sigma_{l+1}\sigma^{(l)})$, then for every $\epsilon > 0$, there exists a weight polynomial $w^{(l)}(i,j)$ such that the supremum norm over $R^{(l)}$*

$$\left\| K\sigma^{(l)} - \Sigma_{l+1}\sigma^{(l)} \right\|_{\infty} < \epsilon \quad (17)$$

Me

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Results: Stronger Representation Theory

General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results

We want to show the following better theorem.

Theorem

*Given a operator neural network \mathcal{O} then some layer $l \in \mathcal{O}$, the let $K : C(R^{(l)}) \rightarrow C(R^{(l)})$ be a bounded **continuous** operator. If we denote the operation of layer l on layer $l - 1$ as $\sigma^{(l+1)} = g(\sum_{l+1} \sigma^{(l)})$, then for every $\epsilon > 0$, there exists a weight polynomial $w^{(l)}(i, j)$ such that the supremum norm over $R^{(l)}$*

$$\left\| K\sigma^{(l)} - \sum_{l+1} \sigma^{(l)} \right\|_{\infty} < \epsilon \quad (18)$$

But how? **Dirac Spikes!**

Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.



Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- Fix $\epsilon > 0$. Given $K : \xi \mapsto f$, let $K_j : \xi \mapsto f(j)$ be a functional on L^q .

Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- Fix $\epsilon > 0$. Given $K : \xi \mapsto f$, let $K_j : \xi \mapsto f(j)$ be a functional on L^q .
- We can find a $C_j : L^q(R) \xrightarrow{g \circ n_2} \mathbb{R}^{m(j)} \xrightarrow{n} \mathbb{R}^1$ so that for all ξ ,

$$|C_j(\xi) - K_j(\xi)| = |C_j(\xi) - f(j)| < \epsilon/2. \quad (19)$$

Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- We know that

$$C_j(\xi) = \sum_{k=1}^{m(j)} a_{jk} g \left(\int_R \xi(i) w_{kj}(i) d\mu(i) \right) \quad (19)$$



Results: Stronger Representation Theory



General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- We wish to turn C_j into a two layer \mathcal{O} . Let,

$$w^{(0)}(i, \ell) = \begin{cases} w_{kj}(i), & \text{if } \ell = j + k, k \in 1, \dots, m(j) \\ 0 & \text{otherwise} \end{cases}$$



Results: Stronger Representation Theory



General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

■ Then

$$C_j(\xi) = \sum_{k=1}^m a_{jk} g \circ \phi[\xi](k + j) \quad (19)$$



Results: Stronger Representation Theory



General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

■ Then

$$C_j(\xi) = \sum_{k=1}^m a_{jk} g \circ \phi[\xi](k + j) \quad (19)$$

■ How do we turn this finite sum into an integral? Dirac time!



Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- We define a dirac spike as follows for every n :

$$\delta_{nkj}(\ell) = cn \exp(-bn^2|\ell - (j+k)|^2) \quad (19)$$

where c, b are set so that $\int_{\mathbb{R}} \delta_{nkj} = 1$



Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- Now let the second weight function be:

$$w_n^{(1)}(\ell, j) = \sum_{k=1}^m a_{jk} \delta_{nkj}(\ell) \quad (19)$$



Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- Putting everything together, for every n let $\mathcal{O}_n : L^p(R) \rightarrow L^1([0, 1])$

$$\mathcal{O}_n : \xi \mapsto \int_R w^{(1)}(\ell, j) \circ[\xi](\ell) d\mu(\ell). \quad (19)$$

Clearly $\mathcal{O}_n \rightarrow \sum_{k=1}^m a_{jk} g \circ \circ[\xi](k + j)$

Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- Therefore for every $\epsilon > 0$ there exists an N such that for all $n > N$, for all ξ , and for all j ,

$$|O_n[\xi](j) - C_j[\xi]| \leq \|O_n[\cdot](j) - C_j[\cdot]\| < \epsilon/2. \quad (19)$$

Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- Therefore for every $\epsilon > 0$ there exists an N such that for all $n > N$, for all ξ , and for all j ,

$$|O_n[\xi](j) - C_j[\xi]| \leq \|O_n[\cdot](j) - C_j[\cdot]\| < \epsilon/2. \quad (19)$$

- Recall that for every j , $\|K_j - C_j\| < \epsilon/2$.

Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- **TRIANGLE TIME!** By the triangle inequality we have that for all j

$$\begin{aligned}\|K_j - \mathcal{O}_n(k)\| &= \|K_j - \mathcal{O}_n(j) + C_j - C_j\| \\ &\leq \|K_j - C_j\| + \|\mathcal{O}_n(j) - C_k\| < \epsilon.\end{aligned}\tag{19}$$

Results: Stronger Representation Theory


General
Artificial
Neural
Networks

William Guss

Introduction

The Core Idea

Results



Proof.

- **TRIANGLE TIME!** By the triangle inequality we have that for all j

$$\begin{aligned}\|K_j - \mathcal{O}_n(k)\| &= \|K_j - \mathcal{O}_n(j) + C_j - C_j\| \\ &\leq \|K_j - C_j\| + \|\mathcal{O}_n(j) - C_k\| < \epsilon.\end{aligned}\tag{19}$$

- Therefore $\|K - \mathcal{O}\| < \epsilon$



Phew that was a lot of math!
Demo Time