



This repository

Search

Pull requests

Issues

Gist



 neghao / NHShareHelper



Watch

1



Star

0



Fork

0



Code



Issues

0



Pull requests

0



Projects

0



Wiki



Pulse



Graphs

Branch: master

NHShareHelper / README.md

Find file

Copy path



neghao

Update README.md

54943b4 19 hours ago

1 contributor

322 lines (277 sloc) | 9.74 KB


Raw

Blame

History



QQ、微博、微信、Facebook、Google、支付宝、Twitter分享



登录结果:成功  
登录类型:2  
错误:(null)

QQ用户信息:切克妖  
错误:The operation couldn't be completed. (Cocoa error -1.)

使用方法：将 NHShareHelper 文件夹拖入到你的工程中

一、在需要使用分享、登录的头文件中

```
#import "NHShareCallTool.h"
```

如你只需要QQ、微博分享、登录，那么把 NHShareHelper 文件夹下其它app的 .h .m 文件删除即可。

二、在AppDelegate.m文件中,重写如下方法：

```

- (BOOL)application:(UIApplication *)application didFinishLaunchingWithOptions:(NSDictionary *)launchOptions {

    //注册app
    [NHShareCallTool registerAppSetAppConsts:@[NHQQ,NHWeiBo,NHWechat,NHFacebook]];

    //需要使用到facebook才需要调用
    [NHFacebook application:application
                  didFinishLaunchingWithOptions:launchOptions
                  enableUpdatesOnAccessTokenChange:YES];

    return YES;
}

- (BOOL)application:(UIApplication *)application
    openURL:(NSURL *)url
    sourceApplication:(NSString *)sourceApplication
    annotation:(id)annotation {
    return [NHShareCallTool application:application
                                openURL:url
                                sourceApplication:sourceApplication
                                annotation:annotation];
}

- (BOOL)application:(UIApplication *)application handleOpenURL:(NSURL *)url{
    return [NHShareCallTool application:application
                                openURL:url
                                sourceApplication:nil
                                annotation:nil];
}

- (BOOL)application:(UIApplication *)application
    openURL:(NSURL *)url
    options:(NSDictionary<UIApplicationOpenURLOptionsKey,id> *)options {
    BOOL handled = [NHShareCallTool application:application
                                openURL:url
                                sourceApplication:options[UIApplicationOpenURLOptionsSourceApplicationKey]
                                annotation:options[UIApplicationOpenURLOptionsAnnotationKey]];
    return handled;
}

```

### 三、使用登陆或者分享的类，调用如下方法：

```

@interface ViewController ()<NHShareCallToolDelegate>

@implementation ViewController
- (void)viewDidLoad {
    [super viewDidLoad];
    [[NHShareCallTool sharedCallTool] addDelegate:self];
}

```

#### 使用方法:

```

//登录 eg: qq登录
[NHShareCallTool loginSetAppConst:NHQQ viewController:nil];

//QQ分享
[NHQQCall sendTitle:NHShareTitle
            urlStr:NHShareUrl
            description:NHShareDescription(@"")
            previewImgURL:@"http://avatar.csdn.net/F/F/C/1_laencho.jpg"
            shareType:type];

//微信分享
[NHWechatCall sendLinkURL:NHShareUrl
              TagName:NHShareTitle

```

```
        Title:NHShareTitle
        Description:NHShareDescription(@"")
        ThumbImage:[UIImage imageNamed:@"test"]
        InScene:scene];

//微博分享
    NSData *data = [NSData dataWithContentsOfFile:[NSBundle mainBundle] pathForResource:@"test" ofType:@"png"];
    [NHWeiBoCall sendTitle:NHShareTitle
                thumbnailData:data
                webpageTitle:NHShareTitle
                webpageTitle:NHShareTitle];
```

分享结果回调代理：

登陆结果代理回调：

```
@protocol NHShareCallToolDelegate <NSObject>
/**
 * 获取QQ用户信息结果
 */
- (void)nh_QQRequestUserinfo:(NHQQUserinfo *)userinfo error:(NSError *)error;

/**
 * 获取微信用户信息结果
 */
- (void)nh_wechatRequestUserinfo:(NHWechatUserinfo *)userinfo error:(NSError *)error;

/**
 * 获取微博用户信息结果
 */
- (void)nh_weiBoRequestUserinfo:(NHWeiBoUserinfo *)userinfo error:(NSError *)error;

/**
 * 登陆结果，调用此方法时还未请求到用户信息
 * 根据项目需要，如果你需要在登录后立即做些什么，请实现此代理方法
 *
 * @param appType 登录类型
 * @param success 是否成功
 * @param errorMsg 错误信息
 */
- (void)nh_loginResultAppType:(NHAppType)appType Success:(BOOL)success errorMsg:(NSString *)errorMsg;

/**
 * 分享结果
 *
 * @param success 是否成功
 * @param errorMsg 错误信息
 * @param shareType 分享类型
 */
- (void)nh_shareResultSuccess:(BOOL)success errorMsg:(NSString *)errorMsg shareType:(NHAppType)shareType;
@end
```

四、工程配置：

具体的第三方SDK配置，请参照相应的官方文档；  
这里说下工程配置：

- 1. 把如下的appID、appSecret设置成你自己的



```

1  < NHShareHelper > NHShareHelper > NHShareHelper > NHShareConfiguration.h > Ni
2
3  #define shareURL @"https://github.com/Neghao/NHShareHelper.git"
4  #define shareTitles @"NHShareHelper分享测试"
5
6  //QQ参数
7  #define QQAppID @"11054672**"
8  #define QQAppKey @"xiJ7fsMcHTAbA1**"
9  #define QQShareSessionTag 991
10 #define QQShareQzoneTag 661
11 #define QQLoginTag 881
12
13 //微信参数
14 #define WXAppID @"wx25baeb3cd821b**"
15 #define WXAppSecret @"a99e53a9518d5218c9b2710c072b625e**"
16 #define WXShareTag 992
17 #define WXPShareTag 662
18 #define WXLoginTag 882
19
20 //微博参数
21 #define WBApID @"34799478**"
22 #define WBApSecret @"9fcb3ea4a0be054f924dd1ea506a0d0d**"
23 #define WBRedirectURL @"http://sns.whalecloud.com"
24 #define WBGetTokeninfo @"https://api.weibo.com/oauth2/get_token_info"
25 #define WBGetUserInfo @"https://api.weibo.com/2/users/show.json"
26 #define WBShareTag 993
27 #define WBLoginTag 883

```

2. URL Schemes配置，下面\*\* 行中的key改成你自己的：

The screenshot shows the 'URL Types' configuration in Xcode. The 'Info' tab is selected. The list of URL types includes:

- Untitled**: Identifier: None, Icon: None, URL Schemes: fb2437370894235\*\*, Role: Editor
- tencentApIdentifier**: Identifier: tencentApIdentifier, Icon: None, URL Schemes: tencent11055188\*\*.content, Role: Editor
- qzoneScheme**: Identifier: qzoneScheme, Icon: None, URL Schemes: mqzone, Role: Editor
- tencent**: Identifier: tencent, Icon: None, URL Schemes: tencent11054672\*\*, Role: Editor
- weixin**: Identifier: weixin, Icon: None, URL Schemes: wx25baeb3cd821b\*\*, Role: Editor
- openSys**: Identifier: openSys, Icon: None, URL Schemes: prefs, Role: Editor
- com.weibo**: Identifier: com.weibo, Icon: None, URL Schemes: wb3479947\*\*, Role: Editor

3. info.plist配置：

info.plist文件右键 > open AS > source code，添加如下配置，注意：是在前面的前面添加如下

```

<key>LSApplicationQueriesSchemes</key>
<array>
    <string>alipay</string>
    <string>wechat</string>
    <string>weixin</string>
    <string>sinaweibohd</string>
    <string>sinaweibo</string>
    <string>sinaweibosso</string>
    <string>weibosdk</string>
    <string>weibosdk2.5</string>

```

```
<string>weibosdk3.1</string>
<string>mqq</string>
<string>mqqapi</string>
<string>mqqwpa</string>
<string>mqqbrowser</string>
<string>mttbrowser</string>
<string>mqq0pensdkSSoLogin</string>
<string>mqqopensdkapiV2</string>
<string>mqqopensdkapiV3</string>
<string>mqqopensdkapiV4</string>
<string>wtloginmqq2</string>
<string>mqzone</string>
<string>mqzoneopensdk</string>
<string>mqzoneopensdkapi</string>
<string>mqzoneopensdkapi19</string>
<string>mqzoneopensdkapiV2</string>
<string>mqqapiwallet</string>
<string>mqqopensdkfriend</string>
<string>mqqopensdkdataline</string>
<string>mqqgamebindinggroup</string>
<string>mqqopensdkgrouptribeshare</string>
<string>tencentapi.qq.reqContent</string>
<string>tencentapi.qzone.reqContent</string>
<string>fbapi</string>
<string>fb-messenger-api</string>
<string>fbauth2</string>
<string>fbshareextension</string>
</array>
```

```
<key>NSAppTransportSecurity</key>
<dict>
  <key>NSExceptionDomains</key>
  <dict>
    <key>alipay.com</key>
    <dict>
      <key>NSIncludesSubdomains</key>
      <true/>
      <key>NSTemporaryExceptionAllowsInsecureHTTPLoads</key>
      <true/>
      <key>NSTemporaryExceptionMinimumTLSVersion</key>
      <string>TLSv1.0</string>
      <key>NSTemporaryExceptionRequiresForwardSecrecy</key>
      <false/>
    </dict>
    <key>alipayobjects.com</key>
    <dict>
      <key>NSIncludesSubdomains</key>
      <true/>
      <key>NSTemporaryExceptionAllowsInsecureHTTPLoads</key>
      <true/>
      <key>NSTemporaryExceptionMinimumTLSVersion</key>
      <string>TLSv1.0</string>
      <key>NSTemporaryExceptionRequiresForwardSecrecy</key>
      <false/>
    </dict>
    <key>qq.com</key>
    <dict>
      <key>NSIncludesSubdomains</key>
      <true/>
      <key>NSThirdPartyExceptionAllowsInsecureHTTPLoads</key>
      <true/>
      <key>NSThirdPartyExceptionRequiresForwardSecrecy</key>
      <false/>
    </dict>
    <key>sina.cn</key>
    <dict>
      <key>NSExceptionMinimumTLSVersion</key>
      <string>TLSv1.0</string>
```

```

        <key>NSIncludesSubdomains</key>
        <true/>
        <key>NSThirdPartyExceptionRequiresForwardSecrecy</key>
        <false/>
    </dict>
    <key>sina.com.cn</key>
    <dict>
        <key>NSIncludesSubdomains</key>
        <true/>
        <key>NSThirdPartyExceptionAllowsInsecureHTTPLoads</key>
        <true/>
        <key>NSThirdPartyExceptionRequiresForwardSecrecy</key>
        <false/>
    </dict>
    <key>sinaimg.cn</key>
    <dict>
        <key>NSIncludesSubdomains</key>
        <true/>
        <key>NSThirdPartyExceptionAllowsInsecureHTTPLoads</key>
        <true/>
        <key>NSThirdPartyExceptionRequiresForwardSecrecy</key>
        <false/>
    </dict>
    <key>sinajs.cn</key>
    <dict>
        <key>NSIncludesSubdomains</key>
        <true/>
        <key>NSThirdPartyExceptionAllowsInsecureHTTPLoads</key>
        <true/>
        <key>NSThirdPartyExceptionRequiresForwardSecrecy</key>
        <false/>
    </dict>
    <key>weibo.cn</key>
    <dict>
        <key>NSExceptionMinimumTLSVersion</key>
        <string>TLSv1.0</string>
        <key>NSIncludesSubdomains</key>
        <true/>
        <key>NSThirdPartyExceptionRequiresForwardSecrecy</key>
        <false/>
    </dict>
    <key>weibo.com</key>
    <dict>
        <key>NSExceptionMinimumTLSVersion</key>
        <string>TLSv1.0</string>
        <key>NSIncludesSubdomains</key>
        <true/>
        <key>NSThirdPartyExceptionAllowsInsecureHTTPLoads</key>
        <true/>
        <key>NSThirdPartyExceptionRequiresForwardSecrecy</key>
        <false/>
    </dict>
</dict>
</dict>

```



阿里配置说明文档：<https://github.com/neghao/NHShareHelper/blob/master/help/AlibabaSetting.md>

五、第三方sdk下载地址：

因sdk包比较大，所以请自动去官网下载相应的sdk包，也更好保证是官网最新版sdk，本来想用cocoapod管理的，但有些公司



的pod库更新得很慢，无法保证sdk的版本，所以还是手动下载吧！下载完成后拖入到 shareSDKs 文件夹下相应的文件夹内：


qq: <http://wiki.open.qq.com/wiki/mobile/SDK>下载

wechat: [https://open.weixin.qq.com/cgi-bin/showdocument?action=dir\\_list&t=resource/res\\_list&verify=1&id=open1419319164&token=&lang=zh\\_CN](https://open.weixin.qq.com/cgi-bin/showdocument?action=dir_list&t=resource/res_list&verify=1&id=open1419319164&token=&lang=zh_CN)

weiBo: <http://open.weibo.com/wiki/SDK>

Alibaba： <https://doc.open.alipay.com/docs/doc.htm?spm=a219a.7629140.0.0.a6mex3&treeld=218&articleId=105326&docType=1>

facebook: <https://developers.facebook.com/docs/ios>



facebook的sdk包会有多个framework库，如果只是使用基础的登录分享功能的话，只需要拖入上图中的几库就可以了。

