

# Lecture: Responsive design and SASS

design website / pages so that it renders well in any type of device

## ① media query

assign CSS to particular type of HTML element on a particular type of media

computer  
printer  
phone  
?

< p class = "screen-only" > For comp screens  
</p>

CSS

create media query

@ media

print {

which media I want to apply to

apply to all classes called "screen-only"

• screen-only {  
display: none;

apply this to print media only.

make invisible.

another media query

@ media (min-width : 500px) {

Apply this if media has  
width  $\geq 500px$   
}

@ media (max-width: 499px) }

Apply this if media has width  
 $\leq 499px$   
}


<meta name = "viewport"

content = "width = device-width ,


initial-scale = 1.0" >

- viewport = visible area of your page
- set width of viewport as width of the device being used

## Flex box



shrink screen



<div class = "container">

```

<div>      A      </div>
<div>      B      </div>
           ;
</div>

```

CSS

• container {

display : flex ;

flex-wrap : wrap ;

}

flexible  
container

allow  
content to  
wrap  
around.

• container > div {

background-color : springgreen ;

}

immediate  
and child of  
class containers...

apply this to

grid layout (grid box)

<div class = "x">

<div class = "y"> 1 </div>

;

<div class = "y"> n </div>

</div>

## CSS

• x {

display : grid;

padding : 20px


grid-column-gap : 20px;


grid-row-gap : 20px;

grid-template-columns :

auto 20px auto;

}



if screen shrunk,  widths get scaled...

---

## CSS Libraries

Bootstrap


( flex, grid, and other things

already  
implemented in  
CSS style  
sheet)

< link rel = " style sheet",

href = " link to bootstrap style  
sheet " >

Bootstrap: each row in  
website → 12 cols



### Syntax

< div class = " container " >

< div class = " row " >

← row..

< div class = " col - 3 " >

< / div >

↑  
this takes up 3 / 12 cols

< div class = " col - lg - 3 col - sm - 6 " >

on a large  
screen,

on a  
small

< / div >

< / div >

< /div>

takes up  
3/12 cols

screen,  
takes  
up  
6/12 cols

### Alerts in bootstrap

< div class = "alert alert-primary"  
role = "alert">

< div class = "alert alert-success "  
role = "alert">

< div class = "alert alert-danger "  
role = "alert">

→ get bootstrap.com

→ Documentation

→ Components

---

Sass ( language built on  
top of CSS)

- programmatically generate CSS  
style sheets

- .scss (extension for CSS  
style sheets)

variables in sass begin with \$

↓  
`$color : red ;`

⋮  
CSS code where you can use `$color`  
...

`.scss`  $\xrightarrow{\text{sass}}$  `.css`

Sass      Input .scss      output .css

→ generates      output .css      from input .scss

\* `.css.map` ← stores the way output .css  
is generated from  
input .scss.

Sass can "watch" a file/

a directory of files. Anytime any  
of them changes, Sass automatically  
recompiles the associated CSS files.

`sass --watch input.scss:output.css`

Github, other website deployment pages have built in support for sass

• SCSS

→ Github

(Github automatically compiles  
• SCSS → .css)

Install sass (free software)

### Nesting CSS using sass

• sass file

```
div {  
  font-size: 18px;  
  p { color: blue;  
  }  
  ul { color: green;  
  }  
}
```

for any p

— descendant of  
div, apply  
blue

for any ul

— descendant of  
div, apply  
green.

etc.

same as

div p {color: blue;} in usual CSS.



# Inheritance in sass



message template

```
% message {
```

```
font-family: sans-serif;
```

```
padding: 20px
```

```
font-size: 18px
```

```
}
```

extend message  
templates styling  
to success class

```
.success {
```

```
@extend % message;
```

```
background-color: green;
```

```
}
```