



Exception Handling – Try-Catch Block

Agenda

1

Try-Catch Block

2

Multiple Catch Block

3

Nested Try Block

Try-Catch Block



Try-Catch Block

- Any part of the code that can generate an error should be put in the **try** block
- Any error should be handled in the **catch** block defined by the **catch** clause
- This block is also called the **catch block**, or the **exception handler**
- The corrective action to handle the exception should be put in the **catch** block

How to Handle exceptions?

```
class ExceptDemo{
    public static void main(String args[]){
        int x, a;
        try{
            x = 0;
            a = 22 / x;
            System.out.println("This will be bypassed.");
        }
        catch (ArithmeticException e){
            System.out.println("Division by zero.");
        }
        System.out.println("After catch statement.");
    }
}
```

Quiz

- What will be the result, if we try to compile and execute the following code as
java Ex1 Wipro Bangalore

```
Class Ex1 {  
    public static void main(String[] xyz) {  
        for(int i=0;i<=args.length;i++)  
            System.out.println(args[i]);  
    }  
}
```

**Compile but throws exception during runtime!
Why this exception is thrown?**

Multiple Catch Block



Multiple Catch Statements

- A single block of code can raise more than one exception
- You can specify two or more **catch** clauses, each catching a different type of exception
- When an exception is thrown, each **catch** statement is inspected in order, and the first one whose type matches that of the exception is executed
- After one **catch** statement executes, the others are bypassed, and execution continues after the **try/catch** block

Multiple Catch Statements (Contd.).

```
class MultiCatch{  
    public static void main(String args[]){  
        try{  
            int l = args.length;  
            System.out.println("l = " +l) ;  
            int b = 42 / l;  
            int arr[] = { 1 };  
            arr[22] = 99;  
        }  
        catch (ArithmeticException e) {  
            System.out.println("Divide by 0: "+ e) ;  
        }  
    }  
}
```

Multiple Catch Statements (Contd.).

```
catch (ArrayIndexOutOfBoundsException e) {  
    System.out.println("Array index oob: "+e);  
}  
System.out.println("After try/catch blocks.");  
}  
}
```

Quiz

- What will be the result, if we try to compile and execute the following code as java Ex2 100

```
class Ex2 {  
    public static void main(String[] args) {  
        try {  
            int i= Integer.parseInt(args[0]);  
            System.out.println(i);  
        }  
        System.out.println("Wipro");           // is there any problem?  
        catch (NumberFormatException e) {  
            System.out.println(e);  
        }  
    }  
}
```

It will throw compilation Error

Multiple Catch Statements involving Exception Superclasses & Subclasses

- When you use multiple catch statements, it is important to remember that exception subclasses must come before any of their exception superclasses
- This is because a catch statement that uses a superclass will catch exceptions of that type as well as exceptions of its subclasses
- Thus, a subclass exception would never be reached if it came after its superclass that manifests as an **unreachable code error**

Quiz

- What will be the result, if we try to compile and execute the following code as java Ex2 100

```
class Ex2 {  
    public static void main(String[] args) {  
        try {  
            int i= Integer.parseInt(args[0]);  
            System.out.println(i);  
        }  
        catch (RuntimeException e) {  
            System.out.println(e);  
        }  
        catch (NumberFormatException e) {  
            System.out.println(e);  
        }  
    }  
}
```

It will throw compilation Error

Nested Try Block



Nested try Statements

- The **try** statement can be nested
- If an inner **try** statement does not have a **catch** handler for a particular exception, the outer block's catch handler will handle the exception
- This continues until one of the **catch** statement succeeds, or until all of the nested **try** statements are exhausted
- If no catch statement matches, then the Java runtime system will handle the exception

Syntax

```
try
{
    statement 1;
    statement 2;
    try
    {
        statement 1;
        statement 2;
    }
    catch(Exception e)
    {
    }
}
catch(Exception e)
{
}
```


Example for nested try

```
class Nested_Try{
    public static void main(String args[]){
        try{
            try{
                System.out.println("Arithmetic Division");
                int b =39/0;
            }catch(ArithmeticException e){
                System.out.println(e);
            }
            try{
                int a[]=new int[5];
                System.out.println("Accessing Array Elements");
                a[5]=4;
            } catch(ArrayIndexOutOfBoundsException e)    {
                System.out.println(e);
            }
            System.out.println ("Inside Parent try");
        } catch(Exception e) {
            System.out.println("Exception caught");
        }
        System.out.println("Outside Parent try");
    }
}
```

Quiz

1. Debug the code

```
public class Tester {  
    public static void main(String[] args) {  
        try {  
            System.out.println("A");  
        }  
        catch (Exception e)  
        {  
            System.out.println("B");  
        }  
        catch (ArithmeticException a) {  
            System.out.println("C");  
        }  
    }  
}
```

Summary

In this session, you were able to :

- Learn about try-catch block
- Learn about multiple catch block
- Learn about nested try block

Assignment

