

Product_Code	GID_900000007767097
productTitle	Flask Tray for Grant Shaking Water Baths
teaserText	Include threaded holes to accept flask clamps or holder for deep well plates (=2ml). Grant Instruemnts™ Flask Tray for Grant Shaking Water Baths are compatible with SR plate holders and racks or can be used alone to accommodate bags and miscellaneous vessels.
productLongDescription	Include threaded holes to accept flask clamps or holder for deep well plates (=2ml). Grant Instruemnts™ Flask Tray for Grant Shaking Water Baths are compatible with SR plate holders and racks or can be used alone to accommodate bags and miscellaneous vessels.
productFeatures	<ul style="list-style-type: none"> • Accommodates flasks from 25 to 1000mL • For use with the following Shaking Water Bath models: <ul style="list-style-type: none"> ◦ LSB12 ◦ LSB18 ◦ OLS26 • Compatible with SH plate holders or SR racks • TF26 Test tube tray also compatible with SR racks • Can be used alone to accommodate bags and miscellaneous vessels.
metaDescription	Flask tray with threaded holes to accept flask clamps or holder for deep well plates (â‰¥2ml), SH plate holders and SR Racks.
eCommDescription240	Grant Instruments Flask Tray for Grant Shaking Water Baths, For Use With: OLS26
keywords	GRATF26
internalKeyword	GRATF26
UNSPSC	41103715
contentAuthor	Unknown_
includes	
warranty	
brand	
footnotes	
compliance	
certifications	
disclaimers	
alerts	
EUsupplierName	
TFLongDescription	

Product_Code	GID_90000000910323
productTitle	Plastic Lid for Grant Stirred Water Baths
teaserText	Helps to reduce evaporation/heat loss and avoid sample contamination. Grant Instruments™ Plastic Lid for Grant Stirred Water Baths is constructed of curved or flat plastic with an integral handle
productLongDescription	Helps to reduce evaporation/heat loss and avoid sample contamination. Grant Instruments™ Plastic Lid for Grant Stirred Water Baths is constructed of curved or flat plastic with an integral handle
productFeatures	<ul style="list-style-type: none"> • Flat or curved moulded plastic • Integral handle • For use with Grant Stirred Water Baths and heated Circulators • Prevents heat from escaping • Reduces sample contamination
metaDescription	Reduces sample contamination and heat loss
eCommDescription240	Grant Instruments Plastic Lid for Grant Stirred Water Baths, For Use With: P12 Plastic Tank, Description: Lid for 12L tank
keywords	lid, cover, plastic, bath, tank, GRAPL12
internalKeyword	lid, cover, plastic, bath, tank, GRAPL12
UNSPSC	41103715
contentAuthor	Stephanie_Winter
includes	
warranty	
brand	
footnotes	
compliance	
certifications	
disclaimers	
alerts	
EUsupplierName	
TFLongDescription	

Product_Code	GID_900000007761771
productTitle	Optima Bridge Plate
teaserText	View and access thermostat on heating and cooling circulators. Grant Instruments™ Optima Bridge Plate is for use with Grant refrigeration units, heating and cooling circulators.
productLongDescription	View and access thermostat on heating and cooling circulators. Grant Instruments™ Optima Bridge Plate is for use with Grant refrigeration units, heating and cooling circulators.
productFeatures	<ul style="list-style-type: none"> • For use with Grant refrigeration units, heating and cooling circulators • Ensures visibility/accessibility of the thermostat whilst optimising bench space
metaDescription	View and access thermostat on heating and cooling circulators
eCommDescription240	Grant Instruments Optima Bridge Plate, For Use With: T Optima heating circulator models to S12, 18, 26, 38 tanks, Stainless Steel
keywords	plate, bridge, cover, visibility, thermostat, accessibility, GRAT-BSL
internalKeyword	plate, bridge, cover, visibility, thermostat, accessibility, GRAT-BSL
UNSPSC	41103715
contentAuthor	Stephanie Winter
includes	
warranty	
brand	
footnotes	
compliance	
certifications	
disclaimers	
alerts	
EUsupplierName	
TFLongDescription	

Product_Code	GID_900000003088388
productTitle	Raised Shelf for Unstirred Water Baths
teaserText	Accommodates shallow vessels. Grant Instruments™ Raised Shelf for Unstirred Water Baths can be used with a variety of other Grant Heating Circulators and Heated Circulating Baths.
productLongDescription	Accommodates shallow vessels. Grant Instruments™ Raised Shelf for Unstirred Water Baths can be used with a variety of other Grant Heating Circulators and Heated Circulating Baths.
productFeatures	<ul style="list-style-type: none"> • Choose from a variety of sizes to fit your tank • For use with either Stainless Steel and Plastic tank models
metaDescription	Reversible, allows two shelf depths.
eCommDescription240	Grant Instruments Raised Shelf for Unstirred Water Baths, Shelf for 26 L Tanks, For Use With: Grant Heated Circulating Baths, Height: 45 or 135 mm
keywords	raise, level, shallow, vessel, GRARS28
internalKeyword	raise, level, shallow, vessel, GRARS28
UNSPSC	41103715
contentAuthor	Stephanie_Winter
includes	
warranty	
brand	
footnotes	
compliance	
certifications	
disclaimers	
alerts	
EUsupplierName	
TFLongDescription	

Product_Code	GID_900000003572676
productTitle	Oxygen/Nitrogen/CO ₂ Flowmeter for Precision™ Water Baths
teaserText	Use Oxygen/Nitrogen/CO ₂ Flowmeter for Precision Dubnoff™ and Shallow-Form Shaking Water Baths.
productLongDescription	Thermo Scientific™ Oxygen/Nitrogen/CO ₂ Flowmeter for Precision™ Baths is for use with Dubnoff™ and Shallow-Form Shaking Water Baths.
productFeatures	<ul style="list-style-type: none"> ■ Independent controls regulate flow of gas to sample environment ■ Permits flow rates from 0 to 10 CFH (0 to 4719 cc/min.)
metaDescription	Use Oxygen/Nitrogen/CO ₂ Flowmeter for Precision Baths with Dubnoff and Shallow-Form Shaking Water Baths.
eCommDescription240	Oxygen/Nitrogen/CO ₂ Flowmeter for Precision Water Baths, Description: Oxygen/Nitrogen/CO ₂ Flowmeter, Flow Rate: 0 to 10 CFH, For Use With: Precision Reciprocal Dubnoff Shaking Water Bath
keywords	flowmeter, water bath accessories, Miscellaneous Accessories for Baths, Bath Accessories, Baths
internalKeyword	miscellaneous
UNSPSC	41103715
contentAuthor	—
includes	
warranty	
brand	
footnotes	
compliance	
certifications	
disclaimers	
alerts	
EUSupplierName	
TFLongDescription	

Product_Code	GID_900000007748168
productTitle	Stainless Steel Tank and Bridge Plate for Baths
teaserText	Combine with any Grant Heating Circulator or Bath. Grant Instruments™ Stainless Steel Tank and Bridge Plate for Baths has a temperature range of –15 to 200°C.
productLongDescription	Combine with any Grant Heating Circulator or Bath. Grant Instruments™ Stainless Steel Tank and Bridge Plate for Baths has a temperature range of –15 to 200°C.
productFeatures	<ul style="list-style-type: none"> • High efficiency stainless steel construction • Temperature range: -15 to 200°C • Includes integral raised feet for ease of carrying, repositioning, and retort access
metaDescription	High efficiency stainless steel tanks include raised feet for carrying, repositioning and retort access.
eCommDescription240	Grant Instruments Stainless Steel Tank and Bridge Plate for Baths, For Use With: Optima range immersion thermostats - T100, TC120, TXF150 or TXF200, Capacity: 5 L, Length: 330 mm
keywords	stainless, visibility, access, bath, tank, GRAST5
internalKeyword	stainless, visibility, access, bath, tank, GRAST5
UNSPSC	41103715
contentAuthor	Stephanie Winter
includes	
warranty	
brand	
footnotes	
compliance	
certifications	
disclaimers	
alerts	
EUsupplierName	
TFLongDescription	

Product_Code	GID_ANZ_FLK6109A256
productTitle	6109A / 7109A Portable Calibration Baths
teaserText	A portable calibration bath with four times more calibration throughput and twice the accuracy of Micro-Baths and dry-block calibrators.
productLongDescription	The Fluke Calibration 6109A and 7109A Portable Calibration Baths are a liquid bath that let process industry professionals calibrate four times more sanitary sensors per batch in less time and with twice the accuracy of other portable baths in this class. Larger than micro baths, up to four tri-clamp sanitary sensors fit easily into this bath for calibration at $\pm 0.1^{\circ}\text{C}$ temperature display accuracy. Throughput is even higher for sanitary RTDs with small or no flanges.
productFeatures	<p>Fluke 6109A and 7109A Portable Calibration Baths</p> <p>A portable calibration bath with four times more calibration throughput and twice the accuracy of Micro-Baths and dry-block calibrators</p> <p>The Fluke Calibration 6109A/ 7109A Portable Calibration Bath is a liquid bath that let process industry professionals calibrate four times more sanitary sensors per batch in less time and with twice the accuracy of other portable baths in this class. Larger than micro baths, up to four tri-clamp sanitary sensors fit easily into this bath for calibration at $\pm 0.1^{\circ}\text{C}$ temperature display accuracy. Throughput is even higher for sanitary RTDs with small or no flanges.</p> <p>6109A covers a wide temperature range from 35°C to 250°C.</p> <p>Key features</p> <ul style="list-style-type: none"> • Calibrate up to four tri-clamp sanitary sensors at the same time • Wide temperature ranges cover most process applications: • 35°C to 250°C • Excellent display accuracy of $\pm 0.1^{\circ}\text{C}$ provides 4:1 test uncertainty ratio (TUR) for critical applications • Easy to transport up stairs and across catwalks • Stainless steel casing withstands harsh sterilizing chemicals and is rust proof • Easy to use and maintain • Global Fluke support and service <p>I own a Fluke Calibration Micro-Bath. Why do I need a 6109A or 7109A bath?</p> <p>If you already own a Fluke Calibration Micro-Bath or dry-block calibrator, thank you for being a customer! We hope you are enjoying the portability and stability of these popular products.</p> <p>However, there are a few reasons why you should consider adding a 6109A or 7109A bath:</p> <ul style="list-style-type: none"> • Errors of just a few tenths of a degree Celsius can cause expensive losses in ruined product. The 6109A and 7109A baths are twice as accurate as a Micro-Bath, helping you to reduce this risk • The 6109A and 7109A have four times the calibration throughput of a Micro-Bath, which can only calibrate a single tri-clamp sensor at a time. • They're made with materials that don't harbor bacteria. Their stainless steel panels and tank are easy to clean and rust resistant—perfect for clean room use. <p>We hope you will continue to use your Fluke Calibration Micro-Bath for many years to come. The 6109A or 7109A baths will also serve you well if you need the throughput, accuracy, and clean room readiness that they provide.</p> <p>Backed by global Fluke support and service</p> <p>The 6109A and 7109A are designed to meet demanding Fluke Calibration metrology specifications, so you can trust that they will perform the way we say they will. Need assistance? We offer world-class support both before and after the sale, via online chat, email, telephone and through our service organizations. Rest easy knowing the value of your investment will be preserved now and into the future.</p>
metaDescription	A portable calibration bath with four times more calibration throughput and twice the accuracy of Micro-Baths and dry-block calibrators.
eCommDescription240	Fluke 6109A / 7109A Portable Calibration Baths, Description: 6109 A Portable Calibration Bath, Temperature Range: 35°C to 250°C , Heat Up Time: 35°C to 100°C : 25 minutes, 100°C to 250°C : 45 minutes, Holds 2.5 L, Temperature Accuracy: 0.1°C
keywords	6109A, 7109A, Portable, Calibration, Baths, FLK6109A-256
internalKeyword	6109A, 7109A, Portable, Calibration, Baths, FLK6109A-256
UNSPSC	41103715
contentAuthor	Unknown
includes	
warranty	
brand	
footnotes	
compliance	
certifications	
disclaimers	
alerts	
EUSupplierName	
TFLongDescription	

Product_Code	GID_900000009741337
productTitle	ARCTIC™ Refrigerated Bath Premium Starter Package
teaserText	Save up to \$980 when you bundle Thermo Scientific™ ARCTIC refrigerated bath circulators and accessories
productLongDescription	Thermo Scientific ARCTIC refrigerated bath circulators provide outstanding cooling power, expansive temperature ranges, powerful force/suction pumps, and sophisticated digital control technology designed to ensure accuracy and reproducibility of your liquid temperature control procedures. Bundle and save up to \$980* off the cost of the ARCTIC refrigerated bath circulators and temperature control accessories
productFeatures	<p>Package includes:</p> <ul style="list-style-type: none"> • AC150 A25 Recirculating bath (-25°C to 150°C) • Silion Oil 180 10L • Plumbing Package • NEScomm software • A25 Trolley with Castors
metaDescription	Fisher Scientific - Thermo Scientific Refrigerated Bath Premium Starter Package, -25 C to 150 C Bundle
eCommDescription240	Thermo Scientific ARCTIC Refrigerated Bath Premium Starter Package, Temperature Range: -25 deg.C to +100 deg.C, Description: Thermo Scientific ARCTIC Refrigerated Bath Premium Starter Package, Electrical Requirements: 115 V 60 Hz, Flow Rate: 20L/min (metric)
keywords	bath circulator
internalKeyword	980, bundle, _KWTAGS, _KWWARI, 1555258, pack, KWWARI_, KWTAGS_
UNSPSC	41103709
contentAuthor	
includes	
warranty	
brand	
footnotes	
compliance	
certifications	
disclaimers	
alerts	
EUsupplierName	
TFLongDescription	

Product_Code	GID_900000007761771
productTitle	Optima Bridge Plate
teaserText	View and access thermostat on heating and cooling circulators. Grant Instruments™ Optima Bridge Plate is for use with Grant refrigeration units, heating and cooling circulators.
productLongDescription	View and access thermostat on heating and cooling circulators. Grant Instruments™ Optima Bridge Plate is for use with Grant refrigeration units, heating and cooling circulators.
productFeatures	<ul style="list-style-type: none"> • For use with Grant refrigeration units, heating and cooling circulators • Ensures visibility/accessibility of the thermostat whilst optimising bench space
metaDescription	View and access thermostat on heating and cooling circulators
eCommDescription240	Grant Instruments Optima Bridge Plate, For Use With: T Optima heating circulator models to S12, 18, 26, 38 tanks, Stainless Steel
keywords	plate, bridge, cover, visibility, thermostat, accessibility, GRAT-BSL
internalKeyword	plate, bridge, cover, visibility, thermostat, accessibility, GRAT-BSL
UNSPSC	41103715
contentAuthor	Stephanie Winter
includes	
warranty	
brand	
footnotes	
compliance	
certifications	
disclaimers	
alerts	
EUsupplierName	
TFLongDescription	

Product_Code	GID_900000007496283
productTitle	Precision™ Circulating Water Bath, Precision CIR 89
teaserText	Achieve outstanding temperature uniformity for your samples with perimeter-directed water flow on Precision circulating water baths. Featuring advanced temperature controller.
productLongDescription	Thermo Scientific™ Precision™ circulating water baths are ideal when temperature uniformity and control are particularly critical, such as when working with enzymes and in serological applications. Available in three different models, these high performance baths feature a microprocessor control and include a removable stainless steel gable cover, diffuser tray, and rubber duck
productFeatures	<ul style="list-style-type: none"> ■ Achieve enhanced temperature uniformity with perimeter-directed water flow ■ Easily clean and maintain bath with coil-free internal design ■ Optimize scheduling with auto-on and auto-off timers ■ Accommodate taller labware with new hinged lid and extended height ■ Help prevent bath overheating and damage with low-fluid protection ■ Easily operate and monitor with icon-based graphical display ■ Protect your work with audible alarms
metaDescription	Precision circulating water baths are ideal for applications in which temperature uniformity and control are particularly critical. Features advanced controller
eCommDescription240	Thermo Scientific Precision Circulating Water Bath, Precision CIR 89, Description: 89L Circulating Water Bath, Capacity: 89 L, 23.5 gal., Electrical Requirements: Global Voltage 100/115 V 200/230 V 50/60 Hz, Model: Precision CIR 89, Temperature Range: Ambient +5 deg. to 100 deg.C
keywords	baths, water baths, lab baths, lab water baths, Precision baths, Precision water baths, circulating baths, circulating water baths, BARTSCIR89
internalKeyword	temperature, uniformity, samples, perimeter-directed, flow, controller, _KWTAGS, _KWWARI, tscir, KWWARI_, KWTAGS_, BARTSCIR89
UNSPSC	41103701
contentAuthor	—
includes	
warranty	
brand	
footnotes	
compliance	
certifications	
disclaimers	
alerts	
EUsupplierName	
TFLongDescription	

Loading pages (1/6) [>] 0% [======>] 10% [======>] 50%
 [======>] 100% Counting pages (2/6)
 [======>] Object 1 of 1 Resolving links (4/6)
 [======>] Object 1 of 1 Loading headers and footers (5/6)
 Printing pages (6/6) [>] Preparing [======>] Page 1 of 10 [======>] Page 2 of 10 [======>] Page 3 of 10
 [======>] Page 4 of 10 [======>] Page 5 of 10
 [======>] Page 6 of 10 [======>] Page 7
 of 10 [======>] Page 8 of 10
 [======>] Page 9 of 10
 [======>] Page 10 of 10 Done Thermo Fisher_Marketing
 Text_Samples 10 SKUs_Catalog Creation_012021 (2).xlsx