

Aim:

Write a program to **sort** (**ascending order**) the given elements using **radix sort** technique.

At the time of execution, the program should print the message on the console as:

Enter array size :

For example, if the user gives the **input** as:

Enter array size : 5

Next, the program should print the following message on the console as:

Enter 5 elements :

if the user gives the **input** as:

Enter 5 elements : 34 67 12 45 22

then the program should **print** the result as:

Before sorting the elements are : 34 67 12 45 22
After sorting the elements are : 12 22 34 45 67

Note: Do use the **printf()** function with a **newline** character (**\n**).

Source Code:RadixSortMain2.c

```
#include<stdio.h>
#include<conio.h>
int largest(int a[],int n)
{
    int large=a[0],i;
    for(i=1;i<n;i++)
    {
        if(large<a[i])
            large=a[i];
    }
    return large;
}
void printArray(int arr[],int n)
{
    for(int i=0;i<n;i++)
        printf("%d ",arr[i]);
    printf("\n");
}
int main()
{
    int size;
    int*arr,i;
    printf("Enter array size : ");
    scanf("%d",&size);
    arr=(int*)malloc(size*sizeof(int));
```

```

printf("Enter %d elements : ",size);
for(i=0;i<size;i++)
{
    scanf("%d",&arr[i]);
}
printf("Before sorting the elements are : ");
printArray(arr,size);
RadixSort(arr,size);
printf("After sorting the elements are : ");
printArray(arr,size);
return 0;
}

void RadixSort(int a[],int n)
{
    int bucket[10][10],bucket_count[10];
    int i,j,k,remainder,NOP=0,divisor=1,large,pass;
    large=largest(a,n);
    while(large>0)
    {
        NOP++;
        large/=10;
    }
    for(pass=0;pass<NOP;pass++)
    {
        for(i=0;i<10;i++)
        {
            bucket_count[i]=0;
        }
        for(i=0;i<n;i++)
        {
            remainder=(a[i]/divisor)%10;
            bucket[remainder][bucket_count[remainder]]=a[i];
            bucket_count[remainder]++;
        }
        i=0;
        for(k=0;k<10;k++)
        {
            for(j=0;j<bucket_count[k];j++)
            {
                a[i]=bucket[k][j];
                i++;
            }
        }
        divisor*=10;
    }
}
}

```

Execution Results - All test cases have succeeded!

Test Case - 1
User Output
Enter array size : 5

Enter 5 elements : 23
43
54
12
65
Before sorting the elements are : 23 43 54 12 65
After sorting the elements are : 12 23 43 54 65

Test Case - 2
User Output
Enter array size : 7
Enter 7 elements : 23
54
136
85
24
65
76
Before sorting the elements are : 23 54 136 85 24 65 76
After sorting the elements are : 23 24 54 65 76 85 136